COLLO	CATIO	DN - Florida												Attach	ment: 4	Exhil	oit: B
												Svc Order	Svc Order	Incremental	Incremental	Incremental	Incremental
												Submitted	Submitted	Charge -	Charge -	Charge -	Charge -
			Interi									Elec	Manually	Manual Svc	Manual Svc		Manual Svc
CATEGOR	₹Y	RATE ELEMENTS		Zone	BCS	USOC			RATES (\$)			per LSR	per LSR	Order vs.	Order vs.	Order vs.	Order vs.
			m									po. 20.1	po. 20.1	Electronic-	Electronic-	Electronic-	Electronic-
														1st	Add'l	Disc 1st	Disc Add'l
																D130 131	DISC Add I
							Rec	Nonrec			Disconnect				Rates (\$)		
			<u> </u>	<u> </u>				First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
DUVCICAL		LOCATION															
PHISICAL		Physical Collocation 2-Wire Cross Connect, Exchange Port 2-															
		Wire Analog - Res			UEPSR	PE1R2	0.0276	8.22	7.22				11.90				
 		Physical Collocation 2-Wire Cross Connect, Exchange Port 2-			OLI OIL	I L IIVZ	0.0270	0.22	1.22				11.50				
		Wire Line Side PBX Trunk - Bus			UEPSP	PE1R2	0.0276	8.22	7.22				11.90				
		Physical Collocation 2-Wire Cross Connect, Exchange Port 2-			021 01	I L IIV.	0.0270	0.22	7.22				11.50				
		Wire Voice Grade PBX Trunk - Res			UEPSE	PE1R2	0.0276	8.22	7.22				11.90				
		Physical Collocation 2-Wire Cross Connect, Exchange Port 2-						-									
	ľ	Wire Analog - Bus			UEPSB	PE1R2	0.0276	8.22	7.22				11.90				
		Physical Collocation 2-Wire Cross Connect, Exchange Port 2-															
		Wire ISDN	<u></u>		UEPSX	PE1R2	0.0276	8.22	7.22		<u></u>		11.90				
		Physical Collocation 2-Wire Cross Connect, Exchange Port 2-			_			_]]		
		Wire ISDN			UEPTX	PE1R2	0.0276	8.22	7.22				11.90				
		Physical Collocation 4-Wire Cross Connect, Exchange Port 4-			l	L		_	_				l	1	1		l
200000		Wire ISDN DS1			UEPEX	PE1R4	0.0552	8.42	7.36				11.90				
PHYSICAL		LOCATION			01.0	DE4D4		0.507.00									
		Physical Collocation - Application Fee - Initial Physical Collocation - Application Fee - Subsequent			CLO CLO	PE1BA PE1CA		2,597.00 2,236.00									
-		Physical Collocation - Application Fee - Subsequent Physical Collocation Administrative Only - Application Fee			CLO	PE1BL		742.00									
—		Physical Collocation Administrative Only - Application Fee Physical Collocation - Space Preparation - Firm Order			CLO	PEIBL		742.00									
		Processing			CLO	PE1SJ		288.93									
-		Physical Collocation - Space Preparation - C.O. Modification per			OLO	1 1 100		200.00									
		square ft.			CLO	PE1SK	2.38										
		Physical Collocation - Space Preparation - Common Systems															
		Modification per Cage			CLO	PE1SM	92.55										
		Physical Collocation - Cable Installation per Cable			CLO	PE1BD		1,750.00		45.16							
		Physical Collocation - Floor Space per Sq. Ft.			CLO	PE1PJ	7.86										
		Physical Collocation - Cable Support Structure, Per Entrance															
		Cable			CLO	PE1PM	18.96										
		Physical Collocation - Power, per Fused Amp			CLO	PE1PL	7.80										
		Physical Collocation - Power Reduction, Application Fee	- 1		CLO	PE1PR		399.43									
		Physical Callegation 420V/ Circle Phase Ctandly D			CI O	DE4ED	5.00							1	1		l
\vdash		Physical Collocation - 120V, Single Phase Standby Power Rate	 	<u> </u>	CLO	PE1FB	5.38			 	-			 	 		-
		Physical Collocation - 240V, Single Phase Standby Power Rate			CLO	PE1FD	10.77										l
-		rnysical Collocation - 240V, Single Phase Standby Power Rate			CLO	L C ILD	10.77										
		Physical Collocation - 120V, Three Phase Standby Power Rate			CLO	PE1FE	16.15							1	1		l
		, z.z zzzz rzor, rmoo r naoo otanaby r onor rato					.5.10										
		Physical Collocation - 277V, Three Phase Standby Power Rate			CLO	PE1FG	37.30										l
		,,															
					UEANL,UEA,UDN,U												
					DC,UAL,UHL,UCL,U												l
					EQ, UDL, UNCVX,												
		Physical Collocation - 2-Wire Cross-Connects			UNLDX, UNCNX	PE1P2	0.0276	8.22	7.22	5.74	4.58						
					CLO, UAL, UDL,												l
					UDN, UEA, UHL,									1	1		l
		Physical Collegation A Wire Cress Conserve			UNCVX, UNCDX, UCL	DE4D4	0.0550	0.40	7.00	F 00	4.00						l
-		Physical Collocation - 4-Wire Cross-Connects	-	 	UCL CLO,UEANL,UEQ,W	PE1P4	0.0552	8.42	7.36	5.90	4.66			 	 		
					DS1L,WDS1S, USL,									1	1		l
					U1TD1, UXTD1,												l
					UNC1X, ULDD1,												l
					USLEL, UNLD1,									1	1		l
		Physical Collocation - DS1 Cross-Connects			UDL	PE1P1	1.32	27.77	15.52	5.93	4.77						l
																	-

COLLOCAT	ION - Florida												Attach	ment: 4	Fyhi	ibit: B
CATEGORY	RATE ELEMENTS	Interi m	Zone	BCS	USOC			RATES (\$)			Svc Order Submitted Elec per LSR	Submitted	Incremental Charge - Manual Svc Order vs. Electronic- 1st		Incremental Charge -	Incremental Charge - Manual Svc Order vs. Electronic- Disc Add'l
						Rec	Nonrec			Disconnect				Rates (\$)		
				CLO, UE3,U1TD3,			First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
	Physical Collocation - DS3 Cross-Connects			UXTD3, UXTS1, UNC3X, UNCSX, ULDD3, U1TS1,ULDS1, UNLD3, UDL CLO, ULDO3, ULD12, ULD48,	PE1P3	16.81	25.48	14.05	7.77	5.01						
				U1TO3, U1T12, U1T48, UDLO3,												
	Physical Collocation - 2-Fiber Cross-Connect			UDL12, UDF	PE1F2	3.34	41.94	30.52	13.91	11.16						
	Physical Collocation - 4-Fiber Cross-Connect			CLO, ULDO3, ULD12, ULD48, U1TO3, U1T12, U1T48, UDLO3, UDL12, UDF	PE1F4	5.92	51.30	39.87	18.29	15.54						
	Physical Collocation - Welded Wire Cage - First 100 Sq. Ft.			CLO	PE1BW	189.45	31.30	33.01	10.23	10.04						
	Physical Collocation - Welded Wire Cage - Add'l 50 Sq. Ft.			CLO	PE1CW	18.58										
	Physical Collocation - Security System Per Central Office Per Assignable Sq. Ft.			CLO	PE1AY	0.0105										
	Physical Collocation - Security Access System - New Access Card Activation, per Card			CLO	PE1A1	0.0577	55.80									
	Physical Collocation-Security Access System-Administrative Change, existing Access Card, per Request, per State, per Card			CLO	PE1AA		15.65									
	Physical Collocation - Security Access System - Replace Lost or Stolen Card, per Card			CLO	PE1AR		45.75									
	Physical Collocation - Security Access - Initial Key, per Key			CLO	PE1AK		26.30									
	Physical Collocation - Security Access - Key, Replace Lost or															
	Stolen Key, per Key			CLO	PE1AL PE1SR		26.30									
	Physical Collocation - Space Availability Report per premises POT Bay Arrangements prior to 6/1/99 - 2-Wire Cross-Connect, per cross-connect	I		CLO UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ,CLO,UDL, UNCVX, UNCDX, UNCNX	PE1PE	0.00	2,159.00									
	POT Bay Arrangements prior to 6/1/99 - 4-Wire Cross-Connect, per cross-connect	I		UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ,CLO, USL, UNCVX, UNCDX	PE1PF	0.00										
	POT Bay Arrangements prior to 6/1/99 - DS1 Cross-Connect, per cross-connect	I		UEANIL, UEA, UDN, U DC, UAL, UHL, UCL, U EQ, CLO, WDS1L, W DS1S, USL, U1TD1, UXTD1, UNC1X, ULDD1, USLEL, UNLD1 UEANIL, UEA, UDN, U DC, UAL, UHL, UCL, U EQ, CLO, UE3, U1TD3, UXTD3, UXTS1, UNC3X, UNCSX, ULDD3, U1TS1, ULDS1,	PE1PG	0.00										
	POT Bay Arrangements prior to 6/1/99 - DS3 Cross-Connect, per cross-connect	ı		UNLD3, UDL, UDLSX	PE1PH	0.00										

COLLOCATI	ON - Florida													ment: 4		bit: B
CATEGORY	RATE ELEMENTS	Interi m	Zone	BCS	USOC			RATES (\$)			1	Submitted	Charge - Manual Svc Order vs. Electronic- 1st	Incremental Charge - Manual Svc Order vs. Electronic- Add'I	Incremental Charge - Manual Svc Order vs. Electronic- Disc 1st	Incrementa Charge - Manual Svo Order vs. Electronic- Disc Add'l
						Rec		curring		g Disconnect				Rates (\$)		
						1100	First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
	POT Bay Arrangements prior to 6/1/99 - 2-Fiber Cross-Connect, per cross-connect	I			PE1B2	0.00										
	POT Bay Arrangements prior to 6/1/99 - 4-Fiber Cross-Connect, per cross-connect	I		UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ,CLO, ULDO3, ULD12, ULD48, U1TO3, U1T12, U1T48, UDLO3, UDL12, UDF	PE1B4	0.00										
	Physical Collocation - Request Resend of CFA Information, per															
	CLLI	ı		CLO	PE1C9		77.54									
	Nonrecurring Collocation Cable Records - per request			CLO	PE1CR		1,525.00	980.22	267.08							
	Nonrecurring Collocation Cable Records - VG/DS0 Cable, per cable record			CLO	PE1CD		656.50	656.50	379.78							
	Nonrecurring Collocation Cable Records - VG/DS0 Cable, per each 100 pair			CLO	PE1CO		9.66	9.66	11.84	11.84						
	Nonrecurring Collocation Cable Records - DS1, per T1TIE			CLO	PE1C0		4.52	4.52	5.54	5.54				1		
	Nonrecurring Collocation Cable Records - DS3, per T3TIE				PE1C3		15.82	15.82	19.40	19.40						
	Nonrecurring Collocation Cable Records - Fiber Cable, per 99															
	fiber records				PE1CB		169.67	169.67	154.89	154.89						
	Physical Collocation - Security Escort - Basic, Per Quarter Hour			CLO	PE1BQ		10.89									
	Physical Collocation - Security Escort - Overtime, Per Quarter Hour			CLO	PE1OQ		13.64									
	Physical Collocation - Security Escort - Premium, Per Quarter			01.0	DE 4 DO		40.40									
	Hour Physical Collocation - Security Escort - Basic, per Half Hour			CLO CLO,CLORS	PE1PQ PE1BT		16.40 33.99	21.54								
	Physical Collocation - Security Escort - Basic, per Hall Hour			CLO,CLORS	PEIBI		33.99	21.54						-		
	Physical Collocation - Security Escort - Overtime, per Half Hour			CLO,CLORS	PE1OT		44.27	27.82								
	Physical Collocation - Security Escort - Premium, per Half Hour			CLO,CLORS	PE1PT		54.55	34.10								
	V to P Conversion, Per Customer Request-Voice Grade			CLO	PE1BV		33.00									
	V to P Conversion, Per Customer Request-DS0	- 1		CLO	PE1BO		33.00									
	V to P Conversion, Per Customer Request-DS1			CLO	PE1B1		52.00									
 	V to P Conversion, Per Customer request-DS3	ı	<u> </u>	CLO	PE1B3		52.00	-	-	-						
	V to P Conversion, Per Customer Request per VG Circuit Reconfigured V to P Conversion, Per Customer Request per DS0 Circuit	ı		CLO	PE1BR		23.00									
	V to P Conversion, Per Customer Request per DSU Circuit Reconfigured V to P Conversion, Per Customer Request per DS1 Circuit	I		CLO	PE1BP		23.00									
	Reconfigured V to P Conversion, Per Customer Request per DS1 Circuit Reconfigured V to P Conversion, Per Customer Request per DS3 Circuit	ı		CLO	PE1BS		33.00									
	Reconfigured V to P Conversion, Cable Pairs Assigned to Collo Space per 700	ı		CLO	PE1BE		37.00									
	prs or fraction thereof Physical Collocation - Co-Carrier Cross Connects - Fiber Cable	ı		CLO	PE1B7		592.00									
	Support Structure, per cable, per linear ft. Physical Collocation - Co-Carrier Cross Connects - Copper/Coax			CLO,UDF	PE1ES	0.001										
	Cable Support Structure, per cable, per lin. ft. Physical Collocation - Co-Carrier Cross Connects Only -				PE1DS	0.0014										
AD IACENT SE	Application Fee, per application		<u> </u>	CLO	PE1DT		584.11		-	-	<u> </u>			<u> </u>		
ADJACENT CO	Adjacent Collocation - Space Charge per Sq. Ft.			CLOAC	PE1JA	0.1635			-	-				 		
 	Adjacent Collocation - Space Charge per Sq. Ft. Adjacent Collocation - Electrical Facility Charge per Linear Ft.		 	CLOAC	PE1JA PE1JC	5.11			 				-		-	

COLLOCAT	ION - Florida												Attach	ment: 4	Exhi	bit: B
CATEGORY	RATE ELEMENTS	Interi m	Zone	BCS	usoc			RATES (\$)			1	Svc Order Submitted Manually per LSR	Incremental Charge - Manual Svc Order vs. Electronic- 1st	Incremental Charge - Manual Svc Order vs. Electronic- Add'I		Incremental Charge - Manual Svc Order vs. Electronic- Disc Add'I
						Dee	Nonrec	urring	Nonrecurring	Disconnect			oss	Rates (\$)		•
						Rec	First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
	Adjacent Collocation - 2-Wire Cross-Connects			CLOAC	PE1P2	0.0213	24.69	23.69	11.77	10.62						
				UEA,UHL,UDL,UCL,												
	Adjacent Collocation - 4-Wire Cross-Connects			CLOAC	PE1P4	0.0426	24.88	23.83	12.04	10.80						
	Adjacent Collocation - DS1 Cross-Connects			USL,CLOAC	PE1P1 PE1P3	1.22 16.56	44.24 41.94	31.98	12.07	10.91						
-	Adjacent Collocation - DS3 Cross-Connects Adjacent Collocation - 2-Fiber Cross-Connect			CLOAC CLOAC	PE1F3 PE1F2	2.81	41.94	30.52 30.52	13.91 13.91	11.15 11.16	-					
	Adjacent Collocation - 4-Fiber Cross-Connect			CLOAC	PE1F4	5.36	51.30	39.87	18.29	15.54						
	Adjacent Collocation - Application Fee			CLOAC	PE1JB	0.00	2,785.00	00.01	10.25	10.04						
	Adjacent Collocation - 120V, Single Phase Standby Power Rate per AC Breaker Amp			CLOAC	PE1FB	5.38	,									
	Adjacent Collocation - 240V, Single Phase Standby Power Rate per AC Breaker Amp			CLOAC	PE1FD	10.77										
	Adjacent Collocation - 120V, Three Phase Standby Power Rate per AC Breaker Amp			CLOAC	PE1FE	16.15										
	Adjacent Collocation - 277V, Three Phase Standby Power Rate per AC Breaker Amp Adjacent Collocation - Cable Support Structure per Entrance			CLOAC	PE1FG	37.30										
PHYSICAL CO	Cable LLOCATION IN THE REMOTE SITE	ı		CLOAC	PE1PM	18.96										
	Physical Collocation in the Remote Site - Application Fee	1		CLORS	PE1RA	1	617.91		328.81							
	Cabinet Space in the Remote Site per Bay/ Rack			CLORS	PE1RB	219.49	2									
	Physical Collocation in the Remote Site - Security Access - Key			CLORS	PE1RD		26.30									
	Physical Collocation in the Remote Site - Space Availability Report per Premises Requested			CLORS	PE1SR		232.69									
	Physical Collocation in the Remote Site - Remote Site CLLI Code Request, per CLLI Code Requested Remote Site DLEC Data (BRSDD), per Compact Disk, per CO			CLORS CLORS	PE1RE PE1RR		75.41 233.51									
PHYSICAL CO	DLLOCATION IN THE REMOTE SITE - ADJACENT			CLORS	PEIRK		233.51									
	Remote Site-Adjacent Collocation - AC Power, per breaker amp			CLORS	PE1RS	6.27										
	Remote Site-Adjacent Collocation - Real Estate, per square foot			CLORS	PE1RT	0.134										
	Remote Site-Adjacent Collocation-Application Fee			CLORS	PE1RU		755.62	755.62								
	If Security Escort and/or Add'l Engineering Fees become nec	essary f	for rem	ote site collocation,	the Parties v	will negotiate ap	opropriate rate	s.								
VIRTUAL CO																
	Virtual Collocation - Application Fee/Planning Fee Initial Request			AMTFS	EAF		4,122.00					11.90				
	Virtual Collocation - Application Fee/Planning Fee Additional Entrance Cable Request	l		AMTFS	EAF		1,249.00					11.90				
	Virtual Collocation - Cable Installation Cost, per cable			AMTFS AMTFS	ESPCX	12.45	965.00					11.90				
	Virtual Collocation - Cable Installation Cost, per cable Virtual Collocation - Floor Space, per sq. ft.			AMTFS	ESPVX	4.25	300.00					11.50				
	Virtual Collocation - Power, per fused amp			AMTFS	ESPAX	6.95			<u> </u>							
	Virtual Collocation - Cable Support Structure, per entrance cable			AMTFS	ESPSX	13.35										
				UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ, AMTFS, UDL, UNCVX, UNCDX,	LIE A CO	0.0522		44				44.63				
	Virtual Collocation - 2-wire Cross Connects (loop)	!	 	UNCNX	UEAC2	0.0502	11.57	11.57	 			11.90				
				UEA,UHL,UCL,UDL, AMTFS, UAL, UDN,												
	Virtual Collocation - 4-wire Cross Connects (loop)			UNCVX, UNCDX AMTFS,UDL12,	UEAC4	0.0502	11.57	11.57			-	11.90				
	Vistori Cellegatine 2 Files Con Constitution			UDLO3, U1T48, U1T12, U1T03, ULDO3, ULD12,	CNICOT	0.71	0.404.00					44.00				
	Virtual Collocation - 2-Fiber Cross Connects	l	<u> </u>	ULD48, UDF	CNC2F	6.71	2,431.00					11.90				L

COLLOCA	TION - Florida												Attach	ment: 4	Exhi	bit: B
											Svc Order	Svc Order	Incremental		Incremental	Incremental
											Submitted	Submitted	Charge -	Charge -	Charge -	Charge -
		Interi									Elec	Manually		Manual Svc		Manual Svc
CATEGORY	RATE ELEMENTS		Zone	BCS	USOC			RATES (\$)			per LSR	per LSR	Order vs.	Order vs.	Order vs.	Order vs.
		m									po. 20.1	po. 2011	Electronic-	Electronic-	Electronic-	Electronic-
													1st	Add'I	Disc 1st	Disc Add'l
															DISC 1St	DISC Add I
\vdash						Rec	Nonrec		Nonrecurring		SOMEC	SOMAN		Rates (\$) SOMAN	COMAN	COMAN
				AMTFS,UDL12,			First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
				UDLO3. U1T48.										'	'	
				U1T12, U1T03,										'	'	
				ULDO3, ULD12,										'	'	
	Virtual Collocation - 4-Fiber Cross Connects			ULD48, UDF	CNC4F	6.71	2,431.00					11.90		·		
-	Virtual Collocation - 4-Fiber Cross Conflects	1	1	USL,ULC,AMTFS,	CNC4F	0.71	2,431.00				1	11.90		<u> </u>		
				ULR, UXTD1,										·		
				UNC1X, ULDD1,										'	'	
	Virtual collocation - Special Access & UNE, cross-connect per			U1TD1, USLEL,										'	'	
	DS1			UNLD1	CNC1X	7.50	155.00	14.00				11.90		'	'	
	D31			USL,ULC,AMTFS,U	CINCIA	7.50	155.00	14.00				11.90				
1 1				E3, U1TD3, UXTS1,									1	1 '	1 '	1
				UXTD3, UNC3X,									Ì	1 '	1 '	Ì
				UNCSX, ULDD3,										1 '	1 '	
	Virtual collocation - Special Access & UNE, cross-connect per			U1TS1, ULDS1,										'	'	
	DS3			UDLSX, UNLD3	CND3X	56.25	151.90	11.83				11.90		·		
 	Virtual Collocation - Co-Carrier Cross Connects - Fiber Cable	1		ODLOA, ONLDO	SINDOA	30.23	151.50	11.03	 			11.50	 	 	$\vdash \vdash \vdash$	
	Support Structure, per linear foot			AMTFS,CLO	VE1CB	0.0028								l '		
	Virtual Collocation - Co-Carrier Cross Connects - Copper/Coax			741111 0,020	12.02	0.0020										
	Cable Support Structure, per linear ft			AMTFS, CLO	VE1CD	0.0041								·		
	Virtual Collocation - Co-Carrier Cross Connects - Fiber Cable			744111 0, 020	12.02	0.0011										
	Support Structure,per cable			AMTFS	VE1CC		535.54					11.90		·		
	Virtual Collocation - Co-Carrier Cross Connects - Copper/Coax			744111	12.00		000.01					11.00				
	Cable Support Structure, per cable			AMTFS	VE1CE		535.54					11.90		·		
	Virtual Collocation Cable Records - per request			AMTFS	VE1BA		1,525.00	1,525.00	267.08	267.08						
	Virtual Collocation Cable Records - VG/DS0 Cable, per cable						.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,								
	record			AMTFS	VE1BB		656.50	656.50	379.78	379.78				'	'	
	Virtual Collocation Cable Records - VG/DS0 Cable, per each															
	100 pair			AMTFS	VE1BC		9.66	9.66	11.84	11.84				·		
	Virtual Collocation Cable Records - DS1, per T1TIE			AMTFS	VE1BD		4.52	4.52	5.54	5.54						
	Virtual Collocation Cable Records - DS3, per T3TIE			AMTFS	VE1BE		15.82	15.82	19.40	19.40						
	Virtual Collocation Cable Records - Fiber Cable, per 99 fiber													,		
	records			AMTFS	VE1BF		169.67	169.67	154.89	154.89				·		
	Virtual collocation - Security Escort - Basic, per quarter hour			AMTFS	SPTBQ		10.89					11.90		,		
	Virtual collocation - Security Escort - Overtime, per quarter hour			AMTFS	SPTOQ		13.64					11.90		<u> </u>		
1 1 =			1 7										1	1	1 7	1
	Virtual collocation - Security Escort - Premium, per quarter hour			AMTFS	SPTPQ		16.40					11.90	ļ	L	<u> </u>	ļ
	Virtual Collocation - 2-wire Cross Connects (loop), per ckts			AMTFS	VE1R2	0.05	11.57					11.90		 '	 '	
	Virtual Collocation - 4-wire Cross Connects (loop), per ckts		ļ	AMTFS	VE1R4	0.05	11.57					11.90	ļ	 '	 '	ļ
\vdash	Virtual Collocation - DS-1/DCS Cross Connects, PER CKTS	1	1	AMTFS	VE11S	8.09	69.64					11.90		 '	 '	
\vdash	Virtual Collocation - DS-1.DSX Cross Connects, PER CKTS	1	1	AMTES	VE11X	0.41	69.64					11.90		 '	 '	
	Virtual Collocation - DS-3/DCS Cross Connects, PER CKT		ļ	AMTFS	VE13S	59.67	528.00					11.90	ļ	 '	 '	ļ
\vdash	Virtual Collocation - DS-3/DSC Cross Connects, PER CKT	1	1	AMTFS	VE13X	10.06	528.00					11.90		 '	 '	
1 1	Vertical colleges and Matter and Co. 5			ANTEC	ODTO								1	1 '	1 '	1
\vdash	Virtual collocation - Maintenance in CO - Basic, per quarter hour	-	 	AMTFS	SPTRE		10.89		-			11.90		 '	├ ──	
	Virtual collocation - Maintenance in CO - Overtime, per quarter			AMTEC	CDTCE		40.01					44.00		1 '	1 '	
\vdash	hour	-	 	AMTFS	SPTOE		13.64		-			11.90		 '	├ ───'	
1 1	Virtual collocation - Maintenance in CO - Premium per quarter			AMTEC	CDTDE		40.40					44.00	1	1 '	1 '	1
WIDTH'S CO	hour	1	1	AMTFS	SPTPE		16.40		1			11.90	 	 '	├ ───	
VIRTUAL CO		1	1		1				1		-	-	1	 '	├ ──	1
	Virtual Collocation - 2-wire Cross Connect, Exchange Port 2-			LIEDOD	VE4D0	0.0500		44.5-				44.00		1 '	1 '	
\vdash	Wire Analog - Res	1	1	UEPSR	VE1R2	0.0502	11.57	11.57				11.90	 		 '	
1 1	Virtual Collocation 2-Wire Cross Connect, Exchange Port 2-			LIEDOD	VE4D0	0.0500						44.00	1	1 '	1 '	1
	Wire Line Side PBX Trunk - Bus	1	1	UEPSP	VE1R2	0.0502	11.57	11.57				11.90	-	 '	├ ───	-
1 1	Virtual Collocation 2-Wire Cross Connect, Exchange Port 2-Wire			UEPSE	VE1R2	0.0502	11.57	11.57				11.90	1	1 '	1 '	1
1					LVE IK/		11.5/	11.5/			1	11.90	I		1 '	I
	Voice Grade PBX Trunk - Res Virtual Collocation 2-Wire Cross Connect, Exchange Port 2-Wire	1		OLI OL	, , , , , , , , , , , , , , , , , , ,	0.0302		11.01								

COLL	OCATIO	ON - Florida												Attach	nent: 4	Exhi	bit: B
												Svc Order	Svc Order	Incremental	Incremental	Incremental	Incremental
												Submitted	Submitted		Charge -	Charge -	Charge -
			Interi	_								Elec	Manually	Manual Svc	Manual Svc	Manual Svc	Manual Svc
CATE	ORY	RATE ELEMENTS	m	Zone	BCS	USOC			RATES (\$)			per LSR	per LSR	Order vs.	Order vs.	Order vs.	Order vs.
														Electronic-	Electronic-	Electronic-	Electronic-
									1st	Add'l	Disc 1st	Disc Add'l					
						Nonrec	urring	Nonrecurring	Disconnect		Į	oss	Rates (\$)	I			
							Rec	First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
		Virtual Collocation 2-Wire Cross Connect, Exchnage Port 2-Wire															
		ISDN			UEPSX	VE1R2	0.0502	11.57	11.57				11.90				
		Virtual Collocation 2-Wire Cross Connect, Exchange Port 2-Wire															
		ISDN			UEPTX	VE1R2	0.0502	11.57	11.57				11.90				
		Virtual Collocation 4-Wire Cross Connect, Exchange Port 4-Wire			UEPEX	VE1R4	0.0502										
		ISDN DS1	11.57	11.57				11.90									
	Note: R	Rates displaying an "R" in Interim column are interim and sub	ject to I	rate tru	e-up as set forth in (General Term	ns and Condition	ons.									

CATEGORY RATE ELEMENTS Interim m Zone BCS USOC RATES (\$) RATES (\$) Submitted Elec Manually per LSR Per	4 Fxhih	Exhibit: B
CATEGORY RATE ELEMENTS Interior 20ne BCS USOC RATES (8) PER Manually Manual Stor Rates (7) PER	mental Incremental I	
CATEGORY RATE ELEMENTS Interior Inte	arge - Charge -	Charge - Charge
CATEGORY RATE ELEMENTS m Zone SCS USOC RATES (\$) per LSR per LSR Code vs. Code vs. Exterior Code vs. Cod		
Bestronic Best		
Nonrecurring Nonrecurring Nonrecurring Nonrecurring Disconnect OSS Fattes OSS Fatt		
Rec Nonecurring Nonecurr		
PHYSICAL COLLOCATION		
Physical Collocation		
Priscal Collocation A-Vive Cross Connect, Exchange Port 2- UEPSR PE1R2	MAN SOMAN	SOMAN SOMAN
Priscal Collocation A-Vive Cross Connect, Exchange Port 2- UEPSR PE1R2	-+	
Wilso Analog - Res		
Physical Collocation - Ayrive Cross Connect. Exchange Perd 2- Wile Page PE182 0.30 12.60 12.60 18.94 8 18.94 8 18.94 8 18.94 8 18.94 8 18.94 8 18.94 8 18.94 8 18.94 18.	8.42	
Wine tune State PBX Trunk - Bus UBFSP PB1812 0.30 12.60 12.60 18.94 6	0.12	
Physical Collocation - Wire Cross Connect, Exchange Port 2-	8.42	
Physical Collocation 2-Wire Cross Connect, Exchange Port 2-Wire Cross Connect, Exchange Port 2-Wire Cross Connect, Exchange Port 2-Wire SISN UEPSX PE1R2 0.30 12.60 12.60 18.94 8 18.94 8 18.94 8 18.94 8 18.94		
Wire Analog - Buts	8.42	
Physical Collocation 2-Wire Cross Connect, Exchange Port 2- UEPSX PE1R2 0.30 12.60 12.60 18.94 8 18.94 8 18.94 8 18.94 8 18.94		
Wire ISDN	8.42	
Physical Collocation 2-Wire Cross Connect, Exchange Port 2- UEPTX	[
Wire ISDN	8.42	
Physical Collocation 4-Wire Cross Connect, Exchange Port 4-	9.42	
Wife ISBN DS1	8.42	
PHYSICAL COLLOCATION	8.42	
Physical Collocation - Application Fee - Subsequent	0.42	$\overline{}$
Physical Collocation - Application Fee - Subsequent		
Physical Collocation - Application Fee CLO PE1BL 740.83		
Physical Collocation - Firm Order CLO PE1SJ 1,187.00 Processing Physical Collocation - Firm Order CLO PE1SJ 1,187.00 Processing Physical Collocation - Space Preparation - C.O. Modification per CLO PE1SK 2.02 Physical Collocation - Space Preparation - Common Systems CLO PE1SL 2.80 Physical Collocation - Space Preparation - Common Systems CLO PE1SL 2.80 Physical Collocation - Space Preparation - Common Systems CLO PE1SM 96.23 Physical Collocation - Floor Space Proparation - Common Systems CLO PE1SM 96.23 Physical Collocation - Floor Space Per Sq. Ft. CLO PE1BD 2,750.00 PE1BJ 7.50 PE1BJ		
Physical Collocation - Space Preparation - C.O. Modification per square ft. CLO PETSK 2.02		
Square ft. CLO PE1SK 2.02		
Physical Collocation - Space Preparation - Common Systems Modification per Square ft Cageless I CLO PE1SL 2.80		
Modification per square ft Cageless		
Physical Collocation - Space Preparation - Common Systems CLO PE1SM 95.23		
Modification per Cage	\longrightarrow	
Physical Collocation - Cable Installation		
Physical Collocation - Floor Space per Sq. Ft. CLO PE1PJ 7.50	\rightarrow	
Physical Collocation - Floor Space - Zone B per Sq. Ft. CLO PE1PK 6.75		
Physical Collocation - Cable Support Structure, Per Entrance Cable		
Cable		
Physical Collocation - Power Reduction, Application Fee		
Physical Collocation - 120V, Single Phase Standby Power Rate I CLO PE1FB 5.52 Physical Collocation - 240V, Single Phase Standby Power Rate I CLO PE1FD 11.05 Physical Collocation - 120V, Three Phase Standby Power Rate I CLO PE1FE 16.58 Physical Collocation - 277V, Three Phase Standby Power Rate I CLO PE1FG 38.27 UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ, UDL, UNCVX, UNLDX, UNCXX PE1P2 0.30 12.60 12.60 Physical Collocation - 2-Wire Cross-Connects CLO, UAL, UDL, UDN, UEA, UHL, UCL, UEA, UHL, UCL, UEA, UDN, UEA, UHL, UCL, UEA, UDN, UEA, UHL, UCL, UEA, UDN, UEA, UHL, UCL, UEA, ULL, UCL, ULL, ULL, ULL, ULL, ULL, ULL		
Physical Collocation - 240V, Single Phase Standby Power Rate I CLO PE1FD 11.05 Physical Collocation - 120V, Three Phase Standby Power Rate I CLO PE1FE 16.58 Physical Collocation - 277V, Three Phase Standby Power Rate I CLO PE1FG 38.27 UEANL, UEA, UDN, UDC, UAL, UHL, UCL, UEQ, UDL, UNCVX, UNLDX, UNCX, UNLDX, UNCX, UNLDX, UNCX, UDN, UEA, UHL, UDN,		
Physical Collocation - 240V, Single Phase Standby Power Rate I CLO PE1FD 11.05 Physical Collocation - 120V, Three Phase Standby Power Rate I CLO PE1FE 16.58 Physical Collocation - 277V, Three Phase Standby Power Rate I CLO PE1FG 38.27 UEANL, UEA, UDN, UDC, UAL, UHL, UCL, UEQ, UDL, UNCVX, UNLDX, UNCX, UNLDX, UNCX, UNLDX, UNCX, UDN, UEA, UHL, UDN,		
Physical Collocation - 120V, Three Phase Standby Power Rate I CLO PE1FE 16.58 Physical Collocation - 277V, Three Phase Standby Power Rate I CLO PE1FG 38.27 UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ, UDL, UNCVX, UNLDX, UNCXX PE1P2 0.30 12.60 12.60 CLO, UAL, UDL, UDN, UEA, UHL, UCL, U EQ, UDL, UNLDX,		
Physical Collocation - 120V, Three Phase Standby Power Rate I CLO PE1FE 16.58 Physical Collocation - 277V, Three Phase Standby Power Rate I CLO PE1FG 38.27 UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ, UDL, UNCVX, UNLDX, UNCXX PE1P2 0.30 12.60 12.60 CLO, UAL, UDL, UDN, UEA, UHL, UCL, U EQ, UDL, UNLDX,		
Physical Collocation - 277V, Three Phase Standby Power Rate I		
Physical Collocation - 277V, Three Phase Standby Power Rate I		
UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ, UDL, UNCVX, UNLDX, UNCNX PE1P2 0.30 12.60 12.60 UD, UL, UD, UDN, UEA, UHL, UDN, UEA	- + +	
UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ, UDL, UNCVX, UNLDX, UNCNX PE1P2 0.30 12.60 12.60 UD, UL, UD, UDN, UEA, UHL, UDN, UEA		
DC,UAL,UHL,UCL,U EQ, UDL, UNCVX, UNLDX, UNCNX PE1P2 0.30 12.60 12.60	- 	
DC,UAL,UHL,UCL,U EQ, UDL, UNCVX, PE1P2 0.30 12.60 12.60		
Physical Collocation - 2-Wire Cross-Connects		
CLO, UAL, UDL, UDN, UEA, UHL,		
UDN, UEA, UHL,	\longrightarrow	
I I I I I I I I I I I I I I I I I I I		
Physical Collocation - 4-Wire Cross-Connects UCL PE1P4 0.50 12.60 12.60		
Prysical Collocation - 4-write Cross-Connects OCL PE IP4 0.50 12.60 12.60 12.60	- - 	
DS1L,WDS1S, USL,		
UTDI, UXTD1.		
UNC1X, ULDD1,		
USLEL, UNLD1,		
Physical Collocation - DS1 Cross-Connects UDL PE1P1 8.00 155.00 27.00		

COLL	OCAT	ION - Georgia												Attach	ment: 4	Exhi	nit: D
COLL	LOCAT	T Georgia	l	l I								Svc Order	Svc Order	Incremental	Incremental		Incremental
												Submitted	Submitted	Charge -	Charge -	Charge -	Charge -
			l									Elec	Manually	Manual Svc	Manual Svc		Manual Svc
CATE	GORY	RATE ELEMENTS	Interi	Zone	BCS	USOC			RATES (\$)			per LSR	per LSR	Order vs.	Order vs.	Order vs.	Order vs.
			m						.,			per Lor	per Lor	Electronic-	Electronic-	Electronic-	Electronic-
														1st	Add'l	Disc 1st	Disc Add'l
																Disc 1st	Disc Add I
							Rec	Nonrec			g Disconnect				Rates (\$)		
							1100	First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
					CLO, UE3,U1TD3,												
					UXTD3, UXTS1,												
					UNC3X, UNCSX,												
					ULDD3,												
					U1TS1,ULDS1,	DE 1 DO	=====										
		Physical Collocation - DS3 Cross-Connects			UNLD3, UDL CLO, ULDO3,	PE1P3	72.00	155.00	27.00			ļ					
					ULD12, ULD48,												
					U1TO3, U1T12,												
					U1T48, UDLO3,												
		Physical Collocation - 2-Fiber Cross-Connect			UDL12. UDF	PE1F2	2.86	52.14	38.72								
-	+	1 Tydical Collocation - 2-1 iber C/055*COllifett	-	<u> </u>	CLO, ULDO3,	1 6 11 6	2.00	JZ. 14	30.12		1	 			 		
			ĺ		ULD12, ULD48,												
			l	1	U1TO3, U1T12,										1		
					U1T48, UDLO3,												
		Physical Collocation - 4-Fiber Cross-Connect			UDL12, UDF	PE1F4	5.08	64.74	51.31								
		Physical Collocation - Welded Wire Cage - First 100 Sq. Ft.			CLO	PE1BW	161.27	•									
		Physical Collocation - Welded Wire Cage - Add'l 50 Sq. Ft.			CLO	PE1CW	15.82										
		Physical Collocation - Security System Per Central Office Per															
		Assignable Sq. Ft.			CLO	PE1AY	0.0172										
		Physical Collocation - Security Access System - New Access															
		Card Activation, per Card			CLO	PE1A1	0.0607	46.20	46.20								
		Physical Collocation - Security Access System - New Access															
		Card Deactivation, per Card			CLO	PE1A4		8.72	8.72								
		Physical Collocation-Security Access System-Administrative															
		Change, existing Access Card, per Request, per State, per Card			CLO	PE1AA		15.40	15.40								
		Physical Collocation - Security Access System- Replace Lost or			01.0	DEAAD		45.00	45.00								
-	1	Stolen Card, per Card			CLO	PE1AR PE1AK		45.02	45.02 26.16								
		Physical Collocation - Security Access - Initial Key, per Key Physical Collocation - Security Access - Key, Replace Lost or			CLO	PETAK		26.16	20.16								
		Stolen Key, per Key			CLO	PE1AL		26.16	26.16								
	+	Physical Collocation - Space Availability Report per premises	Т		CLO	PE1SR		2,148.00	2.148.00								
	+	Friysical Collocation - Space Availability Report per premises	<u> </u>		UEANL,UEA,UDN,U	FLIOR		2,140.00	2,140.00			1					
					DC,UAL,UHL,UCL,U												
					EQ,CLO,UDL,												
		POT Bay Arrangements prior to 6/1/99 - 2-Wire Cross-Connect,			UNCVX, UNCDX,												
		per cross-connect	ĺ		UNCNX	PE1PE	0.40										
				1	UEANL,UEA,UDN,U												
					DC,UAL,UHL,UCL,U												
		POT Bay Arrangements prior to 6/1/99 - 4-Wire Cross-Connect,			EQ,CLO, USL,												
		per cross-connect			UNCVX, UNCDX	PE1PF	1.20										
					UEANL,UEA,UDN,U												
					DC,UAL,UHL,UCL,U												
					EQ,CLO,WDS1L,W												
					DS1S, USL, U1TD1,												
					UXTD1, UNC1X,												
		POT Bay Arrangements prior to 6/1/99 - DS1 Cross-Connect,			ULDD1, USLEL,	DE4D0	4.00										
-		per cross-connect	l	 	UNLD1	PE1PG	1.20				<u> </u>				-		
			l	1	UEANL,UEA,UDN,U										1		
			l	1	DC,UAL,UHL,UCL,U EQ,CLO,UE3,										1		
			l	1	U1TD3, UXTD3,										1		
			l		UXTS1, UNC3X,												
			l	1	UNCSX, ULDD3,										1		
			l		U1TS1, ULDS1,												
		POT Bay Arrangements prior to 6/1/99 - DS3 Cross-Connect,	ĺ		UNLD3, UDL,												
		per cross-connect	l	1	UDLSX	PE1PH	8.00								1		
		History and the second	·		1		2:00			·	·		L	·	L	L	

COLLOC	CATION - Georgia												Attach	ment: 4	Exhi	ibit: B
CATEGOR		Interi m	Zone	BCS	USOC			RATES (\$)				Svc Order Submitted Manually per LSR	Incremental Charge - Manual Svc Order vs. Electronic- 1st	Incremental Charge - Manual Svc Order vs. Electronic- Add'I		Incremental Charge -
						Rec	Nonred			Disconnect				Rates (\$)		
				UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ,CLO, ULDO3, ULD12, ULD48, U1TO3, U1T12,			First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
	POT Bay Arrangements prior to 6/1/99 - 2-Fiber Cross-Connect, per cross-connect			U1T48, UDLO3, UDL12, UDF	PE1B2	38.79										
	POT Bay Arrangements prior to 6/1/99 - 4-Fiber Cross-Connect, per cross-connect			UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ,CLO, ULDO3, ULD12, ULD48, U1TO3, U1T12, U1T48, UDLO3, UDL12, UDF	PE1B4	52.31										
	Physical Collocation - Request Resend of CFA Information, per															
	CLLI Nonrecurring Collocation Cable Records - per request			CLO CLO	PE1C9 PE1CR		77.42 1,706.00									
	Nonrecurring Collocation Cable Records - VG/DS0 Cable, per			CLO	PEICK		1,706.00									
	cable record Nonrecurring Collocation Cable Records - VG/DS0 Cable, per			CLO	PE1CD		922.38									
	each 100 pair			CLO	PE1CO		18.00	18.00								
	Nonrecurring Collocation Cable Records - DS1, per T1TIE			CLO	PE1C1		8.43	8.43								
	Nonrecurring Collocation Cable Records - DS3, per T3TIE			CLO	PE1C3		29.49	29.49								
	Nonrecurring Collocation Cable Records - Fiber Cable, per 99 fiber records			CLO	PE1CB		278.61	278.61								
	Physical Collocation - Security Escort - Basic, per Half Hour			CLO,CLORS	PE1BT		41.00	25.00								
	Physical Collocation - Security Escort - Overtime, per Half Hour			CLO,CLORS	PE1OT		48.00	30.00								
	Physical Collocation - Security Escort - Premium, per Half Hour			CLO,CLORS	PE1PT		55.00	35.00								
	V to P Conversion, Per Customer Request-Voice Grade			CLO	PE1BV		33.00									
	V to P Conversion, Per Customer Request-DS0			CLO	PE1BO		33.00									
	V to P Conversion, Per Customer Request-DS1			CLO	PE1B1		52.00									
	V to P Conversion, Per Customer request-DS3 V to P Conversion, Per Customer Request per VG Circuit			CLO	PE1B3		52.00									
	Reconfigured			CLO	PE1BR		23.00									
	V to P Conversion, Per Customer Request per DS0 Circuit Reconfigured			CLO	PE1BP		23.00									
	V to P Conversion, Per Customer Request per DS1 Circuit Reconfigured V to P Conversion Per Customer Request per DS2 Circuit			CLO	PE1BS		33.00									
	V to P Conversion, Per Customer Request per DS3 Circuit Reconfigured			CLO	PE1BE		37.00									
	V to P Conversion, Cable Pairs Assigned to Collo Space per 700 prs or fraction thereof			CLO	PE1B7		592.00									
	Physical Collocation - Co-Carrier Cross Connects - Fiber Cable Support Structure, per cable, per linear ft.			CLO,UDF	PE1ES	0.001										
	Physical Collocation - Co-Carrier Cross Connects - Copper/Coax Cable Support Structure, per cable, per lin. ft. Physical Collocation, Co. Carrier Cross Connects Coll.			CLO, UE3, USL	PE1DS	0.0015				-						
	Physical Collocation - Co-Carrier Cross Connects Only - Application Fee, per application Physical Collocation - Application to Augment Exsisting Space -			CLO	PE1DT		583.18									
	Simple			CLO	PE1KS		594.05		1.21							
	Physical Collocation - Application to Augment Exsisting Space - Minor			CLO	PE1KM		832.95		1.21							
	Physical Collocation - Application to Augment Exsisting Space - Intermediate			CLO	PE1K1		1,057.00		1.21							
ADJACEN'	IT COLLOCATION				DE / 14											
	Adjacent Collocation - Space Charge per Sq. Ft. Adjacent Collocation - Electrical Facility Charge per Linear Ft.	 	<u> </u>	CLOAC CLOAC	PE1JA PE1JC	0.2542 5.44								1		1

COLLOCAT	ION - Georgia				,							,		ment: 4		bit: B
CATEGORY	RATE ELEMENTS	Interi m	Zone	BCS	usoc			RATES (\$)				Svc Order Submitted Manually per LSR	Incremental Charge - Manual Svc Order vs. Electronic-	Charge - Manual Svc Order vs. Electronic-	Charge - Manual Svc Order vs. Electronic-	Charge - Manual Svo Order vs. Electronic-
													1st	Add'l	Disc 1st	Disc Add'l
						Rec	Nonrec		Nonrecurring					Rates (\$)		
				01010	55.150		First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
	Adjacent Collocation - 2-Wire Cross-Connects			CLOAC	PE1P2	0.598	24.95	23.97	11.80	10.67						
	Adjacent Collocation - 4-Wire Cross-Connects			UEA,UHL,UDL,UCL, CLOAC	PE1P4	0.1196	25.14	24.11	12.15	10.93						
	Adjacent Collocation - 4-Wire Closs-Connects Adjacent Collocation - DS1 Cross-Connects			USL,CLOAC	PE1P1	1.04	44.19	32.13	11.93	10.93						
	Adjacent Collocation - DS1 Cross-Connects			CLOAC	PE1P3	14.12	41.93	30.69	13.71	11.04						
	Adjacent Collocation - 235 Closs-Connect			CLOAC	PE1F2	2.39	41.93	30.69	13.71	11.04						
	Adjacent Collocation - 4-Fiber Cross-Connect			CLOAC	PE1F4	4.57	51.14	39.90	17.96	15.29						
	Adjacent Collocation - Application Fee			CLOAC	PE1JB	4.07	1,555.00	00.00	17.50	10.20						
	Adjacent Collocation - 120V, Single Phase Standby Power Rate			0207.0	. 2.02		1,000.00									
	per AC Breaker Amp			CLOAC	PE1FB	5.39										
	Adjacent Collocation - 240V, Single Phase Standby Power Rate per AC Breaker Amp			CLOAC	PE1FD	10.79										
	Adjacent Collocation - 120V, Three Phase Standby Power Rate	-	 	OLUAU	FEIFU	10.79			 			 	-		 	
	per AC Breaker Amp			CLOAC	PE1FE	16.18										
	Adjacent Collocation - 277V, Three Phase Standby Power Rate per AC Breaker Amp			CLOAC	PE1FG	38.27]		1
	Adjacent Collocation - 240V, Three Phase Standby Power Rate per AC Breaker Amp			CLOAC	PE1JD	37.37										
PHYSICAL CO	PLLOCATION IN THE REMOTE SITE		1	OLOAG	I LIJD	37.37			+							
	Physical Collocation in the Remote Site - Application Fee			CLORS	PE1RA		608.18	608.17	323.63	323.63						
	Cabinet Space in the Remote Site per Bay/ Rack			CLORS	PE1RB	224.82	000.10	000.17	020.00	020.00						
	Physical Collocation in the Remote Site - Security Access - Key			CLORS	PE1RD	22 1102	25.88	25.88								
	Physical Collocation in the Remote Site - Space Availability															
	Report per Premises Requested Physical Collocation in the Remote Site - Remote Site CLLI			CLORS	PE1SR		229.02	229.02								
	Code Request, per CLLI Code Requested			CLORS	PE1RE		74.22	74.22								
	Remote Site DLEC Data (BRSDD), per Compact Disk, per CO			CLORS	PE1RR		232.88									
PHYSICAL CO	LLOCATION IN THE REMOTE SITE - ADJACENT															
	Remote Site-Adjacent Collocation - AC Power, per breaker amp			CLORS	PE1RS	6.27										
	Remote Site-Adjacent Collocation - Real Estate, per square foot			CLORS	PE1RT	0.134										
	Remote Site-Adjacent Collocation-Application Fee			CLORS	PE1RU		755.62	755.62								
NOTE	If Security Escort and/or Add'l Engineering Fees become nec	essary	or rem		the Parties v	vill negotiate a										
VIRTUAL COL	LOCATION			,												
	Virtual Collocation - Application Fee			AMTFS	EAF		2,848.30	2,848.30					19.99	19.99		
	Virtual Collocation - Cable Installation Cost, per cable			AMTFS	ESPCX		2,750.00	2,750.00					19.99	19.99		
	Virtual Collocation - Floor Space, per sq. ft.			AMTFS	ESPVX	3.20										
	Virtual Collocation - Power, per fused amp			AMTFS	ESPAX	3.48								1	1	1
	Virtual Collocation - Cable Support Structure, per entrance cable			AMTFS	ESPSX	13.35										
				UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ, AMTFS, UDL, UNCVX, UNCDX,												
i l	Virtual Collocation - 2-wire Cross Connects (loop)		1	UNCNX	UEAC2	0.0283	24.56	23.56	9.20	8.30			19.99	19.99	19.99	19.99
				UEA,UHL,UCL,UDL, AMTFS, UAL, UDN,	UE 404	0.0522	24 ==	00.70	0.53	0.10			40.53	40.00	40.55	40.55
	Virtual Collocation - 4-wire Cross Connects (loop)			UNCVX, UNCDX	UEAC4	0.0566	24.75	23.70	9.03	8.10			19.99	19.99	19.99	19.99
				AMTFS,UDL12, UDLO3, U1T48, U1T12, U1T03, ULDO3, ULD12,	011005											
1	Virtual Collocation - 2-Fiber Cross Connects			ULD48, UDF	CNC2F	2.88	41.72	30.36	10.43	8.36		l	2.20	2.20	L	L

COLLOCAT	ION - Georgia													ment: 4	Exhi	ibit: B
CATEGORY	RATE ELEMENTS	Interi m	Zone	BCS	USOC			RATES (\$)			Svc Order Submitted Elec per LSR	Svc Order Submitted Manually per LSR	Charge - Manual Svc Order vs. Electronic- 1st	Charge - Manual Svc Order vs. Electronic- Add'l	Incremental Charge - Manual Svc Order vs. Electronic- Disc 1st	Incrementa Charge - Manual Svo Order vs. Electronic- Disc Add'I
						Rec	Nonrec		Nonrecurring					Rates (\$)		
				AMTFS,UDL12,			First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
	Virtual Collocation - 4-Fiber Cross Connects			UDLO3, U1T48, U1T12, U1T03, ULDO3, ULD12, ULD48, UDF	CNC4F	5.76	51.03	39.67	13.71	11.65			2.20	2.20		
	Virtual collocation - Special Access & UNE, cross-connect per DS1			USL,ULC,AMTFS, ULR, UXTD1, UNC1X, ULDD1, U1TD1, USLEL, UNLD1	CNC1X	7.50	155.00	14.00					19.99	19.99		
	Virtual collocation - Special Access & UNE, cross-connect per DS3			USL,ULC,AMTFS,U E3, U1TD3, UXTS1, UXTD3, UNC3X, UNCSX, ULDD3, U1TS1, ULDS1, UDLSX, UNLD3	CND3X	56.25	151.90	11.83					19.99	19.99		
	Virtual Collocation - Co-Carrier Cross Connects - Fiber Cable Support Structure, per linear foot			AMTFS	VE1CB	0.0023										
	Virtual Collocation - Co-Carrier Cross Connects - Copper/Coax Cable Support Structure, per linear ft			AMTFS	VE1CD	0.0034										
	Virtual Collocation - Co-Carrier Cross Connects - Fiber Cable Support Structure,per cable			AMTFS	VE1CC		553.43						19.99			
	Virtual Collocation - Co-Carrier Cross Connects - Copper/Coax Cable Support Structure, per cable			AMTFS	VE1CE		553.43						19.99			
	Virtual Collocation Cable Records - per request Virtual Collocation Cable Records - VG/DS0 Cable, per cable record			AMTFS AMTFS	VE1BA VE1BB		1,706.00 922.38	1,706.00 922.38								
	Virtual Collocation Cable Records - VG/DS0 Cable, per each 100 pair			AMTFS	VE1BC		18.00	18.00								
	Virtual Collocation Cable Records - DS1, per T1TIE			AMTFS	VE1BD		8.43	8.43								
	Virtual Collocation Cable Records - DS3, per T3TIE			AMTFS	VE1BE		29.49	29.49								†
	Virtual Collocation Cable Records - Fiber Cable, per 99 fiber			,	*2.02		20.10	20.10								
	records			AMTFS	VE1BF		278.61	278.61								
	Virtual collocation - Security Escort - Basic, per half hour			AMTFS	SPTBX		41.00	25.00					19.99	19.99		
	Virtual collocation - Security Escort - Overtime, per half hour			AMTFS	SPTOX		48.00	30.00					19.99	19.99		
	Virtual collocation - Security Escort - Premium, per half hour			AMTFS	SPTPX		55.00	35.00					19.99	19.99		
	Virtual collocation - Maintenance in CO - Basic, per half hour			AMTFS	CTRLX		30.64	30.64					19.99	19.99		
	Virtual collocation - Maintenance in CO - Overtime, per half hour			AMTFS	SPTOM		35.77	35.77					19.99	19.99		
	Virtual collocation - Maintenance in CO - Premium per half hour			AMTFS	SPTPM		40.90	40.90					19.99	19.99		
VIRTUAL COL																
	Virtual Collocation - 2-wire Cross Connect, Exchange Port 2- Wire Analog - Res			UEPSR	VE1R2	0.30	12.60	12.60					18.94	8.42		
	Virtual Collocation 2-Wire Cross Connect, Exchange Port 2- Wire Line Side PBX Trunk - Bus			UEPSP	VE1R2	0.30	12.60	12.60					18.94	8.42		
	Virtual Collocation 2-Wire Cross Connect, Exchange Port 2-Wire Voice Grade PBX Trunk - Res			UEPSE	VE1R2	0.30	12.60	12.60					18.94	8.42		
	Virtual Collocation 2-Wire Cross Connect, Exchange Port 2-Wire Analog Bus			UEPSB	VE1R2	0.30	12.60	12.60					18.94	8.42		
	Virtual Collocation 2-Wire Cross Connect, Exchnage Port 2-Wire ISDN			UEPSX	VE1R2	0.30	12.60	12.60					18.94	8.42		
	Virtual Collocation 2-Wire Cross Connect, Exchange Port 2-Wire ISDN			UEPTX	VE1R2	0.30	12.60	12.60					18.94	8.42		
	Virtual Collocation 4-Wire Cross Connect, Exchange Port 4-Wire ISDN DS1			UEPEX	VE1R4	0.50	12.60	12.60					18.94	8.42		

COLL	OCATI	ON - Kentucky												Attach	ment: 4	Evhi	bit: B
COLL	OCAII	l Rentucky	1				1					Svc Order	Svc Order	Incremental		Incremental	
												Submitted	Submitted		Charge -	Charge -	Charge -
												Elec		Manual Svc	Manual Svc		Manual Svc
CATE	ORY	RATE ELEMENTS	Interi	Zone	BCS	USOC			RATES (\$)				,				
OA.L		KATE EEEMENTO	m	20110	500	0000			TOTAL CO			per LSR	per LSR	Order vs.	Order vs.	Order vs.	Order vs.
														Electronic-	Electronic-	Electronic-	Electronic-
														1st	Add'l	Disc 1st	Disc Add'l
								Nonrec	urring	Nonrecurring	Disconnect		1	oss	Rates (\$)	l .	
							Rec	First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
									7144.	101	7.44						
PHYSI	CAL CO	LLOCATION															
	1	Physical Collocation 2-Wire Cross Connect, Exchange Port 2-															
		Wire Analog - Res			UEPSR	PE1R2	0.0333	24.68	23.68	12.14	10.95		7.86				
		Physical Collocation 2-Wire Cross Connect, Exchange Port 2-															
		Wire Line Side PBX Trunk - Bus			UEPSP	PE1R2	0.0333	24.68	23.68	12.14	10.95		7.86				
		Physical Collocation 2-Wire Cross Connect, Exchange Port 2-															
		Wire Voice Grade PBX Trunk - Res			UEPSE	PE1R2	0.0333	24.68	23.68	12.14	10.95		7.86				
		Physical Collocation 2-Wire Cross Connect, Exchange Port 2-															
		Wire Analog - Bus			UEPSB	PE1R2	0.0333	24.68	23.68	12.14	10.95		7.86				
		Physical Collocation 2-Wire Cross Connect, Exchange Port 2-															1
L	<u></u>	Wire ISDN	<u> </u>	<u> </u>	UEPSX	PE1R2	0.0333	24.68	23.68	12.14	10.95	<u></u>	7.86				1
		Physical Collocation 2-Wire Cross Connect, Exchange Port 2-						_									
		Wire ISDN	<u> </u>		UEPTX	PE1R2	0.0333	24.68	23.68	12.14	10.95		7.86				<u> </u>
		Physical Collocation 4-Wire Cross Connect, Exchange Port 4-	1														1
		Wire ISDN DS1			UEPEX	PE1R4	1.48	44.23	31.98	12.81	11.57		7.86				
PHYSI	CAL CO	LLOCATION															
		Physical Collocation - Application Fee - Initial			CLO	PE1BA		3,773.54	3,773.54								
		Physical Collocation - Application Fee - Subsequent			CLO	PE1CA		3,145.35	3,145.35								
		Physical Collocation Administrative Only - Application Fee			CLO	PE1BL		742.12									
		Physical Collocation - Space Preparation - Firm Order															
		Processing			CLO	PE1SJ		1,206.07	1,206.07								
		Physical Collocation - Space Preparation - C.O. Modification per			0.0	55.00											
		square ft.			CLO	PE1SK	2.32										
		Physical Collocation - Space Preparation - Common Systems			0.0	55.00											
-		Modification per square ft Cageless			CLO	PE1SL	3.26										
		Physical Collocation - Space Preparation - Common Systems			CLO	PE1SM	110.57										
-		Modification per Cage Physical Collocation - Cable Installation		<u> </u>	CLO	PE1BD	110.57	1,729.11		45.16							\vdash
		Physical Collocation - Cable Installation Physical Collocation - Floor Space per Sq. Ft.			CLO	PE1PJ	7.99	1,729.11		45.10		1					
		Physical Collocation - Floor Space per Sq. Ft. Physical Collocation - Cable Support Structure, Per Entrance			CLO	PEIPJ	7.99					1					
		Cable			CLO	PE1PM	19.86										
		Physical Collocation - Power -48V DC Power, per Fused Amp			CLO	PE1PL	8.06										
		Physical Collocation - Power Reduction, Application Fee	<u> </u>		CLO	PE1PR	0.00	399.50									
		r nyoloar concoalion i choi neadollon, i ppiloalion i co	<u> </u>		020			000.00									
		Physical Collocation - 120V, Single Phase Standby Power Rate			CLO	PE1FB	5.44										
			†				<u> </u>										
		Physical Collocation - 240V, Single Phase Standby Power Rate	1		CLO	PE1FD	10.88						1				1
	1	. 5	1				1			İ	l				İ	İ	
		Physical Collocation - 120V, Three Phase Standby Power Rate	1		CLO	PE1FE	16.32						1				1
																	1
L	<u></u>	Physical Collocation - 277V, Three Phase Standby Power Rate	<u> </u>	<u></u>	CLO	PE1FG	37.68			<u> </u>							1
1			1		UEANL,UEA,UDN,U												1 '
1			1		DC,UAL,UHL,UCL,U												1
1			1		EQ, UDL, UNCVX,								1				1
	<u> </u>	Physical Collocation - 2-Wire Cross-Connects	<u> </u>		UNLDX, UNCNX	PE1P2	0.0333	24.68	23.68	12.14	10.95						 '
1			1		CLO, UAL, UDL,								1				1
			1		UDN, UEA, UHL,												1 '
		Physical Callagray AMfra Co	1		UNCVX, UNCDX,	DE4D:							1				1
<u> </u>	_	Physical Collocation - 4-Wire Cross-Connects	!	<u> </u>	UCL	PE1P4	0.0665	24.88	23.82	12.77	11.46						├
1			1		CLO,UEANL,UEQ,W								1				1
			1		DS1L,WDS1S, USL,												1
			1	1	U1TD1, UXTD1, UNC1X, ULDD1,	l				Ì			1				1
			1	1	USLEL, UNLD1,	l				Ì			1				1
		Physical Collocation - DS1 Cross-Connects	1	1	UDL	PE1P1	1.48	44.23	31.98	12.81	11.57		1				1
L		1. 11,010th 301100th 101 01000-0011100to	1			1	1.70	77.23	31.30	12.01	11.57	ı	L		·	L	<u> </u>

COLLOCAT	ION - Kentucky												Attach	ment: 4	Fyhi	bit: B
CATEGORY	RATE ELEMENTS	Interi m	Zone	BCS	USOC			RATES (\$)			Svc Order Submitted Elec per LSR	Submitted	Incremental Charge - Manual Svc Order vs. Electronic- 1st		Incremental Charge -	Incremental Charge - Manual Svc Order vs. Electronic- Disc Add'l
						Bas	Nonrec	urring	Nonrecurring	Disconnect		1	oss	Rates (\$)		
						Rec	First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
	Physical Collocation - DS3 Cross-Connects			CLO, UE3,U1TD3, UXTD3, UXTS1, UNC3X, UNCSX, ULDD3, U1TS1,ULDS1, UNLD3, UDL CLO, ULDO3, ULD12, ULD48,	PE1P3	18.89	41.93	30.51	14.75	11.83						
				U1TO3, U1T12, U1T48, UDLO3,												
	Physical Collocation - 2-Fiber Cross-Connect			UDL12, UDF	PE1F2	3.75	41.93	30.51	14.76	11.84						
	Physical Collocation - 4-Fiber Cross-Connect			CLO, ULDO3, ULD12, ULD48, U1TO3, U1T12, U1T48, UDLO3, UDL12, UDF	PE1F4	6.65	51,29	39.87	19.41	16.49						
	Physical Collocation - Welded Wire Cage - First 100 Sq. Ft.			CLO	PE1BW	184.97	01.20	00.01		10.10				İ		
	Physical Collocation - Welded Wire Cage - Add'l 50 Sq. Ft.			CLO	PE1CW	18.14										
	Physical Collocation - Security Access System - Security System per Central Office			CLO	PE1AX	76.10										
	Physical Collocation - Security Access System - New Access Card Activation, per Card			CLO	PE1A1	0.058	55.79	55.79								
	Physical Collocation-Security Access System-Administrative Change, existing Access Card, per Request, per State, per Card			CLO	PE1AA		15.64	15.64								
	Physical Collocation - Security Access System - Replace Lost or Stolen Card, per Card			CLO	PE1AR		45.74	45.74								
	Physical Collocation - Security Access - Initial Key, per Key			CLO	PE1AK		26.29	26.29								
	Physical Collocation - Security Access - Key, Replace Lost or															
	Stolen Key, per Key			CLO	PE1AL		26.29	26.29								
	Physical Collocation - Space Availability Report per premises POT Bay Arrangements prior to 6/1/99 - 2-Wire Cross-Connect, per cross-connect			CLO UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ,CLO,UDL, UNCVX, UNCDX, UNCNX	PE1SR PE1PE	0.113	2,158.67	2,158.67								
	POT Bay Arrangements prior to 6/1/99 - 4-Wire Cross-Connect, per cross-connect			UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ,CLO, USL, UNCVX, UNCDX	PE1PF	0.23										
	POT Bay Arrangements prior to 6/1/99 - DS1 Cross-Connect, per cross-connect			UEANL, UEA, UDN, U DC, UAL, UHL, UCL, U EQ, CLO, WDS1L, W DS1S, USL, U1TD1, UXTD1, UNC1X, ULDD1, USLEL, UNLD1 UEANL, UEA, UDN, U DC, UAL, UHL, UCL, U EQ, CLO, UE3, U1TD3, UXTD3, UXTS1, UNC3X, UNCSX, ULDD3, U1TS1, ULDS1,	PE1PG	1.60										
	POT Bay Arrangements prior to 6/1/99 - DS3 Cross-Connect, per cross-connect			UNLD3, UDL, UDLSX	PE1PH	14.23										

COLLOCA	ATION - Kentucky												Attach	ment: 4	Exhi	ibit: B
CATEGORY		Interi m	Zone	BCS	USOC			RATES (\$)				Svc Order Submitted Manually per LSR	Incremental Charge - Manual Svc Order vs. Electronic- 1st	Incremental Charge - Manual Svc Order vs. Electronic- Add'I		Incremental Charge -
						Rec		curring		Disconnect				Rates (\$)		
	POT Bay Arrangements prior to 6/1/99 - 2-Fiber Cross-Connect, per cross-connect			UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ,CLO, ULDO3, ULD12, ULD48, U1T03, U1T12, U1T48, UDLO3, UDL12, UDF	PE1B2	48.57	First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
	POT Bay Arrangements prior to 6/1/99 - 4-Fiber Cross-Connect, per cross-connect			UEANL, UEA, UDN, U DC, UAL, UHL, UCL, U EQ, CLO, ULDO3, ULD12, ULD48, U1T03, U1T12, U1T48, UDLO3, UDL12, UDF	PE1B4	65.50										
	Physical Collocation - Request Resend of CFA Information, per															
	CLLI Nonrecurring Collocation Cable Records - per request		l	CLO CLO	PE1C9 PE1CR		77.55 1,524.45	980.01	267.02							
	Nonrecurring Collocation Cable Records - VG/DS0 Cable, per															
	cable record Nonrecurring Collocation Cable Records - VG/DS0 Cable, per			CLO	PE1CD		656.37	656.37	379.70							
	each 100 pair			CLO	PE1CO		9.65	9.65	11.84	11.84						
	Nonrecurring Collocation Cable Records - DS1, per T1TIE			CLO	PE1C1		4.52	4.52	5.54	5.54						
	Nonrecurring Collocation Cable Records - DS3, per T3TIE Nonrecurring Collocation Cable Records - Fiber Cable, per 99		ļ	CLO	PE1C3		15.81	15.81	19.39	19.39						
	fiber records			CLO	PE1CB		169.63	169.63	154.85	154.85						
	Physical Collocation - Security Escort - Basic, per Half Hour			CLO,CLORS	PE1BT		33.98	21.53	10 1100	10 1.00						
	Physical Collocation - Security Escort - Overtime, per Half Hour			CLO,CLORS	PE1OT		44.26	27.81								
	Physical Collocation - Security Escort - Premium, per Half Hour			CLO,CLORS	PE1PT		54.54	34.09								
	V to P Conversion, Per Customer Request-Voice Grade			CLO	PE1BV		33.00									
	V to P Conversion, Per Customer Request-DS0			CLO	PE1BO		33.00									
	V to P Conversion, Per Customer Request-DS1			CLO	PE1B1		52.00									
	V to P Conversion, Per Customer request-DS3 V to P Conversion, Per Customer Request per VG Circuit			CLO	PE1B3		52.00									
	Reconfigured			CLO	PE1BR		23.00									
	V to P Conversion, Per Customer Request per DS0 Circuit Reconfigured			CLO	PE1BP		23.00									
	V to P Conversion, Per Customer Request per DS1 Circuit Reconfigured			CLO	PE1BS		33.00									
	V to P Conversion, Per Customer Request per DS3 Circuit Reconfigured			CLO	PE1BE		37.00									
	V to P Conversion, Cable Pairs Assigned to Collo Space per 700 prs or fraction thereof			CLO	PE1B7		592.00									
	Physical Collocation - Co-Carrier Cross Connects - Fiber Cable Support Structure, per cable, per linear ft.			CLO,UDF	PE1ES	0.0012										
	Physical Collocation - Co-Carrier Cross Connects - Copper/Coax Cable Support Structure, per cable, per lin. ft.			CLO, UE3, USL	PE1DS	0.0012										
	Physical Collocation - Co-Carrier Cross Connects Only - Application Fee, per application			CLO	PE1DT	0.0010	584.20									
	Physical Collocation - Application to Augment Exsisting Space - Simple			CLO	PE1KS		594.98		1.21							
	Physical Collocation - Application to Augment Exsisting Space - Minor			CLO	PE1KM		834.26		1.21							
	Physical Collocation - Application to Augment Exsisting Space - Intermediate			CLO	PE1K1		1,059.00		1.21							
ADJACENT	COLLOCATION		1				1,000.00		21							
	Adjacent Collocation - Space Charge per Sq. Ft.			CLOAC	PE1JA	0.0173										
	Adjacent Collocation - Electrical Facility Charge per Linear Ft.			CLOAC	PE1JC	5.35			I]		

COLLOGA	TION - Kentucky												Attach	ment: 4	Exhi	hit: B
JULLUUF											Svc Order	Svc Order	Incremental		Incremental	Incremental
											Submitted	Submitted		Charge -	Charge -	Charge -
											Elec		Manual Svc	Manual Svc		Manual Svc
CATEGORY	RATE ELEMENTS	Interi	Zone	BCS	USOC			RATES (\$)			per LSR	per LSR	Order vs.	Order vs.	Order vs.	Order vs.
		m						***			per Lor	per Lor	Electronic-	Electronic-	Electronic-	Electronic-
															Disc 1st	
													1st	Add'l	DISC 1St	Disc Add'l
						_	Nonrec	urring	Nonrecurring	Disconnect			oss	Rates (\$)		
						Rec	First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
	Adjacent Collocation - 2-Wire Cross-Connects		C	CLOAC	PE1P2	0.0258	24.68	23.68	12.14	10.95						
			L	JEA,UHL,UDL,UCL,												
	Adjacent Collocation - 4-Wire Cross-Connects			CLOAC	PE1P4	0.0515	24.88	23.82	12.77	11.46						
	Adjacent Collocation - DS1 Cross-Connects		L	JSL,CLOAC	PE1P1	1.37	44.23	31.98	12.81	11.57						
	Adjacent Collocation - DS3 Cross-Connects		C	CLOAC	PE1P3	18.61	41.93	30.51	14.75	11.83						
	Adjacent Collocation - 2-Fiber Cross-Connect		C	CLOAC	PE1F2	3.15	41.93	30.51	14.76	11.84						
	Adjacent Collocation - 4-Fiber Cross-Connect		C	CLOAC	PE1F4	6.02	51.29	39.87	19.41	16.49						
	Adjacent Collocation - Application Fee		C	CLOAC	PE1JB		3,165.50									
	Adjacent Collocation - 120V, Single Phase Standby Power Rate															
	per AC Breaker Amp			CLOAC	PE1FB	5.44										
	Adjacent Collocation - 240V, Single Phase Standby Power Rate															
	per AC Breaker Amp	1		CLOAC	PE1FD	10.88										
	Adjacent Collocation - 120V, Three Phase Standby Power Rate															
	per AC Breaker Amp			CLOAC	PE1FE	16.32										
	Adjacent Collocation - 277V, Three Phase Standby Power Rate					i i										
	per AC Breaker Amp	1		CLOAC	PE1FG	37.68					1	1		I	Ì	
PHYSICAL (COLLOCATION IN THE REMOTE SITE															
	Physical Collocation in the Remote Site - Application Fee			CLORS	PE1RA		617.78		338.89							
	Cabinet Space in the Remote Site per Bay/ Rack			CLORS	PE1RB	219.67										
	Physical Collocation in the Remote Site - Security Access - Key			CLORS	PE1RD		26.29									
	Physical Collocation in the Remote Site - Space Availability															
	Report per Premises Requested			CLORS	PE1SR		232.64									
	Physical Collocation in the Remote Site - Remote Site CLLI															
	Code Request, per CLLI Code Requested			CLORS	PE1RE		75.40									
	Remote Site DLEC Data (BRSDD), per Compact Disk, per CO			CLORS	PE1RR		233.42									
PHYSICAL (COLLOCATION IN THE REMOTE SITE - ADJACENT															
	Remote Site-Adjacent Collocation - AC Power, per breaker amp			CLORS	PE1RS	6.27										
	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,															
	Remote Site-Adjacent Collocation - Real Estate, per square foot			CLORS	PE1RT	0.134										
	Remote Site-Adjacent Collocation-Application Fee			CLORS	PE1RU		755.62	755.62								
NOT	E: If Security Escort and/or Add'l Engineering Fees become nec	essarv				will negotiate a										
	DLLOCATION		1				p p	-								
	Virtual Collocation - Application Fee		A	AMTFS	EAF		2.419.86	2,419.86	1.01	1.01		7.86				
	Virtual Collocation - Cable Installation Cost, per cable			AMTFS	ESPCX		1,729.11	1,729.11	45.16	45.16		7.86				
	Virtual Collocation - Floor Space, per sq. ft.			AMTFS	ESPVX	7.99	1,1-2111	.,								
	Virtual Collocation - Power, per fused amp	†		AMTFS	ESPAX	8.06								t	1	
	Virtual Collocation - Cable Support Structure, per entrance	1	t – ť	-										t	1	
	cable	1	Δ.	AMTFS	ESPSX	17.38					1	1		I	Ì	
				JEANL,UEA,UDN,U												
		1		DC,UAL,UHL,UCL,U	1						1	1		I	Ì	
		1		EQ, AMTFS, UDL,	1							1			İ	
		1		JNCVX, UNCDX,												
	Virtual Collocation - 2-wire Cross Connects (loop)	1		JNCNX	UEAC2	0.0309	24.68	23.68	12.14	10.95	1	7.86		I	Ì	
	- Sonosaion 2 mis oreso defined (100p)	1				0.0003	24.00	20.00	12.14	10.00		7.00		†	1	
		1	I h	JEA,UHL,UCL,UDL,	1							1			İ	
		1		AMTFS, UAL, UDN,												
	Virtual Collocation - 4-wire Cross Connects (loop)	1		JNCVX, UNCDX	UEAC4	0.0619	24.88	23.82	12.77	11.46	1	7.86		I	Ì	
	The principle of the principle (1999)	1		AMTFS,UDL12,		0.00.0	2	20.02	,					†	1	
		1		JDLO3, U1T48,												
		1		J1T12, U1T03,	1						1	1		I	Ì	
		1		JLDO3, ULD12,												
	Virtual Collocation - 2-Fiber Cross Connects	1		JLD48, UDF	CNC2F	3.80	41.94	30.51	14.76	11.84	1	7.86		I	Ì	
	The state of the s	1		AMTFS,UDL12,		3.00		00.01	0			50			 	
		1		JDLO3, U1T48,	1						1	1		I	Ì	
		1		J1T12, U1T03,	1						1	1		I	Ì	
		1		JLDO3, ULD12,	1						1	1		I	Ì	
	Virtual Collocation - 4-Fiber Cross Connects	1		JLD48, UDF	CNC4F	7.59	51.29	39.87	19.41	16.49	1	7.86		I	Ì	
		1		,			020	30.31		.0.10				1	1	

COLLOCAT	ION - Kentucky			T		T					1 -			ment: 4		ibit: B
CATEGORY	RATE ELEMENTS	Interi m	Zone	BCS	USOC			RATES (\$)				Svc Order Submitted Manually per LSR	Incremental Charge - Manual Svc Order vs. Electronic- 1st	Charge - Manual Svc Order vs. Electronic- Add'l	Incremental Charge - Manual Svc Order vs. Electronic- Disc 1st	Charge -
						Rec	Nonrec		Nonrecurring					Rates (\$)		
				LIOL LILO ANTEO			First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
	Virtual collocation - Special Access & UNE, cross-connect per DS1			USL,ULC,AMTFS, ULR, UXTD1, UNC1X, ULDD1, U1TD1, USLEL, UNLD1	CNC1X	1.48	44.23	31.98	12.81	11.57						
	Virtual collocation - Special Access & UNE, cross-connect per DS3			USL,ULC,AMTFS,U E3, U1TD3, UXTS1, UXTD3, UNC3X, UNCSX, ULDD3, U1TS1, ULDS1, UDLSX, UNLD3	CND3X	18.89	41.93	30.51	14.75	11.83						
	Virtual Collocation - Co-Carrier Cross Connects - Fiber Cable															
	Support Structure, per linear foot Virtual Collocation - Co-Carrier Cross Connects - Copper/Coax			AMTEC	VE1CB	0.003										
	Cable Support Structure, per linear ft Virtual Collocation - Co-Carrier Cross Connects - Fiber Cable			AMTFS	VE1CD	0.0045										+
	Support Structure, per cable			AMTFS	VE1CC		535.55									
	Virtual Collocation - Co-Carrier Cross Connects - Copper/Coax Cable Support Structure, per cable			AMTFS	VE1CE		535.55									
	Virtual Collocation Cable Records - per request			AMTFS	VE1BA		1,524.45	980.01	267.02	267.02						
	Virtual Collocation Cable Records - VG/DS0 Cable, per cable record			AMTFS	VE1BB		656.37	656.37	379.70	379.70						
	Virtual Collocation Cable Records - VG/DS0 Cable, per each 100 pair			AMTFS	VE1BC		9.65	9.65	11.84	11.84						
	Virtual Collocation Cable Records -DS1, per T1TIE			AMTFS	VE1BD		4.52	4.52	5.54	5.54						
	Virtual Collocation Cable Records - DS3, per T3TIE			AMTFS	VE1BE		15.81	15.81	19.39	19.39						<u> </u>
	Virtual Collocation Cable Records - Fiber Cable, per 99 fiber records			AMTFS	VE1BF		169.63	169.63	154.85	154.85						
	Virtual collocation - Security Escort - Basic, per half hour			AMTFS	SPTBX		33.98	21.53								
	Virtual collocation - Security Escort - Overtime, per half hour			AMTFS	SPTOX		44.26	27.81								
	Virtual collocation - Security Escort - Premium, per half hour			AMTFS	SPTPX		54.54	34.09								
	Virtual collocation - Maintenance in CO - Basic, per half hour			AMTFS	CTRLX		56.07	21.53								
	Virtual collocation - Maintenance in CO - Overtime, per half hour			AMTFS	SPTOM		73.23	27.81								<u> </u>
	Virtual collocation - Maintenance in CO - Premium per half hour			AMTFS	SPTPM		90.39	34.09								
VIRTUAL COL																
	Virtual Collocation - 2-wire Cross Connect, Exchange Port 2- Wire Analog - Res			UEPSR	VE1R2	0.0309	24.68	23.68	12.14	10.95		7.86				
	Virtual Collocation 2-Wire Cross Connect, Exchange Port 2- Wire Line Side PBX Trunk - Bus			UEPSP	VE1R2	0.0309	24.68	23.68	12.14	10.95		7.86				
	Wire Line Side PBX Trunk - Bus Virtual Collocation 2-Wire Cross Connect, Exchange Port 2-Wire Voice Grade PBX Trunk - Res			UEPSE	VE1R2	0.0309	24.68	23.68	12.14	10.95		7.86			1	
	Virtual Collocation 2-Wire Cross Connect, Exchange Port 2-Wire Analog Bus			UEPSB	VE1R2	0.0309	24.68	23.68	12.14	10.95		7.86				
	Virtual Collocation 2-Wire Cross Connect, Exchnage Port 2-Wire ISDN			UEPSX	VE1R2	0.0309	24.68	23.68	12.14	10.95		7.86				
	Virtual Collocation 2-Wire Cross Connect, Exchange Port 2-Wire ISDN			UEPTX	VE1R2	0.0309	24.68	23.68	12.14	10.95		7.86				
	Virtual Collocation 4-Wire Cross Connect, Exchange Port 4-Wire ISDN DS1			UEPEX	VE1R2	1.48	44.23	31.98	12.14	11.57		7.86			1	
Notes	Rates displaying an "R" in Interim column are interim and sub	iect to r	ato tru					31.98	12.01	11.37	1	1.00		1	1	+

COLLOCAT	ION - Louisiana												Attach	ment: 4	Exhi	ibit: B
CATEGORY	RATE ELEMENTS	Interi m	Zone	BCS	USOC			RATES (\$)			Svc Order Submitted Elec per LSR	Svc Order Submitted Manually per LSR	Manual Svc Order vs. Electronic- 1st	Charge - Manual Svc Order vs. Electronic- Add'l	Incremental Charge - Manual Svc Order vs. Electronic- Disc 1st	Incremental Charge - Manual Svc Order vs. Electronic- Disc Add'l
						Rec	Nonrec			g Disconnect				Rates (\$)		
						1100	First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
	<u> </u>															
PHYSICAL CO																
	Physical Collocation 2-Wire Cross Connect, Exchange Port 2-			LIEDOD	DE 4 DO	0.0040	44.04	44.40				45.00				
	Wire Analog - Res			UEPSR	PE1R2	0.0318	11.94	11.46			1	15.20				
	Physical Collocation 2-Wire Cross Connect, Exchange Port 2- Wire Line Side PBX Trunk - Bus			UEPSP	PE1R2	0.0318	11.94	11.46				15.20				
	Physical Collocation 2-Wire Cross Connect, Exchange Port 2-			UEFSF	PEIKZ	0.0316	11.94	11.40			1	15.20				-
	Wire Voice Grade PBX Trunk - Res			UEPSE	PE1R2	0.0318	11.94	11.46				15.20				
	Physical Collocation 2-Wire Cross Connect, Exchange Port 2-			OLI OL	I L IIV.	0.0010	11.04	11.40				10.20				
	Wire Analog - Bus			UEPSB	PE1R2	0.0318	11.94	11.46				15.20				
	Physical Collocation 2-Wire Cross Connect, Exchange Port 2-															
	Wire ISDN			UEPSX	PE1R2	0.0318	11.94	11.46				15.20		1	I	
	Physical Collocation 2-Wire Cross Connect, Exchange Port 2-															
	Wire ISDN			UEPTX	PE1R2	0.0318	11.94	11.46				15.20				
	Physical Collocation 4-Wire Cross Connect, Exchange Port 4-							·							1	
	Wire ISDN DS1			UEPEX	PE1R4	0.0636	12.04	11.53				15.20				
PHYSICAL CO				0.0	55.15.1											
-	Physical Collocation - Application Fee - Initial			CLO	PE1BA		1,837.24									
	Physical Collocation - Application Fee - Subsequent Physical Collocation Administrative Only - Application Fee			CLO CLO	PE1CA PE1BL		1,533.41 741.97									
-	Physical Collocation - Space Preparation - Firm Order			CLO	PETBL		741.97				1				-	
	Processing			CLO	PE1SJ		583.33									
-	Physical Collocation - Space Preparation - C.O. Modification per			OLO	1 L 100		303.33									
	square ft.			CLO	PE1SK	2.31										
	Physical Collocation - Space Preparation - Common Systems										1					
	Modification per square ft Cageless			CLO	PE1SL	2.70										
	Physical Collocation - Space Preparation - Common Systems															
	Modification per Cage			CLO	PE1SM	91.60										
	Physical Collocation - Cable Installation			CLO	PE1BD		841.54	841.54								
	Physical Collocation - Floor Space per Sq. Ft.			CLO	PE1PJ	5.30										
	Physical Collocation - Cable Support Structure, Per Entrance			0.0												
	Cable			CLO	PE1PM	18.31										
-	Physical Collocation - Power -48V DC Power, per Fused Amp	- 1		CLO	PE1PL	8.32					1					
	Physical Collocation - 120V, Single Phase Standby Power Rate			CLO	PE1FB	5.45										
h + + -	Physical Collocation - 120V, Single Phase Standby Power Rate			CLO	PEIFB	5.45					1					1
	Physical Collocation - 240V, Single Phase Standby Power Rate			CLO	PE1FD	10.92										
	1 Hydrodi Collocation 240V, Gingle I Hade Standby I Gwel Rate			OLO	12112	10.02										
	Physical Collocation - 120V, Three Phase Standby Power Rate			CLO	PE1FE	16.37										
	Physical Collocation - 277V, Three Phase Standby Power Rate			CLO	PE1FG	37.80										
				UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ, UDL, UNCVX,												
	Physical Collocation - 2-Wire Cross-Connects			UNLDX, UNCNX	PE1P2	0.0318	11.94	11.46								<u> </u>
				CLO, UAL, UDL, UDN, UEA, UHL, UNCVX, UNCDX,												
	Physical Collocation - 4-Wire Cross-Connects			UCL	PE1P4	0.0636	12.04	11.53							1	1
	Physical Collegation, DC4 Copp. Compares			CLO,UEANL,UEQ,W DS1L,WDS1S, USL, U1TD1, UXTD1, UNC1X, ULDD1, USLEL, UNLD1, UDL	PE1P1	404	04.00	45.47								
	Physical Collocation - DS1 Cross-Connects		<u> </u>	UDL	ILEILI	1.04	21.39	15.47	i	1	1	i	l	i	I	ь

COLLOCAT	ION - Louisiana												Attach	ment: 4	Fyhi	bit: B
CATEGORY	RATE ELEMENTS	Interi m	Zone	BCS	USOC			RATES (\$)			Svc Order Submitted Elec per LSR	Submitted	Incremental Charge - Manual Svc Order vs. Electronic- 1st		Incremental Charge -	Incremental Charge - Manual Svc Order vs. Electronic- Disc Add'l
							Nonrec	urrina	Nonrecurrin	g Disconnect				Rates (\$)		
						Rec	First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
	Physical Collocation - DS3 Cross-Connects			CLO, UE3,U1TD3, UXTD3, UXTS1, UNC3X, UNCSX, ULDD3, U1TS1,ULDS1, UNLD3, UDL CLO, ULDO3, ULD12, ULD48,	PE1P3	13.21	20.28	14.76								
				U1TO3, U1T12, U1T48, UDLO3,												
1 1	Physical Collocation - 2-Fiber Cross-Connect			UDL12, UDF	PE1F2	2.62	20.28	14.76								
	Physical Collocation - 4-Fiber Cross-Connect			CLO, ULDO3, ULD12, ULD48, U1TO3, U1T12, U1T48, UDLO3, UDL12, UDF	PE1F4	4.65	24.81	19.29								
	Physical Collocation - 4-Fiber Cross-Connect Physical Collocation - Welded Wire Cage - First 100 Sq. Ft.			CLO	PE1BW	184.50	24.01	19.29								
 	Physical Collocation - Welded Wire Cage - Add'l 50 Sq. Ft.			CLO	PE1CW	18.10										
	Physical Collocation - Security System Per Central Office Per Assignable Sq. Ft.			CLO	PE1AY	0.0224										
	Physical Collocation - Security Access System - New Access Card Activation, per Card			CLO	PE1A1	0.0579	27.50									
	Physical Collocation-Security Access System-Administrative Change, existing Access Card, per Request, per State, per Card			CLO	PE1AA		7.74	7.74								
	Physical Collocation - Security Access System - Replace Lost or Stolen Card, per Card			CLO	PE1AR		22.64	22.64								
	Physical Collocation - Security Access - Initial Key, per Key			CLO	PE1AK		13.01	13.01								
	Physical Collocation - Security Access - Key, Replace Lost or															
	Stolen Key, per Key Physical Collocation - Space Availability Report per premises			CLO CLO	PE1AL PE1SR		13.01 1,044.07	13.01 1,044.07								
	POT Bay Arrangements prior to 6/1/99 - 2-Wire Cross-Connect, per cross-connect			UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ,CLO,UDL, UNCVX, UNCDX, UNCNX	PE1PE	0.079	1,044.07	1,044.07								
	POT Bay Arrangements prior to 6/1/99 - 4-Wire Cross-Connect, per cross-connect			UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ,CLO, USL, UNCVX, UNCDX	PE1PF	0.158										
	POT Bay Arrangements prior to 6/1/99 - DS1 Cross-Connect, per cross-connect POT Bay Arrangements prior to 6/1/99 - DS3 Cross-Connect,			UEANIL, UEA, UDN, U DC, UAL, UHL, UCL, U EQ, CLO, WDS1L, W DS1S, USL, U1TD1, UXTD1, UNC1X, ULDD1, USLEL, UNLD1 UEANIL, UEA, UDN, U DC, UAL, UHL, UCL, U EQ, CLO, UE3, U1TD3, UXTD3, UXTS1, UNC3X, UNCSX, ULDD3, U1TS1, ULDS1, UNLD3, UDL,	PE1PG	1.12										
	per cross-connect			UDLSX	PE1PH	9.95										

COLLO	CATIO	ON - Louisiana												Attach	ment: 4	Exhi	ibit: B
CATEGOR		RATE ELEMENTS	Interi m	Zone	BCS	USOC			RATES (\$)				Svc Order Submitted Manually per LSR	Incremental Charge - Manual Svc Order vs. Electronic- 1st	Incremental Charge - Manual Svc Order vs. Electronic- Add'I		Incremental Charge -
							Rec	Nonred		Nonrecurring					Rates (\$)		
					UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ,CLO, ULDO3, ULD12, ULD48, U1TO3, U1T12,			First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
		POT Bay Arrangements prior to 6/1/99 - 2-Fiber Cross-Connect, per cross-connect			U1T48, UDLO3, UDL12, UDF	PE1B2	33.96										
		POT Bay Arrangements prior to 6/1/99 - 4-Fiber Cross-Connect, per cross-connect			UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ,CLO, ULDO3, ULD12, ULD48, U1TO3, U1T12, U1T48, UDLO3, UDL12, UDF	PE1B4	45.80										
		Physical Collocation - Request Resend of CFA Information, per															
		CLLI			CLO	PE1C9	10.07	77.43									
		Recurring Collocation Cable Records - per request Recurring Collocation Cable Records - VG/DS0 Cable, per cable			CLO	PE1CU	10.97										
		record Recurring Collocation Cable Records - VG/DS0 Cable, per each			CLO	PE1CE	5.29										
		100 pair			CLO	PE1CT	0.08										
		Recurring Collocation Cable Records - DS1, per T1TIE			CLO	PE1C2	0.04										
		Recurring Collocation Cable Records - DS3, per T3TIE Recurring Collocation Cable Records - Fiber Cable, per 99 fiber			CLO	PE1C4	0.13										
-		records Physical Collocation - Security Escort - Basic, per Half Hour			CLO CLO,CLORS	PE1CG PE1BT	1.37	16.44	10.42								
		Physical Collocation - Security Escort - Overtime, per Half Hour			CLO,CLORS	PE1OT		21.41	13.45								
		Physical Collocation - Security Escort - Premium, per Half Hour			CLO,CLORS	PE1PT		26.38	16.49								
		V to P Conversion, Per Customer Request-Voice Grade			CLO	PE1BV		33.00									
		V to P Conversion, Per Customer Request-DS0			CLO	PE1BO		33.00									
-		V to P Conversion, Per Customer Request-DS1 V to P Conversion, Per Customer request-DS3			CLO CLO	PE1B1 PE1B3		52.00 52.00							-		
		V to P Conversion, Per Customer Request per VG Circuit															
		Reconfigured V to P Conversion, Per Customer Request per DS0 Circuit			CLO	PE1BR		23.00									
		Reconfigured V to P Conversion, Per Customer Request per DS1 Circuit			CLO	PE1BP		23.00							1		1
		Reconfigured V to P Conversion, Per Customer Request per DS3 Circuit			CLO	PE1BS		33.00									
		Reconfigured V to P Conversion, Cable Pairs Assigned to Collo Space per 700			CLO	PE1BE		37.00									
		prs or fraction thereof			CLO	PE1B7		592.00									
		Physical Collocation - Co-Carrier Cross Connects - Fiber Cable Support Structure, per cable, per linear ft.			CLO,UDF	PE1ES	0.001										
		Physical Collocation - Co-Carrier Cross Connects - Copper/Coax Cable Support Structure, per cable, per lin. ft.			CLO, UE3, USL	PE1DS	0.0015										
		Physical Collocation - Co-Carrier Cross Connects Only - Application Fee, per application Description - Collection - Application to Augment Evolution Space			CLO	PE1DT		583.30									
		Physical Collocation - Application to Augment Exsisting Space - Simple			CLO	PE1KS		596.35		1.22							
		Physical Collocation - Application to Augment Exsisting Space - Minor			CLO	PE1KM		836.18		1.22							
		Physical Collocation - Application to Augment Exsisting Space - Intermediate			CLO	PE1K1		1,061.00		1.22							
ADJACEN		LLOCATION															
		Adjacent Collocation - Space Charge per Sq. Ft. Adjacent Collocation - Electrical Facility Charge per Linear Ft.			CLOAC CLOAC	PE1JA PE1JC	0.0552 5.61								1		

COLI	OCATI	ION - Louisiana												Attach	ment: 4	Exhil	oit: B
JULL												Svc Order	Svc Order	Incremental		Incremental	Incremental
												Submitted	Submitted		Charge -	Charge -	Charge -
												Elec		Manual Svc	Manual Svc	Manual Svc	Manual Svc
CATE	ORY	RATE ELEMENTS	Interi	Zone	BCS	USOC			RATES (\$)			per LSR	per LSR	Order vs.	Order vs.	Order vs.	Order vs.
			m						,			per Lor	per Lor	Electronic-	Electronic-	Electronic-	Electronic-
																Disc 1st	
														1st	Add'l	DISC 1St	Disc Add'l
							_	Nonrec	urring	Nonrecurring	g Disconnect			oss	Rates (\$)	L L	
							Rec	First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
		Adjacent Collocation - 2-Wire Cross-Connects			CLOAC	PE1P2	0.0245	11.94	11.46								
					UEA,UHL,UDL,UCL,												
		Adjacent Collocation - 4-Wire Cross-Connects			CLOAC	PE1P4	0.0491	12.04	11.53								
		Adjacent Collocation - DS1 Cross-Connects			USL,CLOAC	PE1P1	0.9605	21.39	15.47								
		Adjacent Collocation - DS3 Cross-Connects			CLOAC	PE1P3	13.01	20.28	14.76								
		Adjacent Collocation - 2-Fiber Cross-Connect			CLOAC	PE1F2	2.20	20.28	14.76								
		Adjacent Collocation - 4-Fiber Cross-Connect			CLOAC	PE1F4	4.21	24.81	19.29								
		Adjacent Collocation - Application Fee			CLOAC	PE1JB		1,543.20									
		Adjacent Collocation - 120V, Single Phase Standby Power Rate						,									
		per AC Breaker Amp			CLOAC	PE1FB	5.45										
		Adjacent Collocation - 240V, Single Phase Standby Power Rate				Ì						1					
	1	per AC Breaker Amp	1		CLOAC	PE1FD	10.92				I				Ì		
	l	Adjacent Collocation - 120V, Three Phase Standby Power Rate	1			İ					İ				İ		
		per AC Breaker Amp	1		CLOAC	PE1FE	16.37				1						
		Adjacent Collocation - 277V, Three Phase Standby Power Rate	1			i -					t				1		
	1	per AC Breaker Amp	1		CLOAC	PE1FG	37.80				I				Ì		
PHYSIC	CAL CO	LLOCATION IN THE REMOTE SITE			020710		01.00										
	1	Physical Collocation in the Remote Site - Application Fee			CLORS	PE1RA		298.80	298.80								
		Cabinet Space in the Remote Site per Bay/ Rack			CLORS	PE1RB	225.39	200.00	200.00								
		Cabinet opace in the remote cite per Bay react			020110		220.00										
		Physical Collocation in the Remote Site - Security Access - Key			CLORS	PE1RD		13.01	13.01								
		Physical Collocation in the Remote Site - Space Availability			OLORO	LIND		10.01	10.01								
		Report per Premises Requested			CLORS	PE1SR		112.52	112.52								
		Physical Collocation in the Remote Site - Remote Site CLLI			OLONO	LIOI		112.02	112.02								
		Code Request, per CLLI Code Requested			CLORS	PE1RE		36.47	36.47								
		Remote Site DLEC Data (BRSDD), per Compact Disk, per CO			CLORS	PE1RR		233.21	30.47								
DHYSI	CAL CO	LLOCATION IN THE REMOTE SITE - ADJACENT			OLONO	LIKK		200.21									
111101	JAL OU	LEGORATION IN THE REMOTE SITE - ADDAGENT									1	1					
		Remote Site-Adjacent Collocation - AC Power, per breaker amp			CLORS	PE1RS	6.27										
		remote one-Adjacent conocation - Ac I ower, per breaker amp			CLOIKO	LIKO	0.21										
		Remote Site-Adjacent Collocation - Real Estate, per square foot			CLORS	PE1RT	0.134										
		Remote Site-Adjacent Collocation-Real Estate, per square root			CLORS	PE1RU	0.134	755.62	755.62								
-	NOTE:	If Security Escort and/or Add'l Engineering Fees become nec	occary (or rom			vill pogotiato a				-						
VIDTII		LOCATION	essai y	Or reine	ote site conocation,	lile Failles v	in negotiate a	opropriate rate	3.		-						
VIKTO	AL COL	Virtual Collocation - Application Fee			AMTFS	EAF		1,770,40			-		15.20				
-		Virtual Collocation - Cable Installation Cost, per cable			AMTFS	ESPCX		841.54			-		15.20				
-	1	Virtual Collocation - Cable Installation Cost, per cable Virtual Collocation - Floor Space, per sq. ft.	ł		AMTFS	ESPVX	3.20	041.04				1	15.20		-		
-	-		 	\vdash	AMTFS	ESPAX	3.20 8.32				 	1					
-	 	Virtual Collocation - Power, per fused amp Virtual Collocation - Cable Support Structure, per entrance	 		MINITO	LJFAA	0.32			-	-				-		
	1	cable	1		AMTFS	ESPSX	16.02				I				Ì		
-	 	Cable	 		UEANL,UEA,UDN,U	EOPOX	16.02			-	-				-		
			1								1						
1			1		DC,UAL,UHL,UCL,U]				I				Ì		
	1		1		EQ, AMTFS, UDL,	1]				1	I]		l		
		Maria Callanation Only Constitution (Installa	1		UNCVX, UNCDX,	115 400	0.0000	44.54	44 **		1		45.00				
<u> </u>	<u> </u>	Virtual Collocation - 2-wire Cross Connects (loop)	!	 	UNCNX	UEAC2	0.0296	11.94	11.46		.		15.20		1		
			1								1						
	1		1		UEA,UHL,UCL,UDL,	1]				1	I]		l		
1		Vistoria Callagation Assista Casas Communication	1		AMTFS, UAL, UDN,	LIEACA	0.050:	40.01	44.50		I		45.00		Ì		
<u> </u>	<u> </u>	Virtual Collocation - 4-wire Cross Connects (loop)	!	 	UNCVX, UNCDX	UEAC4	0.0591	12.04	11.53		.		15.20				
			1		AMTFS,UDL12,]				I				Ì		
1			1		UDLO3, U1T48,]				I				Ì		
			1		U1T12, U1T03,						1						
			1		ULDO3, ULD12,	l	_				1						
	ļ	Virtual Collocation - 2-Fiber Cross Connects	ļ		ULD48, UDF	CNC2F	2.65	20.29	14.76		.		15.20		ļ		
			1		AMTFS,UDL12,						1						
1			1		UDLO3, U1T48,]				I				Ì		Į.
			1		U1T12, U1T03,						1						
			1		ULDO3, ULD12,	l]				I				Ì		
		Virtual Collocation - 4-Fiber Cross Connects			ULD48, UDF	CNC4F	5.31	24.81	19.29		l .	l	15.20		<u>l</u>		

COLLOCAT	ION - Louisiana			•							1			ment: 4		bit: B
CATEGORY	RATE ELEMENTS	Interi m	Zone	BCS	USOC			RATES (\$)				Submitted	Incremental Charge - Manual Svc Order vs. Electronic-	Incremental Charge - Manual Svc Order vs. Electronic-	Charge -	Incrementa Charge - Manual Svo Order vs. Electronic-
													1st	Add'l	Disc 1st	Disc Add'l
						Rec	Nonrec			g Disconnect				Rates (\$)		
				HOLLII O ANTEO			First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
	Virtual collocation - Special Access & UNE, cross-connect per DS1			USL,ULC,AMTFS, ULR, UXTD1, UNC1X, ULDD1, U1TD1, USLEL, UNLD1	CNC1X	1.04	21.39	15.47				15.20				
	Virtual collocation - Special Access & UNE, cross-connect per			USL,ULC,AMTFS,U E3, U1TD3, UXTS1, UXTD3, UNC3X, UNCSX, ULDD3, U1TS1, ULDS1,												
	DS3			UDLSX, UNLD3	CND3X	13.21	20.28	14.76				15.20				
	Virtual Collocation - Co-Carrier Cross Connects - Fiber Cable Support Structure, per linear foot			AMTFS	VE1CB	0.0024										
	Virtual Collocation - Co-Carrier Cross Connects - Copper/Coax Cable Support Structure, per linear ft Virtual Collocation - Co-Carrier Cross Connects - Fiber Cable			AMTFS	VE1CD	0.0036										
	Support Structure, per cable Virtual Collocation - Co-Carrier Cross Connects - Piber Cable Virtual Collocation - Co-Carrier Cross Connects - Copper/Coax			AMTFS	VE1CC		534.79					15.20				
	Cable Support Structure, per cable			AMTFS	VE1CE		534.79					15.20				
	Virtual Collocation Cable Records - per request			AMTFS	VE1BA	10.97	00 0					10.20				
	Virtual Collocation Cable Records - VG/DS0 Cable, per cable record			AMTFS	VE1BB	5.29										
	Virtual Collocation Cable Records - VG/DS0 Cable, per each 100 pair			AMTFS	VE1BC	0.08										
	Virtual Collocation Cable Records - DS1, per T1TIE			AMTFS	VE1BD	0.04										
	Virtual Collocation Cable Records - DS3, per T3TIE			AMTFS	VE1BE	0.13										
	Virtual Collocation Cable Records - Fiber Cable, per 99 fiber records			AMTFS	VE1BF	1.37	10.11					45.00				
	Virtual collocation - Security Escort - Basic, per half hour			AMTFS AMTFS	SPTBX SPTOX		16.44 21.41	10.42 13.45				15.20 15.20				
	Virtual collocation - Security Escort - Overtime, per half hour Virtual collocation - Security Escort - Premium, per half hour			AMTES	SPTOX		26.38	13.45				15.20				
	Virtual collocation - Security Escott - Premium, per man mour Virtual collocation - Maintenance in CO - Basic, per half hour			AMTFS	CTRLX		27.12	10.42				15.20				
	Virtual collocation - Maintenance in CO - Overtime, per half hour			AMTFS	SPTOM		35.42	13.45				15.20				
	Virtual collocation - Maintenance in CO - Premium per half hour			AMTFS	SPTPM		43.72	16.49				15.20				<u> </u>
VIRTUAL COL	LOCATION Virtual Collocation - 2-wire Cross Connect, Exchange Port 2-Wire Analog - Res			UEPSR	VE1R2	0.0296	11.94	11.46				15.20				
	Virtual Collocation 2-Wire Cross Connect, Exchange Port 2- Wire Line Side PBX Trunk - Bus			UEPSP	VE1R2	0.0296	11.94	11.46				15.20				
	Virtual Collocation 2-Wire Cross Connect, Exchange Port 2-Wire Voice Grade PBX Trunk - Res			UEPSE	VE1R2	0.0296	11.94	11.46				15.20				
	Virtual Collocation 2-Wire Cross Connect, Exchange Port 2-Wire Analog Bus			UEPSB	VE1R2	0.0296	11.94	11.46				15.20				
	Virtual Collocation 2-Wire Cross Connect, Exchnage Port 2-Wire ISDN			UEPSX	VE1R2	0.0296	11.94	11.46				15.20				
	Virtual Collocation 2-Wire Cross Connect, Exchange Port 2-Wire ISDN			UEPTX	VE1R2	0.0296	11.94	11.46				15.20				
	Virtual Collocation 4-Wire Cross Connect, Exchange Port 4-Wire ISDN DS1			UEPEX	VE1R4	0.0591	12.04	11.53				15.20				
Note:	Rates displaying an "R" in Interim column are interim and sub	ject to	rate tru	e-up as set forth in	General Tern	ns and Condition	ons.									

COLL	CATI	ON - Mississippi												Attach	ment: 4	Evhi	bit: B
COLL	JCAII	ON - MISSISSIPPI	1									Svc Order	Svc Order	Incremental		Incremental	
												Submitted	Submitted		Charge -	Charge -	Charge -
												Elec		Manual Svc	Manual Svc		Manual Svc
CATEG	ORY	RATE ELEMENTS	Interi	Zone	BCS	USOC			RATES (\$)				,				
OA! LO	O	NATE ELEMENTO	m	20.10	500	0000			TOTAL CO			per LSR	per LSR	Order vs.	Order vs.	Order vs.	Order vs.
														Electronic-	Electronic-	Electronic-	Electronic-
														1st	Add'l	Disc 1st	Disc Add'l
								Nonrec	urring	Nonrecurring	Disconnect			oss	Rates (\$)		
							Rec	First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
									7144.		7.44					00	
PHYSIC	AL COL	LOCATION															
		Physical Collocation 2-Wire Cross Connect, Exchange Port 2-															
		Wire Analog - Res			UEPSR	PE1R2	0.0288	12.37	11.87	6.04	5.45		15.75				
		Physical Collocation 2-Wire Cross Connect, Exchange Port 2-						_									
		Wire Line Side PBX Trunk - Bus			UEPSP	PE1R2	0.0288	12.37	11.87	6.04	5.45		15.75				
		Physical Collocation 2-Wire Cross Connect, Exchange Port 2-															
		Wire Voice Grade PBX Trunk - Res			UEPSE	PE1R2	0.0288	12.37	11.87	6.04	5.45		15.75				
		Physical Collocation 2-Wire Cross Connect, Exchange Port 2-															
		Wire Analog - Bus			UEPSB	PE1R2	0.0288	12.37	11.87	6.04	5.45		15.75				
		Physical Collocation 2-Wire Cross Connect, Exchange Port 2-															
		Wire ISDN	<u> </u>		UEPSX	PE1R2	0.0288	12.37	11.87	6.04	5.45		15.75				
		Physical Collocation 2-Wire Cross Connect, Exchange Port 2-	1]
		Wire ISDN	ļ		UEPTX	PE1R2	0.0288	12.37	11.87	6.04	5.45		15.75				
1 T		Physical Collocation 4-Wire Cross Connect, Exchange Port 4-	1										1]
		Wire ISDN DS1	ļ		UEPEX	PE1R4	0.0576	12.47	11.94	6.59	5.91		15.75				
PHYSIC	AL COL	LOCATION															
		Physical Collocation - Application Fee - Initial			CLO	PE1BA		1,890.38									
		Physical Collocation - Application Fee - Subsequent			CLO	PE1CA		1,575.69									
		Physical Collocation Administrative Only - Application Fee			CLO	PE1BL		740.76									
		Physical Collocation - Space Preparation - Firm Order			01.0	DE401		00440									
		Processing			CLO	PE1SJ		604.19									
		Physical Collocation - Space Preparation - C.O. Modification per square ft.			CLO	PE1SK	2.30										
		Physical Collocation - Space Preparation - Common Systems			CLO	PEISK	2.30										
		Modification per square ft Cageless			CLO	PE1SL	2.52										
		Physical Collocation - Space Preparation - Common Systems	'		CLO	FLIOL	2.52										
		Modification per Cage			CLO	PE1SM	85.67										
+		Physical Collocation - Cable Installation	<u> </u>		CLO	PE1BD	00.01	926.27	926.27	22.62							
		Physical Collocation - Floor Space per Sq. Ft.			CLO	PE1PJ	5.74										
		Physical Collocation - Cable Support Structure, Per Entrance															
		Cable			CLO	PE1PM	17.42										
		Physical Collocation - Power -48V DC Power, per Fused Amp			CLO	PE1PL	7.33										
		Physical Collocation - Power Reduction, Application Fee			CLO	PE1PR		398.76									
		•															
		Physical Collocation - 120V, Single Phase Standby Power Rate	- 1		CLO	PE1FB	5.29										
		Physical Collocation - 240V, Single Phase Standby Power Rate	- 1		CLO	PE1FD	10.58										
1 T			1										1]
\vdash		Physical Collocation - 120V, Three Phase Standby Power Rate			CLO	PE1FE	15.87										ļ
		Physical Colleges of The City Co. 11 Co. 12	1 .		01.0	DE450							1				1
\vdash		Physical Collocation - 277V, Three Phase Standby Power Rate	<u> </u>	 	CLO	PE1FG	36.65								ļ		
			1		UEANL,UEA,UDN,U								1				Ì
					DC,UAL,UHL,UCL,U												
					EQ. UDL. UNCVX.												
		Physical Collocation - 2-Wire Cross-Connects			UNLDX, UNCNX	PE1P2	0.0288	12.37	11.87	6.04	5.45						
\vdash		i nyaicai Conocation - 2-14116 Cross-Connects	1		CLO, UAL, UDL,	I LIFZ	0.0200	12.31	11.07	0.04	5.45	1					
			1		UDN, UEA, UHL,								1				1
			1		UNCVX, UNCDX,								1				1
		Physical Collocation - 4-Wire Cross-Connects	1		UCL	PE1P4	0.0576	12.47	11.94	6.59	5.91		1				1
		,	1		CLO,UEANL,UEQ,W		2.22.0			2.00	3.01						
			1		DS1L,WDS1S, USL,								1				1
			1		U1TD1, UXTD1,								1				1
			1		UNC1X, ULDD1,												
			1		USLEL, UNLD1,								1				1
		Physical Collocation - DS1 Cross-Connects	1	1	UDL	PE1P1	1.14	22.16	16.02	6.60	5.97	1	l		l	l	I

COLLOCAT	ION - Mississippi												Attach	ment: 4	Exhi	bit: B
CATEGORY	RATE ELEMENTS	Interi m	Zone	BCS	USOC			RATES (\$)			Svc Order Submitted Elec per LSR	Submitted	Incremental Charge - Manual Svc Order vs. Electronic- 1st		Incremental Charge -	Incremental Charge - Manual Svc Order vs. Electronic- Disc Add'l
						Rec	Nonrec			g Disconnect				Rates (\$)	l	-
						Rec	First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
	Physical Collocation - DS3 Cross-Connects			CLO, UE3,U1TD3, UXTD3, UXTS1, UNC3X, UNCSX, ULDD3, U1TS1,ULDS1, UNLD3, UDL CLO, ULDO3,	PE1P3	14.49	21.01	15.29	7.61	6.10						
			l	ULD12, ULD48, U1TO3, U1T12, U1T48, UDLO3,	DE 150			47.00								
	Physical Collocation - 2-Fiber Cross-Connect			UDL12, UDF CLO, ULDO3,	PE1F2	2.87	21.01	15.29	7.61	6.10				1		
	Physical Collocation - 4-Fiber Cross-Connect		 	ULD12, ULD48, U1TO3, U1T12, U1T48, UDLO3, UDL12, UDF	PE1F4	5.10	25.70	19.97	10.01	8.50						
	Physical Collocation - Welded Wire Cage - First 100 Sq. Ft.			CLO	PE1BW	183.20	200	10.01	10.01	0.00						
	Physical Collocation - Welded Wire Cage - Add'l 50 Sq. Ft.		(CLO	PE1CW	17.97										
	Physical Collocation - Security Access System - Security System per Central Office	ı	(CLO	PE1AX	75.23										
	Physical Collocation - Security Access System - New Access Card Activation, per Card	ı	(CLO	PE1A1	0.0576	27.95	27.95								
	Physical Collocation-Security Access System-Administrative Change, existing Access Card, per Request, per State, per Card			CLO	PE1AA		7.84	7.84								
	Physical Collocation - Security Access System - Replace Lost or Stolen Card, per Card		l ,	CLO	PE1AR		22.91	22.91								Ĭ
 	Physical Collocation - Security Access - Initial Key, per Key			CLO	PE1AK		13.17	13.17						1		
	Physical Collocation - Security Access - Key, Replace Lost or															
	Stolen Key, per Key			CLO	PE1AL		13.17	13.17								
	Physical Collocation - Space Availability Report per premises POT Bay Arrangements prior to 6/1/99 - 2-Wire Cross-Connect, per cross-connect	I	[[]	CLO UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ,CLO,UDL, UNCVX, UNCDX, UNCNX	PE1SR PE1PE	0.0867	1,081.40	1,081.40								
	POT Bay Arrangements prior to 6/1/99 - 4-Wire Cross-Connect, per cross-connect		[[UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ,CLO, USL, UNCVX, UNCDX	PE1PF	0.1734										
	POT Bay Arrangements prior to 6/1/99 - DS1 Cross-Connect, per cross-connect			UEANL, UEA, UDN, U DC, UAL, UHL, UCL, U EQ, CLO, WDS1L, W DS1S, USL, U1TD1, UXTD1, UNC1X, ULDD1, USLEL, UNLD1 UEANL, UEA, UDN, U DC, UAL, UHL, UCL, U EQ, CLO, UE3, U1TD3, UXTD3, UXTS1, UNC3X, UNCSX, ULDD3, U1TS1, ULDS1,	PE1PG	1.22										
	POT Bay Arrangements prior to 6/1/99 - DS3 Cross-Connect, per cross-connect			UNLD3, UDL, UDLSX	PE1PH	10.91										<u> </u>

COLLO	CATIO	ON - Mississippi												Attach	ment: 4	Exhi	ibit: B
CATEGOR		RATE ELEMENTS	Interi m	Zone	BCS	usoc			RATES (\$)				Svc Order Submitted Manually per LSR	Incremental Charge - Manual Svc Order vs. Electronic- 1st	Incremental Charge - Manual Svc Order vs. Electronic- Add'I		Incremental Charge -
							Rec	Nonred			Disconnect				Rates (\$)		
\vdash				ļ	LIEANII LIEA LIBATTI			First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
		POT Bay Arrangements prior to 6/1/99 - 2-Fiber Cross-Connect, per cross-connect			UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ,CLO, ULDO3, ULD12, ULD48, U1TO3, U1T12, U1T48, UDLO3, UDL12, UDF	PE1B2	37.26										
		POT Bay Arrangements prior to 6/1/99 - 4-Fiber Cross-Connect, per cross-connect			UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ,CLO, ULDO3, ULD12, ULD48, U1TO3, U1T12, U1T48, UDLO3, UDL12, UDF	PE1B4	50.24										
		Physical Collocation - Request Resend of CFA Information, per															
-		CLLI Nonrecurring Collocation Cable Records - per request			CLO CLO	PE1C9 PE1CR		77.41 763.69	490.94	133.77					-		
		Nonrecurring Collocation Cable Records - per request Nonrecurring Collocation Cable Records - VG/DS0 Cable, per			CLO	PETCR		763.69	490.94	133.77							
		cable record			CLO	PE1CD		328.81		190.22							
		Nonrecurring Collocation Cable Records - VG/DS0 Cable, per															
-		each 100 pair Nonrecurring Collocation Cable Records - DS1, per T1TIE			CLO CLO	PE1CO PE1C1		4.84 2.27	4.84 2.27	5.93 2.78	5.93 2.78				-		
-		Nonrecurring Collocation Cable Records - DS1, per TTTLE Nonrecurring Collocation Cable Records - DS3, per T3TIE			CLO	PE1C1		7.92	7.92	9.72	9.72				-		
		Nonrecurring Collocation Cable Records - Fiber Cable, per 99			OLO	1 1 103		1.52	1.02	5.12	5.12						
		fiber records			CLO	PE1CB		84.98	84.98	77.58	77.58						
		Physical Collocation - Security Escort - Basic, per Half Hour			CLO,CLORS	PE1BT		17.02	10.79								
		Physical Collocation - Security Escort - Overtime, per Half Hour			CLO,CLORS	PE1OT		22.17	13.94								
		Physical Collocation - Security Escort - Premium, per Half Hour			CLO,CLORS	PE1PT		27.32	17.08								
		V to P Conversion, Per Customer Request-Voice Grade			CLO	PE1BV		33.00	11.00	İ					1		
		V to P Conversion, Per Customer Request-DS0			CLO	PE1BO		33.00									
		V to P Conversion, Per Customer Request-DS1			CLO	PE1B1		52.00									
		V to P Conversion, Per Customer request-DS3			CLO	PE1B3		52.00									
		V to P Conversion, Per Customer Request per VG Circuit Reconfigured			CLO	PE1BR		23.00									
		V to P Conversion, Per Customer Request per DS0 Circuit Reconfigured			CLO	PE1BP		23.00									
		V to P Conversion, Per Customer Request per DS1 Circuit Reconfigured			CLO	PE1BS		33.00									
		V to P Conversion, Per Customer Request per DS3 Circuit Reconfigured			CLO	PE1BE		37.00									
		V to P Conversion, Cable Pairs Assigned to Collo Space per 700 prs or fraction thereof			CLO	PE1B7		592.00									
		Physical Collocation - Co-Carrier Cross Connects - Fiber Cable Support Structure, per cable, per linear ft.			CLO,UDF	PE1ES	0.001										
		Physical Collocation - Co-Carrier Cross Connects - Copper/Coax Cable Support Structure, per cable, per lin. ft.			CLO, UE3, USL	PE1DS	0.0015										
		Physical Collocation - Co-Carrier Cross Connects Only - Application Fee, per application			CLO	PE1DT		583.13									
		Physical Collocation - Application to Augment Exsisting Space - Simple			CLO	PE1KS		597.34		1.22							
		Physical Collocation - Application to Augment Exsisting Space - Minor			CLO	PE1KM		837.57		1.22			-				
		Physical Collocation - Application to Augment Exsisting Space - Intermediate			CLO	PE1K1		1,063.00		1.22							
ADJACEN		LLOCATION		ļ	CLOAC	DE4.IA	0.0070					1					
		Adjacent Collocation - Space Charge per Sq. Ft. Adjacent Collocation - Electrical Facility Charge per Linear Ft.			CLOAC CLOAC	PE1JA PE1JC	0.0678 4.68			1					1		1

COLLO	CATI	ON - Mississippi												Attach	ment: 4	Exhil	oit: B
JULLU	JAII	он плозозаррі										Svc Order	Svc Order	Incremental		Incremental	Incremental
												Submitted	Submitted		Charge -	Charge -	Charge -
												Elec	Manually		Manual Svc	Manual Svc	Manual Svc
CATEGO	RY	RATE ELEMENTS	Interi	Zone	BCS	USOC			RATES (\$)			per LSR	per LSR	Order vs.	Order vs.	Order vs.	Order vs.
			m						- (17)			per LSK	per LOK	Electronic-	Electronic-	Electronic-	Electronic-
																Disc 1st	
														1st	Add'l	DISC 1St	Disc Add'l
							_	Nonrec	urring	Nonrecurring	Disconnect			oss	Rates (\$)	L L	
							Rec	First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
		Adjacent Collocation - 2-Wire Cross-Connects			CLOAC	PE1P2	0.0223	12.37	11.87	6.04	5.45						
		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			UEA,UHL,UDL,UCL,												
		Adjacent Collocation - 4-Wire Cross-Connects			CLOAC	PE1P4	0.0446	12.47	11.94	6.59	5.91						
		Adjacent Collocation - DS1 Cross-Connects			USL,CLOAC	PE1P1	1.05	22.16	16.02	6.60	5.97						
		Adjacent Collocation - DS3 Cross-Connects			CLOAC	PE1P3	14.27	21.01	15.29	7.61	6.10						
		Adjacent Collocation - 2-Fiber Cross-Connect			CLOAC	PE1F2	2.42	21.01	15.29	7.61	6.10						
		Adjacent Collocation - 4-Fiber Cross-Connect			CLOAC	PE1F4	4.62	25.70	19.97	10.01	8.50						
		Adjacent Collocation - Application Fee			CLOAC	PE1JB		1,585.83									
		Adjacent Collocation - 120V, Single Phase Standby Power Rate						.,									
		per AC Breaker Amp			CLOAC	PE1FB	5.29										
		Adjacent Collocation - 240V, Single Phase Standby Power Rate					5.29			1		 	 	†	 		
		per AC Breaker Amp			CLOAC	PE1FD	10.58					1	1				
 		Adjacent Collocation - 120V, Three Phase Standby Power Rate	 		525/10		10.50			1				 	 		
		per AC Breaker Amp	1		CLOAC	PE1FE	15.87							Ì	Ì		
-		Adjacent Collocation - 277V, Three Phase Standby Power Rate			CLOAC	FLIFE	13.07										
		per AC Breaker Amp			CLOAC	PE1FG	36.65										
DUVEICA	1 00	LOCATION IN THE REMOTE SITE			CLOAC	PEIFG	30.03										
FITSICA	AL COL	Physical Collocation in the Remote Site - Application Fee	<u> </u>		CLORS	PE1RA		309.48		168.63							
-			<u> </u>		CLORS	PE1RB	210.05	309.46		100.03							
-		Cabinet Space in the Remote Site per Bay/ Rack	-		CLORS	PETRB	210.05										
		District College Control of the Description Control of the Assessment Control			01.000	DE4DD		40.47	10.17								
		Physical Collocation in the Remote Site - Security Access - Key			CLORS	PE1RD		13.17	13.17								
		Physical Collocation in the Remote Site - Space Availability			0.000	55105											
		Report per Premises Requested			CLORS	PE1SR		116.54	116.54								
		Physical Collocation in the Remote Site - Remote Site CLLI															
		Code Request, per CLLI Code Requested			CLORS	PE1RE		37.77	37.77								
		Remote Site DLEC Data (BRSDD), per Compact Disk, per CO			CLORS	PE1RR		233.14									
PHYSIC/	IL COL	LOCATION IN THE REMOTE SITE - ADJACENT															
		Remote Site-Adjacent Collocation - AC Power, per breaker amp			CLORS	PE1RS	6.27										
		Remote Site-Adjacent Collocation - Real Estate, per square foot			CLORS	PE1RT	0.134										
		Remote Site-Adjacent Collocation-Application Fee			CLORS	PE1RU		755.62	755.62								
		If Security Escort and/or Add'l Engineering Fees become nec	essary f	or rem	ote site collocation,	the Parties v	will negotiate ap	opropriate rate	S.								
VIRTUAL	. COLL	OCATION															
		Virtual Collocation - Application Fee			AMTFS	EAF		1,212.25		0.51			15.75				
		Virtual Collocation - Cable Installation Cost, per cable			AMTFS	ESPCX		926.27		22.62			15.75				
		Virtual Collocation - Floor Space, per sq. ft.			AMTFS	ESPVX	5.74										
		Virtual Collocation - Power, per fused amp			AMTFS	ESPAX	7.33										
		Virtual Collocation - Cable Support Structure, per entrance															
		cable	<u> </u>		AMTFS	ESPSX	15.24			<u> </u>		<u> </u>	<u> </u>	<u> </u>	<u> </u>		
					UEANL,UEA,UDN,U												
					DC,UAL,UHL,UCL,U												
					EQ, AMTFS, UDL,							1	1				
					UNCVX, UNCDX,							1	1				
		Virtual Collocation - 2-wire Cross Connects (loop)	1		UNCNX	UEAC2	0.0268	12.37	11.87	6.04	5.45		15.75	Ì	Ì		
		(-	T		.=		5.51	2.10	İ	1	İ	İ		
			1		UEA,UHL,UCL,UDL,									Ì	Ì		
			1		AMTFS, UAL, UDN,							İ	İ	Ì	İ		
		Virtual Collocation - 4-wire Cross Connects (loop)			UNCVX, UNCDX	UEAC4	0.0536	12.47	11.94	6.59	5.91	1	15.75				
 		I I I I I I I I I I I I I I I I			AMTFS,UDL12,	1	3.3330			0.50	0.01			1	1		
					UDLO3, U1T48,							1	1				
			1		U1T12, U1T03,									Ì	Ì		
			1		ULDO3, ULD12,							l	l	Ì	İ		
		Virtual Collocation - 2-Fiber Cross Connects			ULD48, UDF	CNC2F	2.91	21.01	15.29	7.61	6.10	1	15.75				
 		The product of the cross controls	 		AMTFS,UDL12,	5.102	2.01	21.01	10.20	7.01	0.10		10.70				
			1		UDLO3, U1T48,							l	l	Ì	İ		
					U1T12, U1T03,							1	1				
			1		ULDO3, ULD12,							l	l	Ì	İ		
		Virtual Collocation - 4-Fiber Cross Connects	1		ULD48, UDF	CNC4F	5.82	25.70	19.97	10.01	8.50	l	15.75	Ì	İ		
$oxed{oxed}$		VIII GOI GOI GOOGA GOO GOO GOO GOO GOO GOO GOO GOO G	1		0LD40, 0DF	OINC4F	5.02	20.70	19.97	10.01	0.50	1	10.75	1	1		

COLLOCAT	ION - Mississippi													ment: 4	1	ibit: B
CATEGORY	RATE ELEMENTS	Interi m	Zone	BCS	USOC			RATES (\$)				Svc Order Submitted Manually per LSR	Incremental Charge - Manual Svc Order vs. Electronic- 1st	Charge - Manual Svc Order vs. Electronic- Add'l	Incremental Charge - Manual Svc Order vs. Electronic- Disc 1st	Incremental Charge - Manual Svo Order vs. Electronic- Disc Add'l
						Rec	Nonrec		Nonrecurring					Rates (\$)		
							First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
	Virtual Collocation - Special Access & UNE, cross-connect per DS1			USL,ULC,AMTFS, ULR, UXTD1, UNC1X, ULDD1, U1TD1, USLEL, UNLD1	CNC1X	1.14	22.16	16.02	6.60	5.97		15.75				
	Virtual collocation - Special Access & UNE, cross-connect per DS3			USL,ULC,AMTFS,U E3, U1TD3, UXTS1, UXTD3, UNC3X, UNCSX, ULDD3, U1TS1, ULDS1, UDLSX, UNLD3	CND3X	14.49	21.01	15.29	7.61	6.10		15.75				
	Virtual Collocation - Co-Carrier Cross Connects - Fiber Cable			UDLSA, UNLDS	CINDSA	14.49	21.01	15.29	7.01	6.10		15.75				
	Support Structure, per linear foot Virtual Collocation - Co-Carrier Cross Connects - Riber Cable Virtual Collocation - Co-Carrier Cross Connects - Copper/Coax			AMTFS	VE1CB	0.0025										
	Cable Support Structure, per linear ft Virtual Collocation - Co-Carrier Cross Connects - Fiber Cable			AMTFS	VE1CD	0.0037										
	Support Structure,per cable			AMTFS	VE1CC		534.65					15.75				
	Virtual Collocation - Co-Carrier Cross Connects - Copper/Coax Cable Support Structure, per cable			AMTFS	VE1CE		534.65					15.75				
	Virtual Collocation Cable Records - per request			AMTFS	VE1BA		763.69	490.94	133.77	133.77		15.75				
	Virtual Collocation Cable Records - VG/DS0 Cable, per cable			AWITO	VETDA		705.05	430.34	133.77	100.77						
	record Virtual Collocation Cable Records - VG/DS0 Cable, per each			AMTFS	VE1BB		328.81	328.81	190.22	190.22						_
	100 pair			AMTFS	VE1BC		4.84	4.84	5.93	5.93						
	Virtual Collocation Cable Records - DS1, per T1TIE			AMTFS	VE1BD		2.27	2.27	2.78	2.78						
	Virtual Collocation Cable Records - DS3, per T3TIE			AMTFS	VE1BE		7.92	7.92	9.72	9.72						
	Virtual Collocation Cable Records - Fiber Cable, per 99 fiber records			AMTFS	VE1BF		84.98	84.98	77.58	77.58						
	Virtual collocation - Security Escort - Basic, per half hour			AMTFS	SPTBX		17.02	10.79				15.75				
	Virtual collocation - Security Escort - Overtime, per half hour			AMTFS	SPTOX		22.17	13.94				15.75				
	Virtual collocation - Security Escort - Premium, per half hour			AMTFS	SPTPX		27.32	17.08				15.75				
	Virtual collocation - Maintenance in CO - Basic, per half hour			AMTFS	CTRLX		28.09	10.79				15.75				
	Virtual collocation - Maintenance in CO - Overtime, per half hour			AMTFS	SPTOM		36.69	13.94				15.75				
METHALO	Virtual collocation - Maintenance in CO - Premium per half hour			AMTFS	SPTPM		45.28	17.08				15.75				<u> </u>
VIRTUAL COL					 											
	Virtual Collocation - 2-wire Cross Connect, Exchange Port 2- Wire Analog - Res			UEPSR	VE1R2	0.0268	12.37	11.87	6.04	5.45		15.75				
	Virtual Collocation 2-Wire Cross Connect, Exchange Port 2- Wire Line Side PBX Trunk - Bus			UEPSP	VE1R2	0.0268	12.37	11.87	6.04	5.45		15.75				
	Virtual Collocation 2-Wire Cross Connect, Exchange Port 2-Wire Voice Grade PBX Trunk - Res			UEPSE	VE1R2	0.0268	12.37	11.87	6.04	5.45		15.75				
	Virtual Collocation 2-Wire Cross Connect, Exchange Port 2-Wire Analog Bus			UEPSB	VE1R2	0.0268	12.37	11.87	6.04	5.45		15.75				
	Virtual Collocation 2-Wire Cross Connect, Exchnage Port 2-Wire ISDN			UEPSX	VE1R2	0.0268	12.37	11.87	6.04	5.45		15.75				
	Virtual Collocation 2-Wire Cross Connect, Exchange Port 2-Wire ISDN			UEPTX	VE1R2	0.0268	12.37	11.87	6.04	5.45		15.75				
	Virtual Collocation 4-Wire Cross Connect, Exchange Port 4-Wire ISDN DS1			UEPEX	VE1R4	0.0536	12.47	11.94	6.59	5.91		15.75				

COLL	CAT!	ON - North Carolina												A441			hit. D
COLL	JCAII	ON - NORTH Carolina			I		I					Cvo Ordor	Svo Ordor	Attach Incremental	ment: 4 Incremental		bit: B Incremental
													Submitted		Charge -	Charge -	Charge -
												Elec		Manual Svc	Manual Svc		Manual Svc
CATEG	ORY	RATE ELEMENTS	Interi	Zone	BCS	USOC			RATES (\$)					Order vs.	Order vs.	Order vs.	Order vs.
0/1120	•		m			0000			(4)			per LSR	per LSR			Electronic-	Electronic-
														Electronic- 1st	Electronic- Add'l	Disc 1st	Disc Add'l
														181	Add I	DISC 1St	DISC Add 1
							Rec	Nonrec	urring	Nonrecurrin	ng Disconnect			oss	Rates (\$)	•	
							Rec	First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
PHYSIC	AL COL	LOCATION															
		Physical Collocation 2-Wire Cross Connect, Exchange Port 2-															ļ '
		Wire Analog - Res			UEPSR	PE1R2	0.32	41.78	39.23					26.94	12.76		
		Physical Collocation 2-Wire Cross Connect, Exchange Port 2-				DE 100											
		Wire Line Side PBX Trunk - Bus			UEPSP	PE1R2	0.32	41.78	39.23					26.94	12.76		
		Physical Collocation 2-Wire Cross Connect, Exchange Port 2- Wire Voice Grade PBX Trunk - Res			UEPSE	PE1R2	0.32	41.78	39.23					26.94	12.76		
		Physical Collocation 2-Wire Cross Connect, Exchange Port 2-			UEFSE	PEIKZ	0.32	41.70	39.23					26.94	12.76		
		Wire Analog - Bus			UEPSB	PE1R2	0.32	41.78	39.23					26.94	12.76		
H		Physical Collocation 2-Wire Cross Connect, Exchange Port 2-	-	<u> </u>	021 00	1 L 111/2	0.32	41.70	33.23	t	+	 	 	20.94	12.10	 	
		Wire ISDN	l	1	UEPSX	PE1R2	0.32	41.78	39.23	I			1	26.94	12.76	1	1
		Physical Collocation 2-Wire Cross Connect, Exchange Port 2-		†			0.02	71.70	00.20	†	1	1		20.04	12.70	1	
		Wire ISDN	l	1	UEPTX	PE1R2	0.32	41.78	39.23	I			1	26.94	12.76	1	1
		Physical Collocation 4-Wire Cross Connect, Exchange Port 4-						-							1		
		Wire ISDN DS1	<u></u>	L	UEPEX	PE1R4	0.64	41.91	39.25	<u> </u>	<u> </u>	<u> </u>	<u> </u>	26.94	12.76	<u> </u>	<u> </u>
PHYSIC	AL COL	LOCATION															
		Physical Collocation - Application Fee - Initial	ı		CLO	PE1BA		2,322.00									
		Physical Collocation - Application Fee - Subsequent			CLO	PE1CA		2,311.00									
		Physical Collocation Administrative Only - Application Fee			CLO	PE1BL		741.44									
		Physical Collocation - Space Preparation - Firm Order															
		Processing			CLO	PE1SJ		1,196.00									
		Physical Collocation - Space Preparation - C.O. Modification per	Ι.		0.0	DE 4014	0.40										
		square ft.			CLO	PE1SK	2.42										
		Physical Collocation - Space Preparation - Common Systems Modification per square ft Cageless	Ι.		CLO	PE1SL	2.88										
		Physical Collocation - Space Preparation - Common Systems			CLO	PETSL	2.88										
		Modification per Cage	١,		CLO	PE1SM	97.98										ļ '
-		Space Preparation Fees - Power Per Nominal -48V Dc Amp	l i		CLO	PE1FH	5.76					1					
		Physical Collocation - Cable Installation	i		CLO	PE1BD	0.10	1,701.00	1,701.00								
		Physical Collocation - Floor Space per Sq. Ft.	i i		CLO	PE1PJ	2.30	1,1.0.1.00	.,								
		Physical Collocation - Cable Support Structure, Per Entrance															
		Cable	- 1		CLO	PE1PM	20.57										
		Physical Collocation - Power -48V DC Power, per Fused Amp	I		CLO	PE1PL	7.65										
		Physical Collocation - Power Reduction, Application Fee	ı		CLO	PE1PR		399.13									
									·						1		1
		Physical Collocation - 120V, Single Phase Standby Power Rate	l	<u> </u>	CLO	PE1FB	5.50								1		1
		District College (co. 10.40) (Co. 1.5)	١.	1	0.0	DE4E2				1			1			1	1
\vdash		Physical Collocation - 240V, Single Phase Standby Power Rate	I	<u> </u>	CLO	PE1FD	11.01			.	1				1		├
		Physical Collocation 120V/ Three Phase Standby Bower Bet-		1	CLO	PE1FE	16.51			1			1			1	1
\vdash		Physical Collocation - 120V, Three Phase Standby Power Rate	- ' -	1	CLO	FEIFE	10.51			+	+				+		
		Physical Collocation - 277V, Three Phase Standby Power Rate			CLO	PE1FG	38.12			1					1		1 '
			- '-	1	0_0		30.12			 	+	 			 		\vdash
			l	1	UEANL.UEA.UDN.U]			I			1		I	1	1 '
			l	1	DC,UAL,UHL,UCL,U]			I			1		I	1	1 '
			l	1	EQ, UDL, UNCVX,]			I			1		I	1	1 '
		Physical Collocation - 2-Wire Cross-Connects	I	<u>L</u>	UNLDX, UNCNX	PE1P2	0.0309	33.53	31.65						<u></u>	<u> </u>	<u> </u>
	•				CLO, UAL, UDL,												
			l	1	UDN, UEA, UHL,]			I			1		I	1	1 '
			l .	1	UNCVX, UNCDX,	L				I			1		I	1	1
\vdash		Physical Collocation - 4-Wire Cross-Connects		<u> </u>	UCL	PE1P4	0.0618	33.67	31.70			ļ					↓
				1	CLO,UEANL,UEQ,W					1			1			1	1
			l	1	DS1L,WDS1S, USL,]			I			1		I	1	1
			l	1	U1TD1, UXTD1, UNC1X, ULDD1,]			I			1		I	1	1
			l		USLEL, UNLD1,					1					1		1
		Physical Collocation - DS1 Cross-Connects			UDL	PE1P1	1.38	52.87	39.86	1					1		1
-		, o.o.a. Johnoudilon Do i Grood-Confidence	<u>'</u>	1	UU-	p = 0 1	1.00	JZ.01	55.00	1	1	1	·		1	1	

COLLOCA.	FION - North Carolina												Attach	ment: 4	Exhi	nit: D
COLLOCA	HON - NOTH Carolina	1									Svc Order	Svc Order	Incremental	Incremental		Incremental
											Submitted	Submitted		Charge -	Charge -	Charge -
		١									Elec	Manually	Manual Svc	Manual Svc		Manual Svc
CATEGORY	RATE ELEMENTS	Interi	Zone	BCS	USOC			RATES (\$)			per LSR	per LSR	Order vs.	Order vs.	Order vs.	Order vs.
		m						.,			per Lor	per Lor	Electronic-	Electronic-	Electronic-	Electronic-
													1st	Add'l	Disc 1st	Disc Add'l
															Disc 1st	Disc Add I
						Rec	Nonrec			g Disconnect				Rates (\$)		
						1100	First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
				CLO, UE3,U1TD3,												
				UXTD3, UXTS1,												
				UNC3X, UNCSX,												
				ULDD3,												
	B	١.		U1TS1,ULDS1,	DE 4 D 0	4= 00										
—	Physical Collocation - DS3 Cross-Connects	ı		UNLD3, UDL CLO, ULDO3,	PE1P3	17.62	51.97	38.59								
				ULD12, ULD48,												
				U1TO3, U1T12,												
				U1T48, UDLO3,												
	Physical Collocation - 2-Fiber Cross-Connect			UDL12. UDF	PE1F2	3.50	51.97	38.59								
 	i nysicai conocation - 2-i ibei cross-connect			CLO, ULDO3,	LIFE	3.50	51.97	30.39		†			 	 		
		1		ULD12, ULD48,						1			1	1		
		1		U1TO3, U1T12,						1			1	1		
				U1T48, UDLO3,												
	Physical Collocation - 4-Fiber Cross-Connect	1		UDL12, UDF	PE1F4	6.20	64.53	51.15								
	Physical Collocation - Welded Wire Cage - First 100 Sq. Ft.	T T		CLO	PE1BW	1	559.81	******								
	Physical Collocation - Welded Wire Cage - Add'l 50 Sq. Ft.	- 1		CLO	PE1CW		25.37									
	Physical Collocation - Security System Per Central Office Per															
	Assignable Sq. Ft.			CLO	PE1AY	0.0135										
	Physical Collocation - Security Access System - Security System															
	per Central Office	- 1		CLO	PE1AX	41.03										
	Physical Collocation - Security Access System - New Access															
	Card Activation, per Card	I		CLO	PE1A1	0.062	15.00									
	Physical Collocation-Security Access System-Administrative	١.		0.0	55444											
-	Change, existing Access Card, per Request, per State, per Card			CLO	PE1AA		15.51									
	Physical Collocation - Security Access System - Replace Lost or Stolen Card, per Card			CLO	PE1AR		15.00									
-	Physical Collocation - Security Access - Initial Key, per Key			CLO	PE1AK		15.00				1					
	Physical Collocation - Security Access - Key, Replace Lost or			OLO	LIAK	<u> </u>	15.00									
	Stolen Key, per Key			CLO	PE1AL		15.00									
	Physical Collocation - Space Availability Report per premises			CLO	PE1SR		2,140.00	2,140.00								
	The second secon			UEANL,UEA,UDN,U			_,	_,								
				DC,UAL,UHL,UCL,U												
				EQ,CLO,UDL,												
	POT Bay Arrangements prior to 6/1/99 - 2-Wire Cross-Connect,			UNCVX, UNCDX,												
	per cross-connect			UNCNX	PE1PE	0.1054				1						
		1]	UEANL,UEA,UDN,U									1]		
		1		DC,UAL,UHL,UCL,U						1			1	1		
	POT Bay Arrangements prior to 6/1/99 - 4-Wire Cross-Connect,			EQ,CLO, USL,												
	per cross-connect			UNCVX, UNCDX	PE1PF	0.2108										
				UEANL,UEA,UDN,U												
				DC,UAL,UHL,UCL,U												
				EQ,CLO,WDS1L,W DS1S, USL, U1TD1,												
				UXTD1, UNC1X,												
	POT Bay Arrangements prior to 6/1/99 - DS1 Cross-Connect,			ULDD1, USLEL,												
	per cross-connect			UNLD1	PE1PG	1.49										
	1	1		UEANL,UEA,UDN,U						1			1	1		
				DC,UAL,UHL,UCL,U						1						
				EQ,CLO,UE3,												
				U1TD3, UXTD3,						1						
		1		UXTS1, UNC3X,						1			1	1		
		1		UNCSX, ULDD3,						1			1	1		
		1		U1TS1, ULDS1,						1			1	1		
	POT Bay Arrangements prior to 6/1/99 - DS3 Cross-Connect,	1		UNLD3, UDL,	DE (D) .					1			1	1		
	per cross-connect			UDLSX	PE1PH	13.27]					

COLLO	CATIO	ON - North Carolina												Attach	ment: 4	Exhi	ibit: B
CATEGOR		RATE ELEMENTS	Interi m	Zone	BCS	USOC			RATES (\$)				Svc Order Submitted Manually per LSR	Incremental Charge - Manual Svc Order vs. Electronic- 1st	Incremental Charge - Manual Svc Order vs. Electronic- Add'I		Incremental Charge -
							Rec		curring	Nonrecurring					Rates (\$)		
					UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ,CLO, ULDO3, ULD12, ULD48, U1TO3, U1T12,			First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
		POT Bay Arrangements prior to 6/1/99 - 2-Fiber Cross-Connect, per cross-connect			U1T48, UDLO3, UDL12, UDF	PE1B2	45.30										
		POT Bay Arrangements prior to 6/1/99 - 4-Fiber Cross-Connect, per cross-connect			UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ,CLO, ULDO3, ULD12, ULD48, U1TO3, U1T12, U1T48, UDLO3, UDL12, UDF	PE1B4	61.09										
		Physical Collocation - Request Resend of CFA Information, per															
		CLLI			CLO CLO	PE1C9 PE1CR		77.48 1,707.00									ļ
		Nonrecurring Collocation Cable Records - per request Nonrecurring Collocation Cable Records - VG/DS0 Cable, per			CLO	PETCR		1,707.00									
		Cable record Nonrecurring Collocation Cable Records - VG/DS0 Cable, per			CLO	PE1CD		923.08									
		each 100 pair			CLO	PE1CO		18.02	18.02								
		Nonrecurring Collocation Cable Records - DS1, per T1TIE			CLO	PE1C1		8.43	8.43								
		Nonrecurring Collocation Cable Records - DS3, per T3TIE			CLO	PE1C3		29.51	29.51								
		Nonrecurring Collocation Cable Records - Fiber Cable, per 99 fiber records			CLO	PE1CB		278.82	278.82								
		Physical Collocation - Security Escort - Basic, per Half Hour			CLO,CLORS	PE1BT		33.68	21.34								-
		Physical Collocation - Security Escort - Overtime, per Half Hour			CLO,CLORS	PE1OT		43.87	27.57								
		Physical Collocation - Security Escort - Premium, per Half Hour			CLO,CLORS	PE1PT		54.06	33.80								
		V to P Conversion, Per Customer Request-Voice Grade			CLO	PE1BV		33.00	00.00								1
		V to P Conversion, Per Customer Request-DS0			CLO	PE1BO		33.00									
		V to P Conversion, Per Customer Request-DS1			CLO	PE1B1		52.00									
		V to P Conversion, Per Customer request-DS3 V to P Conversion, Per Customer Request per VG Circuit			CLO	PE1B3		52.00									ļ
		V to P Conversion, Per Customer Request per V3 Circuit Reconfigured V to P Conversion, Per Customer Request per DS0 Circuit			CLO	PE1BR		23.00									
		Reconfigured			CLO	PE1BP		23.00									
		V to P Conversion, Per Customer Request per DS1 Circuit Reconfigured			CLO	PE1BS		33.00									
		V to P Conversion, Per Customer Request per DS3 Circuit Reconfigured VED Research Cobin Pairs Assigned to Callo Space and 700.			CLO	PE1BE		37.00									
		V to P Conversion, Cable Pairs Assigned to Collo Space per 700 prs or fraction thereof			CLO	PE1B7		592.00									
		Physical Collocation - Co-Carrier Cross Connects - Fiber Cable Support Structure, per cable, per linear ft.			CLO,UDF	PE1ES	0.0028										
		Physical Collocation - Co-Carrier Cross Connects - Copper/Coax Cable Support Structure, per cable, per lin. ft.			CLO, UE3, USL	PE1DS	0.0041										
		Physical Collocation - Co-Carrier Cross Connects Only - Application Fee, per application Physical Collegation - Application to Augment Evolution Space			CLO	PE1DT		583.66									
		Physical Collocation - Application to Augment Exsisting Space - Simple Physical Collocation - Application to Augment Exsisting Space -			CLO	PE1KS		575.93		1.16							
		Minor			CLO	PE1KM		806.66		1.16							
AD IACES		Physical Collocation - Application to Augment Exsisting Space - Intermediate LLOCATION			CLO	PE1K1		1,023.00		1.16							
ADJACEN		Adjacent Collocation - Space Charge per Sq. Ft.			CLOAC	PE1JA	0.1555										1
 		Adjacent Collocation - Space Charge per 34. Ft. Adjacent Collocation - Electrical Facility Charge per Linear Ft.	1		CLOAC	PE1JC	5.78			+							†

COLI	OCATI	ION - North Carolina												Attach	ment: 4	Exhi	bit: B
							1					Svc Order	Svc Order	Incremental		Incremental	Incremental
												Submitted	Submitted		Charge -	Charge -	Charge -
												Elec	Manually		Manual Svc	Manual Svc	Manual Svc
CATE	ORY	RATE ELEMENTS	Interi	Zone	BCS	USOC			RATES (\$)			per LSR	per LSR	Order vs.	Order vs.	Order vs.	Order vs.
			m									per LSK	per LSK				
														Electronic-	Electronic-	Electronic-	Electronic-
														1st	Add'l	Disc 1st	Disc Add'l
	1			-			1	Nonrec		Monroourrin	g Disconnect	1		000	Rates (\$)		
							Rec										
								First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
		Adjacent Collocation - 2-Wire Cross-Connects			CLOAC	PE1P2	0.0239	33.53	31.65								
					UEA,UHL,UDL,UCL,												
		Adjacent Collocation - 4-Wire Cross-Connects			CLOAC	PE1P4	0.0477	33.67	31.70								
		Adjacent Collocation - DS1 Cross-Connects			USL,CLOAC	PE1P1	1.28	52.87	39.86								
		Adjacent Collocation - DS3 Cross-Connects			CLOAC	PE1P3	17.35	51.97	38.59								
		Adjacent Collocation - 2-Fiber Cross-Connect			CLOAC	PE1F2	2.94	51.97	38.59								
		Adjacent Collocation - 4-Fiber Cross-Connect			CLOAC	PE1F4	5.62	64.53	51.15								
		Adjacent Collocation - Application Fee	 		CLOAC	PE1JB	0.02	3,139.00	01.10			<u> </u>					
-			1		CLOAC	I LIJD		3,133.00									
		Adjacent Collocation - 120V, Single Phase Standby Power Rate			CLOAC	DE4ES					1	1					
<u> </u>	1	per AC Breaker Amp	<u> </u>	 	CLOAC	PE1FB	5.50			ļ	-	1	.	ļ		ļ	
1		Adjacent Collocation - 240V, Single Phase Standby Power Rate	1]				1	1	I	1	1	1	
L		per AC Breaker Amp	<u> </u>		CLOAC	PE1FD	11.01				L	<u> </u>					
		Adjacent Collocation - 120V, Three Phase Standby Power Rate															
		per AC Breaker Amp			CLOAC	PE1FE	16.51				1	1					
		Adjacent Collocation - 277V, Three Phase Standby Power Rate				1	į i					1	İ				
		per AC Breaker Amp			CLOAC	PE1FG	38.12				1	1					
PHACI	CAL CO	LLOCATION IN THE REMOTE SITE	1		020.10		55.12			<u> </u>	-	1					
111131	T CO	Physical Collocation in the Remote Site - Application Fee	 	\vdash	CLORS	PE1RA	+ +	865.34	865.34	1	+	1	 	1	1		
						PE1RB	254.02	000.34	000.34			ļ					
		Cabinet Space in the Remote Site per Bay/ Rack			CLORS	PETRB	254.02										
		Physical Collocation in the Remote Site - Security Access - Key			CLORS	PE1RD		26.06	26.06								
		Physical Collocation in the Remote Site - Space Availability															
		Report per Premises Requested			CLORS	PE1SR		230.60	230.60								
		Physical Collocation in the Remote Site - Remote Site CLLI															
		Code Request, per CLLI Code Requested			CLORS	PE1RE		74.74	74.74								
		Remote Site DLEC Data (BRSDD), per Compact Disk, per CO			CLORS	PE1RR		232.94	14.14								
DUVE	CAL CO	LLOCATION IN THE REMOTE SITE - ADJACENT	 		CLORG	I LIKK		202.04				<u> </u>					
FILISI	CAL CO	LLOCATION IN THE REMOTE SITE - ADJACENT															
					0.000	55150											
		Remote Site-Adjacent Collocation - AC Power, per breaker amp			CLORS	PE1RS	6.27										
		Remote Site-Adjacent Collocation - Real Estate, per square foot			CLORS	PE1RT	0.134										
		Remote Site-Adjacent Collocation-Application Fee			CLORS	PE1RU		755.62	755.62								
	NOTE:	If Security Escort and/or Add'l Engineering Fees become nec	essary	or remo	ote site collocation,	the Parties v	will negotiate a	propriate rate	s.								
VIRTU		LOCATION					i i										
	1	Virtual Collocation - Application Fee	1		AMTFS	EAF		2.848.30	2,848.30					26.94	12.76		
		Virtual Collocation - Cable Installation Cost, per cable	 		AMTFS	ESPCX		2,750.00	2,750.00			<u> </u>		26.94	12.76		
-	1	Virtual Collocation - Cable Installation Cost, per cable Virtual Collocation - Floor Space, per sq. ft.	 	H	AMTFS	ESPVX	3.20	۷,750.00	۷,750.00	-	+	1	 	20.94	12.70	-	
<u> </u>	1		-	—						1	+	1	1	1	1	 	
L	<u> </u>	Virtual Collocation - Power, per fused amp		lacksquare	AMTFS	ESPAX	3.48					 					
1	1	Virtual Collocation - Cable Support Structure, per entrance	1								1	I	l	Ì			
		cable			AMTFS	ESPSX	13.35										
1			1		UEANL,UEA,UDN,U]						1]	
1			1		DC,UAL,UHL,UCL,U		1				1	1	I	1	1	1	
					EQ, AMTFS, UDL,						1	1					
1			1		UNCVX, UNCDX,]				1	1	I	1	1	1	
1		Virtual Collocation - 2-wire Cross Connects (loop)	1		UNCNX	UEAC2	0.09	41.78	39.23	4.75	4.75	1	I	26.94	12.76	1	
\vdash	t	VIII. SSIIOOGIIOTI Z WIIO OTOGO OOTITIOOG (100p)	 	\vdash	JO. 1/A	JL/102	0.03	71.70	55.25	7.73	4.73	 	 	20.34	12.70	l	
					HEVITH TICL TICL						1	1					
1			1		UEA,UHL,UCL,UDL,]				1	1	I	1	1	1	
1			1		AMTFS, UAL, UDN,							1	I			1	
		Virtual Collocation - 4-wire Cross Connects (loop)			UNCVX, UNCDX	UEAC4	0.18	41.91	39.25	4.73	4.73			26.94	12.76		
1			1		AMTFS,UDL12,]				1	1	I	1	1	1	
1			1		UDLO3, U1T48,		1				1	1	I	1	1	1	
1			1		U1T12, U1T03,]				1	1	I	1	1	1	
					ULDO3, ULD12,						1	1					
1		Virtual Collocation - 2-Fiber Cross Connects	1		ULD48, UDF	CNC2F	15.99	67.34	48.55		1	1	I	26.94	12.76	1	
—	1	VIII. SSHOOLIGH E I IDOI OFOSS CONTIDUIS	 	\vdash	AMTFS,UDL12,	511021	10.00	07.54	70.00	1	+	1	 	20.34	12.70	1	
1			1]				1	1	I	1	1	1	
					UDLO3, U1T48,	1						1	1	1			
					U1T12, U1T03,						1	1					
1	1		1		ULDO3, ULD12,						1	I	l	Ì			
L	<u> </u>	Virtual Collocation - 4-Fiber Cross Connects	<u></u>		ULD48, UDF	CNC4F	28.74	82.35	63.56			<u> </u>		26.94	12.76		

COLLOCAT	ION - North Carolina					1					Ι -			ment: 4	1	ibit: B
CATEGORY	RATE ELEMENTS	Interi m	Zone	BCS	usoc			RATES (\$)				Svc Order Submitted Manually per LSR	Order vs. Electronic- 1st	Charge - Manual Svc Order vs. Electronic- Add'l	Incremental Charge - Manual Svc Order vs. Electronic- Disc 1st	Incrementa Charge - Manual Svo Order vs. Electronic- Disc Add'l
						Rec	Nonrec			g Disconnect				Rates (\$)		
			L	IOL LILO AMETEO			First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
	Virtual collocation - Special Access & UNE, cross-connect per DS1			USL,ULC,AMTFS, ULR, UXTD1, UNC1X, ULDD1, U1TD1, USLEL, UNLD1	CNC1X	0.97	71.02	51.08					26.94	12.76		
	Virtual collocation - Special Access & UNE, cross-connect per DS3		E U U	USL,ULC,AMTFS,U E3, U1TD3, UXTS1, UXTD3, UNC3X, UNCSX, ULDD3, U1TS1, ULDS1, UDLSX, UNLD3	CND3X	56.25	151.90	11.83					26.94	12.76		
	Virtual Collocation - Co-Carrier Cross Connects - Fiber Cable															
	Support Structure, per linear foot Virtual Collocation - Co-Carrier Cross Connects - Copper/Coax			AMTFS	VE1CB	0.0028										
	Cable Support Structure, per linear ft		P	AMTFS	VE1CD	0.0041										
	Virtual Collocation - Co-Carrier Cross Connects - Fiber Cable Support Structure,per cable			AMTFS	VE1CC		532.72						26.94	12.76		
	Virtual Collocation - Co-Carrier Cross Connects - Copper/Coax															
	Cable Support Structure, per cable			AMTFS	VE1CE		532.72						26.94	12.76		
	Virtual Collocation Cable Records - per request		ı	AMTFS	VE1BA		1,707.00									
	Virtual Collocation Cable Records - VG/DS0 Cable, per cable record		,	AMTFS	VE1BB		923.08									
	Virtual Collocation Cable Records - VG/DS0 Cable, per each 100 pair			AMTFS	VE1BC		18.02	18.02								
	Virtual Collocation Cable Records - DS1, per T1TIE		A	AMTFS	VE1BD		8.43	8.43								
	Virtual Collocation Cable Records - DS3, per T3TIE		A	AMTFS	VE1BE		29.51	29.51								
	Virtual Collocation Cable Records - Fiber Cable, per 99 fiber records			AMTFS	VE1BF		278.82	278.82								
	Virtual collocation - Security Escort - Basic, per half hour		A	AMTFS	SPTBX		41.00	25.00					26.94	12.76		
	Virtual collocation - Security Escort - Overtime, per half hour			AMTFS	SPTOX		48.00	30.00					26.94	12.76		
	Virtual collocation - Security Escort - Premium, per half hour			AMTFS	SPTPX		55.00	35.00					26.94	12.76		
	Virtual collocation - Maintenance in CO - Basic, per half hour		1	AMTFS	CTRLX		30.64	30.64					26.94	12.76		
	Virtual collocation - Maintenance in CO - Overtime, per half hour		ı	AMTFS	SPTOM		35.77	35.77					26.94	12.76		
	Virtual collocation - Maintenance in CO - Premium per half hour		1	AMTFS	SPTPM		40.90	40.90					26.94	12.76		
VIRTUAL COL																
	Virtual Collocation - 2-wire Cross Connect, Exchange Port 2- Wire Analog - Res		l	UEPSR	VE1R2	0.09	41.78	39.23					26.94	12.76		
	Virtual Collocation 2-Wire Cross Connect, Exchange Port 2- Wire Line Side PBX Trunk - Bus		l	UEPSP	VE1R2	0.09	41.78	39.23					26.94	12.76		
	Virtual Collocation 2-Wire Cross Connect, Exchange Port 2-Wire Voice Grade PBX Trunk - Res			UEPSE	VE1R2	0.09	41.78	39.23					26.94	12.76		
	Virtual Collocation 2-Wire Cross Connect, Exchange Port 2-Wire Analog Bus			UEPSB	VE1R2	0.09	41.78	39.23					26.94	12.76		
	Virtual Collocation 2-Wire Cross Connect, Exchnage Port 2-Wire ISDN			JEPSX	VE1R2	0.09	41.78	39.23					26.94	12.76		
	Virtual Collocation 2-Wire Cross Connect, Exchange Port 2-Wire															
	ISDN Virtual Collocation 4-Wire Cross Connect, Exchange Port 4-Wire		l	UEPTX	VE1R2	0.09	41.78	39.23					26.94	12.76		
	ISDN DS1			UEPEX e-up as set forth in	VE1R4	0.18	41.91	39.25					26.94	12.76		

COLLOCAT	TION - South Carolina													ment: 4	Exhi	bit: B
CATEGORY	RATE ELEMENTS	Interi m	Zone	BCS	USOC			RATES (\$)			Svc Order Submitted Elec per LSR	Svc Order Submitted Manually per LSR	Charge - Manual Svc Order vs. Electronic- 1st	Charge - Manual Svc Order vs. Electronic- Add'I	Incremental Charge - Manual Svc Order vs. Electronic- Disc 1st	Incremental Charge - Manual Svc Order vs. Electronic- Disc Add'l
						Rec	Nonrec		Nonrecurring		001150	001111		Rates (\$)	0011411	001441
	<u> </u>		1			-	First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
PHYSICAL CO	DI LOCATION														1	
FITTSICAL CO	Physical Collocation 2-Wire Cross Connect, Exchange Port 2-															
	Wire Analog - Res			UEPSR	PE1R2	0.0341	12.32	11.83	6.04	5.45		15.69				
	Physical Collocation 2-Wire Cross Connect, Exchange Port 2-			02. 0.0		0.0011	.2.02	11.00	0.01	0.10		10.00				
	Wire Line Side PBX Trunk - Bus			UEPSP	PE1R2	0.0341	12.32	11.83	6.04	5.45		15.69				
	Physical Collocation 2-Wire Cross Connect, Exchange Port 2-								9.9.							
	Wire Voice Grade PBX Trunk - Res			UEPSE	PE1R2	0.0341	12.32	11.83	6.04	5.45		15.69				
	Physical Collocation 2-Wire Cross Connect, Exchange Port 2-															
	Wire Analog - Bus			UEPSB	PE1R2	0.0341	12.32	11.83	6.04	5.45		15.69				
	Physical Collocation 2-Wire Cross Connect, Exchange Port 2-															
$oxed{oxed}$	Wire ISDN			UEPSX	PE1R2	0.0341	12.32	11.83	6.04	5.45	ļ	15.69				ļ
	Physical Collocation 2-Wire Cross Connect, Exchange Port 2-															
	Wire ISDN		ļ	UEPTX	PE1R2	0.0341	12.32	11.83	6.04	5.45		15.69				
	Physical Collocation 4-Wire Cross Connect, Exchange Port 4-			HEDEV	DE4D4	4.40	00.00	45.00	0.40	5.00		45.00				
PHYSICAL CO	Wire ISDN DS1		-	UEPEX	PE1R4	1.12	22.08	15.96	6.42	5.80		15.69				
PHI SICAL CO	Physical Collocation - Application Fee - Initial			CLO	PE1BA		1,883.67	1,883.67							1	
	Physical Collocation - Application Fee - Subsequent			CLO	PE1CA		1,570.10	1,570.10								
	Physical Collocation Administrative Only - Application Fee			CLO	PE1BL		743.66	1,070.10								
	Physical Collocation - Space Preparation - Firm Order			CLO	LIDE		7-10.00									
	Processing			CLO	PE1SJ		602.05	602.05								
	Physical Collocation - Space Preparation - C.O. Modification per					İ										
	square ft.			CLO	PE1SK	2.75										
	Physical Collocation - Space Preparation - Common Systems															
	Modification per square ft Cageless			CLO	PE1SL	3.24										
	Physical Collocation - Space Preparation - Common Systems															
	Modification per Cage			CLO	PE1SM	110.16										
	Physical Collocation - Cable Installation		1	CLO	PE1BD		794.22	794.22	22.54	22.54						
	Physical Collocation - Floor Space per Sq. Ft.			CLO	PE1PJ	3.95										
	Physical Collocation - Cable Support Structure, Per Entrance Cable			CLO	PE1PM	21.33										
	Physical Collocation - Power -48V DC Power, per Fused Amp		-	CLO	PE1PL	9.19										
	Physical Collocation - Power Reduction, Application Fee			CLO	PE1PR	5.15	400.33									
	1 Hydrodi Goniocation 1 Gwel (Gadetton), 7 ppiloditon 1 ee	<u> </u>		CLO			400.00									
	Physical Collocation - 120V, Single Phase Standby Power Rate			CLO	PE1FB	5.67										
	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,															
\Box	Physical Collocation - 240V, Single Phase Standby Power Rate	<u></u>		CLO	PE1FD	11.36					<u> </u>			<u> </u>		<u> </u>
				_									_			
	Physical Collocation - 120V, Three Phase Standby Power Rate			CLO	PE1FE	17.03										
ļ	Physical Collocation - 277V, Three Phase Standby Power Rate			CLO	PE1FG	39.33										
	Physical Collocation - 2-Wire Cross-Connects			UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ, UDL, UNCVX, UNLDX, UNCNX	PE1P2	0.0341	12.32	11.83	6.04	5.45						
	Physical Collocation A Wire Cross Connects			CLO, UAL, UDL, UDN, UEA, UHL, UNCVX, UNCDX, UCL	PE1P4	0.0682	12.42	11.90	6.40	5.74						
	Physical Collocation - 4-Wire Cross-Connects Physical Collocation - DS1 Cross-Connects			CLO,UEANL,UEQ,W DS1L,WDS1S, USL, U1TD1, UXTD1, UNC1X, ULDD1, USLEL, UNLD1, UDL	PE1P4	1.12	12.42	15.96	6.42	5.74						
	rnysical Collocation - DST Cross-Connects	l	1	UDL	PEIPI	1.12	22.08	15.96	0.42	5.80	1	1		l	l .	<u> </u>

COLLOCAT	ION - South Carolina												Attach	ment: 4	Fxhi	bit: B
CATEGORY	RATE ELEMENTS	Interi m	Zone	BCS	usoc			RATES (\$)			Svc Order Submitted Elec per LSR	Submitted	Incremental Charge - Manual Svc Order vs. Electronic- 1st	Incremental Charge - Manual Svc Order vs. Electronic- Add'I	Incremental Charge -	Incremental Charge - Manual Svc Order vs. Electronic- Disc Add'l
						Rec	Nonrec			g Disconnect				Rates (\$)		
				CLO, UE3,U1TD3,			First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
	Physical Collocation - DS3 Cross-Connects			UXTD3, UXTS1, UNC3X, UNCSX, ULDD3, U1TS1,ULDS1, UNLD3, UDL CLO, ULDO3, ULD12, ULD48,	PE1P3	14.21	20.94	15.23	7.39	5.93						
				U1TO3, U1T12,												
	Physical Collocation - 2-Fiber Cross-Connect			U1T48, UDLO3, UDL12, UDF	PE1F2	2.82	20.94	15.23	7.40	5.93						1
	Physical Collocation - 4-Fiber Cross-Connect			CLO, ULDO3, ULD12, ULD48, U1TO3, U1T12, U1T48, UDLO3, UDL12, UDF	PE1F4	5.01	25.61	19.90	9.73	8.26						
	Physical Collocation - Welded Wire Cage - First 100 Sq. Ft.			CLO	PE1BW	219.19	20.01	10.00	0.70	0.20						
	Physical Collocation - Welded Wire Cage - Add'l 50 Sq. Ft.			CLO	PE1CW	21.50										
	Physical Collocation - Security Access System - Security System per Central Office			CLO	PE1AX	74.72										
	Physical Collocation - Security Access System - New Access Card Activation, per Card			CLO	PE1A1	0.0601	27.85	27.85								
	Physical Collocation-Security Access System-Administrative Change, existing Access Card, per Request, per State, per Card			CLO	PE1AA		7.81	7.81								
	Physical Collocation - Security Access System - Replace Lost or Stolen Card, per Card			CLO	PE1AR		22.83	22.83								
	Physical Collocation - Security Access - Initial Key, per Key			CLO	PE1AK	1	13.13	13.13								
	Physical Collocation - Security Access - Key, Replace Lost or															
	Stolen Key, per Key			CLO	PE1AL		13.13	13.13								
	Physical Collocation - Space Availability Report per premises POT Bay Arrangements prior to 6/1/99 - 2-Wire Cross-Connect, per cross-connect			CLO UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ,CLO,UDL, UNCVX, UNCDX, UNCNX	PE1SR PE1PE	0.085	1,077.57	1,077.57								
	POT Bay Arrangements prior to 6/1/99 - 4-Wire Cross-Connect, per cross-connect			UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ,CLO, USL, UNCVX, UNCDX	PE1PF	0.1701										
	POT Bay Arrangements prior to 6/1/99 - DS1 Cross-Connect, per cross-connect			UEANIL, UEA, UDN, U DC, UAL, UHL, UCL, U EQ, CLO, WDS1L, W DS1S, USL, U1TD1, UXTD1, UNC1X, ULDD1, USLEL, UNLD1 UEANIL, UEA, UDN, U DC, UAL, UHL, UCL, U EQ, CLO, UE3, U1TD3, UXTD3, UXTS1, UNC3X, UNCSX, ULDD3, U1TS1, ULDS1,	PE1PG	1.20										
	POT Bay Arrangements prior to 6/1/99 - DS3 Cross-Connect, per cross-connect			UNLD3, UDL, UDLSX	PE1PH	10.71										<u> </u>

COLLO	CATI	ON - South Carolina												Attach	ment: 4	Exhi	ibit: B
CATEGO		RATE ELEMENTS	Interi m	Zone	BCS	usoc			RATES (\$)				Svc Order Submitted Manually per LSR	Incremental Charge - Manual Svc Order vs. Electronic- 1st	Incremental Charge - Manual Svc Order vs. Electronic- Add'I		Incremental Charge -
							Rec	Nonred			g Disconnect				Rates (\$)		
\vdash				ļ	LIEANII LIEA LIBATTI			First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
		POT Bay Arrangements prior to 6/1/99 - 2-Fiber Cross-Connect, per cross-connect			UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ,CLO, ULDO3, ULD12, ULD48, U1TO3, U1T12, U1T48, UDLO3, UDL12, UDF	PE1B2	36.55										
		POT Bay Arrangements prior to 6/1/99 - 4-Fiber Cross-Connect, per cross-connect			UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ,CLO, ULDO3, ULD12, ULD48, U1TO3, U1T12, U1T48, UDLO3, UDL12, UDF	PE1B4	49.29										
		Physical Collocation - Request Resend of CFA Information, per															
\vdash		CLLI Nonrecurring Collocation Cable Records - per request			CLO CLO	PE1C9 PE1CR		77.71 760.98	489.20	400.00	133.29						
\vdash		Nonrecurring Collocation Cable Records - per request Nonrecurring Collocation Cable Records - VG/DS0 Cable, per			CLO	PETCR		760.98	489.20	133.29	133.29						
		cable record			CLO	PE1CD		327.65	327.65	189.54	189.54						
		Nonrecurring Collocation Cable Records - VG/DS0 Cable, per															
		each 100 pair			CLO	PE1CO		4.82	4.82	5.91	5.91						
\vdash		Nonrecurring Collocation Cable Records - DS1, per T1TIE Nonrecurring Collocation Cable Records - DS3, per T3TIE			CLO CLO	PE1C1 PE1C3		2.26 7.90	2.26 7.90	2.77 9.68	2.77 9.68						
\vdash		Nonrecurring Collocation Cable Records - Bos, per 13112 Nonrecurring Collocation Cable Records - Fiber Cable, per 99			CLO	FLICS		7.50	7.50	9.00	9.00				1		
		fiber records			CLO	PE1CB		84.68	84.68	77.30	77.30						
		Physical Collocation - Security Escort - Basic, per Half Hour			CLO,CLORS	PE1BT		16.96	10.75								
		Physical Collocation - Security Escort - Overtime, per Half Hour			CLO,CLORS	PE1OT		22.10	13.89								
		Physical Collocation - Security Escort - Premium, per Half Hour			CLO,CLORS	PE1PT		27.23	17.02								
		V to P Conversion, Per Customer Request-Voice Grade			CLO	PE1BV		33.00	17.02								
		V to P Conversion, Per Customer Request-DS0			CLO	PE1BO		33.00									
		V to P Conversion, Per Customer Request-DS1			CLO	PE1B1		52.00									
		V to P Conversion, Per Customer request-DS3			CLO	PE1B3		52.00									
		V to P Conversion, Per Customer Request per VG Circuit Reconfigured			CLO	PE1BR		23.00									
		V to P Conversion, Per Customer Request per DS0 Circuit Reconfigured			CLO	PE1BP		23.00									
-		V to P Conversion, Per Customer Request per DS1 Circuit			CLO	FLIDE		23.00									
igsqcut		Reconfigured			CLO	PE1BS		33.00									
		V to P Conversion, Per Customer Request per DS3 Circuit Reconfigured			CLO	PE1BE		37.00									
		V to P Conversion, Cable Pairs Assigned to Collo Space per 700 prs or fraction thereof			CLO	PE1B7		592.00									
		Physical Collocation - Co-Carrier Cross Connects - Fiber Cable Support Structure, per cable, per linear ft.			CLO,UDF	PE1ES	0.001										
		Physical Collocation - Co-Carrier Cross Connects - Copper/Coax		1													
$\vdash \vdash$		Cable Support Structure, per cable, per lin. ft. Physical Collocation - Co-Carrier Cross Connects Only -			CLO, UE3, USL	PE1DS	0.0015										
 -		Application Fee, per application Physical Collocation - Application to Augment Exsisting Space -			CLO	PE1DT		584.42									-
		Simple			CLO	PE1KS		594.27		1.21							
		Physical Collocation - Application to Augment Exsisting Space - Minor			CLO	PE1KM		833.26		1.21							
		Physical Collocation - Application to Augment Exsisting Space - Intermediate			CLO	PE1K1		1,058.00		1.21							
ADJACE		LLOCATION			0.010	DE / 1:											
1		Adjacent Collocation - Space Charge per Sq. Ft. Adjacent Collocation - Electrical Facility Charge per Linear Ft.	<u> </u>		CLOAC CLOAC	PE1JA PE1JC	0.0939 6.40							ļ	-	ļ	ļ

COLI	OCAT	ION - South Carolina												Attach	ment: 4	Exhi	bit: B
0022	-00/11	Court Garonna										Svc Order	Svc Order	Incremental		Incremental	Incremental
												Submitted	Submitted		Charge -	Charge -	Charge -
												Elec		Manual Svc	Manual Svc	Manual Svc	Manual Svc
CATE	GORY	RATE ELEMENTS	Interi	Zone	BCS	USOC			RATES (\$)			per LSR	per LSR	Order vs.	Order vs.	Order vs.	Order vs.
			m									per LSK	per LSK				
														Electronic-	Electronic-	Electronic-	Electronic-
														1st	Add'l	Disc 1st	Disc Add'l
				1		1		Nonrec	urring	Nonrecurring	Disconnoct		l .	066	Rates (\$)	l .	
				1			Rec			First		SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
		A Francis College Control Control			01.040	DE 4 DO	0.0004	First	Add'I		Add'l	SOMEC	SUMAN	SUMAN	SUMAN	SUMAN	SUMAN
		Adjacent Collocation - 2-Wire Cross-Connects			CLOAC	PE1P2	0.0264	12.32	11.83	6.04	5.45						
					UEA,UHL,UDL,UCL,												
		Adjacent Collocation - 4-Wire Cross-Connects			CLOAC	PE1P4	0.0527	12.42	11.90	6.40	5.74						
		Adjacent Collocation - DS1 Cross-Connects			USL,CLOAC	PE1P1	1.03	22.08	15.96	6.42	5.80						
		Adjacent Collocation - DS3 Cross-Connects			CLOAC	PE1P3	14.00	20.94	15.23	7.39	5.93						
		Adjacent Collocation - 2-Fiber Cross-Connect			CLOAC	PE1F2	2.37	20.94	15.23	7.40	5.93						
		Adjacent Collocation - 4-Fiber Cross-Connect			CLOAC	PE1F4	4.53	25.61	19.90	9.73	8.26						
		Adjacent Collocation - Application Fee			CLOAC	PE1JB		1,580.20									
		Adjacent Collocation - 120V, Single Phase Standby Power Rate															
		per AC Breaker Amp			CLOAC	PE1FB	5.67										
		Adjacent Collocation - 240V, Single Phase Standby Power Rate			.	T	2.07										
		per AC Breaker Amp	1		CLOAC	PE1FD	11.36						1				
-	1	Adjacent Collocation - 120V, Three Phase Standby Power Rate	 	1	525/10		11.50			1		1	l		1	1	
		per AC Breaker Amp	1		CLOAC	PE1FE	17.03						1				
-	1		1	1	CLOAC	FEIFE	17.03			-		1			-		
1		Adjacent Collocation - 277V, Three Phase Standby Power Rate			01.040	DE450	00.00						l				
	<u> </u>	per AC Breaker Amp	<u> </u>	 	CLOAC	PE1FG	39.33			ļ			ļ				
PHYSI	CAL CO	LLOCATION IN THE REMOTE SITE															
		Physical Collocation in the Remote Site - Application Fee			CLORS	PE1RA		308.38	308.38	168.60	168.60						
		Cabinet Space in the Remote Site per Bay/ Rack			CLORS	PE1RB	246.44										
		Physical Collocation in the Remote Site - Security Access - Key			CLORS	PE1RD		13.13	13.13								
		Physical Collocation in the Remote Site - Space Availability															
		Report per Premises Requested			CLORS	PE1SR		116.13	116.13								
		Physical Collocation in the Remote Site - Remote Site CLLI															
		Code Request, per CLLI Code Requested			CLORS	PE1RE		37.64	37.64								
-		Remote Site DLEC Data (BRSDD), per Compact Disk, per CO		1	CLORS	PE1RR		234.50	37.04								
DUVE	CAL CO	LLOCATION IN THE REMOTE SITE - ADJACENT		1	CLORG	FLIKK		234.30							-		
FHISI	CAL CO	LEOCATION IN THE REMOTE SITE - ADJACENT				-											
		D			01.000	DE 4 DO	0.07										
		Remote Site-Adjacent Collocation - AC Power, per breaker amp			CLORS	PE1RS	6.27										
		Remote Site-Adjacent Collocation - Real Estate, per square foot			CLORS	PE1RT	0.134										
		Remote Site-Adjacent Collocation-Application Fee			CLORS	PE1RU		755.62	755.62								
		If Security Escort and/or Add'l Engineering Fees become nec	essary 1	for remo	ote site collocation,	the Parties v	vill negotiate ap	opropriate rate	s.								
VIRTU	AL COL	LOCATION															
		Virtual Collocation - Application Fee			AMTFS	EAF		1,207.95	1,207.95	0.51	0.51		15.69				
		Virtual Collocation - Cable Installation Cost, per cable			AMTFS	ESPCX		794.22	794.22	22.54	22.54		15.69				
		Virtual Collocation - Floor Space, per sq. ft.	1		AMTFS	ESPVX	3.95	-									
		Virtual Collocation - Power, per fused amp			AMTFS	ESPAX	9.19					1	1		1		
1	1	Virtual Collocation - Cable Support Structure, per entrance	1	1	··· •	1	5					t	1		t		
		cable	1		AMTFS	ESPSX	18.66						1				
-	1	Cabic	 	1	UEANL,UEA,UDN,U	LOI OA	10.00			1		1	l		1	1	
			1]						1				
1					DC,UAL,UHL,UCL,U]]		1	1	
1					EQ, AMTFS, UDL,]]		1	1	
1					UNCVX, UNCDX,	l	l				_		l				
		Virtual Collocation - 2-wire Cross Connects (loop)			UNCNX	UEAC2	0.0317	12.32	11.83	6.04	5.45		15.69				
							1						l				
1					UEA,UHL,UCL,UDL,]]		1	1	
1					AMTFS, UAL, UDN,]]		1	1	
		Virtual Collocation - 4-wire Cross Connects (loop)			UNCVX, UNCDX	UEAC4	0.0634	12.42	11.90	6.40	5.74		15.69				
					AMTFS,UDL12,												
					UDLO3, U1T48,		1						l				
			1		U1T12, U1T03,]						1				
			1		ULDO3, ULD12,]					1	1				
		Virtual Collocation - 2-Fiber Cross Connects			ULD48, UDF	CNC2F	2.86	20.94	15.23	7.40	5.93		15.69				
-	1	VIII CONOCATION - 2-1 IDEI CIOSS CONTIECES	1		AMTFS,UDL12,	011021	2.00	20.54	15.23	7.40	5.93	+	13.09		 	-	
			1]					1	1				
					UDLO3, U1T48,								l				
					U1T12, U1T03,								l				
1					ULDO3, ULD12,	0.10:-											
		Virtual Collocation - 4-Fiber Cross Connects			ULD48, UDF	CNC4F	5.71	25.61	19.90	9.73	8.26	1	15.69		1	l	

RATE ELEMENTS Intering Dane BCS USC STATE (S) STATE (S	ULLUCAT	ON - South Carolina		ı		T					1 -			ment: 4	1	bit: B
Virtual collocation - Special Access & UNE, cross-connect par Virtual collocation - Special Access & UNE, cross-connect par Virtual collocation - Special Access & UNE, cross-connect par Virtual collocation - Special Access & UNE, cross-connect par Virtual collocation - Special Access & UNE, cross-connect par Virtual collocation - Special Access & UNE, cross-connect par Virtual collocation - Special Access & UNE, cross-connect par Virtual collocation - Special Access & UNE, cross-connect par Virtual Collocation - Co-Carrier Cross Connects - CopperCost Virtual Collocation - Co-Carrier Cross - Connect - CopperCost Virtual Collocation - Co-Carrier Cross - Connect - CopperCost Virtual Collocatio	ATEGORY	RATE ELEMENTS	Zone	BCS	usoc			RATES (\$)			Submitted Elec	Submitted Manually	Charge - Manual Svc Order vs. Electronic- 1st	Charge - Manual Svc Order vs. Electronic- Add'l	Charge -	Incrementa Charge - Manual Svo Order vs. Electronic- Disc Add'l
Virtual colocation - Special Access & UNE, cross-connect per USL ULC AMPTS, UNCX ULDOTS, UNCX ULDOTS, UNCX ULDOTS, UNCX ULDOTS, UNCX ULDOS, UTTD, UNCX U						Rec										
Virtual collocation - Special Access & UNE, cross-connect per UNE, CALCITY UNEST, ULDOS, UNEST						Nec	First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
E3, UTR3, UTR1, UTR1, UTR1, UTR1, UTR1, UTR1, UTR3, UNCSX, UNCS				ULR, UXTD1, UNC1X, ULDD1, U1TD1, USLEL, UNLD1	CNC1X	1.12	22.08	15.96	6.42	5.80		15.69				
Windle Collocation - Co-Carrier Cross Connects - Fiber Cable Support Structure, per linear for				E3, U1TD3, UXTS1, UXTD3, UNC3X, UNCSX, ULDD3, U1TS1, ULDS1,	CND3X	14 21	20.94	15 23	7 30	5 93		15 69				
Support Structure, per linear front	+			ODLOX, ONLDS	CINDOX	17.21	20.34	13.23	7.55	5.95		10.00				
Cable Support Structure, per Inlear ft AMTFS VETCD 0.0033		Support Structure, per linear foot		AMTFS	VE1CB	0.0022										
Support Structure, per cable				AMTFS	VE1CD	0.0033										
Virtual Collocation Cable Records - Virtual Collocation Cable Records - Virtual Collocation Cable Records - Virtual Collocation Cable Records - Virtual Collocation Cable Records - Virtual Collocation Cable Records - Virtual Collocation Cable Records - Virtual Collocation Cable Records - Virtual Collocation Cable Records - Virtual Collocation Cable Records - Virtual Collocation Cable Records - Virtual Collocation Cable Records - Virtual Collocation Cable Records - Virtual Collocation Cable Records - Virtual Collocation Cable Records - DS3, per T3TIE						3,3333										
Cable Support Structure, per cable				AMTFS	VE1CC		536.56									
Mittual Collocation Cable Records - VG/DSO Cable, per cable AMTFS VE1BA 760,98 489,20 133,29 133,29																
Virtual Collocation Cable Records - VG/DSO Cable, per cable record AMTFS VE1BB 327.65 327.65 189.54 189.54																
Record				AMTFS	VE1BA		760.98	489.20	133.29	133.29						
100 pair		record		AMTFS	VE1BB		327.65	327.65	189.54	189.54						
Virtual Collocation Cable Records - DSA, per T3TIE				AMTFS	VE1BC		4.82	4.82	5.91	5.91						
Virtual Collocation Cable Records - Fiber Cable, per 99 fiber records AMTFS VE1BF 84.68 84.68 77.30 77.30		Virtual Collocation Cable Records - DS1, per T1TIE		AMTFS	VE1BD		2.26	2.26	2.77	2.77						
Records				AMTFS	VE1BE		7.90	7.90	9.68	9.68						
Virtual collocation - Security Escort - Basic, per half hour AMTFS SPTDX 16.96 10.75 15.69				AMTFS	VE1BF		84.68	84.68	77.30	77.30						
Virtual collocation - Security Escort - Premium, per half hour AMTFS SPTPX 27.23 17.02 15.69		Virtual collocation - Security Escort - Basic, per half hour		AMTFS	SPTBX		16.96	10.75				15.69				
Virtual collocation - Maintenance in CO - Basic, per half hour AMTFS CTRLX 27.99 10.75 15.69		Virtual collocation - Security Escort - Overtime, per half hour		AMTFS	SPTOX		22.10	13.89				15.69				
Virtual collocation - Maintenance in CO - Overtime, per half hour AMTFS SPTOM 36.56 13.89 15.69																
Virtual collocation - Maintenance in CO - Premium per half hour AMTFS SPTPM 45.12 17.02 15.69		Virtual collocation - Maintenance in CO - Basic, per half hour		AMTFS	CTRLX		27.99	10.75				15.69				
VIRTUAL COLLOCATION Virtual Collocation - 2-wire Cross Connect, Exchange Port 2- Wire Analog - Res UEPSR VE1R2 0.0317 12.32 11.83 6.04 5.45 15.69 Virtual Collocation 2-Wire Cross Connect, Exchange Port 2- Wire Line Side PBX Trunk - Bus UEPSP VE1R2 0.0317 12.32 11.83 6.04 5.45 15.69 Virtual Collocation 2-Wire Cross Connect, Exchange Port 2-Wire Voice Grade PBX Trunk - Res UEPSE VE1R2 0.0317 12.32 11.83 6.04 5.45 15.69 Virtual Collocation 2-Wire Cross Connect, Exchange Port 2-Wire Analog Bus UEPSB VE1R2 0.0317 12.32 11.83 6.04 5.45 15.69 Virtual Collocation 2-Wire Cross Connect, Exchange Port 2-Wire ISDN UEPSB VE1R2 0.0317 12.32 11.83 6.04 5.45 15.69 VETR2 0.0317 12.32 11.83 6.04 5.45 15.69		Virtual collocation - Maintenance in CO - Overtime, per half hour		AMTFS	SPTOM		36.56	13.89				15.69				
Virtual Collocation - 2-wire Cross Connect, Exchange Port 2-				AMTFS	SPTPM		45.12	17.02				15.69				
Wire Analog - Res	RTUAL COL															
Wire Line Side PBX Trunk - Bus UEPSP VE1R2 0.0317 12.32 11.83 6.04 5.45 15.69				UEPSR	VE1R2	0.0317	12.32	11.83	6.04	5.45		15.69				
Virtual Collocation 2-Wire Cross Connect, Exchange Port 2-Wire Voice Grade PBX Trunk - Res UEPSE VE1R2 0.0317 12.32 11.83 6.04 5.45 15.69 VIrtual Collocation 2-Wire Cross Connect, Exchange Port 2-Wire Analog Bus UEPSB VE1R2 0.0317 12.32 11.83 6.04 5.45 15.69 VIrtual Collocation 2-Wire Cross Connect, Exchange Port 2-Wire SDN UEPSX VE1R2 0.0317 12.32 11.83 6.04 5.45 15.69 VE1R2 VE1R2 VE1R2 0.0317 12.32 11.83 6.04 5.45 15.69 VE1R2 VE1R		Virtual Collocation 2-Wire Cross Connect, Exchange Port 2-			VF1R2											
Virtual Collocation 2-Wire Cross Connect, Exchange Port 2-Wire UEPSB VE1R2 0.0317 12.32 11.83 6.04 5.45 15.69		Virtual Collocation 2-Wire Cross Connect, Exchange Port 2-Wire														
Analog Bus				UEPSE	VE1R2	0.0317	12.32	11.83	6.04	5.45		15.69				
ISDN		Analog Bus		UEPSB	VE1R2	0.0317	12.32	11.83	6.04	5.45		15.69				
ISDN UEPTX VE1R2 0.0317 12.32 11.83 6.04 5.45 15.69		ISDN		UEPSX	VE1R2	0.0317	12.32	11.83	6.04	5.45		15.69				
				UEPTX	VE1R2	0.0317	12.32	11.83	6.04	5.45		15.69				
Virtual Collocation 4-Wire Cross Connect, Exchange Port 4-Wire ISDN DS1 UEPEX VE1R4 1.12 22.08 15.96 6.42 5.80 15.69		Virtual Collocation 4-Wire Cross Connect, Exchange Port 4-Wire														

COLLOCAT	ION - Tennessee												Attach	ment: 4	Exhi	ibit: B
CATEGORY	RATE ELEMENTS	Interi m	Zone	BCS	USOC			RATES (\$)			Submitted Elec per LSR	Svc Order Submitted Manually per LSR	Incremental Charge - Manual Svc Order vs. Electronic- 1st	Charge - Manual Svc Order vs. Electronic- Add'l	Charge -	Incremental Charge - Manual Svc Order vs. Electronic- Disc Add'l
						Rec	Nonrecurring First	Add'l	Nonrecurring First	g Disconnect Add'l		SOMAN	OSS SOMAN	Rates (\$) SOMAN	SOMAN	SOMAN
							101	7144		71441	0020			00		
PHYSICAL CO																
	Physical Collocation 2-Wire Cross Connect, Exchange Port 2- Wire Analog - Res			UEPSR	PE1R2	0.30	19.20	19.20					20.35	10.54	13.32	1.40
	Physical Collocation 2-Wire Cross Connect, Exchange Port 2-			02. 0.0		0.00	10.20	10.20					20.00	10.01	10.02	
	Wire Line Side PBX Trunk - Bus			UEPSP	PE1R2	0.30	19.20	19.20					20.35	10.54	13.32	1.40
	Physical Collocation 2-Wire Cross Connect, Exchange Port 2-			LIEDOE	DE4D0	0.00	40.00	40.00					00.05	40.54	40.00	4.40
-	Wire Voice Grade PBX Trunk - Res Physical Collocation 2-Wire Cross Connect, Exchange Port 2-			UEPSE	PE1R2	0.30	19.20	19.20					20.35	10.54	13.32	1.40
	Wire Analog - Bus			UEPSB	PE1R2	0.30	19.20	19.20					20.35	10.54	13.32	1.40
	Physical Collocation 2-Wire Cross Connect, Exchange Port 2-															
	Wire ISDN			UEPSX	PE1R2	0.30	19.20	19.20					20.35	10.54	13.32	1.40
	Physical Collocation 2-Wire Cross Connect, Exchange Port 2- Wire ISDN			UEPTX	PE1R2	0.30	19.20	19.20					20.35	10.54	13.32	1.40
	Physical Collocation 4-Wire Cross Connect, Exchange Port 4-															
PHYSICAL CO	Wire ISDN DS1			UEPEX	PE1R4	0.50	19.20	19.20					20.35	10.54	13.32	1.40
PHYSICAL CO	Physical Collocation - Cageless - Application Fee			CLO	PE1CH		2,633.00	2,633.00	1		-					
	Physical Collocation - Cageless - Application - ee Physical Collocation Administrative Only - Application Fee			CLO	PE1BL		743.25	2,055.00								
	Physical Collocation - Space Preparation - Firm Order	i		CLO	PE1SJ		1,204.00	1,204.00								
	Physical Collocation - Space Preparation - C.O. Modification per						.,	.,								
	square ft.	- 1		CLO	PE1SK	2.74										
	Physical Collocation - Space Preparation - Common Systems Modification per square ft Cageless	_		CLO	PE1SL	2.95										
	Physical Collocation - Space Preparation - Common Systems															
	Modification per Cage	ı		CLO	PE1SM	100.14										
	Physical Collocation - Cageless - Cable Installation Cost, per cable			CLO	PE1ZA		1,749.00									
	Physical Collocation - Cageless - Floor Space, per sq. ft.			CLO	PE1ZB	3.91	.,									
	Physical Collocation - Floor Space per Sq. Ft.	- 1		CLO	PE1PJ	5.94										
	Physical Collocation - Cageless - Cable Support Structure			CLO	PE1CJ	17.87										
	Physical Collocation - Cable Support Structure, Per Entrance															
	Cable	- 1		CLO	PE1PM	19.80										
	Physical Collocation - Cageless - Floor Space Power, per Fused															
	Amp			CLO	PE1ZC	6.79										
-	Physical Collocation - Power -48V DC Power, per Fused Amp			CLO CLO	PE1PL PE1PR	8.87	400.40				-					
-	Physical Collocation - Power Reduction, Application Fee	- 1		CLO	PETPR		400.10				-					
	Physical Collocation - 120V, Single Phase Standby Power Rate	1		CLO	PE1FB	5.60										
	Physical Collocation - 240V, Single Phase Standby Power Rate			CLO	PE1FD	11.22										
	Physical Collocation - 240V, Single Phase Standby Power Rate	-		CLO	PEIFU	11.22										
	Physical Collocation - 120V, Three Phase Standby Power Rate	I		CLO	PE1FE	16.82										
	Physical Collocation - 277V, Three Phase Standby Power Rate	ı		CLO	PE1FG	38.84										
	Physical Collocation - 2-Wire Cross-Connects	ı		UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ, UDL, UNCVX, UNLDX, UNCNX	PE1P2	0.033	33.82	31.92								
				CLO, UAL, UDL, UDN, UEA, UHL, UNCVX, UNCDX,												
	Physical Collocation - 4-Wire Cross-Connects	I		UCL	PE1P4	0.066	33.94	31.95								

COLLOCAT	ION - Tennessee													ment: 4		bit: B
CATEGORY	RATE ELEMENTS	Interi m	Zone	BCS	usoc			RATES (\$)			Svc Order Submitted Elec per LSR	Svc Order Submitted Manually per LSR	Incremental Charge - Manual Svc Order vs. Electronic- 1st	Incremental Charge - Manual Svc Order vs. Electronic- Add'I	Charge -	Incremental Charge - Manual Svc Order vs. Electronic- Disc Add'l
						Rec	Nonrecurring First	Add'l	Nonrecurring First	Disconnect Add'l	001150	SOMAN		Rates (\$) SOMAN	SOMAN	SOMAN
				CLO,UEANL,UEQ,W DS1L,WDS1S, USL, U1TD1, UXTD1, UNC1X, ULDD1, USLEL, UNLD1,			FIISL	Add 1	FIISL	Addi	SOMEC	SUMAN	SOMAN	SOMAN	SOMAN	SOMAN
	Physical Collocation - DS1 Cross-Connects	1		UDL	PE1P1	1.51	53.27	40.16								
	Physical Collocation - DS3 Cross-Connects	I		CLO, UE3,U1TD3, UXTD3, UXTS1, UNC3X, UNCSX, ULDD3, U1TS1,ULDS1, UNLD3, UDL	PE1P3	19.26	52.37	38.89								
	Physical Collocation - 2-Fiber Cross-Connect	ı		CLO, ULDO3, ULD12, ULD48, U1TO3, U1T12, U1T48, UDLO3, UDL12, UDF CLO, ULDO3,	PE1F2	15.64	41.56	29.82	12.96	10.34			2.69	2.69	1.56	1.56
	Physical Collocation - Cageless - 2-Fiber Cross-Connect			ULD12, ULD48, U1TO3, U1T12, U1T48, UDLO3, UDL12, UDF CLO, ULDO3,	PE1CK	3.03	41.56	29.82	12.96	10.34						
	Physical Collocation - 4-Fiber Cross-Connect	I		ULD12, ULD48, U1TO3, U1T12, U1T48, UDLO3, UDL12, UDF	PE1F4	28.11	50.53	38.78	16.97	14.35			2.69	2.69	1.56	1.56
	Physical Collocation - Cageless - 4-Fiber Cross-Connect			CLO, ULDO3, ULD12, ULD48, U1TO3, U1T12, U1T48, UDLO3, UDL12, UDF	PE1CL	6.06	50.53	38.78	16.97	14.35						
	Physical Collocation - Welded Wire Cage - First 100 Sq. Ft.	ı		CLO	PE1BW	218.53										
	Physical Collocation - Welded Wire Cage - Add'l 50 Sq. Ft. Physical Collocation - Security Access System - Security System			CLO	PE1CW	21.44										
	per Central Office Physical Collocation - Security Access System - New Access			CLO	PE1AX	55.99										
	Card Activation, per Card Physical Collocation-Security Access System-Administrative			CLO	PE1A1	0.059	55.67	55.67								
	Change, existing Access Card, per Request, per State, per Card Physical Collocation - Security Access System - Replace Lost or			CLO	PE1AA		15.61	15.61								
	Stolen Card, per Card		<u> </u>	CLO	PE1AR		45.64	45.64								
	Physical Collocation - Security Access - Initial Key, per Key Physical Collocation - Security Access - Key, Replace Lost or		 	CLO	PE1AK		26.24	26.24								
	Stolen Key, per Key			CLO	PE1AL		26.24	26.24								
	Physical Collocation - Space Availability Report per premises POT Bay Arrangements prior to 6/1/99 - 2-Wire Cross-Connect, per cross-connect	ı		CLO UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ,CLO,UDL, UNCVX, UNCDX, UNCNX	PE1SR PE1PE	0.40	2,027.00	2,154.00								
	POT Bay Arrangements prior to 6/1/99 - 4-Wire Cross-Connect, per cross-connect	I		UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ,CLO, USL,	PE1PF	1.20										

COLLOCAT	ION - Tennessee												Attach	ment: 4	Exhi	bit: B
CATEGORY	RATE ELEMENTS	Interi m	Zone	BCS	usoc			RATES (\$)			Svc Order Submitted Elec per LSR	Svc Order Submitted Manually per LSR	Incremental Charge - Manual Svc Order vs. Electronic- 1st	Incremental Charge - Manual Svc Order vs. Electronic- Add'l	Incremental Charge - Manual Svc Order vs. Electronic- Disc 1st	Incremental Charge - Manual Svo Order vs. Electronic- Disc Add'l
						_	Nonrecurring		Nonrecurring	g Disconnect			oss	Rates (\$)	L	L
						Rec	First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
	POT Bay Arrangements prior to 6/1/99 - DS1 Cross-Connect, per cross-connect	ı		UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ,CLO,WDS1L,W DS1S, USL, U1TD1, UXTD1, UNC1X, ULDD1, USLEL, UNLD1	PE1PG	1.20										
	POT Bay Arrangements prior to 6/1/99 - DS3 Cross-Connect, per cross-connect	ı		UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ,CLO,UE3, U1TD3, UXTD3, UXTS1, UNC3X, UNCSX, ULDD3, U1TS1, ULDS1, UNLD3, UDL, UDLSX	PE1PH	8.00										
	POT Bay Arrangements prior to 6/1/99 - 2-Fiber Cross-Connect, Per Cross-Connect			UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ,CLO, ULDO3, ULD12, ULD48, U1TO3, U1T12, U1T48, UDLO3, UDL12, UDF	PE1PH	38.79										
	POT Bay Arrangements prior to 6/1/99 - 4-Fiber Cross-Connect, per cross-connect			UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U EQ,CLO, ULDO3, ULD12, ULD48, U1TO3, U1T12, U1T48, UDLO3, UDL12, UDF	PE1B4	52.31										
	Physical Collocation - Request Resend of CFA Information, per				DE 100											
	CLLI Nonrecurring Collocation Cable Records - per request	-		CLO CLO	PE1C9 PE1CR		77.67 1,711.00		1							
	Nonrecurring Collocation Cable Records - VG/DS0 Cable, per cable record	i		CLO	PE1CD		925.06									
	Nonrecurring Collocation Cable Records - VG/DS0 Cable, per															
	each 100 pair			CLO	PE1CO		18.05	18.05								
	Nonrecurring Collocation Cable Records - DS1, per T1TIE Nonrecurring Collocation Cable Records - DS3, per T3TIE	-		CLO CLO	PE1C1 PE1C3	-	8.45 29.57	8.45 29.57	+		1				-	
	Nonrecurring Collocation Cable Records - Fiber Cable, per 99 fiber records	j		CLO	PE1CB		279.42	279.42								
	Physcial Collocation - Cageless - Security Escort - Basic, per Half Hour			CLO	PE1ZM		33.15	20.44								
	Physical Collocation - Cageless - Security Escort - Overtime, per Half Hour			CLO	PE1ZN		41.50	25.61								
	Physical Collocation - Cageless - Security Escort - Premium, per Half Hour			CLO	PE1ZO		49.86	30.79								
	Physical Collocation - Security Escort - Basic, per Half Hour		<u> </u>	CLO,CLORS	PE1BT		33.91	21.49			1				ļ	ļ
	Physical Collocation - Security Escort - Overtime, per Half Hour		<u> </u>	CLO,CLORS	PE1OT		44.17	27.76								
	Physical Collocation - Security Escort - Premium, per Half Hour	<u> </u>	1	CLO,CLORS	PE1PT		54.42	34.02	_							
	V to P Conversion, Per Customer Request-Voice Grade V to P Conversion, Per Customer Request-DS0	-		CLO CLO	PE1BV PE1BO		33.00 33.00		+	 	1				 	
	V to P Conversion, Per Customer Request-DS0 V to P Conversion, Per Customer Request-DS1	H	-	CLO	PE1BO PE1B1	1	52.00		+	+	+			-	-	-
- 	V to P Conversion, Per Customer request-DS3			CLO	PE1B3		52.00		 	-	+			 	†	†
	V to P Conversion, Per Customer Request per VG Circuit Reconfigured	i		CLO	PE1BR		23.00									
	V to P Conversion, Per Customer Request per DS0 Circuit Reconfigured	1		CLO	PE1BP		23.00									

COLLOCAT	ION - Tennessee			ı		1					1			ment: 4		ibit: B
CATEGORY	RATE ELEMENTS	Interi m	Zone	BCS	USOC			RATES (\$)				Submitted Manually	Incremental Charge - Manual Svc Order vs. Electronic- 1st	Incremental Charge - Manual Svc Order vs. Electronic- Add'I	Incremental Charge - Manual Svc Order vs. Electronic- Disc 1st	Incremental Charge - Manual Svc Order vs. Electronic- Disc Add'l
						Rec	Nonrecurring			g Disconnect				Rates (\$)		
	VI DO DO DO DO DO DO DO DO DO DO DO DO DO					1100	First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
	V to P Conversion, Per Customer Request per DS1 Circuit Reconfigured			CLO	PE1BS		33.00									
	V to P Conversion, Per Customer Request per DS3 Circuit			OLO	I LIBO		33.00									
	Reconfigured	I		CLO	PE1BE		37.00									
	V to P Conversion, Cable Pairs Assigned to Collo Space per 700															
-	prs or fraction thereof Physical Caged Collocation-App Cost(initial & sub)-Planning,	- 1		CLO	PE1B7		592.00								1	
	per request			CLO	PE1AC	16.16	2,903.66	2,903.66								
							_,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	_,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,								
	Physical Caged Collocation-Space Prep-Grounding, per location			CLO	PE1BB	4.32										
	Physical Caged Collocation-Space Prep-Power Delivery, per 40			CI O	DEACN		140.40									
	amp Feed Physical Caged Collocation-Space Prep-Power Delivery, per 100			CLO	PE1SN		142.40				1				-	+
	amp Feed			CLO	PE1SO		185.72									
	Physical Caged Collocation-Space Prep-Power Delivery, per 200															
	amp Feed			CLO	PE1SP		242.05									<u> </u>
	Physical Caged Collocation-Space Enclosure-Cage Preparation, per first 100 sq. ft.			CLO	PE1S1	110.97										
	Phycical Caged Collocation-Space Enclosure-Cage			OLO	1 2 101	110.57										†
	Preparation2, per add'l 50 sq. ft.			CLO	PE1S5	55.49										
	Physical Caged collocation-Cable Installation-Entrance Fiber															
	Structure, interduct per ft. Phycical Caged Collocation-Cable Installation-Entrance Fiber,			CLO	PE1CP	0.0156										4
	per cable			CLO	PE1CQ	2.56	944.27									
	Physical Caged Collocation-Floor Space-Land & Buildings, per						-									1
	sq. ft.			CLO	PE1FS	5.94										
	Physical Caged Collocation-Cable Support Structure-Cable Racking, per entrance cable			CLO	PE1CS	21.47										
	Physical Caged Collocation-Power-Power Construction, per amp			CLO	PEICS	21.47					1				1	
	DC plant			CLO	PE1PN	3.55										
	Physical Caged Collocation-Power-Power Consumption,per amp															
	AC usage Physical Caged Collocation-2-wire Cross Connects-Voice Grade			CLO	PE1PO	2.03										<u> </u>
	ckts, per ckt.			CLO	PE12C	0.0475	7.68									
	Physical Caged Collocation-4-wire Cross Connects-Voice Grade			020		0.0110	7.00									1
	Ckts, per ckt.			CLO	PE14C	0.0475	7.68									
	Physical Caged Collocation-DS1 Cross Connects-connection to DCS, per ckt.			CLO	DE440	7.00	44.05									
	Physical Caged Collocation-DS1 Cross Connects-Connection to			CLO	PE11S	7.68	41.65				1				1	+
	DSX, per ckt.			CLO	PE11X	0.38	41.65									
	Physical Caged Collocation-DS3 Cross Connects-Connection to															
	DCS, per ckt.		<u> </u>	CLO	PE13S	53.96	298.03				1					
	Physical Caged Collocation-DS3 Cross Connects-Connection to DSX, per ckt.			CLO	PE13X	9.32	298.03									
	Physical Caged Collocation-Security Access-Access Cards, per		<u> </u>		. 2.5%	0.02	200.00				<u> </u>				t	
	5 Cards			CLO	PE1A2		76.10									
	Physical Collocation - Co-Carrier Cross Connects - Fiber Cable			CLO LIDE	DE450	0.0045										
	Support Structure, per cable, per linear ft. Physical Collocation - Cageless - Co-Carrier Cross Connects -		<u> </u>	CLO,UDF	PE1ES	0.0013					-					
	Fiber Cable Support Structure, per linear ft.			CLO	PE1ZH	0.0031										
	Physical Collocation - Cageless - Co-Carrier Cross Connects-															
	Fiber Cable Support Structure, per cable		ļ	CLO	PE1ZK		555.03									
	Physical Collocation - Co-Carrier Cross Connects - Copper/Coax Cable Support Structure, per cable, per lin. ft.			CLO	PE1DS	0.0019										
	Physical Collocation - Cageless - Co-Carrier Cross Connects -		1	OLO	FLIDS	0.0019				†						
	Copper/Coax Cable Support Structure, per linear ft.		<u>L</u>	CLO	PE1ZJ	0.0045					<u> </u>					
	Physical Collocation - Cageless - Co-Carrier Cross Connects -															
	Copper/Coax Cable Support Structure, per cable		<u> </u>	CLO	PE1ZL		555.03							l	1	<u> </u>

COLLOCAT	TION - Tennessee													ment: 4		ibit: B
CATEGORY	RATE ELEMENTS	Interi m	Zone	BCS	USOC			RATES (\$)			Svc Order Submitted Elec per LSR	Svc Order Submitted Manually per LSR	Incremental Charge - Manual Svc Order vs. Electronic- 1st	Incremental Charge - Manual Svc Order vs. Electronic- Add'l	Charge -	Incremental Charge - Manual Svc Order vs. Electronic- Disc Add'l
						Rec	Nonrecurring		Nonrecurring	Disconnect		•	oss	Rates (\$)	•	•
						Rec	First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
	Physical Collocation - Co-Carrier Cross Connects Only -															
	Application Fee, per application			CLO	PE1DT		585.09									
ADJACENT C	OLLOCATION															
	Adjacent Collocation - Space Charge per Sq. Ft.			CLOAC	PE1JA	0.0656										
	Adjacent Collocation - Electrical Facility Charge per Linear Ft.			CLOAC	PE1JC	5.53										
	Adjacent Collocation - 2-Wire Cross-Connects			CLOAC	PE1P2	0.34	11.12	10.18	11.33	10.23			1.77	1.77	1.12	1.12
	Adianat Callantina A Wina Carra Carranta			UEA,UHL,UDL,UCL, CLOAC	PE1P4	0.00	44.20	40.04	44.00	10.44			1.77	4 77	1.12	4.40
	Adjacent Collocation - 4-Wire Cross-Connects Adjacent Collocation - DS1 Cross-Connects			USL,CLOAC	PE1P4 PE1P1	0.33 1.70	11.30 28.39	10.31 16.88	11.62 11.65	10.44			1.77	1.77 1.77		1.12 1.12
	Adjacent Collocation - DS3 Cross-Connects			CLOAC	PE1P3	19.03	26.23	15.51	13.40	10.54			1.77	1.77		1.12
	Adjacent Collocation - 2-Fiber Cross-Connect			CLOAC	PE1F2	3.49		15.51	13.40	10.77			1.77	1.77		1.12
 	Adjacent Collocation - 2-Fiber Cross-Connect Adjacent Collocation - 4-Fiber Cross-Connect			CLOAC	PE1F4	6.50	29.75	19.02	17.60	14.97	 	 	1.77	1.77	1.12	1.12
	Adjacent Collocation - 4-1 iber Cross-Connect Adjacent Collocation - Application Fee			CLOAC	PE1JB	0.30	2,973.00	13.02	17.00	17.31	 	 	1.77	1.77	1.12	1.12
 	Adjacent Collocation - 120V, Single Phase Standby Power Rate				. 2.02	†	2,0.0.00							1	1	
	per AC Breaker Amp	1		CLOAC	PE1FB	5.81					1	1	1	I	I	
	Adjacent Collocation - 240V, Single Phase Standby Power Rate per AC Breaker Amp			CLOAC	PE1FD	11.64										
	Adjacent Collocation - 120V, Three Phase Standby Power Rate														1	
	per AC Breaker Amp			CLOAC	PE1FE	17.45										
	Adjacent Collocation - 277V, Three Phase Standby Power Rate			CLOAC	PE1FG	40.30										
BUVEICAL C	per AC Breaker Amp DLLOCATION IN THE REMOTE SITE			CLOAC	PETFG	40.30										
PHISICAL C	Physical Collocation in the Remote Site - Application Fee			CLORS	PE1RA	-	580.20		312.76					-	-	
	Cabinet Space in the Remote Site per Bay/ Rack			CLORS	PE1RB	220.41	300.20		312.70							
	Cabinot opase in the Homete Cite per Bay, Hack			020110		220.11										
	Physical Collocation in the Remote Site - Security Access - Key			CLORS	PE1RD		24.69									
	Physical Collocation in the Remote Site - Space Availability															
	Report per Premises Requested			CLORS	PE1SR		218.49									
	Physical Collocation in the Remote Site - Remote Site CLLI															
	Code Request, per CLLI Code Requested			CLORS	PE1RE		70.81									
	Remote Site DLEC Data (BRSDD), per Compact Disk, per CO			CLORS	PE1RR		234.15									
PHYSICAL C	DLLOCATION IN THE REMOTE SITE - ADJACENT															
	Remote Site-Adjacent Collocation - AC Power, per breaker amp			CLORS	PE1RS	6.27										
	Remote Site-Adjacent Collocation - Real Estate, per square foot			CLORS	PE1RT	0.134										
	Remote Site-Adjacent Collocation-Application Fee			CLORS	PE1RU		755.62	755.62								
	: If Security Escort and/or Add'l Engineering Fees become nec	essary f	or rem	ote site collocation,	the Parties v	will negotiate a	ppropriate rate	s.								
VIRTUAL CO		1		AMTEC	EAE	 	2 000 00	2 022 02	ļ —				0.07	0.01	0.07	4.44
	Virtual Collocation - Application Fee Virtual Collocation - Cable Installation Cost, per cable	 	-	AMTFS AMTFS	EAF ESPCX	-	2,633.00 1,749.00	2,633.00 1,749.00	 		 	 	2.07 2.07	2.81 2.81	0.67 0.67	1.41 1.41
	Virtual Collocation - Cable Installation Cost, per cable Virtual Collocation - Floor Space, per sq. ft.	1		AMTFS	ESPVX	3.91	1,749.00	1,749.00	+		 	 	2.07	∠.81	0.67	1.41
	Virtual Collocation - Proof Space, per sq. ft.			AMTFS	ESPAX	6.79										
	Virtual Collocation - Cable Support Structure, per entrance			AWITTO	LOI AX	0.73										
	cable			AMTFS	ESPSX	17.87										
				UEANL,UEA,UDN,U DC,UAL,UHL,UCL,U												
		1		EQ, AMTFS, UDL,		1					1	1	1	I		
	Vitra and California Control C	1		UNCVX, UNCDX,	115460						1	1				
	Virtual Collocation - 2-wire Cross Connects (loop)	 		UNCNX	UEAC2	0.57	11.62	9.90	10.38	8.66			2.07	2.81	0.67	1.41
				UEA,UHL,UCL,UDL, AMTFS, UAL, UDN,												
	Virtual Collocation - 4-wire Cross Connects (loop)	<u> </u>		UNCVX, UNCDX	UEAC4	0.57	11.81	10.04	10.44	8.67			2.07	2.81	0.67	1.41
				AMTFS,UDL12, UDLO3, U1T48, U1T12, U1T03,												
	Virtual Collocation - 2-Fiber Cross Connects			ULDO3, ULD12, ULD48, UDF	CNC2F	3.03	41.56	29.82	12.96	10.34			2.69	2.69	1.56	1.56

COLL	CATIO	ON - Tennessee												Attach	ment: 4	Fxhi	bit: B
33220												Svc Order	Svc Order	Incremental			Incremental
												Submitted	Submitted	Charge -	Charge -	Charge -	Charge -
			Interi									Elec	Manually		Manual Svc	Manual Svc	Manual Svc
CATEG	ORY	RATE ELEMENTS	m	Zone	BCS	USOC			RATES (\$)			per LSR	per LSR	Order vs.	Order vs.	Order vs.	Order vs.
			""											Electronic-	Electronic-	Electronic-	Electronic-
														1st	Add'l	Disc 1st	Disc Add'l
L																	
							Rec	Nonrecurring			g Disconnect				Rates (\$)		
-					ANTEO LIDI 40			First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
					AMTFS,UDL12,												
					UDLO3, U1T48, U1T12. U1T03.												
					ULDO3, ULD12,												
		Virtual Collocation - 4-Fiber Cross Connects			ULD48, UDF	CNC4F	6.06	50.53	38.78	16.97	14.35			2.69	2.69	1.56	1.56
		VII (dai Collocation - 4-1 iber Cross Connects			USL,ULC,AMTFS,	CINC4I	0.00	30.33	30.70	10.97	14.33			2.09	2.09	1.50	1.50
					ULR, UXTD1,												
					UNC1X, ULDD1,												
		Virtual collocation - Special Access & UNE, cross-connect per			U1TD1, USLEL.												
		DS1			UNLD1	CNC1X	1.32	32.22	17.76	10.46	8.75			2.07	2.81	0.67	1.41
					USL,ULC,AMTFS,U												
					E3, U1TD3, UXTS1,												
			l		UXTD3, UNC3X,					1							
					UNCSX, ULDD3,												
		Virtual collocation - Special Acess & UNE, cross-connect per			U1TS1, ULDS1,												
		DS3			UDLSX, UNLD3	CND3X	12.32	29.97	16.30	12.03	8.99			2.07	2.81	0.67	1.41
		Virtual Collocation - Co-Carrier Cross Connects - Fiber Cable															
		Support Structure, per linear foot			AMTFS	VE1CB	0.0031										
		Virtual Collocation - Co-Carrier Cross Connects - Copper/Coax															
		Cable Support Structure, per linear ft			AMTFS	VE1CD	0.0045										
		Virtual Collocation - Co-Carrier Cross Connects - Fiber Cable															
		Support Structure,per cable			AMTFS	VE1CC		555.03						2.07	2.81	0.67	1.41
		Virtual Collocation - Co-Carrier Cross Connects - Copper/Coax			AMTEC	VE40E		555.00						2.07	2.81	0.07	4 44
		Cable Support Structure, per cable Virtual Collocation Cable Records - per request			AMTFS AMTFS	VE1CE VE1BA		555.03 1,711.00		-				2.07	2.81	0.67	1.41
		Virtual Collocation Cable Records - per request Virtual Collocation Cable Records - VG/DS0 Cable, per cable			AMIFS	VETBA		1,711.00									
		record			AMTFS	VE1BB		925.06									
		Virtual Collocation Cable Records - VG/DS0 Cable, per each			AWITTO	VLIDD		923.00									
		100 pair			AMTFS	VE1BC		18.05	18.05								
		Virtual Collocation Cable Records - DS1, per T1TIE			AMTFS	VE1BD		8.45	8.45								
		Virtual Collocation Cable Records - DS3, per T3TIE			AMTFS	VE1BE		29.57	29.57								
		Virtual Collocation Cable Records - Fiber Cable, per 99 fiber															
		records			AMTFS	VE1BF		279.42	279.42								
		Virtual collocation - Security Escort - Basic, per half hour			AMTFS	SPTBX		33.15	20.44					2.07	2.81	0.67	1.41
		Virtual collocation - Security Escort - Overtime, per half hour			AMTFS	SPTOX		41.50	25.61					2.07	2.81	0.67	1.41
		Virtual collocation - Security Escort - Premium, per half hour			AMTFS	SPTPX		49.86	30.79					2.07	2.81	0.67	1.41
		Virtual collocation - Maintenance in CO - Basic, per half hour			AMTFS	CTRLX		30.64	30.64					2.07	2.81	0.67	1.41
		 	l							1							
$\vdash \!$		Virtual collocation - Maintenance in CO - Overtime, per half hour	ļ		AMTFS	SPTOM		35.77	35.77			ļ		2.07	2.81	0.67	1.41
		Manual college Matter and Co. D	1			ODTD::				I							
VIDTU		Virtual collocation - Maintenance in CO - Premium per half hour OCATION	 	-	AMTFS	SPTPM		40.90	40.90	 	 	1		2.07	2.81	0.67	1.41
VIKTUA	L COLL		 	-						 	 	1		 	 		
		Virtual Collocation - 2-wire Cross Connect, Exchange Port 2- Wire Analog - Res	l		UEPSR	VE1R2	0.30	19.20	19.20	1				20.35	10.54	13.32	1.40
		Virtual Collocation 2-Wire Cross Connect, Exchange Port 2-			UEFOR	VEIRZ	0.30	19.20	19.20					20.33	10.54	13.32	1.40
		Wire Line Side PBX Trunk - Bus	1		UEPSP	VE1R2	0.30	19.20	19.20	I				20.35	10.54	13.32	1.40
+		Virtual Collocation 2-Wire Cross Connect, Exchange Port 2-Wire			OLI 01	v L 11\Z	0.30	13.20	19.20	 	<u> </u>	 		20.35	10.34	13.32	1.40
		Voice Grade PBX Trunk - Res	l		UEPSE	VE1R2	0.30	19.20	19.20	1				20.35	10.54	13.32	1.40
		Virtual Collocation 2-Wire Cross Connect, Exchange Port 2-Wire	1				3.00	.0.20	.0.20	<u> </u>				20.00		.0.02	10
		Analog Bus	1		UEPSB	VE1R2	0.30	19.20	19.20	I				20.35	10.54	13.32	1.40
		Virtual Collocation 2-Wire Cross Connect, Exchnage Port 2-Wire					5.50			1	İ						1
		ISDN	1		UEPSX	VE1R2	0.30	19.20	19.20	I				20.35	10.54	13.32	1.40
		Virtual Collocation 2-Wire Cross Connect, Exchange Port 2-Wire															
L		ISDN	<u></u>	<u>L</u>	UEPTX	VE1R2	0.30	19.20	19.20	<u> </u>	<u> </u>	<u></u>	<u> </u>	20.35	10.54	13.32	1.40
		Virtual Collocation 4-Wire Cross Connect, Exchange Port 4-Wire															
		ISDN DS1			UEPEX	VE1R4	0.50	19.20	19.20					20.35	10.54	13.32	1.40
		Rates displaying an "R" in Interim column are interim and sub	inct to	rato tru	e-un as set forth in (General Tern	ns and Condition	ons.				1					

Attachment 5

Access to Numbers and Number Portability

TABLE OF CONTENTS

1.	NON-DISCRIMINATORY ACCESS TO TELEPHONE NUMBERS	3
2.	LOCAL SERVICE PROVIDER NUMBER PORTABILITY - PERMANENT	
SC	OLUTION (LNP)	3
3.	OPERATIONAL SUPPORT SYSTEM (OSS) RATES	4

ACCESS TO NUMBERS AND NUMBER PORTABILITY

1. NON-DISCRIMINATORY ACCESS TO TELEPHONE NUMBERS

- During the term of this Agreement, where Global Connection is utilizing its own switch, Global Connection shall contact the North American Numbering Plan Administrator, NeuStar, for the assignment of numbering resources. In order to be assigned a Central Office Code, Global Connection will be required to complete the Central Office Code (NXX) Assignment Request and Confirmation Form (Code Request Form) in accordance with Industry Numbering Committee's Central Office Code (NXX) Assignment Guidelines (INC 95-0407-008).
- Where BellSouth provides local switching or resold services to Global Connection, BellSouth will provide Global Connection with on-line access to intermediate telephone numbers as defined by applicable FCC rules and regulations on a first come first served basis. Global Connection acknowledges that such access to numbers shall be in accordance with the appropriate FCC rules and regulations. Global Connection acknowledges that there may be instances where there is a shortage of telephone numbers in a particular rate center; and in such instances, BellSouth may request that Global Connection return unused intermediate numbers to BellSouth. Global Connection shall return unused intermediate numbers to BellSouth upon BellSouth's request. BellSouth shall make all such requests on a nondiscriminatory basis.
- BellSouth will allow Global Connection to designate up to 100 intermediate telephone numbers per rate center for Global Connection's sole use. Assignment, reservation and use of telephone numbers shall be governed by applicable FCC rules and regulations. Global Connection acknowledges that there may be instances where there is a shortage of telephone numbers in a particular rate center and BellSouth has the right to limit access to blocks of intermediate telephone numbers. These instances include: 1) where jeopardy status has been declared by the North American Numbering Plan (NANP) for a particular Numbering Plan Area (NPA); or 2) where a rate center has less than six months supply of numbering resources.

2. LOCAL SERVICE PROVIDER NUMBER PORTABILITY - PERMANENT SOLUTION (LNP)

- 2.1 The Parties will offer Number Portability in accordance with rules, regulations and guidelines adopted by the Commission, the FCC and industry fora.
- 2.2 <u>End User Line Charge</u>. Where Global Connection subscribes to BellSouth's local switching, BellSouth shall bill and Global Connection shall pay the end user line

charge associated with implementing LNP as set forth in BellSouth's FCC Tariff No. 1. This charge is not subject to the resale discount set forth in Attachment 1 of this Agreement.

- To limit service outage, BellSouth and Global Connection will adhere to the process flows and cutover guidelines for porting numbers as outlined in the LNP Reference Guide, as amended from time to time. The LNP Reference Guide, incorporated herein by reference, is accessible via the Internet at the following site: http://www.interconnection.bellsouth.com. All intervals referenced in the LNP Reference Guide shall apply to both BellSouth and Global Connection.
- 2.4 The Parties will set Location Routing Number (LRN) unconditional or 10-digit triggers where applicable. Where triggers are set, the porting Party will remove the ported number at the same time the trigger is removed.
- A trigger order is a service order issued in advance of the porting of a number. A trigger order 1) initiates call queries to the AIN SS7 network in advance of the number being ported; and 2) provides for the new service provider to be in control of when a number ports.
- Where triggers are not set, the Parties shall coordinate the porting of the number between service providers so as to minimize service interruptions to the End User.
- 2.7 BellSouth and Global Connection will work cooperatively to implement changes to LNP process flows ordered by the FCC or as recommended by standard industry forums addressing LNP.

3. OPERATIONAL SUPPORT SYSTEM (OSS) RATES

3.1 The terms, conditions and rates for OSS are as set forth in Attachment 2.

Attachment 6

Pre-Ordering, Ordering, Provisioning, Maintenance and Repair

TABLE OF CONTENTS

1.	QUALITY OF PRE-ORDERING, ORDERING, PROVISIONING, MAINTENANCE AND REPAIR.	3
2.	ACCESS TO OPERATIONS SUPPORT SYSTEMS	3
3.	MISCELLANEOUS	5

PRE-ORDERING, ORDERING, PROVISIONING, MAINTENANCE AND REPAIR

1. QUALITY OF PRE-ORDERING, ORDERING, PROVISIONING, MAINTENANCE AND REPAIR

- 1.1 BellSouth shall provide to Global Connection nondiscriminatory access to its Operations Support Systems (OSS) and the necessary information contained therein in order that Global Connection can perform the functions of pre-ordering, ordering, provisioning, maintenance and repair, and billing.. BellSouth shall provide Global Connection with all relevant documentation (manuals, user guides, specifications, etc.) regarding business rules and other formatting information as well as practices and procedures necessary to ensure requests are efficiently processed. All documentation will be readily accessible at BellSouth's interconnection website and are incorporated herein by reference. BellSouth shall ensure that its OSS are designed to accommodate access requests for both current and projected demand of Global Connection and other CLECs in the aggregate.
- BellSouth shall provision services during its regular working hours. To the extent Global Connection requests provisioning of service to be performed outside BellSouth's regular working hours, or the work so requested requires BellSouth's technicians or project manager to work outside of regular working hours, overtime charges shall apply. Notwithstanding the foregoing, if such work is performed outside of regular working hours by a BellSouth technician or project manager during his or her scheduled shift and BellSouth does not incur any overtime charges in performing the work on behalf of Global Connection, BellSouth will not assess Global Connection additional charges beyond the rates and charges specified in this Agreement.

2. ACCESS TO OPERATIONS SUPPORT SYSTEMS

- 2.1 BellSouth shall provide Global Connection nondiscriminatory access to its OSS and the necessary information contained therein in order that Global Connection can perform the functions of pre-ordering, ordering, provisioning, maintenance and repair, and billing. BellSouth shall provide nondiscriminatory access to the OSS through manual and/or electronic interfaces as described in this Attachment. It is the sole responsibility of Global Connection to obtain the technical capability to access and utilize BellSouth's OSS interfaces. Specifications for Global Connection's access and use of BellSouth's electronic interfaces are set forth at BellSouth's interconnection website and are incorporated herein by reference.
- 2.1.1 <u>Pre-Ordering</u>. BellSouth will provide electronic access to its OSS and the information contained therein in order that Global Connection can perform the following pre-ordering functions: service address validation, telephone number selection, service and feature availability, due date information, customer record

information and loop makeup information. Mechanized access is provided by electronic interfaces whose specifications for access and use are set forth at BellSouth's interconnection website and are incorporated herein by reference. The process by which BellSouth and Global Connection will manage these electronic interfaces to include the development and introduction of new interfaces will be governed by the change management process as described below. Global Connection shall provide to BellSouth access to customer record information, including circuit numbers associated with each telephone number where applicable. Global Connection shall provide such information within four (4) hours after request via electronic access where available. If electronic access is not available, Global Connection shall provide to BellSouth paper copies of customer record information, including circuit numbers associated with each telephone number where applicable. If BellSouth requests the information before noon, the customer record information shall be provided the same day. If BellSouth requests the information after noon, the customer record information shall be provided by noon the following day.

- 2.1.2 The Parties agree not to view, copy, or otherwise obtain access to the customer record information of any customer without that customer's permission. Global Connection will obtain access to customer record information only in strict compliance with applicable laws, rules, or regulations of the state in which the service is provided. BellSouth reserves the right to audit Global Connection's access to customer record information. If a BellSouth audit of Global Connection's access to customer record information reveals that Global Connection is accessing customer record information without having obtained the proper End User authorization, BellSouth upon reasonable notice to Global Connection may take corrective action, including but not limited to suspending or terminating Global Connection's electronic access to BellSouth's OSS functionality. All such information obtained through an audit shall be deemed Information covered by the Proprietary and Confidential Information section in the General Terms and Conditions of this Agreement.
- 2.1.3 Ordering. BellSouth will make available to Global Connection electronic interfaces for the purpose of exchanging order information, including order status and completion notification, for non-complex and certain complex resale requests and certain network elements. Specifications for access and use of BellSouth's electronic interfaces are set forth at BellSouth's interconnection website and are incorporated herein by reference. The process by which BellSouth and Global Connection will manage these electronic interfaces to include the development and introduction of new interfaces will be governed by the change management process as described below.
- 2.1.4 <u>Maintenance and Repair</u>. BellSouth will make available to Global Connection electronic interfaces for the purpose of reporting and monitoring service troubles. Specifications for access and use of BellSouth's maintenance and repair electronic interfaces are set forth at BellSouth's interconnection website and are incorporated herein by reference. The process by which BellSouth and Global Connection will

manage these electronic interfaces to include the development and introduction of new interfaces will be governed by the change management process as described below. Requests for trouble repair are billed in accordance with the provisions of this Agreement. BellSouth and Global Connection agree to adhere to BellSouth's Operational Understanding, as amended from time to time during this Agreement and as incorporated herein by reference. The Operational Understanding may be accessed via BellSouth's interconnection website.

- 2.1.5 <u>Billing</u>. BellSouth will provide Global Connection nondiscriminatory access to billing information as specified in Attachment 7 to this Agreement.
- 2.2 Change Management. BellSouth and Global Connection agree that the collaborative change management process known as the Change Control Process (CCP) will be used to manage changes to existing interfaces, introduction of new interfaces and retirement of interfaces. BellSouth and Global Connection agree to comply with the provisions of the documented Change Control Process as may be amended from time to time and incorporated herein by reference. The change management process will cover changes to BellSouth's electronic interfaces, BellSouth's testing environment, associated manual process improvements, and relevant documentation. The process will define a procedure for resolution of change management disputes. Documentation of the CCP as well as related information and processes will be clearly organized and readily accessible to Global Connection at BellSouth's interconnection website.
- 2.3 Rates. Charges for use of OSS shall be as set forth in this Agreement.

3. MISCELLANEOUS

- 3.1 <u>Pending Orders.</u> Orders placed in the hold or pending status by Global Connection will be held for a maximum of thirty (30) calendar days from the date the order is placed on hold. After such time, Global Connection shall be required to submit a new service request. Incorrect or invalid requests returned to Global Connection for correction or clarification will be held for thirty (30) calendar days. If Global Connection does not return a corrected request within thirty (30) calendar days, BellSouth will cancel the request.
- 3.2 <u>Single Point of Contact</u>. Global Connection will be the single point of contact with BellSouth for ordering activity for network elements and other services used by Global Connection to provide services to its End Users, except that BellSouth may accept a request directly from another CLEC, or BellSouth, acting with authorization of the affected End User. Global Connection and BellSouth shall each execute a blanket letter of authorization with respect to customer requests so that prior proof of End User authorization will not be necessary with every request (except in the case of a local service freeze). The Parties shall each be entitled to adopt their own internal processes for verification of customer authorization for requests, provided, however, that such processes shall comply with applicable state and federal law and industry and regulatory guidelines. Pursuant to a request from

another carrier, BellSouth may disconnect any network element being used by Global Connection to provide service to that End User and may reuse such network elements or facilities to enable such other carrier to provide service to the End User. BellSouth will notify Global Connection that such a request has been processed but will not be required to notify Global Connection in advance of such processing.

- 3.2.1 Neither BellSouth nor Global Connection shall prevent or delay an End User from migrating to another carrier because of unpaid bills, denied service, or contract terms.
- 3.2.2 BellSouth shall return a Firm Order Confirmation (FOC) and Local Service Request (LSR) rejection/clarification within the intervals in accordance with the Service Quality Measurement (SQM) set forth in Attachment 9 of this Agreement.
- 3.2.3 Global Connection shall return a FOC to BellSouth within thirty-six (36) hours after Global Connection's receipt from BellSouth of a valid LSR.
- 3.2.4 Global Connection shall provide a Reject Response to BellSouth within twenty-four (24) hours after BellSouth's submission of an LSR which is incomplete or incorrectly formatted.
- 3.3 <u>Use of Facilities</u>. When a customer of Global Connection elects to discontinue service and to transfer service to another local exchange carrier, including BellSouth, BellSouth shall have the right to reuse the facilities provided to Global Connection by BellSouth. In addition, where BellSouth provides local switching, BellSouth may disconnect and reuse facilities when the facility is in a denied state and BellSouth has received a request to establish new service or transfer of service from a customer or a customer's CLEC at the same address served by the denied facility. BellSouth will notify Global Connection that such a request has been processed after the disconnect order has been completed.
- 3.4 <u>Contact Numbers</u>. The Parties agree to provide one another with toll-free nation-wide (50 states) contact numbers for the purpose of ordering, provisioning and maintenance of services.
- 3.5 <u>Subscription Functions</u>. In cases where BellSouth performs subscription functions for an interexchange carrier (IXC) (i.e. PIC and LPIC changes via Customer Account Record Exchange (CARE)), BellSouth will in all possible instances provide the affected IXCs with the Operating Company Number (OCN) of the local provider for the purpose of obtaining End User billing account and other End User information required under subscription requirements.
- 3.5.1 When Global Connection's End User, served by resale or loop and port combinations, changes its PIC or LPIC, and per BellSouth's FCC or state tariff the interexchange carrier elects to charge the End User the PIC or LPIC change charge, BellSouth will bill the PIC or LPIC change charge to Global Connection,

which has the billing relationship with that End User, and Global Connection may pass such charge to the End User.

- Cancellation Charges. If Global Connection cancels a request for network 3.6 elements or resold services, any costs incurred by BellSouth in conjunction with the provisioning of that request will be recovered in accordance with BellSouth's Private Line Tariff or BellSouth's FCC No. 1 Tariff, Section 5.4, as applicable. Notwithstanding the foregoing, if Global Connection places an LSR based upon BellSouth's loop makeup information, and such information is inaccurate resulting in the inability of BellSouth to provision the network elements requested and another spare compatible facility cannot be found with the transmission characteristics of the network elements originally requested, cancellation charges described in this Section shall not apply. Where Global Connection places a single LSR for multiple network elements or services based upon loop makeup information, and information as to some, but not all, of the network elements or services is inaccurate, if BellSouth cannot provision the network elements or services that were the subject of the inaccurate loop makeup information, Global Connection may cancel its request for those network elements or services without incurring cancellation charges as described in this Section. In such instance, should Global Connection elect to cancel the entire LSR, cancellation charges as described in this Section shall apply to those elements and services that were not the subject of inaccurate loop makeup.
- 3.7 <u>Service Date Advancement Charges (a.k.a. Expedites)</u>. For Service Date Advancement requests by Global Connection, Service Date Advancement charges will apply for intervals less than the standard interval as outlined in the BellSouth Product and Services Interval Guide. The charges as outlined in BellSouth's FCC No. 1 Tariff, Section 5, will apply as applicable.

Attachment 7

Billing

TABLE OF CONTENTS

1.	PAYMENT AND BILLING ARRANGEMENTS	3
2.	BILLING DISPUTES	7
3.	RAO HOSTING	8
4.	OPTIONAL DAILY USAGE FILE	11
5.	ACCESS DAILY USAGE FILE	14
6.	ENHANCED OPTIONAL DAILY USAGE FILE (EODUF)	16
Ra	tes	Exhibit A

BILLING

1. PAYMENT AND BILLING ARRANGEMENTS

The terms and conditions set forth in this Attachment shall apply to all services ordered and provisioned pursuant to this Agreement.

- 1.1 <u>Billing</u>. BellSouth will bill through the Carrier Access Billing System (CABS), Integrated Billing System (IBS) and/or the Customer Records Information System (CRIS) depending on the particular service(s) provided to Global Connection under this Agreement. BellSouth will format all bills in Carrier Billing Output Specification (CBOS) Standard or CLUB/EDI format, depending on the type of service provided. For those services where standards have not yet been developed, BellSouth's billing format will change as necessary when standards are finalized by the applicable industry forum.
- 1.1.1 For any service(s) BellSouth receives from Global Connection, Global Connection shall bill BellSouth in CBOS format.
- 1.1.2 Any switched access charges associated with interexchange carrier access to the resold local exchange lines will be billed by, and due to BellSouth.
- 1.1.3 BellSouth will render bills each month on established bill days for each of Global Connection's accounts. If either Party requests multiple billing media or additional copies of the bills, the billing Party will provide these at a reasonable cost.
- 1.1.4 BellSouth will bill Global Connection in advance for all services to be provided during the ensuing billing period except charges associated with service usage and nonrecurring charges, which will be billed in arrears.
- 1.1.4.1 Charges for services will be calculated on an individual End User account level, including, if applicable, any charge for usage or usage allowances. BellSouth will also bill Global Connection, and Global Connection will be responsible for and remit to BellSouth, all charges applicable to said services including but not limited to 911 and E911 charges, End Users common line charges, federal subscriber line charges, telecommunications relay charges (TRS), and franchise fees, unless otherwise ordered by a Commission.
- 1.1.5 BellSouth will not perform billing and collection services for Global Connection as a result of the execution of this Agreement.
- 1.1.6 In the event that this Agreement or an amendment to this Agreement effects a rate change to recurring rate elements that are billed in advance, BellSouth will make an adjustment to such recurring rates billed in advance at the previously effective rate. The adjustment shall reflect billing at the new rates from the Effective Date of the Agreement or amendment.

- 1.2 Establishing Accounts. After submitting a credit profile and deposit, if required, and after receiving certification as a local exchange carrier from the appropriate regulatory agency, Global Connection will provide the appropriate BellSouth advisory team/local contract manager the necessary documentation to enable BellSouth to establish accounts for Local Interconnection, Network Elements and Other Services, Collocation and/or resold services. Such documentation shall include the Application for Master Account, if applicable, proof of authority to provide telecommunications services, the appropriate Operating Company Numbers (OCN) for each state as assigned by the National Exchange Carriers Association (NECA), Carrier Identification Code (CIC), Access Customer Name and Abbreviation (ACNA), Blanket Letter of Authorization (LOA), Misdirected Number form, and a tax exemption certificate, if applicable. Notwithstanding anything to the contrary in this Agreement, Global Connection may not order services under a new account established in accordance with this Section 1.2 until 30 days after all information specified in this Section 1.2 is received from Global Connection.
- 1.2.1 OCN. If Global Connection needs to change its OCN(s) under which it operates when Global Connection has already been conducting business utilizing those OCN(s), Global Connection shall bear all costs incurred by BellSouth to convert Global Connection to the new OCN(s). OCN conversion charges include all time required to make system updates to all of Global Connection's End User customer records and will be handled by the BFR/NBR process.
- 1.2.2 <u>Payment Responsibility</u>. Payment of all charges will be the responsibility of Global Connection. Global Connection shall make payment to BellSouth for all services billed. Payments made by Global Connection to BellSouth as payment on account will be credited to Global Connection's accounts receivable master account. BellSouth will not become involved in billing disputes that may arise between Global Connection and Global Connection's customer.
- 1.3 <u>Payment Due.</u> Payment for services provided is due on or before the next bill date in immediately available funds. Payment is considered to have been made when received by BellSouth.
- 1.4 <u>Due Dates</u>. If the payment due date falls on a Sunday or on a holiday that is observed on a Monday, the payment due date shall be the first non-holiday day following such Sunday or holiday. If the payment due date falls on a Saturday or on a holiday which is observed on Tuesday, Wednesday, Thursday, or Friday, the payment due date shall be the last non-holiday day preceding such Saturday or holiday. If payment is not received by the payment due date, a late payment charge, as set forth in Section 1.6, below, shall apply.
- 1.5 <u>Tax Exemption</u>. Upon BellSouth's receipt of tax exemption certificate, the total amount billed to Global Connection will not include those taxes or fees from which Global Connection is exempt. Global Connection will be solely responsible for the

computation, tracking, reporting and payment of all taxes and like fees associated with the services provided to the End User of Global Connection.

- Late Payment. If any portion of the payment is not received by BellSouth on or before the payment due date as set forth preceding, or if any portion of the payment is received by BellSouth in funds that are not immediately available to BellSouth, then a late payment charge shall be due to BellSouth. The late payment charge shall be the portion of the payment not received by the payment due date multiplied by a late factor and will be applied on a per bill basis. The late factor shall be as set forth in Section A2 of the General Subscriber Services Tariff, Section B2 of the Private Line Service Tariff or Section E2 of the Intrastate Access Tariff, as appropriate. In addition to any applicable late payment charges, Global Connection may be charged a fee for all returned checks as set forth in Section A2 of the General Subscriber Services Tariff or pursuant to the applicable state law.
- 1.7 <u>Discontinuing Service to Global Connection</u>. The procedures for discontinuing service to Global Connection are as follows:
- 1.7.1 BellSouth reserves the right to suspend or terminate service in the event of prohibited, unlawful or improper use of BellSouth facilities or service, abuse of BellSouth facilities, or any other violation or noncompliance by Global Connection of the rules and regulations of BellSouth's tariffs.
- 1.7.2 BellSouth reserves the right to suspend or terminate service for nonpayment. If payment of amounts not subject to a billing dispute, as described in Section 2, is not received by the bill date in the month after the original bill date, BellSouth will provide written notice to Global Connection that additional applications for service may be refused, that any pending orders for service may not be completed, and/or that access to ordering systems may be suspended if payment of such amounts, and all other amounts not in dispute that become past due before refusal, incompletion or suspension, is not received by the fifteenth day following the date of the notice. In addition, BellSouth may, at the same time, provide written notice to the person designated by Global Connection to receive notices of noncompliance that BellSouth may discontinue the provision of existing services to Global Connection if payment of such amounts, and all other amounts not in dispute that become past due before discontinuance, is not received by the thirtieth day following the date of the initial notice.
- 1.7.3 In the case of discontinuance of services, all billed charges, as well as applicable termination charges, shall become due.
- 1.7.4 Discontinuance of service on Global Connection's account will effect a discontinuance of service to Global Connection's End Users. BellSouth will reestablish service for Global Connection upon payment of all past due charges and the appropriate connection fee subject to BellSouth's normal application

procedures. Global Connection is solely responsible for notifying the End User of the discontinuance of the service. If within fifteen (15) days after Global Connection's service has been discontinued and no arrangements to reestablish service have been made consistent with this subsection, Global Connection's service will be disconnected.

- 1.8 Deposit Policy. Global Connection shall complete the BellSouth Credit Profile and provide information to BellSouth regarding credit worthiness. Based on the results of the credit analysis, BellSouth reserves the right to secure the account with a suitable form of security deposit. Such security deposit shall take the form of cash, an Irrevocable Letter of Credit (BellSouth form), Surety Bond (BellSouth form) or, in BellSouth's sole discretion, some other form of security proposed by Global Connection. Any such security deposit shall in no way release Global Connection from its obligation to make complete and timely payments of its bill. Global Connection shall pay any applicable deposits prior to the inauguration of service. If, in the sole opinion of BellSouth, circumstances so warrant and/or gross monthly billing has increased beyond the level initially used to determine the level of security deposit, BellSouth reserves the right to request additional security and/or file a Uniform Commercial Code (UCC-1) security interest in Global Connection's "accounts receivables and proceeds." Interest on a security deposit, if provided in cash, shall accrue and be paid in accordance with the terms in the appropriate BellSouth tariff. Security deposits collected under this Section shall not exceed two months' estimated billing. In the event Global Connection fails to remit to BellSouth any deposit requested pursuant to this Section, service to Global Connection may be terminated in accordance with the terms of Section 1.7 of this Attachment, and any security deposits will be applied to Global Connection's account(s). In the event Global Connection defaults on its account, service to Global Connection will be terminated in accordance with the terms of Section 1.7 above, and any security deposits will be applied to Global Connection's account.
- Notices. Notwithstanding anything to the contrary in this Agreement, all bills and notices regarding billing matters, including notices relating to security deposits, disconnection of services for nonpayment of charges, and rejection of additional orders from Global Connection, shall be forwarded to the individual and/or address provided by Global Connection in establishment of its billing account(s) with BellSouth, or to the individual and/or address subsequently provided by Global Connection as the contact for billing information. All monthly bills and notices described in this Section shall be forwarded to the same individual and/or address; provided, however, upon written request from Global Connection to BellSouth's billing organization, the notice of discontinuance of services purchased by Global Connection under this Agreement provided for in Section 1.7.2 of this Attachment shall be sent via certified mail to the individual(s) listed in the Notices provision of the General Terms and Conditions of this Agreement.

1.10 Rates. Rates for Optional Daily Usage File (ODUF), Access Daily Usage File (ADUF), Enhanced Optional Daily Usage File (EODUF) and Centralized Message Distribution Service (CMDS) are set out in Exhibit A to this Attachment. If no rate is identified in this Attachment, the rate for the specific service or function will be as set forth in the applicable BellSouth tariff or as negotiated by the Parties upon request by either Party.

2. BILLING DISPUTES

- 2.1 Each Party agrees to notify the other Party in writing upon the discovery of a billing dispute. Global Connection shall report all billing disputes to BellSouth using the Billing Adjustment Request Form (RF 1461) provided by BellSouth. In the event of a billing dispute, the Parties will endeavor to resolve the dispute within sixty (60) calendar days of the notification date. If the Parties are unable within the 60 day period to reach resolution, then the aggrieved Party may pursue dispute resolution in accordance with the General Terms and Conditions of this Agreement.
- 2.2 For purposes of this Section 2, a billing dispute means a reported dispute of a specific amount of money actually billed by either Party. The dispute must be clearly explained by the disputing Party and supported by written documentation, which clearly shows the basis for disputing charges. A billing dispute will not include the refusal to pay all or part of a bill or bills when no written documentation is provided to support the dispute, nor shall a billing dispute include the refusal to pay other amounts owed by the billed Party until the dispute is resolved. Claims by the billed Party for damages of any kind will not be considered a billing dispute for purposes of this Section. If the billing dispute is resolved in favor of the billing Party, the disputing Party will make immediate payment of any of the disputed amount owed to the billing Party or the billing Party shall have the right to pursue normal treatment procedures. Any credits due to the disputing Party, pursuant to the billing dispute, will be applied to the disputing Party's account by the billing Party immediately upon resolution of the dispute.
- If a Party disputes a charge and does not pay such charge by the payment due date, or if a payment or any portion of a payment is received by either Party after the payment due date, or if a payment or any portion of a payment is received in funds which are not immediately available to the other Party, then a late payment charge and interest, where applicable, shall be assessed. For bills rendered by either Party for payment, the late payment charge for both Parties shall be calculated based on the portion of the payment not received by the payment due date multiplied by the late factor as set forth in the following BellSouth tariffs: for services purchased from the General Subscribers Services Tariff for purposes of resale and for ports and non-designed loops, Section A2 of the General Subscriber Services Tariff; for services purchased from the Private Line Tariff for purposes of resale, Section B2 of the Private Line Service Tariff; and for designed network elements and other

services and local interconnection charges, Section E2 of the Access Service Tariff. The Parties shall assess interest on previously assessed late payment charges only in a state where it has the authority pursuant to its tariffs.

3. RAO HOSTING

- 3.1 RAO Hosting, Calling Card and Third Number Settlement System (CATS) and Non-Intercompany Settlement System (NICS) services provided to Global Connection by BellSouth will be in accordance with the methods and practices regularly applied by BellSouth to its own operations during the term of this Agreement, including such revisions as may be made from time to time by BellSouth.
- 3.2 Global Connection shall furnish all relevant information required by BellSouth for the provision of RAO Hosting, CATS and NICS.
- Charges or credits, as applicable, will be applied by BellSouth to Global Connection on a monthly basis in arrears. Amounts due (excluding adjustments) are payable within thirty (30) days of receipt of the billing statement.
- 3.4 Global Connection must have its own unique hosted RAO code. Where BellSouth is the selected CMDS interfacing host, Global Connection must request that BellSouth establish a unique hosted RAO code for Global Connection. Such request shall be in writing to the BellSouth RAO Hosting coordinator and must be submitted at least eight (8) weeks prior to provision of services pursuant to this Section. Services shall commence on a date mutually agreed by the Parties.
- 3.5 BellSouth will receive messages from Global Connection that are to be processed by BellSouth, another LEC in the BellSouth region or a LEC outside the BellSouth region. Global Connection shall send all messages to BellSouth no later than sixty (60) days after the message date.
- 3.6 BellSouth will perform invoice sequence checking, standard EMI format editing, and balancing of message data with the EMI trailer record counts on all data received from Global Connection.
- 3.7 All data received from Global Connection that is to be processed or billed by another LEC within the BellSouth region will be distributed to that LEC in accordance with the Agreement(s) in effect between BellSouth and the involved LEC.
- 3.8 All data received from Global Connection that is to be placed on the CMDS network for distribution outside the BellSouth region will be handled in accordance with the agreement(s) in effect between BellSouth and its connecting contractor.

- 3.9 BellSouth will receive messages from the CMDS network that are destined to be processed by Global Connection and will forward them to Global Connection on a daily basis for processing.
- 3.10 Transmission of message data between BellSouth and Global Connection will be via CONNECT:Direct or Secure File Transfer Protocol (FTP).
- 3.10.1 Data circuits (private line or dial-up) will be required between BellSouth and Global Connection for the purpose of data transmission when utilizing CONNECT: Direct. Where a dedicated line is required, Global Connection will be responsible for ordering the circuit and coordinating the installation with BellSouth. Global Connection is responsible for any charges associated with this line. Equipment required on the BellSouth end to attach the line to the mainframe computer and to transmit data will be negotiated on an individual case basis. Where a dial-up facility is required, dial circuits will be installed in the BellSouth data center by BellSouth and the associated charges assessed to Global Connection. Additionally, all message toll charges associated with the use of the dial circuit by Global Connection will be the responsibility of Global Connection. Associated equipment on the BellSouth end, including a modem, will be negotiated on an individual case basis between the Parties. All equipment, including modems and software, that is required on the Global Connection end for the purpose of data transmission will be the responsibility of Global Connection.
- 3.10.2 If Global Connection utilizes Secure File Transfer Protocol for data file transmission, purchase of the Secure File Transfer Protocol software will be the responsibility of Global Connection.
- 3.11 All messages and related data exchanged between BellSouth and Global Connection will be formatted for EMI formatted records and packed between appropriate EMI header and trailer records in accordance with accepted industry standards.
- 3.12 Global Connection will maintain recorded message detail necessary to recreate files provided to BellSouth for a period of three (3) calendar months beyond the related message dates.
- 3.13 Should it become necessary for Global Connection to send data to BellSouth more than sixty (60) days past the message date(s), Global Connection will notify BellSouth in advance of the transmission of the data. BellSouth will work with its connecting contractor and/or Global Connection, where necessary, to notify all affected LECs.
- 3.14 In the event that data to be exchanged between the two Parties should become lost or destroyed, the Party responsible for creating the data will make every effort to restore and retransmit such data. If the data cannot be retrieved, the Party

responsible for losing or destroying the data will be liable to the other Party for any resulting lost revenue. Lost revenue may be a combination of revenues that could not be billed to the End Users and associated access revenues. Both Parties will work together to estimate the revenue amount based upon historical data through a method mutually agreed upon. The resulting estimated revenue loss will be paid by the responsible Party to the other Party within three (3) calendar months of the resolution of the amount owed, or as mutually agreed upon by the Parties.

- 3.15 Should an error be detected by the EMI format edits performed by BellSouth on data received from Global Connection, the entire pack containing the affected data will not be processed by BellSouth. BellSouth will notify Global Connection of the error. Global Connection will correct the error(s) and will resend the entire pack to BellSouth for processing. In the event that an out-of-sequence condition occurs on subsequent packs, Global Connection will resend these packs to BellSouth after the pack containing the error has been successfully reprocessed by BellSouth.
- 3.16 In association with message distribution service, BellSouth will provide Global Connection with associated intercompany settlements reports (CATS and NICS) as appropriate.
- 3.17 Notwithstanding anything in this Agreement to the contrary, in no case shall either Party be liable to the other for any direct or consequential damages incurred as a result of the obligations set out in this Section 3.
- 3.18 Intercompany Settlements Messages
- 3.18.1 Intercompany Settlements Messages facilitate the settlement of revenues associated with traffic originated from or billed by Global Connection as a facilities based provider of local exchange telecommunications services outside the BellSouth region. Only traffic that originates in one Bell operating territory and bills in another Bell operating territory is included. Traffic that originates and bills within the same Bell operating territory will be settled on a local basis between Global Connection and the involved company(ies), unless that company is participating in NICS.
- 3.18.2 Both traffic that originates outside the BellSouth region by Global Connection and is billed within the BellSouth region, and traffic that originates within the BellSouth region and is billed outside the BellSouth region by Global Connection, is covered by CATS. Also covered is traffic that either is originated by or billed by Global Connection, involves a company other than Global Connection, qualifies for inclusion in the CATS settlement, and is not originated or billed within the BellSouth region (NICS).

- 3.18.3 Once Global Connection is operating within the BellSouth territory, revenues associated with calls originated and billed within the BellSouth region will be settled via NICS.
- 3.18.4 BellSouth will receive the monthly NICS reports from Telcordia on behalf of Global Connection. BellSouth will distribute copies of these reports to Global Connection on a monthly basis.
- 3.18.5 BellSouth will receive the monthly CATS reports from Telcordia on behalf of Global Connection. BellSouth will distribute copies of these reports to Global Connection on a monthly basis.
- 3.18.6 BellSouth will collect the revenue earned by Global Connection from the Bell operating company in whose territory the messages are billed via CATS, less a per message billing and collection fee of five cents (\$0.05), on behalf of Global Connection. BellSouth will remit the revenue billed by Global Connection to the Bell operating company in whose territory the messages originated, less a per message billing and collection fee of five cents (\$0.05), on behalf on Global Connection. These two amounts will be netted together by BellSouth and the resulting charge or credit issued to Global Connection via a monthly Carrier Access Billing System (CABS) miscellaneous bill.
- 3.18.7 BellSouth will collect the revenue earned by Global Connection within the BellSouth territory from another CLEC also within the BellSouth territory (NICS) where the messages are billed, less a per message billing and collection fee of five cents (\$0.05), on behalf of Global Connection. BellSouth will remit the revenue billed by Global Connection within the BellSouth region to the CLEC also within the BellSouth region, where the messages originated, less a per message billing and collection fee of five cents (\$0.05). These two amounts will be netted together by BellSouth and the resulting charge or credit issued to Global Connection via a monthly CABS miscellaneous bill.
- 3.18.8 BellSouth and Global Connection agree that monthly netted amounts of less than fifty dollars (\$50.00) will not be settled.

4. OPTIONAL DAILY USAGE FILE

- 4.1 Upon written request from Global Connection, BellSouth will provide the Optional Daily Usage File (ODUF) service to Global Connection pursuant to the terms and conditions set forth in this section.
- 4.2 Global Connection shall furnish all relevant information required by BellSouth for the provision of the ODUF.
- 4.3 The ODUF feed will contain billable messages that were carried over the BellSouth Network and processed in the BellSouth Billing System, but billed to a Global Connection customer.

4.4 Charges for the ODUF will appear on Global Connections' monthly bills for the previous month's usage. The charges are as set forth in Exhibit A to this Attachment. Global Connection will be billed at the ODUF rates that are in effect at the end of the previous month. 4.5 The ODUF feed will contain both rated and unrated messages. All messages will be in the standard Alliance for Telecommunications Industry Solutions (ATIS) EMI record format. 4.6 Messages that error in the billing system of Global Connection will be the responsibility of Global Connection. If, however, Global Connection should encounter significant volumes of errored messages that prevent processing by Global Connection within its systems, BellSouth will work with Global Connection to determine the source of the errors and the appropriate resolution. 4.7 The following specifications shall apply to the ODUF feed. 4.7.1 ODUF Messages to be Transmitted 4.7.1.1 The following messages recorded by BellSouth will be transmitted to Global Connection: 4.7.1.1.1 Message recording for per use/per activation type services (examples: Three -Way Calling, Verify, Interrupt, Call Return, etc.) 4.7.1.1.2 Measured billable Local 4.7.1.1.3 Directory Assistance messages 4.7.1.1.4 IntraLATA Toll 4.7.1.1.5 WATS and 800 Service 4.7.1.1.6 N11 4.7.1.1.7 **Information Service Provider Messages** 4.7.1.1.8 **Operator Services Messages** 4.7.1.1.9 Operator Services Message Attempted Calls (Network Element only) 4.7.1.1.10 Credit/Cancel Records 4.7.1.1.11 Usage for Voice Mail Message Service 4.7.1.2 Rated Incollects (messages BellSouth receives from other revenue accounting offices) can also be on ODUF. Rated Incollects will be intermingled with

BellSouth recorded rated and unrated usage. Rated Incollects will not be packed separately.

- 4.7.1.3 BellSouth will perform duplicate record checks on records processed to ODUF. Any duplicate messages detected will be deleted and not sent to Global Connection.
- 4.7.1.4 In the event that Global Connection detects a duplicate on ODUF they receive from BellSouth, Global Connection will drop the duplicate message and will not return the duplicate to BellSouth.
- 4.7.2 ODUF Physical File Characteristics
- 4.7.2.1 ODUF will be distributed to Global Connection via CONNECT:Direct, Secure File Transfer Protocol (FTP) or another mutually agreed medium. The ODUF feed will be a variable block format. The data on the ODUF feed will be in a non-compacted EMI format (175 byte format plus modules). It will be created on a daily basis Monday through Friday except holidays. Details such as dataset name and delivery schedule will be addressed during negotiations of the distribution medium. There will be a maximum of one dataset per workday per OCN.
- 4.7.2.2 Data circuits (private line or dial-up) will be required between BellSouth and Global Connection for the purpose of data transmission as set forth in Section 3.10.1 above.
- 4.7.2.3 If Global Connection utilizes Secure File Transfer Protocol (FTP) for data file transmission, purchase of the Secure File Transfer Protocol (FTP) software will be the responsibility of Global Connection.
- 4.7.3 ODUF Packing Specifications
- 4.7.3.1 A pack will contain a minimum of one message record or a maximum of 99,999 message records plus a pack header record and a pack trailer record. One transmission can contain a maximum of 99 packs and a minimum of one pack.
- 4.7.3.2 The OCN, From RAO, and Invoice Number will control the invoice sequencing. The From RAO will be used to identify to Global Connection which BellSouth RAO that is sending the message. BellSouth and Global Connection will use the invoice sequencing to control data exchange. BellSouth will be notified of sequence failures identified by Global Connection and resend the data as appropriate.

The data will be packed using ATIS EMI records.

- 4.7.4 ODUF Pack Rejection
- 4.7.4.1 Global Connection will notify BellSouth within one business day of rejected packs (via the mutually agreed medium). Packs could be rejected because of pack

sequencing discrepancies or a critical edit failure on the Pack Header or Pack Trailer records (i.e. out-of-balance condition on grand totals, invalid data populated). Standard ATIS EMI error codes will be used. Global Connection will not be required to return the actual rejected data to BellSouth. Rejected packs will be corrected and retransmitted to Global Connection by BellSouth.

4.7.5 ODUF Control Data

4.7.5.1 Global Connection will send one confirmation record per pack that is received from BellSouth. This confirmation record will indicate Global Connection's receipt of the pack and acceptance or rejection of the pack. Pack Status Code(s) will be populated using standard ATIS EMI error codes for packs that were rejected by Global Connection for reasons stated in the above section.

4.7.6 ODUF Testing

4.7.6.1 Upon request from Global Connection, BellSouth shall send ODUF test files to Global Connection. The Parties agree to review and discuss the ODUF content and/or format. For testing of usage results, BellSouth shall request that Global Connection set up a production (live) file. The live test may consist of Global Connection's employees making test calls for the types of services Global Connection requests on ODUF. These test calls are logged by Global Connection, and the logs are provided to BellSouth. These logs will be used to verify the files. Testing will be completed within 30 calendar days from the date on which the initial test file was sent.

5. ACCESS DAILY USAGE FILE

- 5.1 Upon written request from Global Connection, BellSouth will provide the Access Daily Usage File (ADUF) service to Global Connection pursuant to the terms and conditions set forth in this section.
- 5.2 Global Connection shall furnish all relevant information required by BellSouth for the provision of ADUF.
- 5.3 ADUF will contain access messages associated with a port that Global Connection has purchased from BellSouth
- Charges for ADUF will appear on Global Connection's monthly bills for the previous month's usage. The charges are as set forth in Exhibit A to this Attachment. Global Connection will be billed at the ADUF rates that are in effect at the end of the previous month.
- 5.5 Messages that error in the billing system of Global Connection will be the responsibility of Global Connection. If, however, Global Connection should encounter significant volumes of errored messages that prevent processing by

Global Connection within its systems, BellSouth will work with Global Connection to determine the source of the errors and the appropriate resolution.

- 5.6 ADUF Messages To Be Transmitted
- 5.6.1 The following messages recorded by BellSouth will be transmitted to Global Connection:
- 5.6.1.1 Recorded originating and terminating interstate and intrastate access records associated with a port.
- 5.6.1.2 Recorded terminating access records for undetermined jurisdiction access records associated with a port.
- 5.6.2 BellSouth will perform duplicate record checks on records processed to ADUF. Any duplicate messages detected will be dropped and not sent to Global Connection.
- 5.6.3 In the event that Global Connection detects a duplicate on ADUF they receive from BellSouth, Global Connection will drop the duplicate message and will not return the duplicate to BellSouth.
- 5.6.4 ADUF Physical File Characteristics
- ADUF will be distributed to Global Connection via CONNECT:Direct, Secure File Transfer Protocol (FTP) or another mutually agreed medium. The ADUF feed will be a fixed block format. The data on the ADUF feed will be in a non-compacted EMI format (210 byte). It will be created on a daily basis Monday through Friday except holidays. Details such as dataset name and delivery schedule will be addressed during negotiations of the distribution medium. There will be a maximum of one dataset per workday per OCN.
- Data circuits (private line or dial-up) will be required between BellSouth and Global Connection for the purpose of data transmission as set forth in Section 3.10.1 above.
- 5.6.4.3 If Global Connection utilizes Secure File Transfer Protocol (FTP) for data file transmission, purchase of the Secure File Transfer Protocol (FTP) software will be the responsibility of Global Connection.
- 5.6.5 ADUF Packing Specifications
- 5.6.5.1 A pack will contain a minimum of one message record or a maximum of 99,999 message records plus a pack header record and a pack trailer record. One transmission can contain a maximum of 99 packs and a minimum of one pack.

The OCN, From RAO, and Invoice Number will control the invoice sequencing. The From RAO will be used to identify to Global Connection which BellSouth RAO is sending the message. BellSouth and Global Connection will use the invoice sequencing to control data exchange. BellSouth will be notified of sequence failures identified by Global Connection and resend the data as appropriate.

The data will be packed using ATIS EMI records.

- 5.6.6 ADUF Pack Rejection
- 5.6.6.1 Global Connection will notify BellSouth within one business day of rejected packs (via the mutually agreed medium). Packs could be rejected because of pack sequencing discrepancies or a critical edit failure on the Pack Header or Pack Trailer records (i.e. out-of-balance condition on grand totals, invalid data populated). Standard ATIS EMI error codes will be used. Global Connection will not be required to return the actual rejected data to BellSouth. Rejected packs will be corrected and retransmitted to Global Connection by BellSouth.
- 5.6.7 ADUF Control Data
- 5.6.7.1 Global Connection will send one confirmation record per pack that is received from BellSouth. This confirmation record will indicate Global Connection's receipt of the pack and acceptance or rejection of the pack. Pack Status Code(s) will be populated using standard ATIS EMI error codes for packs that were rejected by Global Connection for reasons stated in the above section.
- 5.6.8 ADUF Testing
- 5.6.8.1 Upon request from Global Connection, BellSouth shall send a test file of generic data to Global Connection via Connect:Direct or Text File via E-Mail. The Parties agree to review and discuss the test file's content and/or format.

6. ENHANCED OPTIONAL DAILY USAGE FILE (EODUF)

- Upon written request from Global Connection, BellSouth will provide the Enhanced Optional Daily Usage File (EODUF) service to Global Connection pursuant to the terms and conditions set forth in this section. EODUF will only be sent to existing ODUF subscribers who request the EODUF option.
- Global Connection shall furnish all relevant information required by BellSouth for the provision of the Enhanced Optional Daily Usage File.
- 6.3 The Enhanced Optional Daily Usage File (EODUF) will provide usage data for local calls originating from resold Flat Rate Business and Residential Lines.
- 6.4 Charges for delivery of the Enhanced Optional Daily Usage File will appear on Global Connection's monthly bills for the previous month's usage. The charges

at the EODUF rates that are in effect at the end of the previous month. 6.5 All messages will be in the standard Alliance for Telecommunications Industry Solutions (ATIS) EMI record format. 6.6 Messages that error in the billing system of Global Connection will be the responsibility of Global Connection. If, however, Global Connection should encounter significant volumes of errored messages that prevent processing by Global Connection within its systems, BellSouth will work with Global Connection to determine the source of the errors and the appropriate resolution. 6.7 The following specifications shall apply to the EODUF feed. 6.7.1 Usage To Be Transmitted 6.7.1.1 The following messages recorded by BellSouth will be transmitted to Global Connection: Customer usage data for flat rated local call originating from Global Connection's 6.7.1.1.1 End User lines (1FB or 1FR). The EODUF record for flat rate messages will include: 6.7.1.1.2 Date of Call 6.7.1.1.3 From Number 6.7.1.1.4 To Number 6.7.1.1.5 Connect Time 6.7.1.1.6 Conversation Time 6.7.1.1.7 Method of Recording 6.7.1.1.8 From RAO 6.7.1.1.9 Rate Class 6.7.1.1.10 Message Type 6.7.1.1.11 **Billing Indicators** 6.7.1.1.12 Bill to Number 6.7.1.2 BellSouth will perform duplicate record checks on EODUF records processed to Optional Daily Usage File. Any duplicate messages detected will be deleted and

are as set forth in Exhibit A to this Attachment. Global Connection will be billed

not sent to Global Connection.

- 6.7.1.3 In the event that Global Connection detects a duplicate on Enhanced Optional Daily Usage File they receive from BellSouth, Global Connection will drop the duplicate message (Global Connection will not return the duplicate to BellSouth).
- 6.7.2 Physical File Characteristics
- 6.7.2.1 The EODUF feed will be distributed to Global Connection over their existing Optional Daily Usage File (ODUF) feed. The EODUF messages will be intermingled among Global Connection's Optional Daily Usage File (ODUF) messages. The EODUF will be a variable block format (2476) with an LRECL of 2472. The data on the EODUF will be in a non-compacted EMI format (175 byte format plus modules). It will be created on a daily basis (Monday through Friday except holidays).
- 6.7.2.2 Data circuits (private line or dial-up) may be required between BellSouth and Global Connection for the purpose of data transmission. Where a dedicated line is required, Global Connection will be responsible for ordering the circuit, overseeing its installation and coordinating the installation with BellSouth. Global Connection will also be responsible for any charges associated with this line. Equipment required on the BellSouth end to attach the line to the mainframe computer and to transmit successfully ongoing will be negotiated on an individual case basis. Where a dial-up facility is required, dial circuits will be installed in the BellSouth data center by BellSouth and the associated charges assessed to Global Connection. Additionally, all message toll charges associated with the use of the dial circuit by Global Connection will be the responsibility of Global Connection. Associated equipment on the BellSouth end, including a modem, will be negotiated on an individual case basis between the Parties. All equipment, including modems and software, that is required on Global Connection's end for the purpose of data transmission will be the responsibility of Global Connection.
- 6.7.3 Packing Specifications
- 6.7.3.1 A pack will contain a minimum of one message record or a maximum of 99,999 message records plus a pack header record and a pack trailer record. One transmission can contain a maximum of 99 packs and a minimum of one pack.
- 6.7.3.2 The Operating Company Number (OCN), From Revenue Accounting Office (RAO), and Invoice Number will control the invoice sequencing. The From RAO will be used to identify to Global Connection which BellSouth RAO is sending the message. BellSouth and Global Connection will use the invoice sequencing to control data exchange. BellSouth will be notified of sequence failures identified by Global Connection and resend the data as appropriate.
- 6.7.3.3 The data will be packed using ATIS EMI records.

ODUF/ADUF	/EODUF/CMDS - Alabama												Attach	ment: 7	Exhi	ibit: A
CATEGORY	RATE ELEMENTS	Interi m	Zone	BCS	usoc			RATES (\$)				Submitted Manually	Charge -	Charge -	Charge -	Incremental Charge - Manual Svc Order vs. Electronic- Disc Add'l
						Rec	Nonre	curring	Nonrecurring	Disconnect			oss	Rates (\$)		
						Rec	First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
ODUF/ADUF/O	EDUF/CMDS															
ACCES	SS DAILY USAGE FILE (ADUF)															
	ADUF: Message Processing, per message				N/A	0.007037										
	ADUF: Data Transmission (CONNECT:DIRECT), per message				N/A	0.000113										
OPTIO	NAL DAILY USAGE FILE (ODUF)															
	ODUF: Recording, per message				N/A	0.000011										
	ODUF: Message Processing, per message				N/A	0.004101										
	ODUF: Message Processing, per Magnetic Tape provisioned				N/A	42.67										
	ODUF: Data Transmission (CONNECT:DIRECT), per message				N/A	0.000094										
CENTR	ALIZED MESSAGE DISTRIBUTION SERVICE (CMDS)															
	CMDS: Message Processing, per message			·	N/A	0.004										
	CMDS: Data Transmission (CONNECT:DIRECT), per message				N/A	0.001										
ENHAN	ICED OPTIONAL DAILY USAGE FILE (EODUF)					2.00										
	EODUF: Message Processing, per message				N/A	0.22			<u> </u>		l					ļ
Notes:	If no rate is identified in the contract, the rate for the specific	service	or fun	ction will be as set	forth in appli	cable BellSout	h tariff or as n	egotiated by t	he Parties upor	n request by ei	ther Party.					

Version 1Q03: 02/28/03

ODUF/ADUF	/EODUF/CMDS - Florida												Attach	ment: 7	Exhi	ibit: A
CATEGORY	RATE ELEMENTS	Interi m	Zone	BCS	usoc	RATES (\$)					Submitted Manually	Charge -	Charge -	Charge - Manual Svc Order vs.	Incremental Charge - Manual Svc Order vs. Electronic- Disc Add'l	
						Rec	Nonre	curring	Nonrecurring	g Disconnect			oss	Rates (\$)		
						Rec	First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
ODUF/ADUF/O																
ACCES	SS DAILY USAGE FILE (ADUF)															
	ADUF: Message Processing, per message				N/A	0.001656										
	ADUF: Data Transmission (CONNECT:DIRECT), per message				N/A	0.0001245										
OPTIO	NAL DAILY USAGE FILE (ODUF)															
	ODUF: Recording, per message				N/A	0.0000071										
	ODUF: Message Processing, per message				N/A	0.002146										
	ODUF: Message Processing, per Magnetic Tape provisioned				N/A	35.91										
	ODUF: Data Transmission (CONNECT:DIRECT), per message				N/A	0.00010375										
CENTR	ALIZED MESSAGE DISTRIBUTION SERVICE (CMDS)															
	CMDS: Message Processing, per message			·	N/A	0.004										
	CMDS: Data Transmission (CONNECT:DIRECT), per message			_	N/A	0.001										
ENHA	ICED OPTIONAL DAILY USAGE FILE (EODUF)		ļ													
	EODUF: Message Processing, per message				N/A	0.080698			1	l	l					1
Notes:	If no rate is identified in the contract, the rate for the specific	service	or fun	ction will be as set	forth in appli	cable BellSout	h tariff or as n	egotiated by t	he Parties upor	n request by ei	ther Party.					

ODUF/ADUF	/EODUF/CMDS - Georgia												Attach	ment: 7	Exhi	bit: A
CATEGORY	RATE ELEMENTS	Interi m	Zone	BCS	usoc	RATES (\$)					Submitted Manually	Charge -	Charge -	Charge - Manual Svc Order vs.	Incremental Charge - Manual Svc Order vs. Electronic- Disc Add'l	
						Rec	Nonre	curring	Nonrecurring	g Disconnect			oss	Rates (\$)		
						Rec	First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
ODUF/ADUF/C																
ACCES	SS DAILY USAGE FILE (ADUF)															
	ADUF: Message Processing, per message				N/A	0.0136327										
	ADUF: Data Transmission (CONNECT:DIRECT), per message				N/A	0.0000434										
OPTIO	NAL DAILY USAGE FILE (ODUF)															
	ODUF: Recording, per message				N/A	0.0001275										
	ODUF: Message Processing, per message				N/A	0.0082548										
	ODUF: Message Processing, per Magnetic Tape provisioned				N/A	28.85										
	ODUF: Data Transmission (CONNECT:DIRECT), per message				N/A	0.0000434										
CENT	ALIZED MESSAGE DISTRIBUTION SERVICE (CMDS)															
	CMDS: Message Processing, per message				N/A	0.004										
	CMDS: Data Transmission (CONNECT:DIRECT), per message				N/A	0.001										
ENHA	ICED OPTIONAL DAILY USAGE FILE (EODUF)															
	EODUF: Message Processing, per message				N/A	0.0034555										
Notes:	If no rate is identified in the contract, the rate for the specific	service	or fun	ction will be as set	forth in appli	cable BellSout	h tariff or as n	egotiated by t	he Parties upor	n request by ei	ther Party.					

ODUF/ADUF	/ADUF/EODUF/CMDS - Kentucky												Attach	ment: 7	Exhi	ibit: A
CATEGORY	RATE ELEMENTS	Interi m	Zone	BCS	usoc	RATES (\$) Nonrecurring Nonrecurring Disconnect				Submitted	Charge -	Charge -	Charge - Manual Svc Order vs.	Incremental Charge - Manual Svc Order vs. Electronic- Disc Add'l		
						Rec	Nonre	curring	Nonrecurring	Disconnect			oss	Rates (\$)		
						Rec	First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
ODUF/ADUF/C																
ACCES	SS DAILY USAGE FILE (ADUF)															
	ADUF: Message Processing, per message				N/A	0.001857										
	ADUF: Data Transmission (CONNECT:DIRECT), per message				N/A	0.0001245										
OPTIO	NAL DAILY USAGE FILE (ODUF)															
	ODUF: Recording, per message				N/A	0.0000136										
	ODUF: Message Processing, per message				N/A	0.002506										
	ODUF: Message Processing, per Magnetic Tape provisioned				N/A	35.90										
	ODUF: Data Transmission (CONNECT:DIRECT), per message				N/A	0.00010372										
CENTE	ALIZED MESSAGE DISTRIBUTION SERVICE (CMDS)															
	CMDS: Message Processing, per message				N/A	0.004										ļ
	CMDS: Data Transmission (CONNECT:DIRECT), per message				N/A	0.001										
ENHA	ICED OPTIONAL DAILY USAGE FILE (EODUF)															
	EODUF: Message Processing, per message				N/A	0.235889										
Notes:	If no rate is identified in the contract, the rate for the specific	service	or fun	ction will be as set t	forth in appli	cable BellSout	h tariff or as n	egotiated by the	he Parties upor	n request by ei	ther Party.					

ODUF/ADUF	/EODUF/CMDS - Louisiana												Attach	ment: 7	Exhi	ibit: A		
CATEGORY	RATE ELEMENTS	Interi m	Zone	BCS	usoc	RATES (\$) Nonrecurring Nonrecurring Disconnect				Submitted Manually	Charge -	Charge -	Charge -	Incremental Charge - Manual Svc Order vs. Electronic- Disc Add'l				
						Rec	Nonre	curring	Nonrecurring	Disconnect			oss	Rates (\$)				
						Rec	First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN		
ODUF/ADUF/O	EDUF/CMDS																	
ACCES	SS DAILY USAGE FILE (ADUF)																	
	ADUF: Message Processing, per message				N/A	0.007983												
	ADUF: Data Transmission (CONNECT:DIRECT), per message				N/A	0.00012681												
OPTIO	NAL DAILY USAGE FILE (ODUF)																	
	ODUF: Recording, per message				N/A	0.0000117												
	ODUF: Message Processing, per message				N/A	0.004641												
	ODUF: Message Processing, per Magnetic Tape provisioned				N/A	48.45												
	ODUF: Data Transmission (CONNECT:DIRECT), per message				N/A	0.00010568												
CENTR	ALIZED MESSAGE DISTRIBUTION SERVICE (CMDS)																	
	CMDS: Message Processing, per message				N/A	0.004												
	CMDS: Data Transmission (CONNECT:DIRECT), per message			_	N/A	0.001												
ENHA	ICED OPTIONAL DAILY USAGE FILE (EODUF)		ļ			0.050045												
	EODUF: Message Processing, per message		<u> </u>		N/A	0.250015			l		L					ļ		
Notes:	If no rate is identified in the contract, the rate for the specific	service	or fun	ction will be as set	forth in appli	cable BellSout	h tariff or as n	Notes: If no rate is identified in the contract, the rate for the specific service or function will be as set forth in applicable BellSouth tariff or as negotiated by the Parties upon request by either Party.										

ODUF/ADUF	F/EODUF/CMDS - Mississippi												Attach	ment: 7	Exhi	ibit: A
CATEGORY	RATE ELEMENTS	Interi m	Zone	BCS	usoc	RATES (\$) Nonrecurring Nonrecurring Disconnect					Submitted Manually	Charge -	Charge -	Charge - Manual Svc Order vs.	Incremental Charge - Manual Svc Order vs. Electronic- Disc Add'l	
						Rec	Nonre	curring	Nonrecurring	g Disconnect			oss	Rates (\$)		
						Rec	First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
ODUF/ADUF/C	EDUF/CMDS															
ACCES	SS DAILY USAGE FILE (ADUF)															
	ADUF: Message Processing, per message				N/A	0.008087										
	ADUF: Data Transmission (CONNECT:DIRECT), per message				N/A	0.00012803										
OPTIO	NAL DAILY USAGE FILE (ODUF)															
	ODUF: Recording, per message				N/A	0.0000063										
	ODUF: Message Processing, per message				N/A	0.004707										
	ODUF: Message Processing, per Magnetic Tape provisioned				N/A	49.04										
	ODUF: Data Transmission (CONNECT:DIRECT), per message				N/A	0.00010669										
CENTE	RALIZED MESSAGE DISTRIBUTION SERVICE (CMDS)															
	CMDS: Message Processing, per message			·	N/A	0.004										
	CMDS: Data Transmission (CONNECT:DIRECT), per message			_	N/A	0.001										
ENHA	NCED OPTIONAL DAILY USAGE FILE (EODUF)					0.050404										
	EODUF: Message Processing, per message	l			N/A	0.250424			1	<u> </u>	l					ļ
Notes:	If no rate is identified in the contract, the rate for the specific	service	or fun	ction will be as set	forth in appli	cable BellSout	h tariff or as n	egotiated by t	he Parties upor	n request by ei	ther Party.					

ODUF/ADUF	F/EODUF/CMDS - North Carolina												Attach	ment: 7	Exhi	ibit: A		
CATEGORY	RATE ELEMENTS	Interi m	Zone	BCS	usoc	RATES (\$)					Submitted Manually	Charge -	Charge -	Charge - Manual Svc Order vs.	Incremental Charge - Manual Svc Order vs. Electronic- Disc Add'l			
						Rec	Nonre	curring	Nonrecurring	g Disconnect			oss	Rates (\$)				
						Rec	First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN		
ODUF/ADUF/C	DEDUF/CMDS																	
ACCES	SS DAILY USAGE FILE (ADUF)																	
	ADUF: Message Processing, per message				N/A	0.01435												
	ADUF: Data Transmission (CONNECT:DIRECT), per message				N/A	0.0001277												
OPTIO	NAL DAILY USAGE FILE (ODUF)																	
	ODUF: Recording, per message				N/A	0.0003												
	ODUF: Message Processing, per message				N/A	0.0032												
	ODUF: Message Processing, per Magnetic Tape provisioned				N/A	54.61												
	ODUF: Data Transmission (CONNECT:DIRECT), per message				N/A	0.00004												
CENT	RALIZED MESSAGE DISTRIBUTION SERVICE (CMDS)																	
	CMDS: Message Processing, per message				N/A	0.004												
	CMDS: Data Transmission (CONNECT:DIRECT), per message				N/A	0.001												
ENHA	NCED OPTIONAL DAILY USAGE FILE (EODUF)																	
	EODUF: Message Processing, per message		<u> </u>		N/A	0.2285406			1	<u> </u>	l					ļ		
Notes:	If no rate is identified in the contract, the rate for the specific	service	or fun	ction will be as set	forth in appli	cable BellSout	Notes: If no rate is identified in the contract, the rate for the specific service or function will be as set forth in applicable BellSouth tariff or as negotiated by the Parties upon request by either Party.											

ODUF/ADUF	ADUF/EODUF/CMDS - South Carolina												Attach	ment: 7	Exhi	ibit: A
CATEGORY	RATE ELEMENTS	Interi m	Zone	BCS	usoc	RATES (\$) Rec Nonrecurring Nonrecurring Disconnect				Submitted	Charge -	Charge -	Charge - Manual Svc Order vs.	Incremental Charge - Manual Svc Order vs. Electronic- Disc Add'l		
						Das	Nonre	curring	Nonrecurring	Disconnect			oss	Rates (\$)	•	
						Rec	First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
ODUF/ADUF/O																
ACCES	SS DAILY USAGE FILE (ADUF)															
	ADUF: Message Processing, per message				N/A	0.008061										
	ADUF: Data Transmission (CONNECT:DIRECT), per message				N/A	0.00013036										
OPTIO	NAL DAILY USAGE FILE (ODUF)															
	ODUF: Recording, per message				N/A	0.0000216										
	ODUF: Message Processing, per message				N/A	0.004704										
	ODUF: Message Processing, per Magnetic Tape provisioned				N/A	48.87										
	ODUF: Data Transmission (CONNECT:DIRECT), per message				N/A	0.00010863										
CENTR	ALIZED MESSAGE DISTRIBUTION SERVICE (CMDS)															
	CMDS: Message Processing, per message				N/A	0.004										
	CMDS: Data Transmission (CONNECT:DIRECT), per message				N/A	0.001										
ENHAN	ICED OPTIONAL DAILY USAGE FILE (EODUF)															
	EODUF: Message Processing, per message				N/A	0.258301										
Notes:	If no rate is identified in the contract, the rate for the specific	service	or fun	ction will be as set t	forth in appli	cable BellSout	h tariff or as n	egotiated by the	he Parties upor	request by ei	ther Party.					

ODUF/ADUF	F/EODUF/CMDS - Tennessee												Attach	ment: 7	Exhi	ibit: A
CATEGORY	RATE ELEMENTS	Interi m	Zone	BCS	USOC	RATES (\$)				Submitted Manually	Charge -	Charge -	Charge - Manual Svc Order vs.	Incremental Charge - Manual Svc Order vs. Electronic- Disc Add'l		
						Rec	Nonrecurring		Nonrecurring	g Disconnect			oss	Rates (\$)	•	
						Rec	First	Add'l	First	Add'l	SOMEC	SOMAN	SOMAN	SOMAN	SOMAN	SOMAN
ODUF/ADUF/C	EDUF/CMDS															
ACCES	SS DAILY USAGE FILE (ADUF)															
	ADUF: Message Processing, per message				N/A	0.004										
	ADUF: Data Transmission (CONNECT:DIRECT), per message				N/A	0.001										
OPTIO	NAL DAILY USAGE FILE (ODUF)															
	ODUF: Recording, per message				N/A	0.0000044										
	ODUF: Message Processing, per message				N/A	0.0027366										
	ODUF: Message Processing, per Magnetic Tape provisioned				N/A	52.75										
	ODUF: Data Transmission (CONNECT:DIRECT), per message				N/A	0.0000339										
CENT	RALIZED MESSAGE DISTRIBUTION SERVICE (CMDS)															
	CMDS: Message Processing, per message				N/A	0.004										
	CMDS: Data Transmission (CONNECT:DIRECT), per message				N/A	0.001										
ENHA	NCED OPTIONAL DAILY USAGE FILE (EODUF)															
	EODUF: Message Processing, per message				N/A	0.004										
Notes:	Notes: If no rate is identified in the contract, the rate for the specific service or function will be as set forth in applicable BellSouth tariff or as negotiated by the Parties upon request by either Party.															

Attachment 8

Rights-of-Way, Conduits and Pole Attachments

Rights-of-Way, Conduits and Pole Attachments

BellSouth will provide nondiscriminatory access to any pole, duct, conduit, or right-of-way owned or controlled by BellSouth pursuant to 47 U.S.C. § 224, as amended by the Act, pursuant to terms and conditions of a license agreement subsequently negotiated with BellSouth's Competitive Structure Provisioning Center.

Attachment 9

Performance Measurements

Version 1Q03: 04/11/03

PERFORMANCE MEASUREMENTS

Upon a particular Commission's issuance of an Order pertaining to Performance Measurements in a proceeding expressly applicable to all CLECs generally, BellSouth shall implement in that state such Performance Measurements as of the date specified by the Commission. Performance Measurements that have been Ordered in a particular state can currently be accessed via the internet at https://pmap.bellsouth.com. The following Service Quality Measurements (SQM) plan adopted by the Florida Commission on February 14, 2002, as it presently exists and as it may be modified in the future, is being included as the performance measurements currently in place for the state of Tennessee. At such time that the TRA issues a subsequent Order pertaining to Performance Measurements, such Performance Measurements shall supersede the SQM contained in the Agreement.

Version 1Q03: 04/11/03

BellSouth Service Quality Measurement Plan (SQM)

Tennessee Performance Metrics

Measurement Descriptions
Version 1.00

Issue Date: December 1, 2002

Introduction

The BellSouth Service Quality Measurement Plan (SQM) describes in detail the measurements produced to evaluate the quality of service delivered to BellSouth's customers both wholesale and retail. The SQM was developed to respond to the requirements of the Communications Act of 1996 Section 251 (96 Act) which required BellSouth to provide non-discriminatory access to Competitive Local Exchange Carriers (CLEC)¹ and their Retail Customers. The reports produced by the SQM provide regulators, CLECs and BellSouth the information necessary to monitor the delivery of non-discriminatory access.

This plan results from the many divergent forces evolving from the 96 Act. The 96 Act, the Georgia Public Service Commission (GPSC) Order (Docket 7892-U 12/30/97), LCUG 1-7.0, the FCC's NPRM (CC Docket 98-56 RM9101 04/17/98), the Louisiana Public Service Commission (LPSC) Order (Docket U-22252 Subdocket C 04/19/98), the Florida Public Service Commission Order (Docket 000121-TP), numerous arbitration cases, LPSC sponsored collaborative workshops (10/98-02/00), and proceedings in Alabama, Mississippi, and North Carolina have and continue to influence the SQM.

The SQM and the reports flowing from it must change to reflect the dynamic requirements of the industry. New measurements are added as new products, systems, and processes are developed and fielded. New products and services are added as the markets for them develop and the processes stabilize. The measurements are also changed to reflect changes in systems, correct errors, and respond to both 3rd Party audit requirements and the Tennessee Regulatory Authority.

This document is intended for use by someone with knowledge of telecommunications industry, information technologies and a functional knowledge of the subject areas covered by the BellSouth Performance Measurements and the reports that flow from them.

Once it is approved, the most current copy of this document can be found on the web at URL: http://pmap.bellsouth.com in the Documentation/Exhibits folder.

Report Publication Dates

Each month, preliminary SQM reports will be posted to BellSouth's SQM web site (http://pmap.bellsouth.com) by 8:00 A.M. EST on the 21st day of each month or the first business day after the 21st. The validated SQM reports will be posted by 8:00 A.M. on the last day of the month. Reports not posted by this time will be considered late for SEEM payment purposes. Validated SEEM reports will be posted on the 15th of the following month. SEEM payments due will also be paid on the 15th of the following month. For instance: May data will be posted in preliminary SQM reports on June 21. Final validated SQM reports will be posted on the 15th of the following month. Final validated SEEM reports will be posted and payments mailed on the 15th of the following month. BellSouth shall retain the performance measurement raw data files for a period of 18 months and further retain the monthly reports produced in PMAP for a period of three years.

1. Alternative Local Exchange Companies (ALEC) and Competing Local Providers (CLP) are referred to as Competitive Local Exchange Carriers (CLEC) in this document.



Report Delivery Methods

CLEC SQM and SEEM reports will be considered delivered when posted to the web site. The Tennessee Regulatory Authority has access to the web site. In addition, a copy of the Monthly State Summary reports will be filed with the TRA as soon as possible after the last day of each month.

Version 1.00 iii Issue Date: December 1, 2002



Contents

Section 1:	Operations Support Systems (OSS)	
	Average Response Time and Response Interval (Pre-Ordering/Ordering)	1-1
OSS-2:	Interface Availability (Pre-Ordering/Ordering)	1-5
OSS-3:	Interface Availability (Maintenance & Repair)	1-8
OSS-4:	Response Interval (Maintenance & Repair)	1-10
PO-1:	Loop Makeup - Response Time - Manual	1-12
PO-2:	Loop Make Up - Response Time - Electronic	1-14
Section 2:	Ordering	
O-1:	Acknowledgement Message Timeliness	2-1
O-2:	Acknowledgement Message Completeness	2-3
O-3:	Percent Flow-Through Service Requests (Summary)	2-5
O-4:	Percent Flow-Through Service Requests (Detail)	2-8
O-5:	Flow-Through Error Analysis	
O-6:	CLEC LSR Information	
•	LSR Flow Through Matrix	2-15
O-7:	Percent Rejected Service Requests	2-18
O-8:	Reject Interval	
O-9:	Firm Order Confirmation Timeliness	
O-10:	Service Inquiry with LSR Firm Order Confirmation (FOC) Response Time Manual	2-27
O-11:	Firm Order Confirmation and Reject Response Completeness	2-29
O-12:	Speed of Answer in Ordering Center	2-31
Section 3:	Provisioning	
P-1:	Mean Held Order Interval & Distribution Intervals	3-1
P-2:	Average Jeopardy Notice Interval & Percentage of Orders Given Jeopardy Notices	3-4
P-3:	Percent Missed Initial Installation Appointments	3-7
P-3A:	Percent Missed Installation Appointments Including Subsequent Appointments	3-10
P-4:	Average Completion Interval (OCI) & Order Completion Interval Distribution	3-13
P-4A:	Average Order Completion and Completion Notice Interval (AOCCNI) Distribution	3-16
P-5:	Average Completion Notice Interval	3-20
P-6:	% Completions/Attempts without Notice or < 24 hours Notice	3-23
P-7:	Coordinated Customer Conversions Interval	
P-7A:	Coordinated Customer Conversions – Hot Cut Timeliness % Within Interval and Average Interval	
P-7B:	Coordinated Customer Conversions – Average Recovery Time	
P-7C:	Hot Cut Conversions - % Provisioning Troubles Received Within 7 days of a completed Service Order	
P-8:	Cooperative Acceptance Testing - % of xDSL Loops Successfully Tested	3-33
P-9:	% Provisioning Troubles within 30 days of Service Order Completion	3-35
P-10:	Total Service Order Cycle Time (TSOCT)	3-38
P-11:	Service Order Accuracy	
P-12:	LNP-Average Disconnect Timeliness Interval & Disconnect Timeliness Interval Distribution	3-4:
Section 4:	Maintenance & Repair	
M&R-1:	Missed Repair Appointments	4-1
M&R-2:	Customer Trouble Report Rate	4-4



M&P.	-3: Maintenance Average Duration	
M&R	-4: Percent Repeat Troubles within 30 Days	4-10
	-5: Out of Service (OOS) > 24 Hours	
M&R	-6: Average Answer Time – Repair Centers	4-16
M&R	-7: Mean Time To Notify CLEC of Network Outages	4-17
Section	5: Billing	
B-1:	Invoice Accuracy	5-1
B-2:	Mean Time to Deliver Invoices	
B-3:	Usage Data Delivery Accuracy	
B-4:	Usage Data Delivery Completeness	
B-5:	Usage Data Delivery Timeliness	
B-6:	Mean Time to Deliver Usage	
B-7:	Recurring Charge Completeness	
B-8:	Non-Recurring Charge Completeness	
B-9: B-10:	Percent Daily Usage Feed Errors Corrected in X Business Days Percent Billing Errors Corrected in X Days	5 10
B-10.	Percent Billing Errors Corrected in X Days	3-1/
Section	6: Operator Services And Directory Assistance	
OS-1:		6-1
OS-2:		6-3
DA-1:		6-4
DA-2:	: Speed to Answer Performance/Percent Answered within "X" Seconds – Directory Assistance (DA)	6-5
Section	7: Database Update Information	
D-1:	Average Database Update Interval	7-1
D-2:	Percent Database Update Accuracy	7-3
D-3:	Percent NXXs and LRNs Loaded by the LERG Effective Date	7-5
Section	8: E911	
E-1:	Timeliness	8-1
E-2:	Accuracy	
E-3:	Mean Interval	
Section	9: Trunk Group Performance	
	1: Trunk Group Performance-Aggregate	Q 1
TGP-	Trunk Group Performance – CLEC Specific Trunk Group Performance – CLEC Specific	9_?
101 2	2. Trunk Group Performance CEEE Speeme	, ,
	10: Collocation	
C-1:	Collocation Average Response Time	10-1
C-2:	Collocation Average Arrangement Time	
C-3:	Collocation Percent of Due Dates Missed	10-3
Section	11: Change Management	
CM-1		
CM-2		11-3
CM-3		
CM-4		11-5
CM-5	Notification of CLEC Interface Outages	11-7
Append	lix A: Reporting Scope	A-1
A-1:	Standard Service Groupings	A-1
A-2:	Standard Service Order Activities	

CCCS 685 of 869



Appendi	x B: Glossary of Acronyms and Terms	B-1
Appendi	ix C: BellSouth Audit Policy	C-1
C-1:	BellSouth's Internal Audit Policy	C-1
C-2:	BellSouth's External Audit Policy	



Section 1: Operations Support Systems (OSS)

OSS-1: Average Response Time and Response Interval (Pre-Ordering/ Ordering)

Definition

Average response time and response intervals are the average times and number of requests responded to within certain intervals for accessing legacy data associated with appointment scheduling, service & feature availability, address verification, request for Telephone numbers (TNs), and Customer Service Records (CSRs).

Exclusions

Syntactically incorrect queries.

Business Rules

The average response time for retrieving pre-order/order information from a given legacy system is determined by summing the response times for all requests submitted to the legacy systems during the reporting period and dividing by the total number of legacy system requests for that month.

The date/time stamp shall begin when BST receives a query at the BellSouth Gateway and shall end when the query is transmitted from the BST Gateway (applies to both TAG and LENS). For BellSouth, the response interval starts when the client application (RNS or ROS) submits a request to the legacy system and ends when the appropriate response is returned to the client application. The number of accesses to the legacy systems during the reporting period which take less than 2.3 seconds, the number of accesses which take more than 6 seconds, and the number which are less than or equal to 6.3 seconds are also captured.

Calculation

Response Time = (a - b)

- a = Date & Time of Legacy Response
- b = Date & Time of Legacy Request

Average Response Time = $c \div d$

- c = Sum of Response Times
- d = Number of Legacy Requests During the Reporting Period

Report Structure

- · Interface Type
- Not CLEC Specific
- Not product/service specific
- Regional Level

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report Month	Report Month
Legacy Contract (per reporting dimension)	Legacy Contract (per reporting dimension)
Response Interval	Response Interval
Regional Scope	Regional Scope

Version 1.00 1-1 Issue Date: December 1, 2002



SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
 RSAG – Address (Regional Street Address Guide-Address) – stores street address information used to validate customer addresses. CLECs and BellSouth query this legacy system. RSAG – TN (Regional Street Address Guide-Telephone number) – contains information about facilities available and telephone numbers working at a given address. CLECs and BellSouth query this legacy system. ATLAS (Application for Telephone Number Load Administration and Selection) – acts as a warehouse for storing telephone numbers that are available for assignment by the system. It enables CLECs and BellSouth service reps to select and reserve telephone numbers. CLECs and BellSouth query this legacy system. COFFI (Central Office Feature File Interface) – stores information about product and service offerings and availability. CLECs query this legacy system. DSAP (DOE Support Application) – provides due date information. CLECs and BellSouth query this legacy system. CRIS (Customer Record Information System) – Source of CSR (Customer Service Record) information. Contains information about individual customers including listings, addresses, features, services, etc. CLECs and BellSouth can query for CSR information. P/SIMS (Product/Services Inventory Management system) – provides information on capacity, tariffs, inventory and service availability. CLECs query this legacy system. OASIS (Obtain Available Services Information Systems) – Information on feature and rate availability. BellSouth queries this legacy system. 	• Parity + 2 seconds

Table 1: Legacy System Access Times For RNS

System	Contract	Data	< 2.3 sec.	> 6 sec.	<u>≤</u> 6.3 sec.	Avg. Sec.	# of Calls
RSAG	RSAG-TN	Address	X	X	X	X	X
RSAG	RSAG-ADDR	Address	X	X	X	x	х
ATLAS	ATLAS-TN	TN	X	X	X	x	Х
DSAP	DSAP-DDI	Schedule	X	X	X	X	х
CRIS	CRSACCTS	CSR	X	X	X	X	х
OASIS	OASISCAR	Feature/Service	X	X	X	X	Х
OASIS	OASISLPC	Feature/Service	X	X	X	X	х
OASIS	OASISMTN	Feature/Service	X	X	X	X	х
OASIS	OASISBIG	Feature/Service	X	X	X	X	Х

Table 2: Legacy System Access Times For R0S

System	Contract	Data	< 2.3 sec.	> 6 sec.	<u><</u> 6.3 sec.	Avg. sec.	# of Calls
RSAG	RSAG-TN	Address	х	X	х	х	х
RSAG	RSAG-ADDR	Address	Х	X	Х	Х	х
ATLAS	ATLAS-TN	TN	Х	X	X	X	Х

Version 1.00 1-2 Issue Date: December 1, 2002



Table 2: Legacy System Access Times For R0S

System	Contract	Data	< 2.3 sec.	> 6 sec.	<u><</u> 6.3 sec.	Avg. sec.	# of Calls
DSAP	DSAP-DDI	Schedule	х	X	X	х	X
CRIS	CRSOCSR	CSR	Х	X	X	Х	X
OASIS	OASISBIG	Feature/Service	X	X	X	X	X

Table 3: Legacy System Access Times For LENS

System	Contract	Data	< 2.3 sec.	> 6 sec.	<u><</u> 6.3 sec.	Avg. sec.	# of Calls
RSAG	RSAG-TN	Address	X	X	X	х	X
RSAG	RSAG-ADDR	Address	X	X	X	X	X
ATLAS	ATLAS-TN	TN	X	X	X	X	X
DSAP	DSAP	Schedule	X	X	X	X	X
CRIS	CRSECSRL	CSR	X	X	X	X	X
COFFI	COFFI/USOC	Feature/Service	X	X	X	X	X
P/SIMS	PSIMS/ORB	Feature/Service	х	X	X	X	X

Table 4: Legacy System Access Times For TAG

System	Contract	Data	< 2.3 sec.	> 6 sec.	<u><</u> 6.3 sec.	Avg. sec.	# of Calls
RSAG	RSAG-TN	Address	x	X	X	x	X
RSAG	RSAG-ADDR	Address	X	X	X	Х	Х
ATLAS	ATLAS-TN	TN	X	X	X	X	X
ATLAS	ATLAS-MLH	TN	X	X	X	х	Х
ATLAS	ATLAS-DID	TN	X	X	X	Х	Х
DSAP	DSAP-DDI	Schedule	X	X	X	X	X
CRIS	TAG-CSR	CSR	X	X	X	х	Х
P/SIMS	PSIM/ORB	Feature/Service	X	X	X	Х	X

SEEM Measure

SEEM Measure			
Yes	Tier I		
	Tier II	X	

Note: CLEC specific data is not available in this measure. Queries of this sort do not have company specific signatures.

OSS-1: Average Response Time and Response Interval (Pre-Ordering/Ordering)

SEEM Disaggregation - Analog/Benchmark

SEEM Disaggregation	SEEM Analog/Benchmark
 RSAG – Address (Regional Street Address Guide-Address) – stores street address information used to validate customer addresses. CLECs and BellSouth query this legacy system. RSAG – TN (Regional Street Address Guide-Telephone number) – contains information about facilities available and telephone numbers working at a given address. CLECs and BellSouth query this legacy system. ATLAS (Application for Telephone Number Load Administration and Selection) – acts as a warehouse for storing telephone numbers that are available for assignment by the system. It enables CLECs and BellSouth service reps to select and reserve telephone numbers. CLECs and BellSouth query this legacy system. COFFI (Central Office Feature File Interface) – stores information about product and service offerings and availability. CLECs query this legacy system. DSAP (DOE Support Application) – provides due date information. CLECs and BellSouth query this legacy system. CRIS (Customer Record Information System) – Source of CSR (Customer Service Record) information. Contains information about individual customers including listings, addresses, features, services, etc. CLECs and BellSouth can query for CSR information. P/SIMS (Product/Services Inventory Management system) – provides information on capacity, tariffs, inventory and service availability. CLECs query this legacy system. OASIS (Obtain Available Services Information Systems) – Information on feature and rate availability. BellSouth queries this legacy system. 	• Parity + 2 Seconds

SEEM OSS Legacy Systems

System	BellSouth	CLEC			
Telephone Number/Address					
RSAG-ADDR	RNS, ROS	TAG, LENS			
RSAG-TN	RNS, ROS	TAG, LENS			
Atlas	RNS,ROS	TAG. LENS			
	Appointment Scheduling				
DSAP	RNS, ROS	TAG, LENS			
	CSR Data				
CRSACCTS	RNS				
CRSOCSR	ROS				
CRSECSRL		LENS			
TAG-CSR		TAG			
Service/Feature Availability					
OASISBIG	RNS, ROS				
PSIMS/ORB, COFFI		LENS, TAG			

Version 1.00 1-4 Issue Date: December 1, 2002



OSS-2: Interface Availability (Pre-Ordering)Ordering)

Definition

Percent of time OSS interface is functionally available compared to scheduled availability. Availability percentages for CLEC interface systems and for all Legacy systems accessed by them are captured. ("Functional Availability" is the amount of time in hours during the reporting period that the legacy systems are available to users. The planned System Scheduled Availability is the time in hours per day that the legacy system is scheduled to be available.)

Scheduled availability is posted on the ICS Operations internet site: (www.interconnection.bellsouth.com/oss/osshour.html)

Exclusions

None

Business Rules

This measurement captures the functional availability of applications/interfaces as a percentage of scheduled availability for the same systems. Only full outages are included in the calculation for this measure. Full outages are defined as occurrences of either of the following:

- Application/Interface application is down or totally inoperative.
- Application is totally inoperative for customers attempting to access or use the application. This includes transport outages when they
 may be directly associated with a specific application.

Comparison to an internal benchmark provides a vehicle for determining whether or not CLECs and retail BellSouth entities are given comparable opportunities for use of pre-ordering and ordering systems.

(Note: Scheduled maintenance will not be performed between the hours of 8:00 a.m through 9:00 p.m. Monday through Friday.)

Calculation

Interface Availability (Pre-Ordering/Ordering) = $(a \div b) \times 100$

- a = Functional Availability
- b = Scheduled Availability

Report Structure

- · Interface Type
- · Not CLEC Specific
- · Not product/service specific
- · Regional Level

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report Month	Report Month
 Legacy Contract Type (per reporting dimension) 	Legacy Contract Type (per reporting dimension)
Regional Scope	Regional Scope
Hours of Downtime	Hours of Downtime

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
Regional Level	• ≥ 99.5%

OSS Interface Availability OSS Interface

OSS Interface	Applicable to	% Availability
EDI	CLEC	х
LENS	CLEC	X
LEO	CLEC	X
LESOG	CLEC	X
PSIMS	CLEC	X
TAG	CLEC	X
LNP Gateway	CLEC	X
COG	CLEC	X
SOG	CLEC	X
DOM	CLEC	X
DOE	CLEC/BellSouth	X
CRIS	CLEC/BellSouth	X
ATLAS/COFFI	CLEC/BellSouth	X
BOCRIS	CLEC/BellSouth	X
DSAP	CLEC/BellSouth	X
RSAG	CLEC/BellSouth	X
SOCS	CLEC/BellSouth	X
SONGS	CLEC/BellSouth	X
RNS	BellSouth	X
ROS	BellSouth	X

SEEM Measure

SEEM Measure				
Yes	Tier I			
	Tier II	X		

SEEM Disaggregation - Analog/Benchmark

SEEM Disaggregation	SEEM Analog/Benchmark		
Regional Level	• ≥ 99.5%		

SEEM OSS Interface Availability

OSS Interface	Applicable to	% Availability
EDI	CLEC	X
LENS	CLEC	X
LEO	CLEC	X
LESOG	CLEC	X
PSIMS	CLEC	X



OSS Interface Applicable to % Availability TAG CLEC Х LNP Gateway CLEC X COG CLEC X SOG CLEC \mathbf{X} DOM CLEC X



OSS-3: Interface Availability (Maintenance & Repair)

Definition

This measures the percentage of time the OSS Interface is functionally available compared to scheduled availability percentage for the CLEC and BellSouth interface systems and for the legacy systems accessed by them are captured.

Scheduled availability is posted on the ICS Operations internet site: (www.interconnection.bellsouth.com/oss/osshour.html)

Exclusions

None

Business Rules

This measure is designed to compare the OSS availability versus scheduled availability of BellSouth's legacy systems.

Note: Only full outages are used in the calculation of Application Availability. A full outage is incurred when any of the following circumstances exists:

- The application or system is down.
- The application or system is inaccessible, for any reason, by the customers who normally access the application or system.
- More than one work center cannot access the application or system for any reason.
- When only one work center accesses an application or system and 40% or more of the clients in that work center cannot access the application.
- When 40% of the functions the clients normally perform or 40% of the functionality that is normally provided by an application or system is unavailable.

(Note: Scheduled maintenance will not be performed between the hours of 8:00 a.m through 9:00 p.m. Monday through Friday.)

Calculation

OSS Interface Availability (a \div b) X 100

- a = Functional Availability
- b = Scheduled Availability

Report Structure

- · Interface Type
- · Not CLEC Specific
- Not product/service specific
- · Regional Level

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance		
 Availability of CLEC TAFI Availability of LMOS HOST, MARCH, SOCS, CRIS, PREDICTOR, LNP and OSPCM ECTA 	Availability of BellSouth TAFI Availability of LMOS HOST, MARCH, SOCS, CRIS, PREDICTOR, LNP and OSPCM		

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark			
Regional Level	• ≥ 99.5%			



OSS Interface Availability (M&R)

OSS Interface	% Availability		
BellSouth TAFI	x		
CLEC TAFI	x		
CLEC ECTA	x		
BellSouth & CLEC	X		
CRIS	x		
LMOS HOST	X		
LNP	x		
MARCH	x		
OSPCM	x		
PREDICTOR	x		
SOCS	x		

SEEM Measure

SEEM Measure			
Yes	Tier I		
	Tier II	X	

SEEM Disaggregation - Analog/Benchmark

SEEM Disaggregation	SEEM Analog/Benchmark			
Regional Level	• ≥ 99.5%			

OSS Interface Availability (M&R)

OSS Interface	% Availability		
CLEC TAFI	х		
CLEC ECTA	x		



OSS-4: Response Interval (Maintenance & Repair)

Definition

The response intervals are determined by subtracting the time a request is received on the BellSouth side of the interface from the time the response is received from the legacy system. Percentages of requests falling into each interval category are reported, along with the actual number of requests falling into those categories.

Exclusions

None

Business Rules

This measure is designed to monitor the time required for the CLEC and BellSouth interface system to obtain from BellSouth's legacy systems the information required to handle maintenance and repair functions. The clock starts on the date and time when the request is received on the BellSouth side of the interface and the clock stops when the response has been transmitted through that same point to the requester.

Note: The OSS Response Interval BellSouth Total Report is a combination of BellSouth Residence and Business Total.

Calculation

OSS Response Interval = (a - b)

- a = Query Response Date and Time
- b = Query Request Date and Time

Percent Response Interval (per category) = $(c \div d) \times 100$

- c = Number of Response Intervals in category "X"
- d = Number of Queries Submitted in the Reporting Period

where, "X" is
$$\leq 4$$
, $> 4 \leq 10$, ≤ 10 , > 10 , or > 30 seconds.

Average Interval = $(e \div f)$

- e = Sum of Response Intervals
- f = Number of Queries Submitted in the Reporting Period

Report Structure

- Not CLEC Specific
- Not product/service specific
- · Regional Level

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance		
CLEC Transaction Intervals	BellSouth Business and Residential Transactions Intervals		

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark		
Regional Level	Average Interval		



Legacy System Access Times for M&R

System	BellSouth & CLEC	Count					
		<u>≤</u> 4	> 4 <u><</u> 10	<u>≤</u> 10	> 10	> 30	Avg. Int.
CRIS	х	X	X	X	X	X	Х
DLETH	X	X	X	X	X	X	Х
DLR	X	X	X	X	X	X	Х
LMOS	X	X	X	X	X	X	Х
LMOSupd	X	X	X	X	X	X	Х
LNP	x	X	X	X	X	X	Х
MARCH	х	X	X	X	X	X	х
OSPCM	х	X	X	X	X	X	х
Predictor	х	X	X	X	X	X	х
SOCS	х	X	X	X	X	X	х
NIW	х	x	X	x	X	X	Х

SEEM Measure

SEEM Measure		
Yes	Tier I	
	Tier II	X

SEEM Disaggregation - Analog/Benchmark

SEEM Disaggregation	SEEM Analog/Benchmark
• Region	Average Interval



PO-1: Loop Makeup - Response Time - Manual

Definition

This report measures the average interval and percent within the interval from the submission of a Manual Loop Makeup Service Inquiry (LMUSI) to the distribution of Loop Makeup information back to the CLEC.

Exclusions

- Inquiries, which are submitted electronically.
- Designated Holidays are excluded from the interval calculation.
- Weekends are excluded from the interval calculation.
- · Canceled Inquiries

Business Rules

The CLEC Manual Loop Makeup Service Inquiry (LMUSI) process includes inquiries submitted via mail or FAX to BellSouth's Complex Resale Support Group (CRSG)

This measurement combines three intervals:

- 1. From receipt of a valid Service Inquiry for Loop Makeup to hand off to the Service Advocacy Center (SAC) for "Look-up."
- 2. From SAC start date to SAC complete date
- From SAC complete date to date the Complex Resale Support Group (CRSG) distributes loop makeup information back to the CLEC.

The "Receive Date" is defined as the date the Manual LMUSI is received by the CRSG. It is counted as day Zero. LMU "Return Date" is defined as the date the LMU information is sent back to the CLEC from BellSouth. The interval calculation is reset to Zero when a CLEC initiated change occurs on the Manual LMU request.

Note: The Loop Make Up Service Inquiry Form does not require the CLEC to furnish the type of Loop. The CLEC determines whether the loop makeup will support the type of service they wish to order or not and qualifies the loop. If the loop makeup will support the service, a firm order LSR is submitted by the CLEC.

(A valid Service Inquiry is an inquiry that has all required fields populated correctly and has not been returned for clarification.)

Calculation

Response Interval = (a - b)

- a = Date the LMUSI returned to CLEC
- b = Date the LMUSI is received

Average Interval = $(c \div d)$

- c = Sum of all Response Intervals
- d = Total Number of LMUSIs received within the reporting period

Percent within interval = $(e \div f) \times 100$

- e = Total LMUSIs received within the interval
- f = Total Number of LMUSIs processed within the reporting period

Report Structure

- · CLEC Aggregate
- · CLEC Specific
- · Geographic Scope
 - State
 - Region
- Interval for manual LMUs:
 - 0 < 1 day
 - $>1-\leq 2$ days
 - $>2-\leq 3$ days



 $0 - \leq 3 \text{ days}$

 $>3-\leq 6$ days

 $>6 - \le 10 \text{ days}$

> 10 days

· Average Interval in days

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report Month	
Total Number of Inquiries	
SI Intervals	
State and Region	

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
• Loops	Benchmark • 95% ≤ 3 Business Days

SEEM Measure

SEEM Measure		
Yes	Tier I	
	Tier II	X

SEEM Disaggregation - Analog/Benchmark

SEEM Disaggregation	SEEM Analog/Benchmark
• Loops	Benchmark • 95% ≤ 3 Business Days



PO-2: Loop Make Up - Response Time - Electronic

Definition

This report measures the average interval and the percent within the interval from the electronic submission of a Loop Makeup Service Inquiry (LMUSI) to the distribution of Loop Makeup information back to the CLEC.

Exclusions

- Manually submitted inquiries.
- Designated Holidays are excluded from the interval calculation.
- Canceled Requests.

Business Rules

The response interval starts when the CLEC's Mechanized Loop Makeup Service Inquiry (LMUSI) is submitted electronically through the Operational Support Systems interface, LENS, TAG or RoboTAG. It ends when BellSouth's Loop Facility Assignment and Control System (LFACS) responds electronically to the CLEC with the requested Loop Makeup data via LENS, TAG or RoboTAG Interfaces.

Note: The Loop Make Up Service Inquiry Form does not require the CLEC to furnish the type of Loop. The CLEC determines whether the loop makeup will support the type of service they wish to order or not and qualifies the loop. If the loop makeup will support the service, a firm order LSR is submitted by the CLEC. EDI is not a pre-ordering system, and, therefore, is not applicable in this measure.

Calculation

Response Interval = (a - b)

- a = Date and Time the LMUSI returned to CLEC
- b = Date and Time the LMUSI is received

Average Interval = $(c \div d)$

- c = Sum of all response intervals
- d = Total Number of LMUSIs received within the reporting period

Percent within interval = $(e \div f) \times 100$

- e = Total LMUSIs received within the interval
- f = Total Number of LMUSIs processed within the reporting period

Report Structure

- · CLEC Aggregate
- CLEC Specific
- · Geographic Scope
 - State
 - Region
- Interval for electronic LMUs:
 - 0 < 1 minute
 - $>1-\leq 5$ minutes
 - $0 \le 5 \text{ minutes}$
 - $> 5 \le 8$ minutes
 - $> 8 \le 15$ minutes
 - > 15 minutes
- · Average Interval in minutes



Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report MonthLegacy ContractResponse IntervalRegional Scope	Not Applicable

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
• Loop	Benchmark • 95% ≤ 1 Minute

SEEM Measure

SEEM Measure		
Yes	Tier I	
	Tier II	X

SEEM Disaggregation - Analog/Benchmark

SEEM Disaggregation	SEEM Analog/Benchmark
• Loop	• 95% ≤ 1 Minute



Section 2: Ordering

O-1: Acknowledgement Message Timeliness

Definition

This measurement provides the response interval from the time a Message/LSR is electronically submitted via EDI or TAG until an acknowledgement notice is sent by the system.

Exclusions

None

Business Rules

The process includes EDI & TAG system functional acknowledgements for all Local Service Requests (LSRs) which are electronically submitted by the CLEC. The start time is the receipt time of the LSR at BellSouth's side of the interface (gateway). The end time is when the acknowledgement is transmitted by BellSouth at BellSouth's side of the interface (gateway). For those CLECs using EDI, if more than one CLEC uses the same ordering center, an Acknowledgement Message will be returned to the "Aggregator", however, BellSouth will not be able to determine which specific CLEC this message represented.

Calculation

Response Interval = (a - b)

- a = Date and Time Acknowledgement Notices returned to CLEC
- b = Date and Time Messages/LSRs electronically submitted by the CLEC via EDI or TAG respectively

Average Response Interval = $(c \div d)$

- c = Sum of all Response Intervals
- d = Total number of electronically submitted Messages/LSRs received, via EDI or TAG respectively, in the Reporting Period.

Reporting Structure

- · CLEC Aggregate
- CLEC Specific
- Geographic Scope
 - Region
- · Electronically Submitted LSRs
 - $0 \le 10$ minutes
- $> 10 \leq 20$ minutes
- $> 20 \le 30$ minutes
- $0 \le 3\overline{0}$ minutes
- $> 30 \le 45$ minutes
- > 45 \leq 60 minutes
- $> 60 \le 120$ minutes
- > 120 minutes
- · Average interval for electronically submitted LSRs in minutes

(A) BELLSOUTH®

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report MonthRecord of Functional Acknowledgements	Not Applicable

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	Retail Analog/Benchmark
• EDI	• EDI – 95% ≤ 30 Minutes
• TAG	• TAG – 95% ≤ 30 Minutes

SEEM Measure

SEEM Measure				
Yes	Tier I	X		
	Tier II	X		

SEEM Disaggregation - Analog/Benchmark

SEEM Disaggregation	SEEM Analog/Benchmark
• EDI	• EDI – 95% ≤ 30 Minutes
• TAG	• TAG – 95% ≤ 30 Minutes

BELLSOUTH

O-2: Acknowledgement Message Completeness

Definition

This measurement provides the percent of Messages/LSRs received via EDI or TAG, which are acknowledged electronically.

Exclusions

Manually submitted LSRs

Business Rules

EDI and TAG send Functional Acknowledgements for all LSRs, which are electronically submitted by a CLEC. For those CLECs using EDI, if more than one CLEC uses the same ordering center, an Acknowledgement Message will be returned to the "Aggregator", however, BellSouth will not be able to determine which specific CLEC this message represented. The Acknowledgement Message is returned prior to the determination of whether the LSR will be partially mechanized or fully mechanized.

Calculation

Acknowledgement Completeness = $(a \div b) \times 100$

- a = Total number of Functional Acknowledgements returned in the reporting period for Messages/LSRs electronically submitted by EDI or TAG respectively
- b = Total number of electronically submitted Messages/LSRs received in the reporting period by EDI or TAG respectively

Report Structure

- · CLEC Aggregate
- · CLEC Specific
- Geographic Scope
 - Region

Note: Acknowledgement message is generated before the system recognizes whether this message (LSR) will be partially or fully mechanized.

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report MonthRecord of functional acknowledgements	Not Applicable

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
• EDI	• Benchmark: 100%
• TAG	

SEEM Measure

SEEM Measure				
Yes	Tier I	X		
	Tier II	X		

SEEM Disaggregation	SEEM Analog/Benchmark
• EDI	Benchmark: 100%
• TAG	

(A) **BELLSOUTH** *

O-3: Percent Flow-Through Service Requests (Summary)

Definition

The percentage of Local Service Requests (LSR) and LNP Local Service Requests (LNP LSRs) submitted electronically via the CLEC mechanized ordering process that flow through and reach a status for a FOC to be issued, without manual intervention.

Exclusions

- · Fatal Rejects
- Auto Clarification
- Manual Fallout for Percent Flow-Through only
- · CLEC System Fallout

Business Rules

The CLEC mechanized ordering process includes all LSRs, including supplements (subsequent versions) which are submitted through one of the three gateway interfaces (TAG, EDI and LENS), that flow through and reach a status for a FOC to be issued, without manual intervention. These LSRs can be divided into two classes of service: Business and Residence, and two types of service: Resale, and Unbundled Network Elements (UNE). The CLEC mechanized ordering process does not include LSRs which are submitted manually (for example, fax and courier) or are not designed to flow through (for example, Manual Fallout.)

Fatal Rejects: Errors that prevent an LSR, submitted electronically by the CLEC, from being processed further. When an LSR is submitted by a CLEC, LEO/LNP Gateway will perform edit checks to ensure the data received is correctly formatted and complete. For example, if the PON field contains an invalid character, LEO/LNP Gateway will reject the LSR and the CLEC will receive a Fatal Reject.

Auto-Clarification: Clarifications that occur due to invalid data within the LSR. LESOG/LAUTO will perform data validity checks to ensure the data within the LSR is correct and valid. For example, if the address on the LSR is not valid according to RSAG, or if the LNP is not available for the NPA NXXX requested, the CLEC will receive an Auto-Clarification.

Manual Fallout: Planned Fallout that occur by design. Certain LSRs are designed to fallout of the Mechanized Order Process due to their complexity. These LSRs are manually processed by the LCSC. When a CLEC submits an LSR, LESOG/LAUTO will determine if the LSR should be forwarded to LCSC for manual handling. Following are the categories for Manual Fallout:

sion orders

- Complex*
- Special pricing plans
- Some Partial migrations
- New telephone number not yet posted to BOCRIS
- Pending order review required
- CSR inaccuracies such as invalid or missing CSR data in
- 10. Low volume such as activity type "T" (move)
- 11. More than 25 business lines, or more than 15 loops

Denials-restore and conversion, or disconnect and conver-

Class of service invalid in certain states with some types of

- 12. Transfer of calls option for the CLEC end users
- 13. Directory Listings (Indentions and Captions)

- Expedites (requested by the CLEC)
- * See "LSR Flow-Through Matrix" on page 15, for a list of services, including complex services, and whether LSRs issued for the services are eligible to flow through.

Total System Fallout: Errors that require manual review by the LCSC to determine if the error is caused by the CLEC, or is due to BellSouth system functionality. If it is determined the error is caused by the CLEC, the LSR will be sent back to the CLEC for clarification. If it is determined the error is BellSouth caused, the LCSC representative will correct the error, and the LSR will continue to be processed.

Z Status: LSRs that receive a supplemental LSR submission prior to final disposition of the original LSR.

(A) **BELLSOUTH** *

O-3: Percent Flow-Through Service Requests (Summary)

Calculation

Percent Flow Through = $a \div [b - (c + d + e + f)] \times 100$

- a = The total number of LSRs that flow through LESOG/LAUTO and reach a status for a FOC to be issued
- b = the number of LSRs passed from LEO/LNP Gateway to LESOG/LAUTO
- c =the number of LSRs that fall out for manual processing
- d = the number of LSRs that are returned to the CLEC for clarification
- e = the number of LSRs that contain errors made by CLECs
- f =the number of LSRs that receive a Z status.

Percent Achieved Flow Through = $a \div [b-(c+d+e)] \times 100$

- a = the number of LSRs that flow through LESOG/LAUTO and reach a status for a FOC to be issued.
- b = the number of LSRs passed from LEO/LNP Gateway to LESOG/LAUTO
- c =the number of LSRs that are returned to the CLEC for clarification
- d = the number of LSRs that contain errors made by CLECs
- e = the number of LSRs that receive Z status

Report Structure

- · CLEC Aggregate
 - Region

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report Month	Report Month
 Total Number of LSRs Received, by Interface, by CLEC 	Total Number of Errors by Type
- TAG	- BellSouth System Error
- EDI	
- LENS	
 Total Number of Errors by Type, by CLEC 	
- Fatal Rejects	
- Auto Clarification	
- CLEC Caused System Fallout	
Total Number of Errors by Error Code	
Total Fallout for Manual Processing	


SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark ^a
Residence	Benchmark: 95%
Business	Benchmark: 90%
• UNE	Benchmark: 85%
• LNP	Benchmark: 85%

a. Benchmarks do not apply to the "Percent Achieved Flow Through."

SEEM Measure

SEEM Measure		
Yes	Tier I	
	Tier II	X



SEEM Disaggregation	SEEM Analog/Benchmark ^a
Residence	Benchmark: 95%
Business	Benchmark: 90%
• UNE	Benchmark: 85%
• LNP	• Benchmark: 85%

a. Benchmarks do not apply to the "Percent Achieved Flow Through."

(A) **BELLSOUTH** *

O-4: Percent Flow-Through Service Requests (Detail)

Definition

A detailed list, by CLEC, of the percentage of Local Service Requests (LSR) and LNP Local Service Requests (LNP LSRs) submitted electronically via the CLEC mechanized ordering process that flow through and reach a status for a FOC to be issued, without manual or human intervention.

Exclusions

- · Fatal Rejects
- Auto Clarification
- · Manual Fallout for Percent Flow-Through only
- CLEC System Fallout

Business Rules

The CLEC mechanized ordering process includes all LSRs, including supplements (subsequent versions) which are submitted through one of the three gateway interfaces (TAG, EDI, and LENS), that flow through and reach a status for a FOC to be issued, without manual intervention. These LSRs can be divided into two classes of service: Business and Residence, and two types of service: Resale, and Unbundled Network Elements (UNE). The CLEC mechanized ordering process does not include LSRs, which are submitted manually (for example, fax and courier) or are not designed to flow through (for example, Manual Fallout.)

Definitions:

Fatal Rejects: Errors that prevent an LSR, submitted electronically by the CLEC, from being processed further. When an LSR is submitted by a CLEC, LEO/LNP Gateway will perform edit checks to ensure the data received is correctly formatted and complete. For example, if the PON field contains an invalid character, LEO/LNP Gateway will reject the LSR and the CLEC will receive a Fatal Reject.

Auto-Clarification: Clarifications that occur due to invalid data within the LSR. LESOG/LAUTO will perform data validity checks to ensure the data within the LSR is correct and valid. For example, if the address on the LSR is not valid according to RSAG, or if the LNP is not available for the NPA NXXX requested, the CLEC will receive an Auto-Clarification.

Manual Fallout: Planned Fallout that occur by design. Certain LSRs are designed to fallout of the Mechanized Order Process due to their complexity. These LSRs are manually processed by the LCSC. When a CLEC submits an LSR, LESOG/LAUTO will determine if the LSR should be forwarded to LCSC for manual handling. Following are the categories for Manual Fallout:

- Complex*
- Special pricing plans
- 3. Some Partial migrations
- 4. New telephone number not yet posted to BOCRIS
- Pending order review required
- CSR inaccuracies such as invalid or missing CSR data in CRIS

- Denials-restore and conversion, or disconnect and conversion orders
- Class of service invalid in certain states with some types of
- 10. Low volume such as activity type "T" (move)
- 11. More than 25 business lines, or more than 15 loops
- 12. Transfer of calls option for the CLEC end users
- 13. Directory Listings (Indentions and Captions)

- Expedites (requested by the CLEC)
- * See "LSR Flow-Through Matrix" on page 15. for a list of services, including complex services, and whether LSRs issued for the services are eligible to flow through.

Total System Fallout: Errors that require manual review by the LCSC to determine if the error is caused by the CLEC, or is due to BellSouth system functionality. If it is determined the error is caused by the CLEC, the LSR will be sent back to the CLEC for clarification. If it is determined the error is BellSouth caused, the LCSC representative will correct the error, and the LSR will continue to be processed.

Z Status: LSRs that receive a supplemental LSR submission prior to final disposition of the original LSR.

(A) **BELLSO**UTH®

Calculation

Percent Flow Through = $a \div [b - (c + d + e + f)] \times 100$

- a = The total number of LSRs that flow through LESOG/LAUTO and reach a status for a FOC to be issued
- b = the number of LSRs passed from LEO/LNP Gateway to LESOG/LAUTO
- c =the number of LSRs that fall out for manual processing
- d = the number of LSRs that are returned to the CLEC for clarification
- e = the number of LSRs that contain errors made by CLECs
- f = the number of LSRs that receive a Z status.

Percent Achieved Flow Through = $a \div [b-(c+d+e)] \times 100$

- a = the number of LSRs that flow through LESOG/LAUTO and reach a status for a FOC to be issued.
- b = the number of LSRs passed from LEO/LNP Gateway to LESOG/LAUTO
- c =the number of LSRs that are returned to the CLEC for clarification
- d = the number of LSRs that contain errors made by CLECs
- e = the number of LSRs that receive Z status

Report Structure

Provides the flow through percentage for each CLEC (by alias designation) submitting LSRs through the CLEC mechanized ordering process. The report provides the following:

- CLEC (by alias designation)
- · Number of fatal rejects
- · Mechanized interface used
- · Total mechanized LSRs
- Total manual fallout
- Number of auto clarifications returned to CLEC
- · Number of validated LSRs
- · Number of BellSouth caused fallout
- · Number of CLEC caused fallout
- · Number of Service Orders Issued
- · Base calculation
- · CLEC error excluded calculation

Data Retained

outh Performance
rpe
i

SQM Level of Disaggregation	SQM Analog/Benchmark ^a
Residence	Benchmark: 95%
Business	Benchmark: 90%
• UNE	Benchmark: 85%

SQM Level of Disaggregation	SQM Analog/Benchmark ^a
• LNP	• Benchmark: 85%

a. Benchmarks do not apply to the "Percent Achieved Flow Through."

SEEM Measure

SEEM Measure		
	Tier I	X
Yes	Tier II	

SEEM Disaggregation	SEEM Analog/Benchmark
Residence	Benchmark: 95%
• Business	Benchmark: 90%
• UNE	Benchmark: 85%
• LNP	Benchmark: 85%

(A) **BELL**SOUTH

O-5: Flow-Through Error Analysis

Definition

An analysis of each error type (by error code) that was experienced by the LSRs that did not flow through or reached a status for a FOC to be issued.

Exclusions

Each Error Analysis is error code specific, therefore exclusions are not applicable.

Business Rules

The CLEC mechanized ordering process includes all LSRs, including supplements (subsequent versions) which are submitted through one of the three gateway interfaces (TAG, EDI, and LENS), that flow through and reach a status for a FOC to be issued. The CLEC mechanized ordering process does not include LSRs which are submitted manually (for example, fax and courier).

Calculation

Total for each error type.

Report Structure

Provides an analysis of each error type (by error code). The report is in descending order by count of each error code and provides the following:

- Error Type (by error code)
- · Count of each error type
- · Percent of each error type
- · Cumulative percent
- · Error Description
- · CLEC Caused Count of each error code
- Percent of aggregate by CLEC caused count
- · Percent of CLEC caused count
- BellSouth Caused Count of each error code
- · Percent of aggregate by BellSouth caused count
- · Percent of BellSouth by BellSouth caused count.

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report Month	Report Month
Total Number of Lsrs Received	Total Number of Errors by Type (by Error Code)
Total Number of Errors by Type (by Error Code) OLEC associations	- BellSouth System Error
- CLEC caused error	

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
Not Applicable	Not Applicable

SEEM Measure

SEEM Measure				
No	Tier I			
	Tier II			

SEEM Disaggregation	SEEM Analog/Benchmark				
Not Applicable	Not Applicable				



O-6: CLEC LSR Information

Definition

A list with the flow through activity of LSRs by CC, PON and Ver, issued by each CLEC during the report period.

Exclusions

- · Fatal Rejects
- · LSRs submitted manually

Business Rules

The CLEC mechanized ordering process includes all LSRs, including supplements (subsequent versions) which are submitted through one of the three gateway interfaces (TAG, EDI, and LENS), that flow through and reach a status for a FOC to be issued. The CLEC mechanized ordering process does not include LSRs which are submitted manually (for example, fax and courier).

Calculation

Not Applicable

Report Structure

Provides a list with the flow through activity of LSRs by CC, PON and Ver, issued by each CLEC during the report period with an explanation of the of the columns and content. This report is available on a CLEC specific basis. The report provides the following for each LSR.

- CC
- PON
- Ver
- Timestamp
- Type
- Err #
- Note or Error Description

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report Month Record of LSRs Received by CC, PON and Ver Record of Timestamp, Type, Err # and Note or Error Description for Each LSR by CC, PON and Ver	Not Applicable

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark			
Not Applicable	Not Applicable			

SEEM Measure

SEEM Measure				
No	Tier I			
	Tier II			



O-6: CLEC LSR Information

SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable



LSR Flow Through Matrix

	Product Type	Reqtype	ACT Type	F/T³	Complex Service	Complex Order	Planned Fallout For Manual Handling ¹	EDI	TAG ²	LENS ⁴
2 wire analog DID trunk port	U,C	A	N,T	No	UNE	Yes	NA	N	N	N
2 wire analog port	U	A	N,T	No	UNE	No	Yes	Y	Y	N
2 wire ISDN digital line	U,C	A	N,T	No	UNE	Yes	NA	N	N	N
2 wire ISDN digital loop	U,C	A	N,T	Yes	UNE	Yes	No	Y	Y	N
3 Way Calling	R,B	E,M	N,C,T,V,W	Yes	No	No	No	Y	Y	Y
4 wire analog voice grade loop	U,C	A	N,T	Yes	UNE	Yes	No	Y	Y	N
4 wire DSO & PRI digital loop	U,C	A	N,T	No	UNE	Yes	NA	N	N	N
4 wire DS1 & PRI digital loop	U,C	A	N,T	No	UNE	Yes	NA	N	N	N
4 wire ISDN DSI digital trunk ports	U,C	A	N,T	No	UNE	Yes	NA	N	N	N
Accupulse	С	Е	N,C,T,V,W	No	Yes	Yes	NA	N	N	N
ADSL	R,B,C	Е	V,W	No	UNE	No	No	Y	Y	N
Area Plus	R,B	E,M	N,C,T,V,W	Yes	No	No	No	Y	Y	Y
Basic Rate ISDN	U,C	A	N,T	No	Yes	Yes	Yes	Y	Y	N
Basic Rate ISDN 2 Wire	С	Е	C, D,T,V,W	No	Yes	Yes	Yes	Y	Y	N
Basic Rate ISDN 2 Wire	С	Е	N,T	No	Yes	Yes	N/A	N	N	N
Basic Rate ISDN 2 Wire UNE P	С	M	N,C,D,V	No	YES	Yes	N/A	N	N	N
Analog Data/Private Line	С	Е	N, C, T, V, W, D, P, Q	No	Yes	Yes	N/A	N	N	N
Call Block	R,B	E,B,M	N,C,T,V,W	Yes	No	No	No	Y	Y	Y
Call Forwarding	R,B	E,B,M	N,C,T,V,W	Yes	No	No	No	Y	Y	Y
Call Return	R,B	E,B,M	N,C,T,V,W	Yes	No	No	No	Y	Y	Y
Call Selector	R,B	E,B,M	N,C,T,V,W	Yes	No	No	No	Y	Y	Y
Call Tracing	R,B	E,B,M	N,C,T,V,W	Yes	No	No	No	Y	Y	Y
Call Waiting	R,B	E,B,M	N,C,T,V,W	Yes	No	No	No	Y	Y	Y
Call Waiting Deluxe	R,B	E,B,M	N,C,T,V,W	Yes	No	No	No	Y	Y	Y
Caller ID	R,B	E,B,M	N,C,T,V,W	Yes	No	No	No	Y	Y	Y
CENTREX	С	P	V,P	No	Yes	Yes	NA	N	N	N
DID ACT W	С	N	W	No	Yes	Yes	Yes	Y	Y	Y
Digital Data Transport	U	Е	N,C,T,V,W	No	UNE	Yes	NA	N	N	N
Directory Listing Indentions	B,U	B,C,E,F, J,M,N	N,C,T,R,V,W,P,Q	No	No	No	Yes	Y	Y	Y
Directory Listings Captions	R,B,U	B,C,E,F, J,M,N	N,C,T,R,V,W,P,Q	No	No	Yes	Yes	Y	Y	Y
Directory Listings (simple)	R,B,U	B,C,E,F, J,M,N	N,C,T,R,V,W,P,Q	Yes	No	No	No	Y	Y	Y
DS3	U	A,M	N,C,V	No	UNE	Yes	NA	N	N	N
DS1Loop	U	A,M	N,C,V	Yes	UNE	Yes	No	Y	Y	N
DSO Loop	U	A, B	N,C,D,T,V	Yes	UNE	Yes	No	Y	Y	N
Enhanced Caller ID	R,B	E,M	C,D,N,T,V,W	Yes	No	No	No	Y	Y	Y



	Product Type	Reqtype	ACT Type	F/T ³	Complex Service	Complex Order	Planned Fallout For Manual Handling ¹	EDI	TAG ²	LENS ⁴
ESSX	C	P	C,D,T,V,S,B,W,L	No	Yes	Yes	NA NA	N	N	N
ESSA		1	,P,Q	NO	165	108	IVA	11	11	11
Flat Rate/Business	В	E, M	C,D,N,T,V,W	Yes	No	No	No	Y	Y	Y
Flat Rate/Residence	R	E, M	C,D,N,T,V,W	Yes	No	No	No	Y	Y	Y
FLEXSERV	С	Е	N,C,D,T,V,W,P,Q	No	Yes	Yes	NA	N	N	N
Frame Relay	С	Е	N,C,D,V,W	No	Yes	Yes	NA	N	N	N
FX	С	Е	N,C,D,T,V,W,P,Q	No	Yes	Yes	NA	N	N	N
Ga. Community Calling	R,B	E, M	C,D,N,T,V,W	Yes	No	No	No	Y	Y	Y
HDSL	U	A	N,C,D	Yes	UNE	No	No	Y	Y	N
Hunting MLH	R,B	E, M	C,D,N,T,V,W	No	C/S4	C/S	Yes	Y	Y	N
Hunting Series Completion	R,B	E, M	C,D,N,T,V,W	Yes	C/S	C/S	No	Y	Y	Y
INP to LNP Conversion	U	C	C	No	UNE	Yes	Yes	Y	Y	N
LightGate	С	Е	N,C,D,T,V,W,P,Q	No	Yes	Yes	NA	N	N	N
Line Sharing	U	A	C,D	Yes	UNE	No	No	Y	Y	Y
Local Number Portability	U	С	C,D,P,V,Q	Yes	UNE	Yes	No	Y	Y	N
LNP With Complex Listing	С	C	P,V,Q,W	No	UNE	Yes	Yes	Y	Y	N
LNP with Partial Migration	U	С	D,P,V,Q	No	UNE	Yes	Yes	Y	Y	N
LNP with Complex Services	С	C	P,V,Q,W	No	UNE	Yes	Yes	Y	Y	N
Loop+INP	U	В	D,P,V,Q	Yes	UNE	No	No	Y	Y	N
Loop+LNP	U	В	C,D,N,V	Yes	UNE	No	No	Y	Y	N
Measured Rate/Bus	R,B	E,M	C,D,T,N,V,W	Yes	No	No	No	Y	Y	Y
Measured Rate/Res	R,B	E,M	C,D,T,N,V,W	Yes	No	No	No	Y	Y	Y
Megalink	С	Е	N,V,W,T,D,C,P,Q	No	Yes	Yes	NA	N	N	N
Megalink-T1	С	E,M	N,V,W,T,D,C,P,Q	No	Yes	Yes	NA	N	N	N
Memory Call	R,B	E, M	C,D,N,T,V,W	Yes	No	No	No	Y	Y	Y
Memory Call Ans. Svc.	R,B	E, M	C,D,N,T,V,W	Yes	No	No	No	Y	Y	Y
Multiserv	С	P	N,C,D,T,V,S,B, W,L,P,Q	No	Yes	Yes	NA	N	N	N
Native Mode LAN Interconnection (NMLI)	С	Е	N,C,D,V,W	No	Yes	Yes	NA	N	N	N
Off-Prem Stations	С	Е	N,C,D,V,W,T,P,Q	No	Yes	Yes	NA	N	N	N
Optional Calling Plan	R,B	E, M	N	Yes	No	No	No	Y	Y	Y
Package/Complete Choice and Area Plus	R,B	E, M	N,T,C,V,W	Yes	No	No	No	Y	Y	Y
Pathlink Primary Rate ISDN	С	Е	N,C,D,T,V,W,P,Q	No	Yes	Yes	NA	N	N	N
Pay Phone Provider	В	Е	C,D,T,N,V,W	No	No	No	NA	N	N	N
PBX Standalone Port	С	F	N,C,D	No	Yes	Yes	Yes	Y	Y	N
PBX Trunks	R,B	Е	N,C,D,V,W,T,P,Q	No	Yes	Yes	Yes	Y	Y	N
Port/Loop PBX	U	M	A,C,D,V	No	No	No	Yes	Y	Y	N
Port/Loop Simple	U	M	A,C,D,V	Yes	No	No	Yes	Y	Y	Y
Preferred Call Forward	R,B,U	Е	C,D,T,N,V,W	Yes	No	No	No	Y	Y	Y
RCF Basic	R,B	Е	N,D,W,T,F	Yes	No	No	No	Y	Y	Y



	Product Type	Reqtype	ACT Type	F/T ³	Complex Service	Complex Order	Planned Fallout For Manual Handling ¹	EDI	TAG ²	LENS ⁴
Remote Access to CF	R,B	E,M	C,D,T,N,V,W	Yes	No	No	No	Y	Y	Y
Repeat Dialing	R,B	E,M	C,D,T,N,V,W	Yes	No	No	No	Y	Y	Y
Ringmaster	R,B	E,M	C,D,T,N,V,W	Yes	No	No	No	Y	Y	Y
Smartpath	R,B	Е	C,D,T,N,V,W	No	Yes	Yes	NA	N	N	N
SmartRING	С	Е	N,D,C,V,W	No	Yes	Yes	NA	N	N	N
Speed Calling	R,B	Е	C,D,T,N,V,W	Yes	No	No	No	Y	Y	Y
Synchronet	С	Е	N	Yes	Yes	Yes	Yes	Y	Y	N
Tie Lines	С	Е	N,C,D,V,W,T,P,Q	No	Yes	Yes	NA	N	N	N
Touchtone	R,B	Е	C,D,T,N,V,W	Yes	No	No	No	Y	Y	Y
Unbundled Loop-Analog 2W, SL1, SL2	U	A,B	C,D,T,N,V,W	Yes	UNE	No	No	Y	Y	Y
WATS	R,B	Е	W,D	No	Yes	Yes	NA	N	N	N
XDSL	C,U	A,B	N,T,C,V,D	Yes	UNE	No	No	Y	Y	N
XDSL Extended LOOP	C,U	A,B	N,T,C,V,D	No	UNE	Yes	NA	N	N	N
Collect Call Block	R,B	Е	N,T,C,V,W,D	Yes	No	No	No	Y	Y	Y
900 Call Block	R,B	Е	N,T,C,V,W,D	Yes	No	No	No	Y	Y	Y
3rd Party Call Block	R,B	Е	N,T,C,V,W,D	Yes	No	No	No	Y	Y	Y
Three Way Call Block	R,B	Е	N,T,C,V,W,D	Yes	No	No	No	Y	Y	Y
PIC/LPIC Change	R,B	Е	T,C,V,	Yes	No	No	No	Y	Y	Y
PIC/LPIC Freeze	R,B	Е	N,T,C,V	Yes	No	No	No	Y	Y	Y

Note¹: Planned Fallout for Manual Handling denotes those services that are electronically submitted and are not intended to flow through due to the complexity of the service.

Note²: The TAG column includes those LSRs submitted via Robo TAG.

Note³: For all services that indicate 'No' for flow-through, the following reasons, in addition to errors or complex services, also prompt manual handling: Expedites from CLECs, special pricing plans, denials – restore and conversion or disconnect and conversion both required, partial migrations (although conversions-as-is flow through), class of service invalid in certain states with some TOS – e.g. government, or cannot be changed when changing main TN on C activity, low volume – e.g. activity type T=move, pending order review required, more than 25 business lines, CSR inaccuracies such as invalid or missing CSR data in CRIS, Directory listing indentions and captions, transfer of calls option for CLEC end user – new TN not yet posted to BOCRIS. Many are unique to the CLEC environment.

Note⁴: Services with C/S in the Complex Service and/or the Complex Order columns can be either complex or simple.

Note⁵: EELs are manually ordered.

Note⁶: LSRs submitted for Resale Products and Services for which there is a temporary promotion or discount plan will be processed identically to those LSRs ordering the same Products or Services without a promotion or discount plan.

Note: The Flow Through Matrix is continually being updated and expanded with additional information about the listed products and services. BellSouth will not change any "Yes" designation to "No" without commission approval. The most current pre-approved matrix will be posted to the PMAP web site (www.pmap.bellsouth.com).



O-7: Percent Rejected Service Requests

Definition

Percent Rejected Service Request is the percent of total Service Requests [(Local Service Requests (LSRs)) or Access Service Requests (ASRs)] received which are rejected due to error or omission. Service Requests are considered valid when they are submitted by the CLEC and pass edit checks to insure the data received is correctly formatted and complete.

Exclusions

- Service Requests canceled by the CLEC prior to being rejected/clarified.
- · Fatal Rejects
- Order Activities of BellSouth or the CLEC associated with internal or administrative use of local services (Record Orders, Test Orders, etc.) where identifiable.

Business Rules

Fully Mechanized: An LSR/Service Request is considered "rejected" when it is submitted electronically but does not pass edit checks in the ordering systems (EDI, LENS, TAG, LESOG, LNP Gateway, LAUTO) and is returned to the CLEC without manual intervention. There are two types of "Rejects" in the Mechanized category:

A **Fatal Reject** occurs when a CLEC attempts to electronically submit an LSR but required fields are either not populated or incorrectly populated and the request is returned to the CLEC before it is considered a valid LSR.

Fatal rejects are reported in a separate column, and for informational purposes ONLY. They are not considered in the calculation of the percent of total LSRs rejected or the total number of rejected LSRs.

An **Auto Clarification** occurs when a valid LSR is electronically submitted but rejected from LESOG or LAUTO because it does not pass further edit checks for order accuracy.

Partially Mechanized: A valid LSR, which is electronically submitted (via EDI, LENS, TAG) but cannot be processed electronically and "falls out" for manual handling. It is then put into "clarification" and sent back (rejected) to the CLEC.

Non-Mechanized: LSRs which are faxed or mailed to the LCSC for processing and "clarified" (rejected) back to the CLEC by the BellSouth service representative.

Interconnection Trunks: Interconnection Trunks are ordered on Access Service Requests (ASRs). ASRs are submitted to and processed by the Local Interconnection Service Center (LISC). Trunk data is reported as a separate category.

Calculation

Percent Rejected Service Requests = $(a \div b) \times 100$

- a = Total Number of Service Requests Rejected in the reporting period
- b = Total Number of Service Requests Received in the reporting period

Report Structure

- · Fully Mechanized, Partially Mechanized, Non-Mechanized
- Trunks
- CLEC Specific
- CLEC Aggregate
- Geographic Scope
- State
- Region
- Product Specific percent Rejected
- · Total percent Rejected

(A) BELLSOUTH®

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report Month	Not Applicable
Total Number of LSRs	
Total Number of Rejects	
State and Region	
Total Number of ASRs (Trunks)	

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
Mechanized, Partially Mechanized and Non-Mechanized	Diagnostic
Resale - Residence	
Resale - Business	
Resale – Design (Special)	
Resale PBX	
Resale Centrex	
Resale ISDN	
LNP Standalone	
INP Standalone	
2W Analog Loop Design	
2W Analog Loop Non-Design	
2W Analog Loop with INP Design	
2W Analog Loop with INP Non-Design	
2W Analog Loop with LNP Design	
 2W Analog Loop with LNP Non-Design 	
• UNE Digital Loop < DS1	
• UNE Digital Loop ≥ DS1	
• UNE Loop + Port Combinations	
UNE Combination Other	
UNE ISDN Loop	
UNE Other Design	
UNE Other Non-Design	
UNE Line Splitting	
• EELs	
• Switch Ports	
• UNE xDSL (ADSL, HDSL, UCL)	
Line Sharing	
Local Interoffice Transport	
Local Interconnection Trunks	

SEEM Measure

	SEEM Measure					
No	Tier I					
	Tier II					

SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable



O-8: Reject Interval

Definition

Reject Interval is the average reject time from receipt of Service Requests [(Local Service Requests (LSRs)) or Access Service Requests (ASRs)] to the distribution of a Reject. Service Requests are considered valid when they are submitted by the CLEC and pass edit checks to insure the data received is correctly formatted and complete.

Exclusions

- Service Requests canceled by CLEC prior to being rejected/clarified.
- · Fatal Rejects
- Designated Holidays are excluded from the interval calculation.
- · LSRs which are identified and classified as "Projects"
- The following hours for Partially mechanized and Non-mechanized LSRs are excluded from the interval calculation:

Residence Resale Group – Monday through Saturday 7:00PM until 7:00AM From 7:00 PM Saturday until 7:00 AM Monday

Business Resale, Complex, UNE Groups – Monday through Friday 6:00PM until 8:00AM From 6:00 PM Friday until 8:00 AM Monday.

Local Interconnection Service Center (LISC) - Monday through Friday 4:30 P.M. until 8:00 A M.

From 4:30 P.M.Friday until 8:00 A.M. Monday

The hours excluded will be altered to reflect changes in the Center operating hours. The LCSC will accept faxed LSRs only during posted hours of operation.

The interval will be the amount of time accrued from receipt of the LSR until normal closing of the center if an LSR is worked using overtime hours.

In the case of a Partially Mechanized LSR received and worked after normal business hours, the interval will be set at one (1) minute.

Business Rules

The Reject interval is determined for each rejected LSR processed during the reporting period. The Reject interval is the elapsed time from when BellSouth receives LSR (date and time stamps in EDI or TAG) until that LSR is rejected back to the CLEC. Elapsed time for each LSR (date and time stamps in EDI or TAG) is accumulated for each reporting dimension. The accumulated time for each reporting dimension is then divided by the associated total number of rejected LSRs to produce the reject interval distribution.

Fully Mechanized: The elapsed time from receipt of a valid electronically submitted LSR (date and time stamp in EDI translator or TAG) until the LSR is rejected (date and time stamp or reject in EDI translator, or TAG). Auto Clarifications are considered in the Fully Mechanized category.

Partially Mechanized: The elapsed time from receipt of a valid electronically submitted LSR (date and time stamp in EDI translator or TAG) until it falls out for manual handling. The stop time on partially mechanized LSRs is when the LCSC Service Representative clarifies the LSR back to the CLEC via EDI translator, or TAG.

Non-Mechanized: The elapsed time from receipt of a valid LSR (date and time stamp of FAX or date and time mailed LSR is received in the LCSC) until notice of the reject (clarification) is returned to the CLEC via LON.

Interconnection Trunks: Interconnection Trunks are ordered on Access Service Requests (ASRs). ASRs are submitted to and processed by the Local Interconnection Service Center (LISC). Trunk data is reported as a separate category.

Calculation

Reject Interval = (a - b)

- a = Date and Time of Service Request Rejection
- b = Date and Time of Service Request Receipt

Average Reject Interval = $(c \div d)$

- c = Sum of all Reject Intervals
- d = Number of Service Requests Rejected in Reporting Period

Reject Interval Distribution = $(e \div f) \times 100$

- e = Service Requests Rejected in reported interval
- f = Total Number of Service Requests Rejected in Reporting Period

Report Structure

- · Fully Mechanized, Partially Mechanized, Non-Mechanized
- · CLEC Specific
- · CLEC Aggregate
- · Geographic Scope
 - State
 - Region
- · Fully Mechanized:
- $0 \leq 4 \text{ minutes}$
- $> 4 \leq 8 \text{ minutes}$
- >8 \leq 12 minutes
- $> 12 \le 60 \text{ minutes}$
- $0 \leq 1 \text{ hour}$
- $> 1 \leq 4 \text{ hours}$
- > 4 \leq 8 hours
- $> 8 \le 12 \text{ hours}$
- $> 12 \le 16 \text{ hours}$
- $> 16 \le 20 \text{ hours}$
- $> 20 \le 24 \text{ hours}$
- > 24 hours
- · Partially Mechanized:
 - $0 \leq 1 \text{ hour}$
- $> 1 \leq 4 \text{ hours}$
- $> 4 \leq 8 \text{ hours}$
- $> 8 \le 10 \text{ hours}$
- $0 \leq 10 \text{ hours}$
- $> 10 \le 18 \text{ hours}$
- $0 \leq 18 \text{ hours}$
- $> 18 \le 24 \text{ hours}$
- > 24 hours
- · Non-mechanized:
 - $0 \leq 1 \text{ hour}$
 - $> 1 \leq 4 \text{ hours}$
 - > 4 \leq 8 hours
 - $> 8 \le 12 \text{ hours}$
 - $> 12 \le 16 \text{ hours}$ $> 16 - \le 20 \text{ hours}$
 - $> 20 \le 24 \text{ hours}$
 - $0 \leq 24 \text{ hours}$
 - > 24 hours
- Trunks:
 - $0 \leq 36 \text{ hours}$
- > 36 hours
- Average Interval is reported in business hours.

(A) BELLSOUTH®

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report Month	Not Applicable
Reject Interval	
Total Number of LSRs	
Total Number of Rejects	
State and Region	
Total Number of ASRs (Trunks)	

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
• Resale – Residence • Resale – Business • Resale – Design (Special) • Resale PBX • Resale Centrex • Resale ISDN • LNP Standalone • INP Standalone • 2W Analog Loop Design • 2W Analog Loop with INP Design • 2W Analog Loop with INP Design • 2W Analog Loop with INP Non-Design • 2W Analog Loop with INP Non-Design • 2W Analog Loop with LNP Non-Design • 2W Analog Loop with LNP Non-Design • 2W Analog Loop with LNP Non-Design • 10 UNE Digital Loop < DS1 • UNE Digital Loop > DS1 • UNE Loop + Port Combinations • UNE Combination Other • UNE ISDN Loop	 SQM Analog/Benchmark Fully Mechanized: - 97% ≤ 1Hour Partially Mechanized: - 95% ≤ 10 Hours Non-Mechanized: - 95% ≤ 24 Hours
 UNE Other Design UNE Other Non-Design UNE Line Splitting EELs Switch Ports UNE xDSL (ADSL, HDSL, UCL) Line Sharing Local Interoffice Transport 	
Local Interconnection Trunks	• Trunks: 95% ≤ 36 Hours

SEEM Measure

SEEM Measure		
Yes	Tier I	X
	Tier II	X

SEEM Disaggregation	SEEM Analog/Benchmark
Fully Mechanized	• 97% ≤ 1 hour

SEEM Disaggregation	SEEM Analog/Benchmark
Partially Mechanized	• 95% ≤ 10 hours
Non-Mechanized	• 95% ≤ 24 hours
Local Interconnection Trunks	• 95% ≤ 36 hours

(A) **BELLSOUTH**

O-9: Firm Order Confirmation Timeliness

Definition

Interval for Return of a Firm Order Confirmation (FOC Interval) is the average response time from receipt of valid LSR to distribution of a Firm Order Confirmation. The interval will include an electronic facilities check.

Exclusions

- Service Requests canceled by CLEC prior to being confirmed.
- Designated Holidays are excluded from the interval calculation.
- · LSRs which are identified and classified as "Projects"
- The following hours for Partially mechanized and Non-mechanized LSRs are excluded from the interval calculation:

Residence Resale Group – Monday through Saturday 7:00PM until 7:00AM From 7:00 PM Saturday until 7:00 AM Monday

Business Resale, Complex, UNE Groups – Monday through Friday 6:00PM until 8:00AM From 6:00 PM Friday until 8:00 AM Monday.

Local Interconnection Service Center (LISC) - From 4:30 P.M. Friday until 8:00 A.M. Monday (ASRs received after 2:00PM will be counted as if received at 8:00AM the next business day.)

The hours excluded will be altered to reflect changes in the Center operating hours. The LCSC will accept faxed LSRs only during posted hours of operation.

The interval will be the amount of time accrued from receipt of the LSR until normal closing of the center if an LSR is worked using overtime hours.

In the case of a Partially Mechanized LSR received and worked after normal business hours, the interval will be set at one (1) minute.

Business Rules

- Fully Mechanized: The elapsed time from receipt of a valid electronically submitted LSR (date and time stamp in EDI or TAG) until the LSR is processed, appropriate service orders are generated and a Firm Order Confirmation is returned to the CLEC via EDI translator or TAG.
- Partially Mechanized: The elapsed time from receipt of a valid electronically submitted LSR (date and time stamp in EDI, or TAG) which falls out for manual handling until appropriate service orders are issued by a BellSouth service representative via Direct Order Entry (DOE) or Service Order Negotiation Generation System (SONGS) to SOCS and a Firm Order Confirmation is returned to the CLEC via EDI translator, or TAG.
- Non-Mechanized: The elapsed time from receipt of a valid paper LSR (date and time stamp of FAX or date and time paper LSRs received in LCSC) until appropriate service orders are issued by a BellSouth service representative via Direct Order Entry (DOE) or Service Order Negotiation Generation System (SONGS) to SOCS and a Firm Order Confirmation is sent to the CLEC via LON.
- Interconnection Trunks: Interconnection Trunks are ordered on Access Service Requests (ASRs). ASRs are submitted to and processed by the Local Interconnection Service Center (LISC). The elapsed time is measured from receipt of a valid ASR (date and time stamp of a FAX or paper ASR received in the LISC) until the appropriate orders are issued by a BellSouth representative and a FOC issued in EXACT. Trunk data is reported as a separate category.

Calculation

Firm Order Confirmation Interval = (a - b)

- a = Date and Time of Firm Order Confirmation
- b = Date and Time of Service Request Receipt

Average FOC Interval = $(c \div d)$

- c = Sum of all Firm Order Confirmation Times
- d = Number of Service Requests Confirmed in Reporting Period

FOC Interval Distribution = $(e \div f) \times 100$

- e = Service Requests Confirmed in Designated Interval
- f = Total Service Requests Confirmed in the Reporting Period

Report Structure

- · Fully Mechanized, Partially Mechanized, Non-Mechanized
 - CLEC Specific
 - CLEC Aggregate
- · Geographic Scope
- State
- Region
- · Fully Mechanized:
 - $0 \leq 15 \text{ minutes}$
- $> 15 \leq 30 \text{ minutes}$
- $> 30 \le 45 \text{ minutes}$
- > 45 \leq 60 minutes
- $> 60 \le 90 \text{ minutes}$
- $> 90 \le 120$ minutes
- $> 120 \le 180 \text{ minutes}$
- $0 \leq 3 \text{ hours}$
- > 3 \leq 6 hours
- $> 6 \le 12 \text{ hours}$
- $> 12 \le 24 \text{ hours}$
- $> 24 \le 48 \text{ hours}$
- > 48 hours
- · Partially Mechanized:
- $0 \leq 4 \text{ hours}$
- > 4 \leq 8 hours
- $> 8 \le 10 \text{ hours}$
- $0 \leq 10 \text{ hours}$
- $> 10 \le 18 \text{ hours}$
- $0 \leq 18 \text{ hours}$
- $> 18 \le 24 \text{ hours}$
- $> 24 \le 48 \text{ hours}$
- > 48 hours
- · Non-mechanized:
 - $0 \leq 4 \text{ hours}$
- > 4 \leq 8 hours
- $> 8 \le 12 \text{ hours}$
- $> 12 \le 16 \text{ hours}$
- $0 \leq 24 \text{ hours}$
- $> 16 \le 20 \text{ hours}$
- $> 20 \le 24 \text{ hours}$
- $> 24 \le 36 \text{ hours}$ $0 - \leq 36 \text{ hours}$
- $> 36 \le 48 \text{ hours}$
- > 48 hours
- Trunks:
 - $0 \leq 48 \text{ hours}$
 - > 48 hours
- · Average Interval is reported in business hours

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report month	Not Applicable
• Interval for FOC	
Total number of LSRs	
State and Region	
Total Number of ASRs (Trunks)	

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
Resale – Residence	• Fully Mechanized: - 95% ≤3 Hours
Resale – Business	Partially Mechanized:
Resale – Design (Special)	- 95% ≤ 10 Hours
Resale PBX	• Non-Mechanized: - 95% ≤ 24 Hours
Resale Centrex	
Resale ISDN	
LNP Standalone	
INP Standalone	
2W Analog Loop Design	
2W Analog Loop Non-Design	
2W Analog Loop with INP Design	
2W Analog Loop with INP Non-Design	
2W Analog Loop with LNP Design	
2W Analog Loop with LNP Non-Design	
• UNE Digital Loop < DS1	
• UNE Digital Loop ≥ DS1	
UNE Loop + Port Combinations	
UNE Combination Other	
UNE ISDN Loop	
UNE Other Design	
UNE Other Non-Design	
UNE Line Splitting	
• EELs	
Switch Ports	
• UNE xDSL (ADSL, HDSL, UCL)	
Line Sharing	
Local Interoffice Transport	
Local Interconnection Trunks	• Trunks: 95% ≤ 48 Hours

SEEM Measure

SEEM Measure		
Yes	Tier I	X
	Tier II	X

SEEM Disaggregation	SEEM Analog/Benchmark
Fully Mechanized	• 95% ≤ 3 Hours
Partially Mechanized	• 95% ≤ 10 Hours
Non-Mechanized	• 95% ≤ 24 Hours
Local Interconnection Trunks	• 95% ≤ 48 Hours

(A) **BELL**SOUTH

O-10: Service Inquiry with LSR Firm Order Confirmation (FOC) Response Time Manual¹

Definition

This report measures the interval and the percent within the interval from the submission of a Service Inquiry (SI) with Firm Order LSR to the distribution of a Firm Order Confirmation (FOC).

Exclusions

- Designated Holidays are excluded from the interval calculation.
- Weekend hours from 5:00PM Friday until 8:00AM Monday are excluded from the interval calculation of the Service Inquiry.
- Canceled Requests
- · Electronically Submitted Requests

Business Rules

This measurement combines four intervals:

- 1. From receipt of a valid Service Inquiry with LSR to hand off to the Service Advocacy Center (SAC) for Loop 'Look-up'.
- 2. From SAC start date to SAC complete date.
- 3. From SAC complete date to the Complex Resale Support Group (CRSG) complete date with hand off to LCSC.
- 4. From receipt of a valid SI/LSR in the LCSC to Firm Order Confirmation.

(A valid Service Inquiry is an inquiry that has all required fields populated correctly and has not been returned for clarification.)

Calculation

FOC Timeliness Interval = (a - b)

- a = Date and Time Firm Order Confirmation (FOC) for SI with LSR returned to CLEC
- b = Date and Time SI with LSR received

Average Interval = $(c \div d)$

- c = Sum of all FOC Timeliness Intervals
- d = Total number of SIs with LSRs received in the reporting period

Percent Within Interval = $(e \div f) \times 100$

- e = Total number of Service Inquiries with LSRs received by the CRSG to distribution of FOC by the Local Carrier Service Center (LCSC)
- f = Total number of Service Inquiries with LSRs received in the reporting period

Report Structure

- · CLEC Aggregate
- CLEC Specific
- · Geographic Scope
 - State
- Region
- Intervals
- $0 \leq 3$ days
- $> 3 \le 5$ days
- $0-\!\le 5~days$
- $> 5 \le 7$ days
- $> 7 \le 10 \text{ days}$
- $> 10 \le 15 \text{ days}$
- >15 days
- · Average Interval measured in days

1. See O-9 for FOC Timeliness



Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report MonthTotal Number of RequestsSI IntervalsState and Region	Not Applicable

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
 xDSL (includes UNE unbundled ADSL, HDSL and UNE Unbundled Copper Loops) Unbundled Interoffice Transport 	• 95% Returned ≤ 5 Business Days

SEEM Measure

SEEM Measure			
No	Tier I		
	Tier II		

SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable

(A) **BELLSOUTH** *

O-11: Firm Order Confirmation and Reject Response Completeness

Definition

A response is expected from BellSouth for every Local Service Request transaction (version). Firm Order Confirmation and Reject Response Completeness is the corresponding number of Local Service Requests received to the combination of Firm Order Confirmation and Reject Responses.

Exclusions

• Service Requests canceled by the CLEC prior to FOC or Rejected/Clarified.

Business Rules

Mechanized – The number of FOCs or Auto Clarifications sent to the CLEC from EDI, or TAG in response to electronically submitted LSRs.

Partially Mechanized – The number of FOCs or Rejects sent to the CLEC from EDI, or TAG in response to electronically submitted LSRs which fall out for manual handling by the LCSC personnel.

Non-Mechanized: The number of FOCs or Rejects sent to the CLECs by FAX server.

Interconnection Trunks: Interconnection Trunks are ordered on Access Service Requests (ASRs). ASRs are submitted to and processed by the Local Interconnection Service Center (LISC). Trunk data is reported as a separate category.

For CLEC Results:

Percent responses is determined by computing the number of Firm Order Confirmations and Rejects transmitted by BellSouth and dividing by the number of Local Service Requests (all versions) received in the reporting period.

Calculation

Firm Order Confirmation / Reject Response Completeness = $(a \div b) \times 100$

- a = Total Number of Service Requests for which a Firm Order Confirmation or Reject is Sent
- b = Total Number of Service Requests Received in the Report Period

Report Structure

Fully Mechanized, Partially Mechanized, Non-Mechanized and Interconnection Trunks

- State and Region
- CLEC Specific
- · CLEC Aggregate

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report month	Not Applicable
Total number of LSRs	
Total number of rejects	
Total number of ASRs (Trunks)	
• Total number of FOCs	

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
Resale Residence	95% Returned
Resale Business	
Resale Design (Special)	
Resale PBX	
Resale Centrex	
Resale ISDN	
LNP Standalone	
INP Standalone	
2W Analog Loop Design	
2W Analog Loop Non-Design	
 2W Analog Loop with INP Design 	
 2W Analog Loop with INP Non-Design 	
2W Analog Loop with LNP Design	
 2W Analog Loop with LNP Non-Design 	
• UNE Digital Loop < DS1	
 UNE Digital Loop ≥ DS1 	
• UNE Loop + Port Combinations	
UNE Combination Other	
UNE ISDN Loop	
UNE Other Design	
UNE Other Non-Design	
UNE Line Splitting	
• EELs	
Switch Ports	
• UNE xDSL (ADSL, HDSL, UCL)	
Line Sharing	
Local Interoffice Transport	
Local Interconnection Trunks	

SEEM Measure

SEEM Measure		
Yes	Tier I	X
	Tier II	X

SEEM Disaggregation - Analog/Benchmark

SEEM Disaggregation	SEEM Analog/Benchmark
 Fully Mechanized Partially Mechanized Non-Mechanized Local Interconnection Trunks 	• 95% Returned

Version 1.00 2-30 Issue Date: December 1, 2002 (A) **BELLSOUTH** *

O-12: Speed of Answer in Ordering Center

Definition

Measures the average time a customer is in queue.

Exclusions

None

Business Rules

The clock starts when the appropriate option is selected (i.e., 1 for Resale Consumer, 2 for Resale Multiline, and 3 for UNE-LNP, etc.) and the call enters the queue for that particular group in the LCSC. The clock stops when a BellSouth service representative in the LCSC answers the call. The speed of answer is determined by measuring and accumulating the elapsed time from the entry of a CLEC call into the BellSouth automatic call distributor (ACD) until a service representative in BellSouth's Local Carrier Service Center (LCSC) answers the CLEC call.

Calculation

Speed of Answer in Ordering Center = $(a \div b)$

- a = Total seconds in queue
- b = Total number of calls answered in the Reporting Period

Report Structure

Aggregate

- CLEC Local Carrier Service Center
- · BellSouth
- Business Service Center
- Residence Service Center

Note: Combination of Residence Service Center and Business Service Center data under development

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Mechanized Tracking Through LCSC Automatic Call	Mechanized Tracking Through BellSouth Retail Center
Distributor	Support System

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
Aggregate	Parity with Retail

SEEM Measure

SEEM Measure		
Yes	Tier I	
	Tier II	X

SEEM Disaggregation	SEEM Analog/Benchmark
 CLEC Local Carrier Service Center BellSouth Business Service Center Residence Service Center 	Parity With Retail



Section 3: Provisioning

P-1: Mean Held Order Interval & Distribution Intervals

Definition

When delays occur in completing CLEC orders, the average period that CLEC orders are held for BellSouth reasons, pending a delayed completion, should be no worse for the CLEC when compared to BellSouth delayed orders. Calculation of the interval is the total days orders are held and pending but not completed that have passed the currently committed due date; divided by the total number of held orders. This report is based on orders still pending, held and past their committed due date. The distribution interval is based on the number of orders held and pending but not completed over 15 and 90 days. (Orders reported in the >90 day interval are also included in the >15 day interval.)

Exclusions

- Order Activities of BellSouth or the CLEC associated with internal or administrative use of local services (Record Orders, Listing Orders, Test Orders, etc.) Test order types may be C, N, R, or T.
- Disconnect (D) & From (F) orders
- · Orders with appointment code of 'A' for Rural orders.

Business Rules

Mean Held Order Interval: This metric is computed at the close of each report period. The held order interval is established by first identifying all orders, at the close of the reporting interval, that both have not been reported as completed in SOCS and have passed the currently committed due date for the order and identifying all orders that have been reported as completed in SOCS after the currently committed due date for the order. For each such order, the number of calendar days between the earliest committed due date on which BellSouth had a company missed appointment and the close of the reporting period is established and represents the held order interval for that particular order. The held order interval is accumulated by the standard groupings, unless otherwise noted, and the reason for the order being held. The total number of days accumulated in a category is then divided by the number of held orders within the same category to produce the mean held order interval. The interval is by calendar days with no exclusions for Holidays or Sundays.

CLEC Specific reporting is by type of held order (facilities, equipment, other), total number of orders held, and the total and average days.

Held Order Distribution Interval: This measure provides data to report total days held and identifies these in categories of >15 days and >90 days. (Orders counted in >90 days are also included in >15 days).

Calculation

Mean Held Order Interval = $a \div b$

- a = Sum of held-over-days for all Past Due Orders Held for the reporting period
- b = Number of Past Due Orders Held and Pending But Not Completed and past the committed due date

Held Order Distribution Interval (for each interval) = $(c \div d) \times 100$

- c = # of Orders Held for ≥ 15 days or # of Orders Held for ≥ 90 days
- d = Total # of Past Due Orders Held and Pending But Not Completed)

Report Structure

- · CLEC Specific
- · CLEC Aggregate
- · BellSouth Aggregate
- Circuit Breakout $< 10, \ge 10$ (except trunks)
- Dispatch/Non-Dispatch

Version 1.00 3-1 Issue Date: December 1, 2002

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report Month CLEC Order Number and PON (PON) Order Submission Date (TICKET_ID) Committed Due Date (DD) Service Type (CLASS_SVC_DESC) Hold Reason Total line/circuit count	 Report Month BellSouth Order Number Order Submission Date Committed Due Date Service Type Hold Reason Total line/circuit count
 Geographic Scope Note: Code in parentheses is the corresponding header found in the raw data file. 	Geographic Scope

SQM LEVEL of Disaggregation	SQM Analog/Benchmark
Resale Residence	Retail Residence
Resale Business	Retail Business
Resale Design	Retail Design
Resale PBX	Retail PBX
Resale Centrex	Retail Centrex
Resale ISDN	Retail ISDN
LNP (Standalone)	Retail Residence and Business (POTS)
INP (Standalone)	Retail Residence and Business (POTS)
2W Analog Loop Design	Retail Residence and Business Dispatch
2W Analog Loop Non-Design	Retail Residence and Business - POTS Excluding Switch- Based Orders
2W Analog Loop With LNP - Design	Retail Residence and Business Dispatch
2W Analog Loop With LNP- Non-Design	Retail Residence and Business - POTS Excluding Switch
2W Analog Loop With INP-Design	Retail Residence and Business Dispatch
2W Analog Loop With INP-Non-Design	Retail Residence and Business - POTS Excluding Switch- Based Orders
UNE Digital Loop < DS1	Retail Digital Loop < DS1
• UNE Digital Loop ≥ DS1	Retail Digital Loop ≥ DS1
UNE Loop + Port Combinations Dispatch In Switch Based	Retail Residence and Business Dispatch In Switch Based
UNE Switch Ports	Retail Residence and Business (POTS)
UNE Combo Other	Retail Residence, Business and Design Dispatch
UNE xDSL (HDSL, ADSL and UCL)	ADSL Provided to Retail
UNE ISDN (Includes UDC)	Retail ISDN - BRI
UNE Line Sharing	ADSL Provided to Retail
UNE Other Design	Retail Design
UNE Other Non-Design	Retail Residence and Business
Local Transport (Unbundled Interoffice Transport)	Retail DS1/DS3 Interoffice



Tennessee Performance Measurements

SQM LEVEL of Disaggregation SQM Analog/Benchmark • Local Interconnection Trunks • Parity with Retail • UNE Line Splitting • ADSL to Retail • EELs • Retail DS1/DS3

SEEM Measure

SEEM Measure			
No	Tier I		
	Tier II		

SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable

P-2: Average Jeopardy Notice Interval & Percentage of Orders Given **Jeopardy Notices**

Definition

When BellSouth can determine in advance that a committed due date is in jeopardy for facility delay, it will provide advance notice to the CLEC.

The interval is from the date/time the notice is released to the CLEC/BellSouth systems until 5pm on the commitment date of the order. The Percent of Orders is the percentage of orders given jeopardy notices for facility delay in the count of orders confirmed in the report period.

Exclusions

- · Orders held for CLEC end user reasons
- Disconnect (D) & From (F) orders

Business Rules

When BellSouth can determine in advance that a committed due date is in jeopardy for facility delay, it will provide advance notice to the CLEC. The number of committed orders in a report period is the number of orders that have a due date in the reporting period. Jeopardy notices for interconnection trunks results are usually zero as these trunks seldom experience facility delays. The Committed due date is considered the Confirmed due date.

Calculation

Jeopardy Interval = a - b

- a = Date and Time of Jeopardy Notice
- b = Date and Time of Scheduled Due Date on Service Order

Average Jeopardy Interval = $c \div d$

- c = Sum of all jeopardy intervals
- d = Number of Orders Notified of Jeopardy in Reporting Period

Percent of Orders Given Jeopardy Notice = $(e \div f) \times 100$

- e = Number of Orders Given Jeopardy Notices in Reporting Period
- f = Number of Orders Confirmed (due) in Reporting Period)

Report Structure

- CLEC Specific
- · CLEC Aggregate
- BellSouth Aggregate
- Mechanized Orders
- · Non-Mechanized Orders
- · Dispatch/Non-Dispatch

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
 Report Month CLEC Order Number and PON Date and Time Jeopardy Notice sent Committed Due Date Service Type 	 Report Month BellSouth Order Number Date and Time Jeopardy Notice sent Committed Due Date Service Type
Note: Code in parentheses is the corresponding header found in the raw data file.	



SQM Disaggregation - Analog/Benchmark

SQM LEVEL of Disaggregation	SQM Analog/Benchmark
Resale Residence	Retail Residence
Resale Business	Retail Business
Resale Design	Retail Design
Resale PBX	Retail PBX
Resale Centrex	Retail Centrex
Resale ISDN	Retail ISDN
• LNP (Standalone)	Retail Residence and Business (POTS)
INP (Standalone)	Retail Residence and Business (POTS)
2W Analog Loop Design	Retail Residence and Business Dispatch
• 2W Analog Loop Non-Design	Retail Residence and Business - POTS Excluding Switch- Based Orders
• 2W Analog Loop With LNP - Design	Retail Residence and Business Dispatch
• 2W Analog Loop With LNP- Non-Design	Retail Residence and Business - POTS Excluding Switch- Based Orders
2W Analog Loop With INP-Design	Retail Residence and Business Dispatch
• 2W Analog Loop With INP-Non-Design	Retail Residence and Business - POTS Excluding Switch- Based Orders
• UNE Digital Loop < DS1	• Retail Digital Loop < DS1
• UNE Digital Loop ≥ DS1	• Retail Digital Loop ≥ DS1
 UNE Loop + Port Combinations Dispatch In Switch Based 	Retail Residence and Business Dispatch In Switch Based
UNE Switch Ports	Retail Residence and Business (POTS)
UNE Combo Other	Retail Residence, Business and Design Dispatch
UNE xDSL (HDSL, ADSL and UCL)	ADSL Provided to Retail
UNE ISDN (Includes UDC)	Retail ISDN - BRI
UNE Line Sharing	ADSL Provided to Retail
UNE Other Design	Retail Design
UNE Other Non-Design	Retail Residence and Business
Local Transport (Unbundled Interoffice Transport)	Retail DS1/DS3 Interoffice
Local Interconnection Trunks	Parity with Retail
UNE Line Splitting	ADSL to Retail
• EELs	Retail DS1/DS3
Average Jeopardy Notice Interval (Electronic only)	• 95% >= 48 Hours

SEEM Measure

SEEM Measure		
No	Tier I	
	Tier II	



SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable

(A) **BELLSO**UTH®

P-3: Percent Missed Initial Installation Appointments

(This metric was not ordered by FPSC)

Definition

"Percent missed initial installation appointments" monitors the reliability of BellSouth commitments with respect to committed due dates to assure that the CLEC can reliably quote expected due dates to their retail customer as compared to BellSouth. This measure is the percentage of total orders processed for which BellSouth is unable to complete the service orders on the committed due dates and reported for Total misses and End User Misses.

Exclusions

- · Canceled Service Orders
- Order Activities of BellSouth or the CLEC associated with internal or administrative use of local services (Record Orders, Listing Orders Test Orders, etc.)
- Disconnect (D) & From (F) orders
- · End User Misses

Business Rules

Percent Missed Initial Installation Appointments (PMI) is the percentage of orders with completion dates in the reporting period that are past the original committed due date. Missed Appointments caused by end-user reasons will be excluded and reported separately. The first commitment date on the service order that is a missed appointment is the missed appointment code used for calculation whether it is a BellSouth missed appointment or an End User missed appointment. The "due date" is any time on the confirmed due date. Which means there cannot be a cutoff time for commitments, as certain types of orders are requested to be worked after standard business hours. Also, during Daylight Savings Time, field technicians are scheduled until 9PM in some areas and the customer is offered a greater range of intervals from which to select.

Calculation

Percent Missed Installation Appointments = $(a \div b) \times 100$

- a = Number of Orders with Completion date in Reporting Period past the Original Committed Due Date
- b = Number of Orders Completed in Reporting Period

Report Structure

- · CLEC Specific
- · CLEC Aggregate
- · BellSouth Aggregate
- Report in Categories of <10 lines/circuits ≥ 10 lines/circuits (except trunks)
- · Dispatch/Non-Dispatch

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report month	Report month
CLEC Order Number and PON (PON)	BellSouth Order Number
Committed Due Date (DD)	Committed Due Date (DD)
Completion Date (CMPLTN DD)	Completion Date (CMPLTN DD)
Status Type	Status Type
Status Notice Date	Status Notice Date
Standard Order Activity	Standard Order Activity
Geographic Scope	Geographic Scope
Note: Code in parentheses is the corresponding header found in the raw data file.	

SQM Disaggregation - Analog/Benchmark

SQM LEVEL of Disaggregation	SQM Analog/Benchmark
Resale Residence	Retail Residence
Resale Business	Retail Business
Resale Design	Retail Design
Resale PBX	Retail PBX
Resale Centrex	Retail Centrex
Resale ISDN	Retail ISDN
LNP (Standalone)	Retail Residence and Business (POTS)
INP (Standalone)	Retail Residence and Business (POTS)
2W Analog Loop Design	Retail Residence and Business Dispatch
2W Analog Loop Non-Design	Retail Residence and Business - POTS Excluding Switch- Based Orders
2W Analog Loop With LNP - Design	Retail Residence and Business Dispatch
2W Analog Loop With LNP- Non-Design	Retail Residence and Business - POTS Excluding Switch- Based Orders
2W Analog Loop With INP-Design	Retail Residence and Business Dispatch
2W Analog Loop With INP-Non-Design	Retail Residence and Business - POTS Excluding Switch- Based Orders
UNE Digital Loop < DS1	Retail Digital Loop < DS1
• UNE Digital Loop ≥ DS1	Retail Digital Loop ≥ DS1
UNE Loop + Port Combinations Dispatch In Switch Based	Retail Residence and Business Dispatch In Switch Based
UNE Switch Ports	Retail Residence and Business (POTS)
UNE Combo Other	Retail Residence, Business and Design Dispatch
UNE xDSL (HDSL, ADSL and UCL) Without Conditioning With Conditioning	ADSL Provided to Retail Without Conditioning With Conditioning (BellSouth does not offer this service to Retail)
UNE ISDN (Includes UDC)	Retail ISDN - BRI
UNE Line Sharing	ADSL Provided to Retail
UNE Other Design	Retail Design
UNE Other Non-Design	Retail Residence and Business
Local Transport (Unbundled Interoffice Transport)	Retail DS1/DS3 Interoffice
Local Interconnection Trunks	Parity with Retail
UNE Line Splitting	ADSL to Retail
• EELs	• Retail DS1/DS3

SEEM Measure

SEEM Measure		
No	Tier I	
	Tier II	

P-3: Percent Missed Initial Installation Appointments

SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable

P-3A: Percent Missed Installation Appointments Including Subsequent Appointments

Definition

"Percent missed installation appointments" monitors the reliability of BellSouth commitments with respect to committed due dates to assure that the CLEC can reliably quote expected due dates to their retail customer as compared to BellSouth. This measure is the percentage of total orders processed for which BellSouth is unable to complete the service orders on the committed due dates and reported for Total misses and End User Misses.

Exclusions

- · Canceled Service Orders
- Order Activities of BellSouth or the CLEC associated with internal or administrative use of local services (Record Orders, Listing Orders Test Orders, etc.) Test order types may be C, N, R, or T.
- Disconnect (D) & From (F) orders
- End User Misses

Business Rules

Percent Missed Installation Appointments (PMI) is the percentage of orders with completion dates in the reporting period that are past the original committed due date. Missed Appointments caused by end-user reasons will be excluded and reported separately. The "due date" is the commitment time (if applicable) on the confirmed due date.

Calculation

Percent Missed Installation Appointments = $(a \div b) \times 100$

- a = Number of Appointments in Reporting Period past the Original (Date/Time as applicable) Committed and Subsequent Committed Due Date
- b = Number of Appointments on Orders Completed in Reporting Period

Report Structure

- · CLEC Specific
- CLEC Aggregate
- · BellSouth Aggregate
- Report in Categories of <10 lines/circuits ≥ 10 lines/circuits (except trunks)
- · Dispatch/Non-Dispatch

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report Month	Report Month
CLEC Order Number and PON (PON)	BellSouth Order Number
Committed Due Date (DD)	Committed Due Date (DD)
Completion Date (CMPLTN DD)	Completion Date (CMPLTN DD)
Status Type	Status Type
Status Notice Date	Status Notice Date
Standard Order Activity	Standard Order Activity
Geographic Scope	Geographic Scope
Note: Code in parentheses is the corresponding header found in the raw data file.	



SQM Disaggregation - Analog/Benchmark

SQM LEVEL of Disaggregation	SQM Analog/Benchmark
Resale Residence	Retail Residence
Resale Business	Retail Business
Resale Design	Retail Design
Resale PBX	Retail PBX
Resale Centrex	Retail Centrex
Resale ISDN	Retail ISDN
LNP (Standalone)	Retail Residence and Business (POTS)
INP (Standalone)	Retail Residence and Business (POTS)
2W Analog Loop Design	Retail Residence and Business Dispatch
2W Analog Loop Non-Design	Retail Residence and Business - POTS Excluding Switch- Based Orders
2W Analog Loop With LNP - Design	Retail Residence and Business Dispatch
2W Analog Loop With LNP- Non-Design	Retail Residence and Business - POTS Excluding Switch- Based Orders
2W Analog Loop With INP-Design	Retail Residence and Business Dispatch
2W Analog Loop With INP-Non-Design	Retail Residence and Business - POTS Excluding Switch- Based Orders
UNE Digital Loop < DS1	• Retail Digital Loop < DS1
• UNE Digital Loop ≥ DS1	• Retail Digital Loop ≥ DS1
UNE Loop + Port Combinations Dispatch In Switch Based	Retail Residence and Business Dispatch In Switch Based
UNE Switch Ports	Retail Residence and Business (POTS)
UNE Combo Other	Retail Residence, Business and Design Dispatch
UNE xDSL (HDSL, ADSL and UCL) Without Conditioning With Conditioning	ADSL Provided to Retail Without Conditioning With Conditioning (BellSouth does not offer this service to Retail)
UNE ISDN (Includes UDC)	Retail ISDN - BRI
UNE Line Sharing	ADSL Provided to Retail
UNE Other Design	Retail Design
UNE Other Non-Design	Retail Residence and Business
Local Transport (Unbundled Interoffice Transport)	Retail DS1/DS3 Interoffice
Local Interconnection Trunks	Parity with Retail
UNE Line Splitting	ADSL to Retail
• EELs	• Retail DS1/DS3

SEEM Measure

SEEM Measure		
Yes	Tier I	X
	Tier II	X

SEEM Disaggregation	SEEM Analog/Benchmark
Resale Residence	Retail Residence
Resale Business	Retail Business
Resale Design	Retail Design
Resale PBX	Retail PBX
Resale Centrex	Retail Centrex
Resale ISDN	Retail ISDN
LNP (Standalone)	Retail Residence and Business (POTS)
INP (Standalone)	Retail Residence and Business (POTS)
2W Analog Loop Design	Retail Residence and Business Dispatch
2W Analog Loop Non-Design	Retail Residence and Business - POTS Excluding Switch- Based Orders
2W Analog Loop With LNP - Design	Retail Residence and Business Dispatch
2W Analog Loop With LNP- Non-Design	Retail Residence and Business - POTS Excluding Switch- Based Orders
2W Analog Loop With INP-Design	Retail Residence and Business Dispatch
2W Analog Loop With INP-Non-Design	Retail Residence and Business - POTS Excluding Switch- Based Orders
UNE Digital Loop < DS1	Retail Digital Loop < DS1
• UNE Digital Loop ≥ DS1	• Retail Digital Loop ≥ DS1
UNE Loop + Port Combinations Dispatch In Switch Based	Retail Residence and Business Dispatch In Switch Based
UNE Switch Ports	Retail Residence and Business (POTS)
UNE Combo Other	Retail Residence, Business and Design Dispatch
UNE xDSL (HDSL, ADSL and UCL) Without Conditioning With Conditioning	ADSL Provided to Retail Without Conditioning With Conditioning (BellSouth does not offer this service to Retail)
UNE ISDN (Includes UDC)	Retail ISDN - BRI
UNE Line Sharing	ADSL Provided to Retail
Local Transport (Unbundled Interoffice Transport)	Retail DS1/DS3 Interoffice
Local Interconnection Trunks	Parity with Retail
UNE Line Splitting	ADSL Provided to Retail
UNE Other Design	Retail Design
UNE Other Non-Design	Retail Residence and Business
• EELs	Retail DS1/DS3



P-4: Average Completion Interval (OCI) & Order Completion Interval Distribution

(This metric not ordered by the FPSC)

Definition

The "average completion interval" measure monitors the interval of time it takes BellSouth to provide service for the CLEC or its own customers. The "Order Completion Interval Distribution" provides the percentages of orders completed within certain time periods. This report measures how well BellSouth meets the interval offered to customers on service orders.

Exclusions

- · Canceled Service Orders
- Order Activities of BellSouth or the CLEC associated with internal or administrative use of local services (Record Orders, Listing Orders, Test Orders, etc.)
- Disconnect (D&F) orders (Except "D" orders associated with LNP Standalone)
- "L" Appointment coded orders (where the customer has requested a later than offered interval)
- · End user-caused misses

Business Rules

The actual completion interval is determined for each order processed during the reporting period. The completion interval is the elapsed time from when BellSouth issues a FOC or SOCS date time stamp receipt of an order from the CLEC to BellSouth's actual order completion date. The clock starts when a valid order number is assigned by SOCS and stops when the technician or system completes the order in SOCS. Elapsed time for each order is accumulated for each reporting dimension. The accumulated time for each reporting dimension is then divided by the associated total number of orders completed. Orders that are worked on zero due dates are calculated with a .33-day interval (8 hours) in order to report a portion of a day interval. These orders are issued and worked/completed on the same day. They can be either flow through orders (no field work-non-dispatched) or field orders (dispatched).

The interval breakout for UNE and Design is: 0-5 = 0 < 5, 5-10 = 5 < 10, 10-15 = 10 < 15, 15-20 = 15 < 20, 20-25 = 20 < 25, 25-30 = 25 < 30, $\ge 30 = 30$ and greater.

Calculation

Completion Interval = (a - b)

- a = Completion Date
- b = FOC/SOCS date time-stamp (application date)

Average Completion Interval = $(c \div d)$

- c = Sum of all Completion Intervals
- d = Count of Orders Completed in Reporting Period

Order Completion Interval Distribution (for each interval) = $(e \div f) \times 100$

- e = Service Orders Completed in "X" days
- f = Total Service Orders Completed in Reporting Period

Report Structure

- · CLEC Specific
- CLEC Aggregate
- · BellSouth Aggregate
- Dispatch/Non-Dispatch categories applicable to all levels except trunks
- Residence & Business reported in day intervals = 0.1,3,4,5,5+
- UNE and Design reported in day intervals =0-5,5-10,10-15,15-20,20-25,25-30, \geq 30
- All Levels are reported <10 line/circuits; ≥ 10 line/circuits (except trunks)
- · ISDN Orders included in Non-Design



Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
 Report Month CLEC Company Name Order Number (PON) Application Date & Time Completion Date (CMPLTN_DT) Service Type (CLASS_SVC_DESC) Geographic Scope 	 Report Month BellSouth Order Number Order Submission Date & Time Order Completion Date & Time Service Type Geographic Scope
Note: Code in parentheses is the corresponding header found in the raw data file.	

SQM LEVEL of Disaggregation	SQM Analog/Benchmark
Resale Residence	Retail Residence
Resale Business	Retail Business
Resale Design	Retail Design
Resale PBX	Retail PBX
Resale Centrex	Retail Centrex
Resale ISDN	Retail ISDN
LNP (Standalone)	Retail Residence and Business (POTS)
INP (Standalone)	Retail Residence and Business (POTS)
2W Analog Loop Design	Retail Residence and Business Dispatch
2W Analog Loop Non-Design	Retail Residence and Business - POTS Excluding Switch- Based Orders
2W Analog Loop With LNP - Design	Retail Residence and Business Dispatch
2W Analog Loop With LNP- Non-Design	Retail Residence and Business - POTS Excluding Switch- Based Orders
2W Analog Loop With INP-Design	Retail Residence and Business Dispatch
2W Analog Loop With INP-Non-Design	Retail Residence and Business - POTS Excluding Switch- Based Orders
UNE Digital Loop < DS1	Retail Digital Loop < DS1
• UNE Digital Loop ≥ DS1	Retail Digital Loop ≤ DS1
 UNE Loop + Port Combinations Dispatch In Switch Based 	Retail Residence and Business Dispatch In Switch Based
UNE Switch Ports	Retail Residence and Business (POTS)
UNE Combo Other	Retail Residence, Business and Design Dispatch
UNE xDSL (HDSL, ADSL and UCL) Without Conditioning With Conditioning	- ≤ 5 Days - ≤ 12 Days
UNE ISDN (Includes UDC)	Retail ISDN - BRI
UNE Line Sharing	ADSL Provided to Retail
Local Transport (Unbundled Interoffice Transport)	Retail DS1/DS3 Interoffice
Local Interconnection Trunks	Parity with Retail

(A) BELLSOUTH®

SQM LEVEL of Disaggregation	SQM Analog/Benchmark
UNE Line Splitting	ADSL to Retail
UNE Other Design	Retail Design
UNE Other Non-Design	Retail Residence and Business
• EELs	• Retail DS1/DS3

SEEM Measure

SEEM Measure		
No	Tier I	
	Tier II	

SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable



P-4A: Average Order Completion and Completion Notice Interval (AOCCNI) Distribution

Definition

The "Order Completion And Completion Notice Interval Distribution" provides the percentages of orders completed within certain time periods. This report measures how well BellSouth meets the interval offered to customers and notice of completion to the CLEC on service orders.

Exclusions

- · Canceled Service Orders
- Order Activities of BellSouth or the CLEC associated with internal or administrative use of local services (Record Orders, Listing Orders, Test Orders, etc.) Test order types may be C, N, R, or T.
- Disconnect (D&F) orders (Except "D" orders associated with LNP Standalone)
- "L" Appointment coded orders (where the customer has requested a later than offered interval)
- · End user-caused misses

Business Rules

The interval is determined for each order processed during the reporting period. The completion interval for AOCCNI is the elapsed time from when BellSouth issues a FOC or SOCS date time stamp receipt of an order from the CLEC to BellSouth's return of the completion notice (CN) to the CLEC. Elapsed time for each order is accumulated for each reporting dimension. The accumulated time for each reporting dimension is then divided by the associated total number of orders completed. Orders that are worked on zero due dates are calculated with a .33-day interval (8 hours) in order to report a portion of a day interval. These orders are issued and worked/completed on the same day. They can be either flow through orders (no field work-non-dispatched) or field orders (dispatched).

The interval breakout for UNE and Design is: 0-5 = 0 < 5, 5-10 = 5 < 10, 10-15 = 10 < 15, 15-20 = 15 < 20, 20-25 = 20 < 25, 25-30 = 25 < 30, $\ge 30 = 30$ and greater.

Calculation

Completion Interval = (a - b)

- a = Date and Time Completion Notice is sent
- b = FOC/SOCS date time-stamp (application date)

Average Completion Interval = $(c \div d)$

- c = Sum of all Completion Intervals
- d = Count of Orders Completed in Reporting Period

Order Completion Interval Distribution (for each interval) = $(e \div f) \times 100$

- e = Service Orders Completed in "X" days
- f = Total Service Orders Completed in Reporting Period

Report Structure

- · CLEC Specific
- · CLEC Aggregate
- · BellSouth Aggregate
- Dispatch/Non-Dispatch categories applicable to all levels except trunks
- Residence & Business reported in day intervals = 0,1,2,3,4,5,5+
- UNE and Design reported in day intervals = 0-5, 5-10, 10-15, 15-20, 20-25, 25-30, \geq 30
- All Levels are reported <10 line/circuits; ≥ 10 line/circuits (except trunks)
- · ISDN Orders included in Non-Design
- Mechanized/Non-Mechanized (Non-Mechanized is not applicable to BellSouth)



Relating to CLEC Experience	Relating to BellSouth Performance
 Report Month CLEC Company Name Order Number (PON) Application Date & Time Completion Date (CMPLTN_DT) Service Type (CLASS_SVC_DESC) Geographic Scope 	 Report Month BellSouth Order Number Order Submission Date & Time Order Completion Date & Time Service Type Geographic Scope
Note: Code in parentheses is the corresponding header found in the raw data file.	

SQM Level of Disaggregation	SQM Analog/Benchmark
Resale Residence	Retail Residence
Resale Business	Retail Business
Resale Design	Retail Design
Resale PBX	Retail PBX
Resale Centrex	Retail Centrex
Resale ISDN	Retail ISDN
LNP (Standalone)	Retail Residence and Business (POTS)
INP (Standalone)	Retail Residence and Business (POTS)
2W Analog Loop Design	Retail Residence and Business Dispatch
2W Analog Loop Non-Design	Retail Residence and Business - POTS Excluding Switch- Based Orders
2W Analog Loop With LNP - Design	Retail Residence and Business Dispatch
2W Analog Loop With LNP- Non-Design	Retail Residence and Business - POTS Excluding Switch- Based Orders
2W Analog Loop With INP-Design	Retail Residence and Business Dispatch
2W Analog Loop With INP-Non-Design	Retail Residence and Business - POTS Excluding Switch- Based Orders
• UNE Digital Loop < DS1	Retail Digital Loop < DS1
• UNE Digital Loop ≥ DS1	Retail Digital Loop ≤ DS1
 UNE Loop + Port Combinations Dispatch In Switch Based 	Retail Residence and Business Dispatch In Switch Based
UNE Switch Ports	Retail Residence and Business (POTS)
UNE Combo Other	Retail Residence, Business and Design Dispatch
UNE xDSL (HDSL, ADSL and UCL) Without Conditioning With Conditioning	- ≤ 5 Days - ≤ 12 Days
UNE ISDN (Includes UDC)	Retail ISDN - BRI
UNE Line Sharing	ADSL Provided to Retail
Local Transport (Unbundled Interoffice Transport)	Retail DS1/DS3 Interoffice
Local Interconnection Trunks	Parity with Retail



Tennessee Performance Measurements

SQM Level of Disaggregation	SQM Analog/Benchmark
UNE Line Splitting	ADSL to Retail
UNE Other Design	Retail Design
UNE Other Non-Design	Retail Residence and Business
• EELs	• Retail DS1/DS3

SEEM Measure

SEEM Measure		
Yes	Tier I	X
	Tier II	X

SEEM Disaggregation	SEEM Analog/Benchmark
Resale Residence	Retail Residence
Resale Business	Retail Business
Resale Design	Retail Design
Resale PBX	Retail PBX
Resale Centrex	Retail Centrex
Resale ISDN	Retail ISDN
LNP (Standalone)	Retail Residence and Business (POTS)
INP (Standalone)	Retail Residence and Business (POTS)
2W Analog Loop Design	Retail Residence and Business Dispatch
2W Analog Loop Non-Design	Retail Residence and Business - POTS Excluding Switch- Based Orders
2W Analog Loop With LNP - Design	Retail Residence and Business Dispatch
2W Analog Loop With LNP- Non-Design	Retail Residence and Business - POTS Excluding Switch- Based Orders
2W Analog Loop With INP-Design	Retail Residence and Business Dispatch
2W Analog Loop With INP-Non-Design	Retail Residence and Business - POTS Excluding Switch- Based Orders
UNE Digital Loop < DS1	Retail Digital Loop < DS1
• UNE Digital Loop ≥ DS1	Retail Digital Loop ≤ DS1
 UNE Loop + Port Combinations Dispatch In Switch Based 	Retail Residence and Business Dispatch In Switch Based
UNE Switch Ports	Retail Residence and Business (POTS)
UNE Combo Other	Retail Residence, Business and Design Dispatch
UNE xDSL (HDSL, ADSL and UCL) Without Conditioning With Conditioning	- ≤ 5 Days - ≤ 12 Days
UNE ISDN (Includes UDC)	Retail ISDN - BRI
UNE Line Sharing	ADSL Provided to Retail
Local Transport (Unbundled Interoffice Transport)	Retail DS1/DS3 Interoffice

(A) BELLSOUTH®

SEEM Disaggregation	SEEM Analog/Benchmark
Local Interconnection Trunks	Parity with Retail
UNE Line Splitting	ADSL Provided to Retail
UNE Other Design	Retail Design
UNE Other Non-Design	Retail Residence and Business
• EELs	• Retail DS1/DS3

P-5: Average Completion Notice Interval

Definitions

The Completion Notice Interval is the elapsed time between the BellSouth reported completion of work and the issuance of a valid completion notice to the CLEC.

Exclusions

- · Cancelled Service Orders
- Order Activities of BellSouth or the CLEC associated with internal or administrative use of local services (Record Orders, Listing Orders, Test Orders, etc.) Test order types may be C, N, R, or T.
- D&F orders (Exception: "D" orders associated with LNP Standalone)

Business Rules

Measurement on interval of completion date and time entered by a field technician on dispatched orders, and 5PM start time on the due date for non-dispatched orders; to the release of a notice to the CLEC/BellSouth of the completion status. The field technician notifies the CLEC the work was complete and then he/she enters the completion time stamp information in his/her computer. This information switches through to the SOCS systems either completing the order or rejecting the order to the Work Management Center (WMC). If the completion is rejected, it is manually corrected and then completed by the WMC. The notice is returned on each individual order.

The start time for all orders is the completion stamp either by the field technician or the 5PM due date stamp; the end time for mechanized orders is the time stamp the notice was transmitted to the CLEC interface (LENS, EDI, OR TAG). For non-mechanized orders the end time will be date and timestamp of order update from the FAX record via LON or C-SOTS system.

Calculation

Completion Notice Interval = (a - b)

- a = Date and Time of Notice of Completion
- b = Date and Time of Work Completion

Average Completion Notice Interval = $c \div d$

- c = Sum of all Completion Notice Intervals
- d = Number of Orders with Notice of Completion in Reporting Period

Report Structure

- · CLEC Specific
- · CLEC Aggregate
- · BellSouth Aggregate
- · Mechanized Orders
- · Non-Mechanized Orders
- · Dispatch/Non-Dispatch
- Reporting intervals in Hours; 0,1-2,2-4,4-8,8-12,12-24, ≥ 24 plus Overall Average Hour Interval (The categories are inclusive of these time intervals: 0-1 = 0.99; 1-2 = 1-1.99; 2-4 = 2-3.99, etc.)
- Reported in categories of <10 line / circuits; ≥ 10 line/circuits (except trunks)

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report Month	Report Month
CLEC Order Number (so_nbr)	BellSouth Order Number (so_nbr)
 Work Completion Date (cmpltn_dt) 	Work Completion Date (cmpltn_dt)
Work Completion Time	Work Completion Time
Completion Notice Availability Date	Completion Notice Availability Date
Completion Notice Availability Time	Completion Notice Availability Time
Service Type	Service Type
Geographic Scope	Geographic Scope
Note: Code in parentheses is the corresponding header found in the raw data file.	NOTE: Code in parentheses is the corresponding header found in the raw data file.

SQM LEVEL of Disaggregation	SQM Analog/Benchmark
Resale Residence	Retail Residence
Resale Business	Retail Business
Resale Design	Retail Design
Resale PBX	Retail PBX
Resale Centrex	Retail Centrex
Resale ISDN	Retail ISDN
LNP (Standalone)	Retail Residence and Business (POTS)
INP (Standalone)	Retail Residence and Business (POTS)
2W Analog Loop Design	Retail Residence and Business Dispatch
2W Analog Loop Non-Design	Retail Residence and Business - POTS Excluding Switch- Based Orders
2W Analog Loop With LNP - Design	Retail Residence and Business Dispatch
2W Analog Loop With LNP- Non-Design	Retail Residence and Business - POTS Excluding Switch- Based Orders
2W Analog Loop With INP-Design	Retail Residence and Business Dispatch
2W Analog Loop With INP-Non-Design	Retail Residence and Business - POTS Excluding Switch- Based Orders
UNE Digital Loop < DS1	Retail Digital Loop < DS1
• UNE Digital Loop ≥ DS1	Retail Digital Loop ≤ DS1
UNE Loop + Port Combinations Dispatch In Switch Based	Retail Residence and Business Dispatch In Switch Based
UNE Switch Ports	Retail Residence and Business (POTS)
UNE Combo Other	Retail Residence, Business and Design Dispatch
UNE xDSL (HDSL, ADSL and UCL)	ADSL Provided to Retail
UNE ISDN (Includes UDC)	Retail ISDN - BRI
UNE Line Sharing	ADSL Provided to Retail
Local Transport (Unbundled Interoffice Transport)	Retail DS1/DS3 Interoffice
Local Interconnection Trunks	Parity with Retail



Tennessee Performance Measurements

SQM LEVEL of Disaggregation	SQM Analog/Benchmark
UNE Line Splitting	ADSL to Retail
UNE Other Design	Retail Design
UNE Other Non-Design	Retail Residence and Business
• EELs	Retail DS1/DS3

SEEM Measure

SEEM Measure		
No	Tier I	
	Tier II	

SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable

(A) **BELLSO**UTH®

P-6: % Completions/Attempts without Notice or < 24 hours Notice

Definition

The purpose of this measure is to report if BellSouth is returning a FOC to the CLEC in time for the CLEC to notify their customer of

Exclusions

- · Cancelled Orders
- Expedited Orders
- "0" dated orders or any request where the subscriber requested an earlier due date of < 24 hours prior to the original commitment date, or any LSR received < 24 hours prior to the original commitment date.

Business Rules

For CLEC Results:

Calculation would exclude any successful or unsuccessful service delivery where the CLEC was informed at least 24 hours in advance. BellSouth may also exclude from calculation any LSRs received from the requesting CLEC with less than 24 hour notice prior to the commitment date.

For BellSouth Results:

BellSouth does not provide a FOC to its retail customers.

Calculation

Percent Completions or Attempts without Notice or with Less Than 24 Hours Notice = $(a \div b) \times 100$

- a = Completion Dispatches (Successful and Unsuccessful) With No FOC or FOC Received < 24 Hours of Original Committed Due Date
- b = All Completions

Report Structure

- · CLEC Specific
- · CLEC Aggregate
- · Dispatch /Non-Dispatch
- Total Orders FOC < 24 Hours
- Total Completed Service Orders
- % FOC < 24 Hours

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Committed Due Date (DD) FOC End Timestamp	Not Applicable
Report MonthCLEC Order Number and PON	
Geographic Scope State / Region	

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
Resale Residence	• <= 5%
Resale Business	
Resale Design	
Resale PBX	
Resale Centrex	
Resale ISDN	
• LNP (Standalone)	
• INP (Standalone)	
2W Analog Loop Design	
2W Analog Loop Non-Design	
2W Analog Loop Design With LNP	
2W Analog Loop Non-Design With LNP	
2W Analog Loop Design With INP	
2W Analog Loop Non-Design With INP	
• UNE Digital Loop < DS1	
 UNE Digital Loop ≥DS1 	
• UNE Loop + Port Combinations	
- Dispatch In	
- Switch Based	
UNE Switch ports	
UNE Combo Other	
UNE xDSL (HDSL, ADSL and UCL)	
UNE ISDN (Includes UDC)	
UNE Line Sharing	
UNE Line Splitting	
Local Transport (Unbundled Interoffice Transport)	
Local Interconnection Trunks	
• EELS	

SEEM Measure

SEEM Measure		
No	Tier I	
Tier II		

SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable



P-7: Coordinated Customer Conversions Interval

Definition

This report measures the average time it takes BellSouth to disconnect an unbundled loop from the BellSouth switch and cross connect it to CLEC equipment. This measurement applies to service orders with INP and LNP, and where the CLEC has requested BellSouth to provide a coordinated cutover.

Exclusions

- Any order canceled by the CLEC will be excluded from this measurement.
- Delays due to CLEC following disconnection of the unbundled loop
- Unbundled Loops where there is no existing subscriber loop and loops where coordination is not requested.

Business Rules

Where the service order includes LNP, the interval includes the total time for the cutover including the translation time to place the line back in service on the ported line. When the service order includes INP, the interval includes the total time for the cutover including the translation time to place the link back in service on the ported line. The interval is calculated for the entire cutover time for the service order and then divided by items worked in that time to give the average per-item interval for each service order.

Calculation

Coordinated Customer Conversions Interval = (a - b)

- a = Completion Date and Time for Cross Connection of a Coordinated Unbundled Loop
- b = Disconnection Date and Time of an Coordinated Unbundled Loop

Percent Coordinated Customer Conversions (for each interval) = $(c \div d) \times 100$

- c = Total number of Coordinated Customer Conversions for each interval
- d = Total Number of Unbundled Loop with Coordinated Conversions (items) for the reporting period

Report Structure

- · CLEC Specific
- · CLEC Aggregate
- The interval breakout is $0-5 = 0-\le 5$, $5-15 = >5-\le 15$, $\ge 15 = 15$ and greater, plus Overall Average Interval.

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report Month	No BellSouth Analog Exists
CLEC Order Number	
Committed Due Date (DD)	
Service Type (CLASS_SVC_DESC)	
Cutover Start Time	
Cutover Completion time	
 Portability Start and Completion Times (INP orders) 	
Total Conversions (Items)	
Note: Code in parentheses is the corresponding header	
found in the raw data file.	

SQM Level of Disaggregation	SQM Analog/Benchmark	l
Unbundled Loops with INP	• 95% ≤ 15 minutes	l
Unbundled Loops with LNP	• 95% ≤ 15 minutes	Ì

P-7: Coordinated Customer Conversions Interval

SEEM Measure

SEEM Measure		
Yes	Tier I	X
Tier II X		

SEEM Disaggregation	SEEM Analog/Benchmark
 Unbundled Loops With INP Unbundled Loops With LNP	• 95% ≤ 15 minutes • 95% ≤ 15 minutes

(A) **BELLSOUTH**

P-7A: Coordinated Customer Conversions – Hot Cut Timeliness % Within Interval and Average Interval

Definition

This category measures whether BellSouth begins the cutover of an unbundled loop on a coordinated and/or a time specific order at the CLEC requested start time. It measures the percentage of orders where the cut begins within 15 minutes of the requested start time of the order and the average interval.

Exclusions

- Any order canceled by the CLEC will be excluded from this measurement.
- Delays caused by the CLEC
- Unbundled Loops where there is no existing subscriber loop and loops where coordination is not requested.
- All unbundled loops on multiple loop orders after the first loop.

Business Rules

This report measures whether BellSouth begins the cutover of an unbundled loop on a coordinated and/or a time specific order at the CLEC requested start time. The cut is considered on time if it starts 15 minutes before or after the requested start time. Using the scheduled time and the actual cutover start time, the measurement will calculate the percent within interval and the average interval. If a cut involves multiple lines, the cut will be considered "on time" if the first line is cut within the interval. ≤ 15 minutes includes intervals that began 15:00 minutes or less before the scheduled cut time and cuts that began 15 minutes or less after the scheduled cut time; >15 minutes, ≤30 minutes includes cuts within 15:00 – 30:00 minutes either prior to or after the scheduled cut time; >30 minutes includes cuts greater than 30:00 minutes either prior to or after the scheduled cut time. If IDLC is involved, a four hour window applies to the start time. (8 A.M. to Noon or 1 P.M. to 5 P.M.) This only applies if BellSouth notifies the CLEC by 10:30 A.M. on the day before the due date that the service is on IDLC.

A Hot Cut is considered complete when one of the following occurs:

- BellSouth performs the hot cut, notifies the CLEC by telephone.
- BellSouth performs the hot cut and attempts to notify the CLEC by telephone, but receives no answer and leaves a phone message.

Calculation

% within Interval = $(a \div b) \times 100$

- a = Total Number of Coordinated Unbundled Loop Orders for the interval
- b = Total Number of Coordinated Unbundled Loop Orders for the reporting period

Interval = (c - d)

- c = Scheduled Time for Cross Connection of a Coordinated Unbundled Loop Order
- d = Actual Start Date and Time of a Coordinated Unbundled Loop Order

Average Interval = $(e \div f)$

- · Sum of all Intervals
- Total Number of Coordinated Unbundled Loop Orders for the reporting period.

Report Structure

- · CLEC Specific
- · CLEC Aggregate

Reported in intervals of early, on time and late cuts % ≤ 15 minutes; % > 15 minutes, ≤30 minutes; % > 30 minutes, plus Overall Average Interval

(A) BELLSOUTH®

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
 Report Month CLEC Order Number (so_nbr) Committed Due Date (DD) Service Type (CLASS_SVC_DESC) Cutover Scheduled Start Time Cutover Actual Start Time Total Conversions Orders 	No BellSouth Analog exists
Note: Code in parentheses is the corresponding header found in the raw data file.	

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
 Product Reporting Level SL1 Time Specific SL1 Non-Time Specific SL2 Time Specific SL2 Non-Time Specific 	95% Within + or – 15 Minutes of Scheduled Start Time
- SL1 IDLC - SL2 IDLC	• 95% Within 4-hour Window

SEEM Measure

SEEM Measure		
Yes	Tier I	X
Tier II X		X

SEEM Disaggregation	SEEM Analog/Benchmark
- SL1 Time Specific - SL1 Non-Time Specific - SL2 Time Specific - SL2 Non-Time Specific	• 95% Within + or – 15 Minutes of Scheduled Start Time
- SL1 IDLC - SL2 IDLC	• 95% Within 4-hour Window

(A) **BELLSOUTH**

P-7B: Coordinated Customer Conversions – Average Recovery Time

Definition

Measures the time between notification and resolution by BellSouth of a service outage found that can be isolated to the BellSouth side of the network. The time between notification and resolution by BellSouth must be measured to ensure that CLEC customers do not experience unjustifiable lengthy service outages during a Coordinated Customer Conversion. This report measures outages associated with Coordinated Customer Conversions prior to service order completion.

Exclusions

- Cutovers where service outages are due to CLEC caused reasons when the CLEC agrees
- Cutovers where service outages are due to end-user caused reasons when the CLEC agrees

Business Rules

Measures the outage duration time related to Coordinated Customer Conversions from the initial trouble notification until the trouble has been restored and the CLEC has been notified. The duration time is defined as the time from the initial trouble notification until the trouble has been restored and the CLEC has been notified. The interval is calculated on the total outage time for the circuits divided by the total number of outages restored during the report period to give the average outage duration.

Calculation

Recovery Time = (a - b)

- a = Date & Time That Trouble is Closed by CLEC
- b = Date & Time Initial Trouble is Opened with BellSouth

Average Recovery Time = $(c \div d)$

- c = Sum of all the Recovery Times
- d = Number of Troubles Referred to the BellSouth

Report Structure

- · CLEC Specific
- · CLEC Aggregate

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report Month	None
CLEC Company Name	
• CLEC Order Number (so_nbr)	
• Committed Due Date (DD)	
• Service Type (CLASS_SVC_DESC)	
 CLEC Acceptance Conflict (CLEC_CONFLICT) 	
 CLEC Conflict Resolved (CLEC_CON_RES) 	
 CLEC Conflict MFC (CLEC_CONFLICT_MFC) 	
Total Conversion Orders	
Note: Code in parentheses is the corresponding header found in the raw data file.	

SQM Level of Disaggregation	SQM Analog/Benchmark
 Unbundled Loops with INP Unbundled Loops with LNP	Diagnostic (To Be Established at The 6 Month Review Period)

SEEM Measure

SEEM Measure		
No	Tier I	
	Tier II	

SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable



P-7C: Hot Cut Conversions - % Provisioning Troubles Received Within 7 days of a completed Service Order

Definition

The Percent Provisioning Troubles received within 7 days of a completed service order associated with a Hot Cut Conversion (CCC) measures the quality and accuracy of Coordinated Customer Conversion Activities.

Exclusions

- · Any order canceled by the CLEC
- Troubles caused by Customer Provided Equipment

Business Rules

Measures the quality and accuracy of completed service orders associated with Coordinated and Non-coordinated Customer Conversions. The first trouble report received on a circuit ID within 7 days following a service order completion is counted in this measure. Subsequent trouble reports are measured in Repeat Report Rate. Reports are calculated searching in the prior report period for completed Coordinated Customer Conversion service orders and following 7 days after the completion of the service order for a trouble report issue date.

Calculation

% Provisioning Troubles within 7 days of service order completion = $(a \div b) \times 100$

- a = The sum of all CCC Circuits with a trouble within 7 days following service order(s) completion
- b = The total number of CCC service order circuits completed in the previous report calendar month

Report Structure

- · CLEC Specific
- CLEC Aggregate
- · Dispatch/Non-Dispatch

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report Month	No BellSouth Analog exists
CLEC Order Number (so nbr)	
• PON	
Order Submission Date (TICKET_ID)	
Order Submission Time (TICKET ID)	
Status Type	
Status Notice Date	
Standard Order Activity	
Geographic Scope	
Total Conversion Circuits	
Note: Code in parentheses is the corresponding header found in the raw data file.	

SQM Level of Disaggregation	SQM Analog/Benchmark
 UNE Loop Design UNE Loop Non-Design	• ≤ 5% (To be reviewed after six month period)

SEEM Measure

SEEM Measure		
Yes	Tier I	X
	Tier II	X

SEEM Disaggregation	SEEM Analog/Benchmark
 UNE Loop Design UNE Loop Non-Design	• ≤ 5% (To be reviewed after six month period)



P-8: Cooperative Acceptance Testing - % of xDSL Loops Successfully Tested

Definition

A loop will be considered successfully cooperatively tested when both the CLEC and ILEC representatives agree that the loop has passed the cooperative testing.

Exclusions

- Testing failures due to CLEC (incorrect contact number, CLEC not ready, etc.)
- xDSL lines with no request for cooperative testing

Business Rules

When a BellSouth technician finishes delivering an order for an xDSL loop where the CLEC order calls for cooperative testing at the customer's premise, the BellSouth technician is to call a toll free number to the CLEC testing center. The BellSouth technician and the CLEC representative at the center then test the line. As an example of the type of testing performed, the testing center may ask the technician to put a short on the line so that the center can run a test to see if it can identify the short. CLEC caused failures will be captured in the raw data files.

Calculation

Cooperative Acceptance Testing - % of xDSL Loops Successfully Tested = $(a \div b) \times 100$

- a = Total number of successful xDSL cooperative tests for xDSL lines where cooperative testing was requested in the reporting period
- b = Total Number of xDSL line tests requested by the CLEC and scheduled in the reporting period

Report Structure

- · CLEC Specific
- CLEC Aggregate
- · Type of Loop tested

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
 Report Month CLEC Company Name (OCN) CLEC Order Number (so_nbr) and PON (PON) Committed Due Date (DD) Service Type (CLASS_SVC_DESC) Acceptance Testing Completed (ACCEPT_TESTING) Acceptance Testing Declined (ACCEPT_TESTING) Total xDSL Orders Missed Appointments Code (SO MISSED CMMT CD) 	No BellSouth Analog Exists
Note : Code in parentheses is the corresponding header found in the raw data file.	

SQM Analog/Benchmark
95% of Lines Successfully Tested

SEEM Measure

SEEM Measure		
Yes	Tier I	X
	Tier II	X

SEEM Disaggregation	SEEM Analog/Benchmark
UNE xDSLADSLHDSLUCLOther	95% of Lines Successfully Tested



P-9: % Provisioning Troubles within 30 days of Service Order Completion

Definition

Percent Provisioning Troubles within 30 days of Service Order Completion measures the quality and accuracy of Service order activities.

Exclusions

- · Canceled Service Orders
- Order Activities of BellSouth or the CLEC associated with internal or administrative use of local services (Record Orders, Listing Orders, Test Orders, etc.) Test order types may be C, N, R, or T.
- D & F orders
- Trouble reports caused and closed out to Customer Provided Equipment (CPE)

Business Rules

Measures the quality and accuracy of completed orders. The first trouble report from a service order after completion is counted in this measure. Subsequent trouble reports are measured in Repeat Report Rate. Reports are calculated searching in the prior report period for completed service orders and following 30 days after completion of the service order for a trouble report issue date.

D & F orders are excluded as there is no subsequent activity following a disconnect.

Note: Standalone LNP historical data is not available in the maintenance systems (LMOS or WFA).

Calculation

% Provisioning Troubles within 30 days of Service Order Activity = $(a \div b) \times 100$

- a = Trouble reports on all completed orders 30 days following service order(s) completion
- b = All Service Orders completed in the previous report calendar month

Report Structure

- · CLEC Specific
- CLEC Aggregate
- BellSouth Aggregate
- Reported in categories of <10 line/circuits; ≥ 10 line/circuits (except trunks)
- Dispatch /Non-Dispatch (except trunks)

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report Month	Report Month
CLEC Order Number and PON	BellSouth Order Number
Order Submission Date (TICKET_ID)	Order Submission Date
 Order Submission Time (TICKET_ID) 	Order Submission Time
Status Type	Status Type
Status Notice Date	Status Notice Date
Standard Order Activity	Standard Order Activity
Geographic Scope	Geographic Scope
Note: Code in parentheses is the corresponding header found in the raw data file.	

SQM LEVEL of Disaggregation	SQM Analog/Benchmark
Resale Residence	Retail Residence

SQM Analog/Benchmark
Retail business
Retail Design
Retail PBX
Retail Centrex
Retail ISDN
Retail Residence and Business (POTS)
Retail Residence and Business (POTS)
Retail Residence and Business Dispatch
Retail Residence and Business - (POTS Excluding Switch- Based Orders)
Retail Residence and Business Dispatch
Retail Residence and Business - (POTS Excluding Switch- Based Orders)
Retail Residence and Business Dispatch
Retail Residence and Business (POTS - Excluding Switch- Based Orders)
• Retail Digital Loop < DS1
• Retail Digital Loop ≥ DS1
ADSL provided to Retail
Retail ISDN BRI
ADSL Provided to Retail
Retail Residence and BusinessDispatch InSwitch-Based
Retail Residence and Business (POTS)
Retail Residence, Business and Design Dispatch (Including Dispatch Out and Dispatch In)
Retail DS1/DS3 Interoffice
Retail Residence and Business
Retail Design
Parity with Retail
ADSL to Retail
• Retail DS1/DS3

SEEM Measure

SEEM Measure		
Yes	Tier I	X
	Tier II	X



SEEM Disaggregation	SEEM Analog/Benchmark
Resale Residence	Retail Residence
Resale Business	Retail business
Resale Design	Retail Design
Resale PBX	Retail PBX
Resale Centrex	Retail Centrex
Resale ISDN	Retail ISDN
LNP (Standalone)	Retail Residence and Business (POTS)
INP (Standalone)	Retail Residence and Business (POTS)
2W Analog Loop Design	Retail Residence and Business Dispatch
2W Analog Loop Non-Design	Retail Residence and Business - (POTS Excluding Switch- Based Orders)
2W Analog Loop With LNP Design	Retail Residence and Business Dispatch
2W Analog Loop With LNP Non-Design	Retail Residence and Business - (POTS Excluding Switch- Based Orders)
2W Analog Loop With INP Design	Retail Residence and Business Dispatch
2W Analog Loop With INP Non-Design	Retail Residence and Business (POTS - Excluding Switch- Based Orders)
• UNE Digital Loop < DS1	Retail Digital Loop < DS1
• UNE Digital Loop ≥ DS1	Retail Digital Loop ≥ DS1
UNE Loop + Port Combinations Dispatch In Switch-Based	Retail Residence and Business Dispatch In Switch-Based
UNE Switch Ports	Retail Residence and Business (POTS)
UNE Combo Other	Retail Residence, Business and Design Dispatch (Including Dispatch Out and Dispatch In)
UNE xDSL (HDSL, ADSL and UCL)	ADSL provided to Retail
UNE ISDN (Includes UDC)	Retail ISDN BRI
UNE Line Sharing	ADSL Provided to Retail
Local Transport (Unbundled Interoffice Transport)	Retail DS1/DS3 Interoffice
Local Interconnection Trunks	Parity with Retail
UNE Line Splitting	ADSL Provided to Retail
UNE Other Non-Design	Retail Residence and Business
UNE Other Design	Retail Design
• EELs	• Retail DS1/DS3

(A) **BELLSOUTH**

P-10: Total Service Order Cycle Time (TSOCT)

Definition

This report measures the total service order cycle time from receipt of a valid service order request to the return of a completion notice

Exclusions

- · Canceled Service Orders
- Order Activities of BellSouth or the CLEC associated with internal or administrative use of local services (Record Orders, Listing Orders, Test Orders, etc.) Test order types may be C, N, R, or T.
- D (Disconnect Except "D" orders associated with LNP Standalone.) and F (From) orders. (From is disconnect side of a move order when the customer moves to a new address).
- "L" Appointment coded orders (where the customer has requested a later than offered interval)
- Orders with CLEC/Subscriber caused delays or CLEC/Subscriber requested due date changes.

Business Rules

The interval is determined for each order processed during the reporting period. This measurement combines three reports: FOC Timeliness, Average Order Completion Interval and Average Completion Notice Interval.

This interval starts with the receipt of a valid service order request and stops when a completion notice is sent to the CLEC Interface (LENS, TAG OR EDI). Elapsed time for each order is accumulated for each reporting dimension. The accumulated time for each reporting dimension is then divided by the associated total number of orders completed. Orders that are worked on zero due dates are calculated with a .33 day interval (8 hours) in order to report a portion of a day interval. These orders are issued and worked/completed on same day. They can be either flow through orders (no field work-non-dispatched) or field orders (dispatched).

Reporting is by Fully Mechanized, Partially Mechanized and Non-Mechanized receipt of LSRs.

Calculation

Total Service Order Cycle Time = (a - b)

- a = Service Order Completion Notice Date
- b = Service Request Receipt Date

Average Total Service Order Cycle Time = $(c \div d)$

- c = Sum of all Total Service Order Cycle Times
- d = Total Number Service Orders Completed in Reporting Period

Total Service Order Cycle Time Interval Distribution (for each interval) = $(e \div f) \times 100$

- e = Total Number of Service Requests Completed in "X" minutes/hours
- f = Total Number of Service Requests Received in Reporting Period

Report Structure

- · CLEC Specific
- CLEC Aggregate
- BellSouth Aggregate
- Fully Mechanized; Partially Mechanized; Non-Mechanized
- Report in categories of <10 line/circuits; > 10 line/circuits (except trunks)
- Dispatch /Non-Dispatch categories applicable to all levels except trunks
- Intervals 0-5, 5-10, 10-15, 15-20, 20-25, 25-30, > 30 Days. The interval breakout is: 0-5=0-<5, 5-10=5-<10, 10-15=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15, 15-20=10-<15 $= 15 - <20, 20 - 25 = 20 - <25, 25 - 30 = 25 - <30, \ge 30 = 30$ and greater.

Tennessee Performance Measurements

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
 Report Month Interval for FOC CLEC Company Name (OCN) Order Number (PON) Submission Date & Time (TICKET_ID) Completion Date (CMPLTN_DT) Service Type (CLASS_SVC_DESC) Geographic Scope Note: Code in parentheses is the corresponding header found in the raw data file 	 Report Month BellSouth Order Number Order Submission Date & Time Order Completion Date & Time Service Type Geographic Scope

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
Resale Residence	Diagnostic
Resale Business	
Resale Design	
Resale PBX	
Resale Centrex	
Resale ISDN	
• LNP (Standalone)	
• INP (Standalone)	
2W Analog Loop Design	
2W Analog Loop Non-Design	
2W Analog Loop With LNP Design	
• 2W Analog Loop With LNP Non-Design	
2W Analog Loop With INP Design	
2W Analog Loop With INP Non-Design	
UNE Switch Ports	
UNE Loop + Port Combinations	
- Dispatch In	
- Switch Based	
UNE Combo Other	
UNE xDSL (HDSL, ADSL and UCL)	
• UNE ISDN (Includes UDC)	
• UNE Line Sharing	
• UNE Other Design	
• UNE Other Non -Design	
• UNE Digital Loops < DS1	
• UNE Digital Loops ≥ DS1	
Local Transport (Unbundled Interoffice Transport)	
Local Interconnection Trunks DUD Line Control	
• UNE Line Splitting	
• EELs	

SEEM Measure

SEEM Measure		
No	Tier I	
	Tier II	



Tennessee Performance Measurements

SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable

(A) BELLSOUTH®

P-11: Service Order Accuracy

Definition

The "service order accuracy" measurement measures the accuracy and completeness of BellSouth service orders by comparing what was ordered and what was completed.

Exclusions

- · Cancelled Service Orders
- Order Activities of BellSouth or the CLEC associated with internal or administrative use of local services (Record Orders, Listing Orders, Test Orders, etc.)
- D & F orders

Business Rules

A statistically valid sample of service orders, completed during a monthly reporting period, is compared to the original account profile and the order that the CLEC sent to BellSouth. An order is "completed without error" if all service attributes and account detail changes (as determined by comparing the original order) completely and accurately reflect the activity specified on the original order and any supplemental CLEC order. For both small and large sample sizes, when a Service Request cannot be matched with a corresponding Service Order, it will not be counted. For small sample sizes an effort will be made to replace the service request.

Service Order Accuracy Sampling Process: A list of all orders completed in the report month is generated. The orders are then listed by the disaggregations specified in the SQM. For each disaggregation, the quantity of completed orders and the error rate for each disaggregation from the previous month are entered into a "Stratified Random Sampling for Proportions" formula. This formula determines the number of orders that are to be reviewed for each disaggregation. Once the sample size for each disaggregation is determined, the specified quantity of orders for each disaggregation are pulled for review.

Calculation

Percent Service Order Accuracy = $(a \div b) \times 100$

- a = Orders Completed without Error
- b = Orders Completed in Reporting Period

Report Structure

- · CLEC Aggregate
- Reported in categories of <10 line/circuits; > = 10 line/circuits
- · Dispatch/Non-Dispatch

Data Retained

Relating to CLEC Experience	Relating to BellSouth Experience
Report Month	No BellSouth Analog Exist
 CLEC Order Number and PON 	
Local Service Request (LSR)	
Order Submission Date	
Committed Due Date	
Service Type	
Standard Order Activity	



SQM Disaggregation - Analog/Benchmark

SQM LEVEL of Disaggregation	SQM Analog/Benchmark:
Resale Residence	95% Accurate
Resale Business	
Resale Design (Specials)	
• UNE Specials (Design)	
• UNE (Non-Design)	
Local Interconnection Trunks	

SEEM Measure

SEEM Measure		
Yes	Tier I	
	Tier II	X

SEEM Disaggregation	SEEM Analog/Benchmark
• Resale	• 95%
• UNE	• 95%
• UNE-P	• 95%



P-12: LNP-Average Disconnect Timeliness Interval & Disconnect Timeliness Interval Distribution

Definition

Disconnect Timeliness is defined as the interval between the time ESI Number Manager receives the valid 'Number Ported' message from NPAC (signifying the CLEC 'Activate') until the time the Disconnect is completed in the Central Office switch. This interval effectively measures BellSouth responsiveness by isolating it from impacts that are caused by CLEC related activities.

Exclusions

- · Canceled Service Orders
- Order Activities of BellSouth or the CLEC associated with internal or administrative use of local services (Record Orders, Listing Orders, Test Orders, etc.) where identifiable.

Business Rules

The Disconnect Timeliness interval is determined for each number ported associated with a disconnect service order processed on an LSR during the reporting period. The Disconnect Timeliness interval is the elapsed time from when BellSouth receives a valid 'Number Ported' message in ESI Number Manager (signifying the CLEC 'Activate') for each telephone number ported until each number on the service order is disconnected in the Central Office switch. Elapsed time for each ported number is accumulated for each reporting dimension. The accumulated time for each reporting dimension is then divided by the total number of selected telephone numbers disconnected in the reporting period.

Calculation

Disconnect Timeliness Interval = (a - b)

- a = Completion Date and Time in Central Office switch for each number on disconnect order
- b = Valid 'Number Ported' message received date & time

Average Disconnect Timeliness Interval = $(c \div d)$

- c = Sum of all Disconnect Timeliness Intervals
- d = Total Number of disconnected numbers completed in reporting period

Disconnect Timeliness Interval Distribution (for each interval) = $(e \div f) \times 100$

- e = Disconnected numbers completed in "X" days
- f = Total disconnect numbers completed in reporting period

Report Structure

- · CLEC Specific
- CLEC Aggregate
- · Geographic Scope
- State, Region

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Order Number	Not Applicable
Telephone Number / Circuit Number	
Committed Due Date	
Receipt Date / Time (ESI Number Manager)	
Date/Time of Recent Change Notice	

BELLSOUTH®

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation:	SQM Analog/Benchmark
• LNP	• 95% ≤ 15 Minutes

SEEM Measure

SEEM Measure		
No	Tier I	
	Tier II	

SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable



Section 4: Maintenance & Repair

M&R-1: Missed Repair Appointments

Definition

The percent of trouble reports not cleared by the committed date and time.

Exclusions

- Trouble tickets canceled at the CLEC request.
- BellSouth trouble reports associated with internal or administrative service.
- Customer Provided Equipment (CPE) troubles or CLEC Equipment Trouble.

Business Rules

The negotiated commitment date and time is established when the repair report is received. The cleared time is the date and time that BellSouth personnel clear the trouble and closes the trouble report in his/her Computer Access Terminal (CAT) or workstation. If this is after the Commitment time, the report is flagged as a "Missed Commitment" or a missed repair appointment. When the data for this measure is collected for BellSouth and a CLEC, it can be used to compare the percentage of the time repair appointments are missed due to BellSouth reasons. (No access reports are not part of this measure because they are not a missed appointment.)

Note: Appointment intervals vary with force availability in the POTS environment. Specials and Trunk intervals are standard interval appointments of no greater than 24 hours. Standalone LNP historical data is not available in the maintenance systems (LMOS or WFA).

Calculation

Percentage of Missed Repair Appointments = $(a \div b) \times 100$

- a = Count of Customer Troubles Not Cleared by the Quoted Commitment Date and Time
- b = Total Trouble reports closed in Reporting Period

Report Structure

- · Dispatch/Non-Dispatch
- · CLEC Specific
- · CLEC Aggregate
- · BellSouth Aggregate

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report Month	Report Month
CLEC Company Name	BellSouth Company Code
Submission Date & Time (TICKET_ID)	Submission Date & Time
Completion Date (CMPLTN_DT)	Completion Date
Service Type (CLASS_SVC_DESC)	Service Type
 Disposition and Cause (CAUSE_CD & CAUSE_DESC) 	Disposition and Cause (Non-Design /Non-Special Only)
Geographic Scope	Trouble Code (Design and Trunking Services)
Note : Code in parentheses is the corresponding header found in the raw data file.	Geographic Scope

Version 1.00 4-1 Issue Date: December 1, 2002

M&R-1: Missed Repair Appointments



Tennessee Performance Measurements

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
Resale Residence	Retail Residence
Resale Business	Retail Business
Resale Design	Retail Design
Resale PBX	Retail PBX
Resale Centrex	Retail Centrex
Resale ISDN	Retail ISDN
2W Analog Loop Design	Retail Residence & Business Dispatch
2W Analog Loop Non – Design	Retail Residence & Business (POTS) (Exclusion of switch- based feature troubles
UNE Digital Loop < DS1	Retail Digital Loop < DS1
UNE Digital Loop ≥ DS1	Retail Digital Loop ≥ DS1
UNE Loop + Port Combinations	Retail Residence & Business
UNE Switch ports	Retail Residence & Business (POTS)
UNE Combo Other	Retail Residence, Business & Design Dispatch
UNE xDSL (HDSL, ADSL and UCL)	ADSL provided to Retail
• UNE ISDN	Retail ISDN – BRI
UNE Line Sharing	ADSL provided to Retail
UNE Other Design	Retail Design
UNE Other Non-Design	Retail Residence and Business
Local Interconnection Trunks	Parity with Retail
Local Transport (Unbundled Interoffice Transport)	Retail DS1/DS3 Interoffice

SEEM Measure

SEEM Measure		
Yes	Tier I	X
	Tier II	X

SEEM Disaggregation	SEEM Analog/Benchmark
Resale Residence	Retail Residence
Resale Business	Retail Business
Resale Design	Retail Design
Resale PBX	Retail PBX
Resale Centrex	Retail Centrex
Resale ISDN	Retail ISDN
2W Analog Loop Design	Retail Residence & Business Dispatch
2W Analog Loop Non – Design	Retail Residence & Business (POTS) (Exclusion of switch- based feature troubles
UNE Digital Loop < DS1	Retail Digital Loop < DS1



Tennessee Performance Measurements

SEEM Disaggregation	SEEM Analog/Benchmark
UNE Digital Loop ≥ DS1	Retail Digital Loop ≥ DS1
UNE Loop + Port Combinations	Retail Residence & Business
UNE Switch ports	Retail Residence & Business (POTS)
UNE Combo Other	Retail Residence, Business & Design Dispatch
UNE xDSL (HDSL, ADSL and UCL)	ADSL provided to Retail
UNE ISDN	Retail ISDN – BRI
UNE Line Sharing	ADSL provided to Retail
UNE Other Design	Retail Design
UNE Other Non-Design	Retail Residence and Business
Local Transport (Unbundled Interoffice Transport)	Retail DS1/DS3 Interoffice
Local Interconnection Trunks	Parity with Retail



M&R-2: Customer Trouble Report Rate

Definition

Initial and repeated customer direct or referred troubles reported within a calendar month per 100 lines/circuits in service.

Exclusions

- Trouble tickets canceled at the CLEC request.
- BellSouth trouble reports associated with internal or administrative service.
- Customer Provided Equipment (CPE) troubles or CLEC Equipment Trouble.

Business Rules

Customer Trouble Report Rate is computed by accumulating the number of maintenance initial and repeated trouble reports during the reporting period. The resulting number of trouble reports are divided by the total "number of service" lines, ports or combination that exist for the CLECs and BellSouth respectively at the end of the report month.

Calculation

Customer Trouble Report Rate = $(a \div b) \times 100$

- a = Count of Initial and Repeated Trouble Reports closed in the Current Period
- b = Number of Service Access Lines in service at End of the Report Period

Report Structure

- · CLEC Specific
- CLEC Aggregate
- · BellSouth Aggregate

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report Month CLEC Company Name Ticket Submission Date & Time (TICKET_ID) Ticket Completion Date (CMPLTN_DT) Service Type (CLASS_SVC_DESC) Disposition and Cause (CAUSE_CD & CAUSE_DESC) # Service Access Lines in Service at the end of period Geographic Scope Note: Code in parentheses is the corresponding header found in the raw data file.	 Report Month BellSouth Company Code Ticket Submission Date & Time Ticket Completion Date Service Type Disposition and Cause (Non-Design /Non-Special Only) Trouble Code (Design and Trunking Services) # Service Access Lines in Service at the end of period Geographic Scope

SQM Level of Disaggregation	SQM Analog/Benchmark
Resale Residence	Retail Residence
Resale Business	Retail Business
Resale Design	Retail Design
Resale PBX	Retail PBX
Resale Centrex	Retail Centrex
Resale ISDN	Retail ISDN
2W Analog Loop Design	Retail Residence & Business Dispatch

SQM Level of Disaggregation	SQM Analog/Benchmark
2W Analog Loop Non – Design	Retail Residence & Business (POTS) (Exclusion of switch- based feature troubles)
UNE Digital Loop < DS1	Retail Digital Loop < DS1
• UNE Digital Loop ≥ DS1	Retail Digital Loop ≥ DS1
UNE Loop + Port Combinations	Retail Residence & Business
UNE Switch Ports	Retail Residence & Business (POTS)
UNE Combo Other	Retail Residence, Business & Design Dispatch
UNE xDSL (HDSL, ADSL and UCL)	ADSL provided to Retail
• UNE ISDN	Retail ISDN – BRI
UNE Line Sharing	ADSL provided to Retail
UNE Other Design	Retail Design
UNE Other Non-Design	Retail Residence and Business
Local Interconnection Trunks	Parity with Retail
Local Transport (Unbundled Interoffice Transport)	Retail DS1/DS3 Interoffice

SEEM Measure

SEEM Measure		
Yes	Tier I	X
	Tier II	X

SEEM Disaggregation	SEEM Analog/Benchmark
Resale Residence	Retail Residence
Resale Business	Retail Business
Resale Design	Retail Design
Resale PBX	Retail PBX
Resale Centrex	Retail Centrex
Resale ISDN	Retail ISDN
2W Analog Loop Design	Retail Residence & Business Dispatch
2W Analog Loop Non – Design	Retail Residence & Business (POTS) (Exclusion of switch- based feature troubles)
UNE Digital Loop < DS1	Retail Digital Loop < DS1
UNE Digital Loop ≥ DS1	Retail Digital Loop ≥ DS1
UNE Loop + Port Combinations	Retail Residence & Business
UNE Switch ports	Retail Residence & Business (POTS)
UNE Combo Other	Retail Residence, Business & Design Dispatch
UNE xDSL (HDSL, ADSL and UCL)	ADSL provided to Retail
• UNE ISDN	Retail ISDN – BRI
UNE Line Sharing	ADSL provided to Retail
UNE Other Design	Retail Design



Tennessee Performance Measurements

SEEM Disaggregation SEEM Analog/Benchmark • UNE Other Non-Design • Retail Residence and Business • Local Transport (Unbundled Interoffice Transport) • Retail DS1/DS3 Interoffice • Local Interconnection Trunks • Parity with Retail



M&R-3: Maintenance Average Duration

Definition

The Average duration of Customer Trouble Reports from the receipt of the Customer Trouble Report to the time the trouble report is cleared.

Exclusions

- Trouble tickets canceled at the CLEC request.
- BellSouth trouble reports associated with internal or administrative service.
- Customer Provided Equipment (CPE) troubles or CLEC Equipment Trouble.

Business Rules

For Average Duration the clock starts on the date and time of the receipt of the correct report information, i.e. correct telephone number, correct circuit identification, trouble description, etc. for the repair request. The clock stops on the date and time the service is restored and the BellSouth or CLEC customer is notified (when the technician completes the trouble ticket on his/her CAT or work systems).

Calculation

Maintenance Duration = (a - b)

- a = Date and Time of Service Restoration
- b = Date and Time Trouble Ticket was Opened

Average Maintenance Duration = $(c \div d)$

- c = Total of all maintenance durations in the reporting period
- d = Total Closed Troubles in the reporting period

Report Structure

- · Dispatch/Non-Dispatch
- · CLEC Specific
- · CLEC Aggregate
- · BellSouth Aggregate

Data Retained

Relating to CLEC Experience:	Relating to BellSouth Performance:
Report month	Report month
Total Tickets (LINE_NBR)	Total Tickets
CLEC Company Name	BellSouth Company Code
Ticket Submission Date & Time (TICKET_ID)	Ticket Submission Date
Ticket Completion Date (CMPLTN_DT)	Ticket Submission Time
Service Type (CLASS_SVC_DESC)	Ticket Completion Date
 Disposition and Cause (CAUSE_CD & CAUSE_DESC) 	Ticket Completion Time
Geographic Scope	Total Duration Time
Note: Code in percepthogon in the corresponding header	Service Type
Note : Code in parentheses is the corresponding header	 Disposition and Cause (Non-Design /Non-Special Only)
found in the raw data file.	Trouble Code (Design and Trunking Services)
	Geographic Scope

SQM Level of Disaggregation	SQM Analog/Benchmark
Resale Residence	Retail Residence
Resale Business	Retail business

SQM Level of Disaggregation	SQM Analog/Benchmark
Resale Design	Retail Design
Resale PBX	Retail PBX
Resale Centrex	Retail Centrex
Resale ISDN	Retail ISDN
2W Analog Loop Design	Retail Residence & Business Dispatch
2W Analog Loop Non – Design	Retail Residence & Business (POTS) (Exclusion of switch-based feature troubles)
UNE Digital Loop < DS1	Retail Digital Loop < DS1
UNE Digital Loop ≥ DS1	Retail Digital Loop ≥ DS1
UNE Loop + Port Combinations	Retail Residence & Business
UNE Switch ports	Retail Residence & Business (POTS)
UNE Combo Other	Retail Residence, Business & Design Dispatch
UNE xDSL (HDSL, ADSL and UCL)	ADSL provided to Retail
UNE ISDN	Retail ISDN – BRI
UNE Line Sharing	ADSL provided to Retail
UNE Other Design	Retail Design
UNE Other Non-Design	Retail Residence and Business
Local Transport (Unbundled Interoffice Transport)	Retail DS1/DS3 Interoffice
Local Interconnection Trunks	Parity with Retail

SEEM Measure

SEEM Measure		
Yes	Tier I	X
	Tier II	X

SEEM Disaggregation	SEEM Analog/Benchmark
Resale Residence	Retail Residence
Resale Business	Retail Business
Resale Design	Retail Design
Resale PBX	Retail PBX
Resale Centrex	Retail Centrex
Resale ISDN	Retail ISDN
2W Analog Loop Design	Retail Residence & Business Dispatch
2W Analog Loop Non – Design	Retail Residence & Business (POTS) (Exclusion of switch- based feature troubles)
UNE Digital Loop < DS1	Retail Digital Loop < DS1
UNE Digital Loop ≥ DS1	Retail Digital Loop ≥ DS1
UNE Loop + Port Combinations	Retail Residence & Business
UNE Switch ports	Retail Residence & Business (POTS)



Tennessee Performance Measurements

SEEM Disaggregation	SEEM Analog/Benchmark
UNE Combo Other	Retail Residence, Business & Design Dispatch
UNE xDSL (HDSL, ADSL and UCL)	ADSL provided to Retail
• UNE ISDN	Retail ISDN – BRI
UNE Line Sharing	ADSL provided to Retail
UNE Other Design	Retail Design
UNE Other Non-Design	Retail Residence and Business
Local Transport (Unbundled Interoffice Transport)	Retail DS1/DS3 Interoffice
Local Interconnection Trunks	Parity with Retail



M&R-4: Percent Repeat Troubles within 30 Days

Definition

Closed trouble reports on the same line/circuit as a previous trouble report received within 30 calendar days as a percent of total troubles closed reported

Exclusions

- Trouble tickets canceled at the CLEC request.
- BellSouth trouble reports associated with internal or administrative service.
- Customer Provided Equipment (CPE) troubles or CLEC Equipment Trouble.

Business Rules

Includes Customer trouble reports received within 30 days of an original Customer trouble report

Calculation

Percent Repeat Troubles within 30 Days = $(a \div b) \times 100$

- a = Count of closed Customer Troubles where more than one trouble report was logged for the same service line within a continuous 30 days
- b = Total Trouble Reports Closed in Reporting Period

Report Structure

- · Dispatch/Non-Dispatch
- CLEC Specific
- · CLEC Aggregate
- · BellSouth Aggregate

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report month	Report month
Total Tickets (LINE_NBR)	Total Tickets
CLEC Company Name	BellSouth Company Code
Ticket Submission Date & Time (TICKET_ID)	Ticket Submission Date
Ticket Completion Date (CMPLTN_DT)	Ticket Submission Time
Total and Percent Repeat Trouble Reports within 30 Days	Ticket Completion Date
(TOT_REPEAT)	Ticket Completion Time
Service Type	Total and Percent Repeat Trouble Reports within 30 Days
 Disposition and Cause (CAUSE_CD & CAUSE_DESC) 	Service Type
Geographic Scope	Disposition and Cause (Non-Design /Non-Special Only)
Note : Code in parentheses is the corresponding header found in the raw data file.	 Trouble Code (Design and Trunking Services) Geographic Scope

SQM Level of Disaggregation	SQM Analog/Benchmark
Resale Residence	Retail Residence
Resale Business	Retail business
Resale Design	Retail Design
Resale PBX	Retail PBX
Resale Centrex	Retail Centrex

BELLSOUTH®

SQM Level of Disaggregation	SQM Analog/Benchmark
Resale ISDN	Retail ISDN
2W Analog Loop Design	Retail Residence & Business Dispatch
2W Analog Loop Non – Design	Retail Residence & Business (POTS) (Exclusion of switch-based feature troubles)
UNE Digital Loop < DS1	Retail Digital Loop < DS1
UNE Digital Loop ≥ DS1	Retail Digital Loop ≥ DS1
UNE Loop + Port Combinations	Retail Residence & Business
UNE Switch ports	Retail Residence & Business (POTS)
UNE Combo Other	Retail Residence, Business & Design Dispatch
UNE xDSL (HDSL, ADSL and UCL)	ADSL provided to Retail
• UNE ISDN	Retail ISDN – BRI
UNE Line Sharing	ADSL provided to Retail
UNE Other Design	Retail Design
UNE Other Non-Design	Retail Residence and Business
Local Transport (Unbundled Interoffice Transport)	Retail DS1/DS3 Interoffice
Local Interconnection Trunks	Parity with Retail

SEEM Measure

SEEM Measure		
Yes	Tier I	X
	Tier II	X

SEEM Disaggregation	SEEM Analog/Benchmark
Resale Residence	Retail Residence
Resale Business	Retail Business
Resale Design	Retail Design
Resale PBX	Retail PBX
Resale Centrex	Retail Centrex
Resale ISDN	Retail ISDN
2W Analog Loop Design	Retail Residence & Business Dispatch
2W Analog Loop Non – Design	Retail Residence & Business (POTS) (Exclusion of switch- based feature troubles)
UNE Digital Loop < DS1	Retail Digital Loop < DS1
UNE Digital Loop ≥ DS1	Retail Digital Loop ≥ DS1
UNE Loop + Port Combinations	Retail Residence & Business
UNE Switch ports	Retail Residence & Business (POTS)
UNE Combo Other	Retail Residence, Business & Design Dispatch
UNE xDSL (HDSL, ADSL and UCL)	ADSL provided to Retail
• UNE ISDN	Retail ISDN – BRI



Tennessee Performance Measurements

SEEM Disaggregation	SEEM Analog/Benchmark
UNE Line Sharing	ADSL provided to Retail
UNE Other Design	Retail Design
UNE Other Non-Design	Retail Residence and Business
Local Transport (Unbundled Interoffice Transport)	Retail DS1/DS3 Interoffice
Local Interconnection Trunks	Parity with Retail



M&R-5: Out of Service (OOS) > 24 Hours

Definition

For Out of Service Troubles (no dial tone, cannot be called or cannot call out) the percentage of Total OOS Troubles cleared in excess of 24 hours. (All design services are considered to be out of service).

Exclusions

- Trouble Reports canceled at the CLEC request
- · BellSouth Trouble Reports associated with administrative service
- Customer Provided Equipment (CPE) Troubles or CLEC Equipment Troubles.

Business Rules

Customer Trouble reports that are out of service and cleared in excess of 24 hours. The clock begins when the trouble report is created in LMOS/WFA and the trouble is counted if the elapsed time exceeds 24 hours.

Calculation

Out of Service (OOS) > 24 hours = $(a \div b) \times 100$

- a = Total Cleared Troubles OOS > 24 Hours
- b = Total OOS Troubles in Reporting Period

Report Structure

- · Dispatch/Non-Dispatch
- CLEC Specific
- · BellSouth Aggregate
- · CLEC Aggregate

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report Month Total Tickets CLEC Company Name Ticket Submission Date & Time (TICKET_ID) Ticket Completion Date (CMPLTN_DT Percentage of Customer Troubles out of Service > 24 Hours (OOS>24_FLAG) Service type (CLASS_SVC_DESC) Disposition and Cause (CAUSE_CD & CAUSE-DESC) Geographic Scope	 Report Month Total Tickets BellSouth Company Code Ticket Submission Date Ticket Submission time Ticket Completion Date Ticket Completion Time Percent of Customer Troubles out of Service > 24 Hours Service type Disposition and Cause (Non-Design/Non-Special only)
Note: Code in parentheses is the corresponding header found in the raw data file.	 Trouble Code (Design and Trunking Services) Geographic Scope

SQM Level of Disaggregation	SQM Analog/Benchmark
Resale Residence	Retail Residence
Resale Business	Retail Business
Resale Design	Retail Design
Resale PBX	Retail PBX
Resale Centrex	Retail Centrex

BELLSOUTH®

SQM Level of Disaggregation	SQM Analog/Benchmark
Resale ISDN	Retail ISDN
2W Analog Loop Design	Retail Residence & Business Dispatch
2W Analog Loop Non – Design	Retail Residence & Business (POTS) (Exclusion of switch- based feature troubles)
UNE Digital Loop < DS1	Retail Digital Loop < DS1
UNE Digital Loop ≥ DS1	Retail Digital Loop ≥ DS1
UNE Loop + Port Combinations	Retail Residence & Business
UNE Switch ports	Retail Residence & Business (POTS)
UNE Combo Other	Retail Residence, Business & Design Dispatch
UNE xDSL (HDSL, ADSL and UCL)	ADSL provided to Retail
UNE ISDN	Retail ISDN – BRI
UNE Line Sharing	ADSL provided to Retail
UNE Other Design	Retail Design
UNE Other Non-Design	Retail Residence and Business
Local Transport (Unbundled Interoffice Transport)	Retail DS1/DS3 Interoffice
Local Interconnection Trunks	Parity with Retail

SEEM Measure

SEEM Measure		
Yes	Tier I	X
	Tier II	X

SEEM Disaggregation	SEEM Analog/Benchmark
Resale Residence	Retail Residence
Resale Business	Retail Business
Resale Design	Retail Design
• Resale PBX	Retail PBX
Resale Centrex	Retail Centrex
Resale ISDN	Retail ISDN
2W Analog Loop Design	Retail Residence & Business Dispatch
• 2W Analog Loop Non – Design	Retail Residence & Business (POTS) (Exclusion of switch- based feature troubles)
UNE Digital Loop < DS1	Retail Digital Loop < DS1
• UNE Digital Loop ≥ DS1	• Retail Digital Loop ≥ DS1
UNE Loop + Port Combinations	Retail Residence & Business
UNE Switch Ports	Retail Residence & Business (POTS)
UNE Combo Other	Retail Residence, Business & Design Dispatch
UNE xDSL (HDSL, ADSL and UCL)	ADSL provided to Retail
• UNE ISDN	Retail ISDN – BRI



Tennessee Performance Measurements

SEEM Disaggregation SEEM Analog/Benchmark • UNE Line Sharing • ADSL provided to Retail • UNE Other Design • Retail Design • UNE Other Non-Design • Retail Residence and Business • Local Transport (Unbundled Interoffice Transport) • Retail DS1/DS3 Interoffice • Local Interconnection Trunks • Parity with Retail



M&R-6: Average Answer Time – Repair Centers

Definition

This report measures the average time a customer is in queue.

Exclusions

None

Business Rules

The clock starts when a CLEC Representative or BellSouth customer makes a choice on the Repair Center's menu and is put in queue for the next repair attendant. The clock stops when the repair attendant answers the call (abandoned calls are not included).

Note: The Total Column is a combined BellSouth Residence and Business number.

Calculation

Answer Time for BellSouth Repair Centers = (a - b)

- a = Time BellSouth Repair Attendant Answers Call
- b = Time of entry into queue after ACD Selection

Average Answer Time for BellSouth Repair Centers = $(c \div d)$

- c = Sum of all Answer Times
- d = Total number of calls by reporting period

Report Structure

- CLEC Aggregate
- · BellSouth Aggregate

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
CLEC Average Answer Time	BellSouth Average Answer Time

SQM Disaggregation - Analog / Benchmark

SQM Level of Disaggregation	Retail Analog / Benchmark
Region. CLEC/BellSouth Service Centers and BellSouth Repair Centers are regional.	For CLEC, Average Answer Times in UNE Center and BRMC are comparable to the Average Answer Times in the BellSouth Repair Centers.

SEEM Measure

SEEM Measure		
No	Tier I	
	Tier II	

SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable



M&R-7: Mean Time To Notify CLEC of Network Outages

Definition

BellSouth will inform the CLEC of any Network outages (key customer accounts)

Exclusions

None

Business Rules

The time it takes for BellSouth to notify the CLEC and appropriate BellSouth personnel of a customer impacting network incident in equipment that may be utilized by the CLEC. When BellSouth becomes aware of a network incident, the CLEC and appropriate BellSouth personnel will be notified electronically. The notification time for each outage will be measured in minutes and divided by the number of outages for the reporting period. The CLECs will be notified the same way and at the same time as BellSouth personnel. These are broadcast messages. It is up to those receiving the message to determine if they have customers affected by the incident.

Calculation

Time to Notify CLEC = (a - b)

- a = Date and Time BellSouth Notified CLEC
- b = Date and time BellSouth detected network incident

Mean Time to Notify CLEC = $(c \div d)$

- c = Sum of all Times to Notify CLEC
- d = Count of Network Incidents

Report Structure

- · BellSouth Aggregate
- · CLEC Aggregate
- · CLEC Specific

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report Month	Report Month
Major Network Events	Major Network Events
• Date/Time of Incident	Date/Time of Incident
Date/Time of Notification	Date/Time of Notification

SQM Disaggregation - Analog / Benchmark

SQM Level of Disaggregation	Retail Analog / Benchmark
BellSouth AggregateCLEC AggregateCLEC Specific	Parity by Design

SEEM Measure

SEEM Measure			
No	Tier I		
	Tier II		



Tennessee Performance Measurements

SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable



Section 5: Billing

B-1: Invoice Accuracy

Definition

This measure provides the percentage of accuracy of the billing invoices rendered to CLECs during the current month.

Exclusions

- Adjustments not related to billing errors (e.g., credits for service outage, special promotion credits, adjustments to satisfy the customer)
- · Test Accounts

Business Rules

The accuracy of billing invoices delivered by BellSouth to the CLEC must enable them to provide a degree of billing accuracy comparative to BellSouth bills rendered to retail customers of BellSouth. CLECs request adjustments on bills determined to be incorrect. The BellSouth Billing verification process includes manually analyzing a sample of local bills from each bill period. The bill verification process draws from a mix of different customer billing options and types of service. An end-to-end auditing process is performed for new products and services. Internal measurements and controls are maintained on all billing processes. The CLEC-specific raw data file (which is available on the PMAP web site) will contain the number of bills and adjustments for the reporting month. The number of bills and bill adjustments will be displayed by OCN and/or ACNA.

Calculation

Invoice Accuracy = $[(a - b) \div a] \times 100$

- a = Absolute Value of Total Billed Revenues during current month
- b = Absolute Value of Billing Related Adjustments during current month

Measure of Adjustments = $[(c-d)/c] \times 100$

- c = Number of Bills in current month
- d= Number of Billing-related Adjustments in current month

Report Structure

- · CLEC Specific
- CLEC Aggregate
- · BellSouth Aggregate
- · Geographic Scope
 - Region
 - State

Version 1.00 5-1 Issue Date: December 1, 2002

BELLSOUTH®

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
 Report Month Invoice Type UNE Resale Interconnection Total Billed Revenue Billing Related Adjustments Number of Bills Number of Adjustments 	 Report Month Retail Type CRIS CABS Total Billed Revenue Billing Related Adjustments

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
Product/Invoice Type Resale	Parity with BellSouth Retail Aggregate
- UNE - Interconnection	

SEEM Measure

SEEM Measure		
Yes	Tier I	X
	Tier II	X

SEEM Disaggregation	SEEM Analog/Benchmark
• Resale • UNE	Parity with Retail
Interconnection	



B-2: Mean Time to Deliver Invoices

Definition

Bill Distribution is calculated as follows: CRIS BILLS-The number of workdays is reported for CRIS bills. This is calculated by counting the Bill Period date as the first work day. Weekends and holidays are excluded when counting workdays. J/N Bills are counted in the CRIS work day category for the purposes of the measurement since their billing account number (Q account) is provided from the CRIS system.

CABS BILLS-The number of calendar days is reported for CABS bills. This is calculated by counting the day following the Bill Period date as the first calendar day. Weekends and holidays are included when counting the calendar days.

Exclusions

None

Business Rules

This report measures the mean interval for timeliness of billing records delivered to CLECs in an agreed upon format. CRIS-based invoices are measured in business days, and CABS-based invoices in calendar days.

Calculation

Invoice Timeliness = (a - b)

- a = Invoice Transmission Date
- b = Close Date of Scheduled Bill Cycle

Mean Time To Deliver Invoices = $(c \div d)$

- c = Sum of all Invoice Timeliness intervals
- d = Count of Invoices Transmitted in Reporting Period

Report Structure

- · CLEC Specific
- · CLEC Aggregate
- · BellSouth Aggregate
- · Geographic Scope
 - Region
 - State

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report Month Invoice Type	Report Month Invoice Type
- UNE - Resale	- CRIS - CABS
- Interconnection - State	Invoice Transmission CountDate of Scheduled Bill Close
Invoice Transmission CountDate of Scheduled Bill Close	

BELLSOUTH®

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
Product/Invoice Type Resale UNE Interconnection State	 CRIS-based invoices will be released for delivery within six (6) business days. CABS-based invoices will be released for delivery within eight (8) calendar days. CLEC Average Delivery Intervals for both CRIS and CABS Invoices are comparable to BellSouth Average delivery for both systems.

SEEM Measure

SEEM Measure		
Yes	Tier I	X
	Tier II	X

SEEM Disaggregation	SEEM Analog/Benchmark
CLEC StateCRISCABSBST-State	Parity with Retail



B-3: Usage Data Delivery Accuracy

Definition

This measurement captures the percentage of recorded usage that is delivered error free and in an acceptable format to the appropriate Competitive Local Exchange Carrier (CLEC). These percentages will provide the necessary data for use as a comparative measurement for BellSouth performance. This measurement captures Data Delivery Accuracy rather than the accuracy of the individual usage recording.

Exclusions

None

Business Rules

The accuracy of the data delivery of usage records delivered by BellSouth to the CLEC must enable them to provide a degree of accuracy comparative to BellSouth bills rendered to their retail customers. If errors are detected in the delivery process, they are investigated, evaluated and documented. Errors are corrected and the data retransmitted to the CLEC.

Calculation

Usage Data Delivery Accuracy (Packs) = $(a - b) \div a \times 100$ (This calculation not ordered by the FPSC)

- a = Total number of usage data packs sent during current month
- b = Total number of usage data packs requiring retransmission during current month

Usage Data Delivery Accuracy (Records) = $(c - d) \div c \times 100$

- c = Total number of usage records sent during current month
- d = Total number of usage records requiring retransmission during current month

Report Structure

- · CLEC Aggregate
- · BellSouth Aggregate
- · Geographic Scope
 - Region

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report Month	Report Month
Record Type	Record Type
- BellSouth Recorded	Number of Records
- Non-BellSouth Recorded	• Packs
Number of Records	
• Packs	

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
• Region	Parity With Retail

SEEM Measure

SEEM Measure		
Yes	Tier I	
	Tier II	X



	SEEM Disaggregation	SEEM Analog/Benchmark
•	CLEC State (In Tennessee, SEEM is based on records.)BellSouth Region	Parity with Retail



B-4: Usage Data Delivery Completeness

Definition

This measurement provides percentage of complete and accurately recorded usage data (usage recorded by BellSouth and usage recorded by other companies and sent to BellSouth for billing) that is processed and transmitted to the CLEC within thirty (30) days of the message recording date. A parity measure is also provided showing completeness of BellSouth messages processed and transmitted via CMDS. BellSouth delivers its own retail usage from recording location to billing location via CMDS as well as delivering billing data to other companies. Timeliness, Completeness and Mean Time to Deliver Usage measures are reported on the same report.

Exclusions

None

Business Rules

The purpose of these measurements is to demonstrate the level of quality of usage data delivered to the appropriate CLEC. Method of delivery is at the option of the CLEC.

Calculation

Usage Data Delivery Completeness = $(a \div b) \times 100$

- a = Total number of Recorded usage records delivered during current month that are within thirty (30) days of the message recording
 date
- b = Total number of Recorded usage records delivered during the current month

Report Structure

- · CLEC Specific
- · CLEC Aggregate
- · BellSouth Aggregate
- Region

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
 Report Month Record Type BellSouth Recorded Non-BellSouth Recorded 	Report Month Record Type

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
• Region	Parity With Retail

SEEM Measure

SEEM Measure		
No	Tier I	
	Tier II	



SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable



B-5: Usage Data Delivery Timeliness

Definition

This measurement provides a percentage of recorded usage data (usage recorded by BellSouth and usage recorded by other companies and sent to BellSouth for billing) that is delivered to the appropriate CLEC within six (6) calendar days from the receipt of the initial recording. A parity measure is also provided showing timeliness of BellSouth messages processed and transmitted via CMDS. Timeliness, Completeness and Mean Time to Deliver Usage measures are reported on the same report.

Exclusions

None

Business Rules

The purpose of this measurement is to demonstrate the level of timeliness for processing and transmission of usage data delivered to the appropriate CLEC. The usage data will be mechanically transmitted or mailed to the CLEC data processing center once daily. The Timeliness interval of usage recorded by other companies is measured from the date BellSouth receives the records to the date BellSouth distributes to the CLEC. Method of delivery is at the option of the CLEC

Calculation

Usage Data Delivery Timeliness Current month = $(a \div b) \times 100$

- a = Total number of usage records sent within six (6) calendar days from initial recording/receipt
- b = Total number of usage records sent

Report Structure

- · CLEC Aggregate
- CLEC Specific
- · BellSouth Aggregate
- Region

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report Month Record Type BellSouth Recorded Non-BellSouth Recorded	Report Month Record Type

SQM Level of Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
• Region	Parity with Retail

SEEM Measure

SEEM Measure		
No	Tier I	
	Tier II	



SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable



B-6: Mean Time to Deliver Usage

Definition

This measurement provides the average time it takes to deliver Usage Records to a CLEC. A parity measure is also provided showing timeliness of BellSouth messages processed and transmitted via CMDS. Timeliness, Completeness and Mean Time to Deliver Usage measures are reported on the same report.

Exclusions

None

Business Rules

The purpose of this measure is to calculate the average number of days it takes BellSouth to deliver usage data to the appropriate CLEC. The calculation reflects the differences between the date the data is transmitted or mailed to the CLEC and the date the data is generated by Customer divided by the total record volume delivery.

Each delivery record is calculated as the time, in days, between when the customer generates the call and when BellSouth delivers the usage data to the CLEC. Each delivery record is categorized by the resulting number of days.

An estimated interval is calculated for each category by taking the total number of usage data records delivered for that period and multiplying it by the total number of days in that period. The mean (average) time to deliver the usage data is calculated by summing all estimated intervals and dividing by the total number of records delivered.

Note: Any usage record falling in the 30+ day interval will be added using an average figure of 31.5 days.

Usage data is mechanically transmitted or mailed to the CLEC data processing center once daily. Method of delivery is at the option of the CLEC.

Calculation

Delivery Interval Record = (a - b)

- a = Date BellSouth delivers the usage data
- b = Date usage data is generated by the customer

Estimated Interval = (c X d)

- c = Number of records delivered in each category
- d = Number of days to deliver for the category

Mean Time to Deliver Usage = $(e \div f)$

- e = Sum of all estimated intervals
- f = Total number of records delivered

Report Structure

- CLEC Aggregate
- · CLEC Specific
- · BellSouth Aggregate
- · Region

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report Month	Report Month
Record Type	Record Type
- BellSouth Recorded	
- Non-BellSouth Recorded	

BELLSOUTH®

SQM Level of Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
• Region	Parity With Retail

SEEM Measure

SEEM Measure		
No	Tier I	
	Tier II	

SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable



B-7: Recurring Charge Completeness

Definition

This measure captures percentage of fractional recurring charges appearing on the correct bill.

Exclusions

None

Business Rules

The effective date of the recurring charge must be within 30 days of the bill date for the charge to appear on the correct bill.

Calculation

Recurring Charge Completeness = $(a \div b) \times 100$

- a = Count of fractional recurring charges that are on the correct bill¹
- b = Total count of fractional recurring charges that are on the correct bill

Report Structure

- · CLEC Specific
- · CLEC Aggregate
- · BellSouth Aggregate

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report month	Report month
Invoice Type	Retail Analog
Total Recurring Charges Billed	Total recurring charges billed
Total Billed On Time	Total Billed On Time

SQM Level of Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
Product/Invoice Type	
Resale	Parity
• UNE	Benchmark 90%
Interconnection	Benchmark 90%

SEEM Measure

SEEM Measure		
No	Tier I	
	Tier II	

SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable

¹Correct bill = next available bill



B-8: Non-Recurring Charge Completeness

Definition

This measure captures percentage of non-recurring charges appearing on the correct bill.

Exclusions

None

Business Rules

The effective date of the non-recurring charge must be within 30 days of the bill date for the charge to appear on the correct bill.

Calculation

Non-Recurring Charge Completeness = $(a \div b) \times 100$

- a = Count of non-recurring charges that are on the correct bill¹
- b = Total count of non-recurring charges that are on the correct bill

Report Structure

- · CLEC Specific
- · CLEC Aggregate
- · BellSouth Aggregate

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report month	Report month
Invoice type	Retail Analog
Total non-recurring charges billed	Total non-recurring charges billed
Total billed on time	Total billed on time

SQM Level of Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
Product/Invoice Type	
Resale	Parity
• UNE	Benchmark 90%
Interconnection	Benchmark 90%

SEEM Measure

SEEM Measure		
No	Tier I	
	Tier II	

SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable

¹Correct bill = next available bill



B-9: Percent Daily Usage Feed Errors Corrected in X Business Days

Definition

Measures the timely correction of Daily Usage Feed (DUF) errors in record information and Pack formats measured separately. Errors included (1) Pack Failure errors and (2) EMI content errors in records.

Exclusions

- Usage that cannot be corrected and resent or usage that the CLEC doesn't want Retransmitted.
- CLEC Problem/Issue/File Retransmission forms disputed by BellSouth SMEs that do not result in an EMI error.
- CLEC notification received by BellSouth > 10 business days from transmission date of errored messages or packs.

Business Rules

This measure will provide the % of errors corrected in X Business days.

Pack Failure errors are defined as a DUF header/trailer error containing one or more of the following conditions: Grand total records not equal to records in pack or sequence/invoice numbers for a from RAO is not sequential

EMI content errors are defined as those records with errors contained in the EMI detail records that cause a message to be unbillable by the CLEC

Only notification received via the CLEC Problem/Issue/File Retransmission form will be included in this measure. To locate the form, go to the PMAP web site (http://www.pmap.bellsouth.com/) and click the Documentation Downloads link, then select the "CLEC Problem/Issue/File Retransmission form."

When circumstances arise for multiple content errors it is not necessary for the form to be filled out in its entirety, the CLECs agree to provide sufficient information for content error research so that a thorough investigation and resolution can be completed.

For each type error condition, a new CLEC Problem/Issue/File Retransmission form should be submitted.

EMI content errors should be attached in a separate file from the CLEC Problem/Issue/File Retransmission form

Elapsed time is measured in business days.

The clock starts when BellSouth receives CLEC's Problem/Issue/File Retransmission form.

The clock stops when BellSouth provides the corrected usage to the CLEC using the predesignated DUF delivery method.

This measure applies only to CLECs that are ODUF and ADUF participants

Calculation

Timeliness of Daily Usage EMI Content Errors Corrected = $(a \div b) \times 100$

- a = Total number of Daily Usage Records with EMI Content Errors Corrected in the reporting month within 10 Business Days.
- b = Total number of Daily Usage Records with EMI Content Errors corrected in reporting month.

Timeliness of Daily Usage Pack Format Errors Corrected = $(c \div d) \times 100$

- c= Total number of Daily Usage Packs with Format Errors Corrected in the reporting month within 4 Business Days.
- d = Total number of Daily Usage Packs with Format Errors corrected in reporting month

Report Structure

- · CLEC Specific
 - Total number of BST disputed Daily Usage Records with EMI Content Errors received in reporting month.
 - Total number of Daily Usage Records with EMI Content Errors received in reporting month.
 - Total number of BST disputed Daily Usage Packs with Format Errors received in reporting month
 - Total number of Daily Usage Packs with Format Errors received in reporting month
- · CLEC Aggregate
- · Geographic Scope
 - Region

(A) BELLSOUTH®

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report monthBellSouth RecordedNon-BellSouth Recorded	• None

SQM Level of Disaggregation - Analog/Benchmark

SQM Level of Disaggre	gation	SQM Analog/Benchmark
• Region	•	Diagnostic

SEEM Measure

SEEM Measure				
No	Tier I			
	Tier II			

SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable



B-10: Percent Billing Errors Corrected in X Days

Definition

Measures timely carrier bill adjustments.

Exclusions

Billing adjustments requests that are rejected by BellSouth or disputed by BellSouth.

Adjustments that are initiated by BellSouth.

Business Rules

This measure applies to CLEC wholesale bill adjustments. IXC Access billing adjustment requests are not reflected in this measure. Elapsed time is measured in business days. Clock starts when BellSouth receives the ALECs Billing Adjustment Request (BAR) form (BAR form and instructions found at WWW.interconnection.bellsouth.com/forms/html/billing & collections.html) and the clock stops when adjustments is made to bill through ACATS or BOCRIS (generally next CLEC bill unless adjustment request after middle of the month). BellSouth will report separately those adjustment requests that are disputed by BellSouth.

Calculation

Percent Billing Errors Corrected in 45 Days = (a / b) X 100

- a = Number of BellSouth Adjustments in 45 Days
- b = Total Number of Adjustment Requests in Reporting Period

Report Structure

- · CLEC Specific
- · CLEC Aggregate
- Geographic Scope:
- · State Specific

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
 Number of BellSouth Adjustments in 45 days Total number of Billing Adjustment Requests in Reporting Period Number of Adjustments disputed by BellSouth (reported separately) 	• None

SQM Disaggregation - Retail Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
• State	Diagnostic

SEEM Measure

SEEM Measure				
No	Tier I			
	Tier II			

BELLSOUTH®

SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable



Section 6: Operator Services And Directory Assistance

OS-1: Speed to Answer Performance/Average Speed to Answer - Toll

Definition

Measurement of the average time in seconds calls wait before answered by a toll operator.

Exclusions

None

Business Rules

The clock starts when the customer enters the queue and the clock stops when a BellSouth representative answers the call or the customer abandons the call. The length of each call is determined by measuring, using a scanning technique, and accumulating the elapsed time from the entry of a customer call into the BellSouth call management system queue until the customer call is abandoned or transferred to BellSouth personnel assigned to handle calls for assistance. The system makes no distinction between CLEC customers and BellSouth customers.

Calculation

Speed to Answer Performance/Average Speed to Answer – Toll = $a \div b$

- a = Total queue time
- b = Total calls answered

Note: Total queue time includes time that answered calls wait in queue as well as time abandoned calls wait in queue prior to abandonment.

Report Structure

- Reported for the aggregate of BellSouth and CLECs
 - State

Data Retained (on Aggregate Basis)

- For the items below, BellSouth's Performance Measurement Analysis Platform (PMAP) receives a final computation; therefore, no raw data file is available in PMAP
- Month
- Call Type (Toll)
- Average Speed of Answer

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
• None	Parity by Design

Version 1.00 6-1 Issue Date: December 1, 2002



SEEM Measure

SEEM Measure		
No	Tier I	
	Tier II	

SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable



OS-2: Speed to Answer Performance/Percent Answered with "X" Seconds – Toll

Definition

Measurement of the percent of toll calls that are answered in less than ten seconds

Exclusions

None

Business Rules

The clock starts when the customer enters the queue and the clock stops when a BellSouth representative answers the call or the customer abandons the call. The length of each call is determined by measuring, using a scanning technique, and accumulating the elapsed time from the entry of a customer call into the BellSouth call management system queue until the customer call is abandoned or transferred to BellSouth personnel assigned to handle calls for assistance. The system makes no distinction between CLEC customers and BellSouth customers.

Calculation

The Percent Answered within "X" Seconds measurement for toll is derived by using the BellCore Statistical Answer Conversion Tables, to convert the Average Speed to Answer measure into a percent of calls answered within "X" seconds. The BellCore Conversion Tables are specific to the defined parameters of work time, number of operators, max queue size and call abandonment rates.

Report Structure

- Reported for the aggregate of BellSouth and CLECs
 - State

Data Retained (on Aggregate Basis)

- For the items below, BellSouth's Performance Measurement Analysis Platform (PMAP) receives a final computation; therefore, no raw data file is available in PMAP
- · Month
- Call Type (Toll)
- · Average Speed of Answer

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation:	SQM Analog/Benchmark
• None	Parity by Design

SEEM Measure

SEEM Measure		
No	Tier I	
	Tier II	

SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable



DA-1: Speed to Answer Performance/Average Speed to Answer – Directory Assistance (DA)

Definition

Measurement of the average time in seconds calls wait before answered by a DA operator.

Exclusions

None

Business Rules

The clock starts when the customer enters the queue and the clock stops when a BellSouth representative answers the call or the customer abandons the call. The length of each call is determined by measuring, using a scanning technique, and accumulating the elapsed time from the entry of a customer call into the BellSouth call management system queue until the customer call is abandoned or transferred to BellSouth personnel assigned to handle calls for assistance. The system makes no distinction between CLEC customers and BellSouth customers.

Calculation

Speed to Answer Performance/Average Speed to Answer – Directory Assistance (DA) = $a \div b$

- a = Total queue time
- b = Total calls answered

Note: Total queue time includes time that answered calls wait in queue as well as time abandoned calls wait in queue prior to abandonment.

Report Structure

- Reported for the aggregate of BellSouth and CLECs
 - State

Data Retained (on Aggregate Basis)

- For the items below, BellSouth's Performance Measurement Analysis Platform (PMAP) receives a final computation; therefore, no raw data file is available in PMAP
- Month
- Call Type (DA)
- Average Speed of Answer

SQM Level of Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
• None	Parity by Design

SEEM Measure

SEEM Measure		
No	Tier I	
	Tier II	

SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable



DA-2: Speed to Answer Performance/Percent Answered within "X" Seconds – Directory Assistance (DA)

Definition

Measurement of the percent of DA calls that are answered in less than twelve seconds.

Exclusions

None

Business Rules

The clock starts when the customer enters the queue and the clock stops when a BellSouth representative answers the call or the customer abandons the call. The length of each call is determined by measuring, using a scanning technique, and accumulating the elapsed time from the entry of a customer call into the BellSouth call management system queue until the customer call is abandoned or transferred to BellSouth personnel assigned to handle calls for assistance. The system makes no distinction between CLEC customers and BellSouth customers.

Calculation

The Percent Answered within "X" Seconds measurement for DA is derived by using the BellCore Statistical Answer Conversion Tables, to convert the Average Speed to Answer measure into a percent of calls answered within "X" seconds. The BellCore Conversion Tables are specific to the defined parameters of work time, number of operators, max queue size and call abandonment rates.

Report Structure

- Reported for the aggregate of BellSouth and CLECs
 - State

Data Retained (on Aggregate Basis)

- For the items below, BellSouth's Performance Measurement Analysis Platform (PMAP) receives a final computation; therefore, no raw data file is available in PMAP.
- · Month
- Call Type (DA)
- · Average Speed of Answer

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
• None	Parity by Design

SEEM Measure

SEEM Measure		
No	Tier I	
	Tier II	

SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable



Section 7: Database Update Information

D-1: Average Database Update Interval

Definition

This report measures the interval from receipt of the database change request to the completion of the update to the database for Line Information Database (LIDB), Directory Assistance and Directory Listings.

Exclusions

- Updates Canceled by the CLEC
- Initial update when supplemented by CLEC
- · BellSouth updates associated with internal or administrative use of local services.

Business Rules

The interval for this measure begins with the date and time stamp when a service order is completed and the completion notice is released to all systems to be updated with the order information including Directory Assistance, Directory Listings, and Line Information Database (LIDB). The end time stamp is the date and time of completion of updates to the system.

For BellSouth Results:

The BellSouth computation is identical to that for the CLEC with the clarifications noted below.

Other Clarifications and Qualification:

- For LIDB, the elapsed time for a BellSouth update is measured from the point in time when the BellSouth file maintenance process makes the LIDB update information available until the date and time reported by BellSouth that database updates are completed.
- Results for the CLECs are captured and reported at the update level by Reporting Dimension (see below).
- The Completion Date is the date upon which BellSouth issues the Update Completion Notice to the CLEC.
- If the CLEC initiates a supplement to the originally submitted update and the supplement reflects changes in customer requirements (rather than responding to BellSouth initiated changes), then the update submission date and time will be the date and time of BellSouth receipt of a syntactically correct update supplement. Update activities responding to BellSouth initiated changes will not result in changes to the update submission date and time used for the purposes of computing the update completion interval.
- · Elapsed time is measured in hours and hundredths of hours rounded to the nearest tenth of an hour.
- Because this should be a highly automated process, the accumulation of elapsed time continues through off-schedule, weekends and holidays; however, scheduled maintenance windows are excluded.

Calculation

Update Interval = (a - b)

- a = Completion Date & Time of Database Update
- b = Submission Date and Time of Database Change

Average Update Interval = $(c \div d)$

- c = Sum of all Update Intervals
- d = Total Number of Updates Completed During Reporting Period

Report Structure

- CLEC Specific (Under development)
- · CLEC Aggregate
- · BellSouth Aggregate



Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
 Database File Submission Time Database File Update Completion Time CLEC Number of Submissions 	 Database File Submission Time Database File Update Completion Time BellSouth Number of Submissions
Total Number of Updates	Total Number of Updates

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation:	SQM Analog/Benchmark
Database Type • LIDB	Parity by Design
 Directory Listings Directory Assistance	

SEEM Measure

SEEM Measure		
No	Tier I	
	Tier II	

SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable

D-2: Percent Database Update Accuracy

Definition

This report measures the accuracy of database updates by BellSouth for Line Information Database (LIDB) Directory Assistance and Directory Listings using a statistically valid sample of LSRs/Orders in a manual review. This manual review is not conducted on BellSouth Retail Orders.

Exclusions

- Updates canceled by the CLEC
- Initial update when supplemented by CLEC
- · CLEC orders that had CLEC errors
- BellSouth updates associated with internal or administrative use of local services.

Business Rules

For each update completed during the reporting period, the original update that the CLEC sent to BellSouth is compared to the database following completion of the update by BellSouth. An update is "completed without error" if the database completely and accurately reflects the activity specified on the original and supplemental update (e.g., orders) submitted by the CLEC. Each database (e.g., LIDB, Directory Assistance and Directory Listings) should be separately tracked and reported.

A statistically valid sample of CLEC Orders will be pulled each month. The sample will be used to test the accuracy of the database update process. This is a manual process.

Calculation

Percent Update Accuracy = $(a \div b) \times 100$

- a = Number of Updates Completed Without Error
- b = Number Updates Completed

Report Structure

- · CLEC Aggregate
- CLEC Specific (not available in this report)
- BellSouth Aggregate (not available in this report)

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
 Report Month CLEC Order Number (so_nbr) and PON (PON) Local Service Request (LSR) Order Submission Date Number of Orders Reviewed 	Not Applicable
Note : Code in parentheses is the corresponding header found in the raw data file.	

SQM Level of Disaggregation	SQM Analog/Benchmark
Database Type	• 95% Accurate
• LIDB	
Directory Listings	



SEEM Measure

SEEM Measure		
No	Tier I	
	Tier II	

SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable

(A) **BELLSOUTH** *

D-3: Percent NXXs and LRNs Loaded by the LERG Effective Date

Definition

Measurement of the percent of NXX(s) and Location Routing Numbers LRN(s) loaded and tested in new end office and/or tandem switches by the Local Exchange Routing Guide (LERG) effective date when facilities are in place. BellSouth has a single provisioning process for both NXX(s) and LRN(s). In this measure BellSouth will identify whether or not a particular NXX has been flagged as LNP capable (set triggers for dips) by the LERG effective date.

An LRN is assigned by the owner of the switch and is placed into the software translations for every switch to be used as an administrative pointer to route NXX(s) in LNP capable switches. The LRN is a result of Local Number Porting and is housed in a national database provided by the Number Portability Administration Center (NPAC). The switch owner is responsible for notifying NPAC and requesting the effective date that will be reflected in the LERG. The national database downloads routing tables into BellSouth's Service Control Point (SCP) regional databases, which are queried by switches when routing ported numbers.

The basic NXX routing process includes the addition of all NXX(s) in the response translations. This addition to response translations is what supports LRN routing. Routing instructions for all NXX(s), including LRN(s), are received from the Advance Routing & Trunking System (ARTS) and all routing, including response, is established based on the information contained in the Translation Work Instructions (TWINs) document.

Exclusions

- Activation requests where the CLEC's interconnection arrangements and facilities are not in place by the LERG effective date.
- · Expedite requests

Business Rules

Data for the initial NXX(s) and LRN(s) in a local calling area will be based on the LERG effective date or completion of the initial interconnection trunk group(s), whichever is longer. Data for additional NXX(s) in the local calling area will be based on the LERG effective date. The LERG effective date is loaded into the system at the request of the CLEC. It is contingent upon the CLEC to engineer, order, and install interconnection arrangements and facilities prior to that date.

The total Count of NXX(s) and LRN(s) that were scheduled to be loaded and those that were loaded by the LERG effective date in BellSouth switches will be captured in the Work Force Administration -Dispatch In database.

Calculation

Percent NXXs/LRNs Loaded and Tested Prior to the LERG Effective Date = $(a \div b) \times 100$

- a = Count of NXXs and LRNs loaded by the LERG effective date
- b = Total NXXs and LRNs to be scheduled and loaded by the LERG effective date

Report Structure

- · CLEC Specific
- · CLEC Aggregate
- BellSouth (Not Applicable)

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Company Name	Not Applicable
Company Code	
• NPA/NXX	
LERG Effective Date	
Loaded Date	



SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
Geographic Scope Region	100% by LERG Effective Date

SEEM Measure

SEEM Measure		
No	Tier I	
	Tier II	

SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable



Section 8: E911

E-1: Timeliness

Definition

Measures the percent of batch orders for E911 database updates (to CLEC resale and BellSouth retail records) processed successfully within a 24-hour period.

Exclusions

- · Any resale order canceled by a CLEC
- · Facilities-based CLEC orders

Business Rules

The 24-hour processing period is calculated based on the date and time processing starts on the batch orders and the date and time processing stops on the batch orders. Mechanical processing starts when SCC (the BellSouth E911 vendor) receives E911 files containing batch orders extracted from the BellSouth Service Order Control System (SOCS). Processing stops when SCC loads the individual records to the E911 database. The E911 database includes updates to the Automatic Location Identification (ALI) database. The system makes no distinction between CLEC resale records and BellSouth retail records.

Calculation

E911 Timeliness = $(a \div b) \times 100$

- a = Number of batch orders processed within 24 hours
- b = Total number of batch orders submitted

Report Structure

Reported for the aggregate of CLEC resale updates and BellSouth retail updates

- State
- Region

Data Retained

- · Report month
- · Aggregate data

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
• None	Parity by Design

SEEM Measure

SEEM Measure		
No	Tier I	
	Tier II	

BELLSOUTH®





SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable



E-2: Accuracy

Definition

Measures the percent of E911 telephone number (TN) record updates (to CLEC resale and BellSouth retail records) processed successfully for E911 (including the Automatic Location Identification (ALI) database).

Exclusions

- · Any resale order canceled by a CLEC
- · Facilities-based CLEC orders

Business Rules

Accuracy is based on the number of records processed without error at the conclusion of the processing cycle. Mechanical processing starts when SCC (the BellSouth E911 vendor) receives E911 files containing telephone number (TN) records extracted from BellSouth's Service Order Control System (SOCS). The system makes no distinction between CLEC resale records and BellSouth retail records.

Calculation

E911 Accuracy = $(a \div b) \times 100$

- a = Number of record individual updates processed with no errors
- b = Total number of individual record updates

Report Structure

Reported for the aggregate of CLEC resale updates and BellSouth retail updates

- State
- · Region

Data Retained

- · Report month
- · Aggregate data

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
• None	Parity by Design

SEEM Measure

SEEM Measure			
No	Tier I		
	Tier II		

SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable



E-3: Mean Interval

Definition

Measures the mean interval processing of E911 batch orders (to update CLEC resale and BellSouth retail records) including processing against the Automatic Location Identification (ALI) database.

Exclusions

- · Any resale order canceled by a CLEC
- · Facilities-based CLEC orders

Business Rules

The processing period is calculated based on the date and time processing starts on the batch orders and the date and time processing stops on the batch orders. Data is posted is 4-hour increments up to and beyond 24 hours. The system makes no distinction between CLEC resale records and BellSouth retail records.

Calculation

E911 Interval = (a - b)

- a = Date and time of batch order completion
- b = Date and time of batch order submission

E911 Mean Interval = $(c \div d)$

- c = Sum of all E911 Intervals
- d = Number of batch orders completed

Report Structure

Reported for the aggregate of CLEC resale updates and BellSouth retail updates

- State
- Region

Data Retained

- · Report month
- · Aggregate data

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
• None	Parity by Design

SEEM Measure

SEEM Measure		
No	Tier I	
	Tier II	

SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable



Section 9: Trunk Group Performance

TGP-1: Trunk Group Performance-Aggregate

Definition

The Trunk Group Performance report displays, over a reporting cycle, aggregate, average trunk group blocking data for each hour of each day of the reporting cycle, for both CLEC affecting and BellSouth affecting trunk groups.

Exclusions

- Trunk Groups for which there was no valid data available for an entire study period
- Duplicate trunk group information

Business Rules

The purpose of the Trunk Group Performance Report is to provide trunk blocking measurements on CLEC and BellSouth trunk groups for comparison only. It is not the intent of the report that it be used for network management and/or engineering.

Monthly Average Blocking:

- The reporting cycle includes both business and non-business days in a calendar month.
- Monthly average blocking values are calculated for each trunk group for each of the 24 time consistent hours across a reporting cycle.

Aggregate Monthly Blocking:

- Used to compare aggregate blocking across trunk groups which terminate traffic at CLEC points of presence versus BellSouth switches.
- · Aggregate monthly blocking data is calculated for each hour of the day across all trunk groups assigned to a category.

Trunk Categorization:

This report displays, over a reporting cycle, aggregate, average blocking data for each hour of a day. Therefore, for each reporting cycle, 24 blocking data points are generated for two aggregate groups of selected trunk groups. These groups are CLEC affecting and BellSouth affecting trunk groups. In order to assign trunk groups to each aggregate group, all trunk groups are first assigned to a category. A trunk group's end points and the type of traffic that is transmitted on it define a category. Selected categories of trunk groups are assigned to the aggregate groups so that trunk reports can be generated. The categories to which trunk groups have been assigned for this report are as follows.

Point A

Point B

CLEC Affecting Categories:

	Category 1:	BellSouth End Office	BellSouth Access Tandem
	Category 3:	BellSouth End Office	CLEC Switch
	Category 4:	BellSouth Local Tandem	CLEC Switch
	Category 5:	BellSouth Access Tandem	CLEC Switch
	Category 10:	BellSouth End Office	BellSouth Local Tandem
	Category 16:	BellSouth Tandem	BellSouth Tandem
BellSouth Affection	ng Categories:		
		Point A	Point B
	Category 9:	BellSouth End Office	BellSouth End Office



Calculation

Monthly Average Blocking:

- For each hour of the day, each day's raw data are summed across all valid measurements days in a report cycle for blocked and attempted calls.
- The sum of the blocked calls is divided by the total number of calls attempted in a reporting period.

Aggregate Monthly Blocking:

- For each hour of the day, the monthly sums of the blocked and attempted calls from each trunk group are separately aggregated over all trunk groups within each assigned category.
- The total blocked calls is divided by the total call attempts within a group to calculate an aggregate monthly blocking for each assigned group.
- The result is an aggregate monthly average blocking value for each of the 24 hours by group.
- The difference between the CLEC and BellSouth affecting trunk groups are also calculated for each hour.

Report Structure

- · CLEC Aggregate
- · BellSouth Aggregate
 - State

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report Month	Report Month
Total Trunk Groups	Total Trunk Groups
Number of Trunk Groups by CLEC	Aggregate Hourly Blocking Per Trunk Group
Hourly Blocking Per Trunk Group	Hourly Usage Per Trunk Group
Hourly Usage Per Trunk Group	Hourly Call Attempts Per Trunk Group
Hourly Call Attempts Per Trunk Group	

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
CLEC Aggregate	Any 2 hour period in 24 hours where CLEC blockage exceeds
BellSouth Aggregate	BellSouth blockage by more than 0.5% using trunk groups 1,
	3, 4, 5, 10, 16 for CLECs and 9 for BellSouth

SEEM Measure

SEEM Measure		
Yes	Tier I	
	Tier II	X

SEEM Disaggregation	SEEM Analog/Benchmark
CLEC Aggregate BellSouth Aggregate	• Any 2 hour period in 24 hours where CLEC blockage exceeds BellSouth blockage by more than 0.5% using trunk groups 1,3,4,5,10,16 for CLECs and 9 for BellSouth

Daint B

TGP-2: Trunk Group Performance – CLEC Specific

Definition

The Trunk Group Performance report displays, over a reporting cycle, aggregate, average trunk group blocking data for each hour of each day of the reporting cycle, for both CLEC affecting and BellSouth affecting trunk groups.

Exclusions

- Trunk Groups for which there was no valid data available for an entire study period
- Duplicate trunk group information

Business Rules

The purpose of the Trunk Group Performance Report is to provide trunk blocking measurements on CLEC and BellSouth trunk groups for comparison only. It is not the intent of the report that it be used for network management and/or engineering.

Monthly Average Blocking:

- The reporting cycle includes both business and non-business days in a calendar month.
- Monthly average blocking values are calculated for each trunk group for each of the 24 time consistent hours across a reporting cycle.

Aggregate Monthly Blocking:

- · Used to compare aggregate blocking across trunk groups which terminate traffic at CLEC points of presence versus BellSouth switches.
- Aggregate monthly blocking data is calculated for each hour of the day across all trunk groups assigned to a category.

Trunk Categorization:

• This report displays, over a reporting cycle, aggregate, average blocking data for each hour of a day. Therefore, for each reporting cycle, 24 blocking data points are generated for two aggregate groups of selected trunk groups. These groups are CLEC affecting and BellSouth affecting trunk groups. In order to assign trunk groups to each aggregate group, all trunk groups are first assigned to a category. A trunk group's end points and the type of traffic that is transmitted on it define a category. Selected categories of trunk groups are assigned to the aggregate groups so that trunk reports can be generated. The categories to which trunk groups have been assigned for this report are as follows.

CLEC Affecting Categories:

	Point A	Point B
Category 1:	BellSouth End Office	BellSouth Access Tandem
Category 3:	BellSouth End Office	CLEC Switch
Category 4:	BellSouth Local Tandem	CLEC Switch
Category 5:	BellSouth Access Tandem	CLEC Switch
Category 10:	BellSouth End Office	BellSouth Local Tandem
Category 16:	BellSouth Tandem	BellSouth Tandem

BellSouth Affecting Categories:

	TOILLA	TOILE
Category 9:	BellSouth End Office	BellSouth End Office

Doint A

Calculation

Monthly Average Blocking:

- For each hour of the day, each day's raw data are summed across all valid measurements days in a report cycle for blocked and attempted calls.
- The sum of the blocked calls is divided by the total number of calls attempted in a reporting period.

Aggregate Monthly Blocking:



- For each hour of the day, the monthly sums of the blocked and attempted calls from each trunk group are separately aggregated over all trunk groups within each assigned category.
- The total blocked calls is divided by the total call attempts within a group to calculate an aggregate monthly blocking for each assigned group.
- The result is an aggregate monthly average blocking value for each of the 24 hours by group.
- The difference between the CLEC and BellSouth affecting trunk groups are also calculated for each hour.

Report Structure

- · CLEC Specific
 - State

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
Report Month	Report Month
Total Trunk Groups	Total Trunk Groups
Number of Trunk Groups by CLEC	Aggregate Hourly Blocking Per Trunk Group
Hourly Blocking Per Trunk Group	Hourly Usage Per Trunk Group
Hourly Usage Per Trunk Group	Hourly Call Attempts Per Trunk Group
Hourly Call Attempts Per Trunk Group	

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
CLEC Trunk Group	• Any 2 hour period in 24 hours where CLEC blockage exceeds BellSouth blockage by more than 0.5% using trunk groups 1,
	3, 4, 5, 10, 16 for CLECs and 9 for BellSouth

SEEM Measure

SEEM Measure		
Yes	Tier I	X
	Tier II	

SEEM Disaggregation	SEEM Analog/Benchmark
CLEC Trunk Group BellSouth Trunk Group	• Any 2 hour period in 24 hours where CLEC blockage exceeds BellSouth blockage by more than 0.5% using trunk groups 1, 3, 4, 5, 10, 16 for CLECs and 9 for BellSouth



Section 10: Collocation

C-1: Collocation Average Response Time

Definition

Measures the average time (counted in calendar days) from the receipt of a complete and accurate collocation application (including receipt of application fee if required) to the date BellSouth returns a response electronically or in writing. Within 10 calendar days after having received a bona fide application for physical collocation, BellSouth must respond as to whether space is available or not.

Exclusions

Any application canceled by the CLEC

Business Rules

The clock starts on the date that BellSouth receives a complete and accurate collocation application accompanied by the appropriate application fee if required. The clock stops on the date that BellSouth returns a response. The clock will restart upon receipt of changes to the original application request.

Calculation

Response Time = (a - b)

- a = Request Response Date
- b = Request Submission Date

Average Response Time = $(c \div d)$

- c = Sum of all Response Times
- d = Count of Responses Returned within Reporting Period

Report Structure

- Individual CLEC (alias) aggregate
- Aggregate of all CLECs

Data Retained

- · Report period
- · Aggregate data

SQM Level of Disaggregation	SQM Analog/Benchmark
• State	Virtual - 15 Calendar Days
Virtual-Initial	Physical Caged - 15 Calendar Days
Virtual-Augment	Physical Cageless - 15 Calendar Days
Physical Caged-Initial	
Physical Caged-Augment	
Physical-Cageless-Initial	
Physical Cageless-Augment	

BELLSOUTH®

SEEM Measure

SEEM Measure		
No	Tier I	
	Tier II	

SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable

(A) **BELLSOUTH** *

C-2: Collocation Average Arrangement Time

Definition

Measures the average time (counted in calendar days) from receipt of a complete and accurate Bona Fide firm order (including receipt of appropriate fee if required) to the date BellSouth completes the collocation arrangement and notifies the CLEC and the CLEC accepts the arrangement.

Exclusions

Any Bona Fide firm order canceled by the CLEC

Business Rules

The clock starts on the date that BellSouth receives a complete and accurate Bone Fide firm order accompanied by the appropriate fee. The clock stops on the date that BellSouth completes the collocation arrangement and notifies the CLEC. The cable assignments associated with the specific collocation request will be provided prior to completion of the arrangement.

Calculation

Arrangement Time = (a - b)

- a = Date Collocation Arrangement is Complete
- b = Date Order for Collocation Arrangement Submitted

Average Arrangement Time = $(c \div d)$

- c = Sum of all Arrangement Times
- d = Total Number of Collocation Arrangements Completed during Reporting Period

Report Structure

- Individual CLEC (alias) aggregate
- · Aggregate of all CLECs

Data Retained

- · Report period
- · Aggregate data

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
State Virtual-Initial Virtual-Augment Physical Caged-Initial Physical Caged-Augment Physical Cageless-Initial Physical Cageless-Augment	 Virtual - 60 Calendar Days Virtual-Augment - 45 Calendar Days (Without Space Increase) Virtual-Augment - 60 Calendar Days (With Space Increase) Physical Caged - 90 Calendar Days (Ordinary) Physical Caged-Augment - 45 Calendar Days (Without Space Increase) Physical Caged-Augment - 90 Calendar Days (With Space Increase) Physical Cagedless - 90 Calendar Days Physical Cagedless-Augment - 45 Calendar Days (Without Space Increase) Physical Cagedless-Augment - 90 Calendar Days (With Space Increase)

SEEM Measure

SEEM Measure		
No	Tier I	
	Tier II	

BELLSOUTH®

SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable

(A) **BELLSOUTH** *

C-3: Collocation Percent of Due Dates Missed

Definition

Measures the percent of missed due dates for both virtual and physical collocation arrangements

Exclusions

Any Bona Fide firm order canceled by the CLEC

Business Rules

Percent Due Dates Missed is the percent of total collocation arrangements which BellSouth is unable to complete by end of the BellSouth committed due date. The clock starts on the date that BellSouth receives a complete and accurate Bona Fide firm order accompanied by the appropriate fee if required. The arrangement is considered a missed due date if it is not completed on or before the committed due date

Calculation

% of Due Dates Missed = $(a \div b) \times 100$

- a = Number of Completed Orders that were not completed within BellSouth Committed Due Date during Reporting Period
- b = Number of Orders Completed in Reporting Period

Report Structure

- Individual CLEC (alias) aggregate
- · Aggregate of all CLECs

Data Retained

- · Report period
- · Aggregate data

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
• State	• \geq 95% on time
Virtual-Initial	
Virtual- Augment	
Physical Caged- Initial	
Physical Caged- Augment	
Physical Cageless- Initial	
Physical Cageless- Augment	

SEEM Measure

SEEM Measure		
Yes	Tier I	X
	Tier II	X

SEEM Disaggregation	SEEM Analog/Benchmark
All Collocation Arrangements	• $\geq 95\%$ on time



Section 11: Change Management

CM-1: Timeliness of Change Management Notices

Definition

Measures whether CLECs receive required software release notices on time to prepare for BellSouth interface/system changes so CLEC interfaces are not impaired by change.

Exclusions

- Changes to release dates for reasons outside BellSouth control, such as the system software vendor changes. For example: a patch to fix a software problem.
- Type 6 Change Requests (Defects/Expedites), as defined by the Change Control Process (CCP)

Business Rules

This metric is designed to measure the percent of change management notices sent to the CLECs according to notification standards and time frames set forth in the Change Control Process. The CCP is used by BellSouth and the CLECs to manage requested changes to the BellSouth Local Interfaces.

The clock starts on the notification date. The clock stops on the software release date. When project events occur (scope changes, analysis information, etc.), the software release date may change. A revised notification would be required and the clock would restart. Based on release constraints for defects/expedites, notification may be less than the agreed upon interval in the CCP for new features.

Calculation

Timeliness of Change Management Notices = $(a \div b) \times 100$

- a = Total number of Change Management Notifications Sent Within Required Time frames
- b = Total Number of Change Management Notifications Sent

Report Structure

· BellSouth Aggregate

Data Retained

- · Report Period
- Notice Date
- · Release Date

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
Region	• 98% on time

SEEM Measure

SEEM Measure		
Yes	Tier I	
	Tier II	X



SEEM Disaggregation	SEEM Analog/Benchmark
• Region	• 98% on time

CM-2: Change Management Notice Average Delay Days

Definition

Measures the average delay days for change management system release notices sent outside the time frame set forth in the Change Control Process.

Exclusions

- Changes to release dates for reasons outside BellSouth control, such as the system vendor
- Type 6 Change Requests (Defects/Expedites), as defined by the Change Control Process

Business Rules

This metric is designed to measure the percent of change management notices sent to the CLECs according to notification standards and time frames set forth in the Change Control Process. The CCP is used by BellSouth and the CLECs to manage requested changes to the BellSouth Local Interfaces.

The clock starts on the notification due date. The clock stops on the software release date. When project events occur (scope changes, analysis information, etc.), the software release date may change. A revised notification would be required and the clock would restart. Based on release constraints for defects/expedites, notification may be less than the agreed upon interval in the CCP for new features

Calculation

Change Management Notice Delay Days = (a - b)

- a = Date Notice Sent
- b = Date Notice Due

Change Management Notice Average Delay Days = $(c \div d)$

- c = Sum of all Change Management Notice Delay Days
- d = Total Number of Notices Sent Late

Report Structure

· BellSouth Aggregate

Data Retained

- · Report Period
- Notice Date
- · Release Date

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
• Region	• ≤ 5 Days

SEEM Measure

SEEM Measure		
No	Tier I	
	Tier II	

SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable



CM-3: Timeliness of Documents Associated with Change

Definition

Measures whether CLECs received requirements or business rule documentation on time to prepare for BellSouth interface/system changes so CLEC interfaces are not impaired by change as set forth in the Change Control Process governed by the CLEC/BellSouth Review Board.

Exclusions

- Documentation for release dates that slip less than 30 days for a change mandated by regulatory or legal entities (Federal Communications Commission [FCC], a state commission/authority, or state and federal courts) or CLEC request.
- Type 6 Change Requests (Defects/Expedites), as defined by the Change Control Process.

Business Rules

This metric is designed to measure the percent of requirements or business rule documentation sent to the CLECs according to documentation standards and time frames set forth in the Change Control Process. The CCP is used by BellSouth and the CLECs to manage requested changes to the BellSouth Local Interfaces.

The clock starts on the business rule documentation release date. The clock stops on the software release date. When project events occur (scope changes, analysis information, etc.), the software release date may change. Revisions to documentation could be required and the clock would restart.

Calculation

Timeliness of Documents Associated with Change = (a ÷ b) X 100

- a = Change Management Documentation Sent Within Required Time frames after Notices
- b = Total Number of Change Management Documentation Sent

Report Structure

· BellSouth Aggregate

Data Retained

- · Report Period
- · Notice Date
- · Release Date

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
Region	• 98% on Time

SEEM Measure

SEEM Measure		
Yes	Tier I	
	Tier II	X

SEEM Disaggregation	SEEM Analog/Benchmark
Region	• 98% on Time



CM-4: Change Management Documentation Average Delay Days

Definition

Measures the average delay days for requirements or business rule documentation sent outside the time frames set forth in the Change

Exclusions

- Documentation for release dates that slip less than 30 days for reasons outside BellSouth control, such as changes due to Regulatory mandate or CLEC request.
- Type 6 Change Requests (Defects/Expedites), as defined by the Change Control Process.

Business Rules

This metric is designed to measure the percent of requirements or business rule documentation sent to the CLECs according to documentation standards and time frames set forth in the Change Control Process. The CCP is used by BellSouth and the CLECs to manage requested changes to the BellSouth Local Interfaces.

The clock starts on the business rule documentation release date. The clock stops on the software release date. When project events occur (scope changes, analysis information, etc.), the software release date may change. Revisions to documentation could be required and the clock would restart.

Calculation

Change Management Documentation Delay Days = (a - b)

- a = Date Documentation Provided
- b = Date Documentation Due

Change Management Documentation Average Delay Days = $(c \div d)$

- c = Sum of all CM Documentation Delay Days
- d = Total Change Management Documents Sent

Report Structure

· BellSouth Aggregate

Data Retained

- · Report Period
- · Notice Date
- · Release Date

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
Region	• ≤ 5 Days

SEEM Measure

SEEM Measure		
No	Tier I	
	Tier II	



SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable

CM-5: Notification of CLEC Interface Outages

Definition

Measures the time it takes BellSouth to notify the CLEC of an outage of an interface.

Exclusions

None

Business Rules

This measure is designed to notify the CLEC of interface outages within 15 minutes of BellSouth's verification that an outage has taken place. This metric will be expressed as a percentage.

Calculation

Notification of CLEC Interface Outages = $(a \div b) \times 100$

- a = Number of Interface Outages where CLECS are notified within 15 minutes
- b = Total Number of Interface Outages

Report Structure

· CLEC Aggregate

Data Retained

Relating to CLEC Experience	Relating to BellSouth Performance
 Number of Interface Outages Number of Notifications ≤ 15 minutes 	Not Applicable

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation	SQM Analog/Benchmark
By interface type for all interfaces accessed by CLECs	• 97% ≤ 15 Minutes

Interface	Applicable to
EDI	CLEC
CSOTS	CLEC
LENS	CLEC
TAG	CLEC
ECTA	CLEC
TAFI	CLEC/BellSouth

SEEM Measure

SEEM Measure		
No	Tier I	
	Tier II	



SEEM Disaggregation	SEEM Analog/Benchmark
Not Applicable	Not Applicable



Appendix A: Reporting Scope

A-1: Standard Service Groupings

See individual reports in the body of the SQM.

A-2: Standard Service Order Activities

These are the generic BellSouth/CLEC service order activities which are included in the Pre-Ordering, Ordering, and Provisioning sections of this document. It is not meant to indicate specific reporting categories.

Service Order Activity Types

- Service Migrations Without Changes
- Service Migrations With Changes
- Move and Change Activities
- Service Disconnects (Unless noted otherwise)
- · New Service Installations

Pre-Ordering Query Types

- Address
- Telephone Number
- Appointment Scheduling
- Customer Service Record
- · Feature Availability
- Service Inquiry

Maintenance Query Types

TAFI - TAFI queries the systems below

- CRIS
- March
- Predictor
- LMOS
- DLR
- DLETH
- LMOSupd
- LNP
- NIW
- OSPCM
- SOCS

Report Levels

- CLEC RESH
- CLEC State
- · CLEC Region
- Aggregate CLEC State



- Aggregate CLEC Region
- BellSouth State
- BellSouth Region



Appendix B: Glossary of Acronyms and Terms

Symbols used in calculations

- Σ A mathematical symbol representing the sum of a series of values following the symbol.
- A mathematical operator representing subtraction.
- + A mathematical operator representing addition.
- ÷ A mathematical operator representing division.
- < A mathematical symbol that indicates the metric on the left of the symbol is less than the metric on the right.
- ≤ A mathematical symbol that indicates the metric on the left of the symbol is less than or equal to the metric on the right.
- > A mathematical symbol that indicates the metric on the left of the symbol is greater than the metric on the right.
- > A mathematical symbol that indicates the metric on the left of the symbol is greater than or equal to the metric on the right.
- () Parentheses, used to group mathematical operations which are completed before operations outside the parentheses.

Α

ACD: Automatic Call Distributor - A service that provides status monitoring of agents in a call center and routes high volume incoming telephone calls to available agents while collecting management information on both callers and attendants.

Aggregate: Sum total of all items in like category, e.g. CLEC aggregate equals the sum total of all CLECs' data for a given reporting level

ALEC: Alternative Local Exchange Company = FL CLEC

ADSL: Asymmetrical Digital Subscriber Line

ASR: Access Service Request - A request for access service terminating delivery of carrier traffic into a Local Exchange Carrier's network.

ATLAS: Application for Telephone Number Load Administration System - The BellSouth Operations System used to administer the pool of available telephone numbers and to reserve selected numbers from the pool for use on pending service requests/service orders.

ATLASTN: ATLAS software contract for Telephone Number.

Auto Clarification: The number of LSRs that were electronically rejected from LESOG and electronically returned to the CLEC for correction.

В

BFR: Bona Fied Request



BILLING: The process and functions by which billing data is collected and by which account information is processed in order to render accurate and timely billing.

BOCRIS: Business Office Customer Record Information System (Front-end to the CRIS database.)

BRI: Basic Rate ISDN

BRC: Business Repair Center – The BellSouth Business Systems trouble receipt center which serves large business and CLEC customers.

BellSouth: BellSouth Telecommunications, Inc.

C

CABS: Carrier Access Billing System

CCC: Coordinated Customer Conversions

CCP: Change Control Process

Centrex: A business telephone service, offered by local exchange carriers, which is similar to a Private Branch Exchange (PBX) but the switching equipment is located in the telephone company Central Office (CO).

CKTID: A unique identifier for elements combined in a service configuration

CLEC: Competitive Local Exchange Carrier

CLP: Competitive Local Provider = NC CLEC

CM: Change Management

CMDS: Centralized Message Distribution System - Telcordia administered national system used to transfer specially formatted messages among companies.

COFFI: Central Office Feature File Interface - Provides information about USOCs and class of service. COFFI is a part of DOE/SONGS. It indicates all services available to a customer.

CRIS: Customer Record Information System - This system is used to retain customer information and render bills for telecommunications service.

CRSACCTS: CRIS software contract for CSR information

CRSG: Complex Resale Support Group

C-SOTS: CLEC Service Order Tracking System

CSR: Customer Service Record

CTTG: Common Transport Trunk Group - Final trunk groups between BellSouth & Independent end offices and the BellSouth access tandems.

D

DA: Directory Assistance

DESIGN: Design Service is defined as any Special or Plain Old Telephone Service Order which requires BellSouth Design Engineering Activities.



DISPOSITION & CAUSE: Types of trouble conditions, e.g. No Trouble Found, Central Office Equipment, Customer Premises Equipment, etc.

DLETH: Display Lengthy Trouble History - A history report that gives all activity on a line record for trouble reports in LMOS.

DLR: Detail Line Record - A report that gives detailed line record information on records maintained in LMOS

DS-0: The worldwide standard speed for one digital voice signal (64000 bps).

DS-1: 24 DS-0s (1.544Mb/sec., i.e. carrier systems)

DOE: Direct Order Entry System - An internal BellSouth service order entry system used by BellSouth Service Representatives to input business service orders in BellSouth format.

DSAP: DOE (Direct Order Entry) Support Application - The BellSouth Operations System which assists a Service Representative or similar carrier agent in negotiating service provisioning commitments for non-designed services and Unbundled Network Elements.

DSAPDDI: DSAP software contract for schedule information.

DSL: Digital Subscriber Line

DUI: Database Update Information

Ε

E911: Provides callers access to the applicable emergency services bureau by dialing a 3-digit universal telephone number.

EDI: Electronic Data Interchange - The computer-to-computer exchange of inter and/or intra-company business documents in a public standard format.

ESSX: BellSouth Centrex Service

F G

Fatal Reject: The number of LSRs that were electronically rejected from LEO, which checks to see of the LSR has all the required fields correctly populated.

Flow-Through: In the context of this document, LSRs submitted electronically via the CLEC mechanized ordering process that flow through to the BellSouth OSS without manual or human intervention.

FOC: Firm Order Confirmation - A notification returned to the CLEC confirming that the LSR has been received and accepted, including the specified commitment date.

FX: Foreign Exchange

Н

HAL: "Hands Off" Assignment Logic - Front end access and error resolution logic used in interfacing BellSouth Operations Systems such as ATLAS, BOCRIS, LMOS, PSIMS, RSAG and SOCS.

HALCRIS: HAL software contract for CSR information

HDSL: High Density Subscriber Loop/Line

Version 1.00 B-3 Issue Date: December 1, 2002



IJK

ILEC: Incumbent Local Exchange Company

INP: Interim Number Portability

ISDN: Integrated Services Digital Network

IPC: Interconnection Purchasing Center

L

LAN: Local Area Network

LAUTO: The automatic processor in the LNP Gateway that validates LSRs and issues service orders.

LCSC: Local Carrier Service Center - The BellSouth center which is dedicated to handling CLEC LSRs, ASRs, and Preordering transactions along with associated expedite requests and escalations.

Legacy System: Term used to refer to BellSouth Operations Support Systems (see OSS)

LENS: Local Exchange Negotiation System - The BellSouth LAN/web server/OS application developed to provide both preordering and ordering electronic interface functions for CLECs.

LEO: Local Exchange Ordering - A BellSouth system which accepts the output of EDI, applies edit and formatting checks, and reformats the Local Service Requests in BellSouth Service Order format.

LERG: Local Exchange Routing Guide

LESOG: Local Exchange Service Order Generator - A BellSouth system which accepts the service order output of LEO and enters the Service Order into the Service Order Control System using terminal emulation technology.

LFACS: Loop Facilities Assessment and Control System

LIDB: Line Information Database

LMOS: Loop Maintenance Operations System - A system that provides a mechanized means of maintaining customer line records and for entering, processing, and tracking trouble reports.

LMOS HOST: LMOS host computer

LMOSupd: LMOS update allows trouble tickets on line records to be entered into LMOS.

LMU: Loop Make-up

LMUS: Loop Make-up Service Inquiry

LNP: Local Number Portability - In the context of this document, the capability for a subscriber to retain his current telephone number as he transfers to a different local service provider.

LNP Gateway: Local Number Portability (gateway)- A system that provides both internal and external communications with various interfaces and process including:

- (1). Linking BellSouth to the Number Portability Administration Center (NPAC).
- (2). Allowing for inter-company communications between BellSouth and the CLECs for electronic ordering.
- (3). Providing interface between NPAC and AIN SMS for LNP routing processes.



LOOPS: Transmission paths from the central office to the customer premises.

LRN: Location Routing Number

LSR: Local Service Request – A request for local resale service or unbundled network elements from a CLEC.

M

Maintenance & Repair: The process and function by which trouble reports are passed to BellSouth and by which the related service problems are resolved.

MARCH: A memory administration system that translates line-related service order data into switch provisioning messages and automatically transmits the messages to targeted stored program control system switches.

Ν

NBR: New Business Request

NC: "No Circuits" - All circuits busy announcement.

NIW: Network Information Warehouse - A system that stores central office blockage data for use in processing trouble reports.

NMLI: Native Mode LAN Interconnection

NPA: Numbering Plan Area

NXX: The "exchange" portion of a telephone number.

0

OASIS: Obtain Availability Services Information System - A BellSouth front-end processor, which acts as an interface between COFFI and RNS. This system takes the USOCs in COFFI and translates them to English for display in RNS.

OASISBSN: OASIS software contract for feature/service

OASISCAR: OASIS software contract for feature/service

OASISLPC: OASIS software contract for feature/service

OASISMTN: OASIS software contract for feature/service

OASISNET: OASIS software contract for feature/service

OASISOCP: OASIS software contract for feature/service

ORDERING: The process and functions by which resale services or unbundled network elements are ordered from Bell-South as well as the process by which an LSR or ASR is placed with BellSouth.

Order Types: The following order types are used in this document:

- (1). T The "to" portion of a change of address. This Order Type is used to connect main service at a new address when a customer moves from one address to another in any of the nine states within the BellSouth region. A "T" Order Type is always pared with an "F" Order Type which will have the same telephone number following the "F" Order Type Code unless the orders are within different states.
- (2). N Orders establishing a new account. Also, this Order Type Code is occasionally used when changing from one type of system to another such as when changing from PBX to Centrex.



- (3). C Order Type used for the following conditions: changes or partial connections or disconnections of service or equipment; change of telephone number, grade or class of main line, additional lines, auxiliary lines, PBX trunks and stations; addition of trunks or lines to existing accounts; move of equipment (other than change of address); temporary suspension and restoration of service at customer's request.
- (4). R Order Type used for the following conditions: additions, removals or changes in directory listings; responsibility change orders, addition, removal or changes in directory and billing information; other record corrections where no "field work" is involved.

OSPCM: Outside Plant Contract Management System - A system that provides scheduling and completion information on outside plant construction activities.

OSS: Operations Support System - A support system or database which is used to mechanize the flow or performance of work. The term is used to refer to the overall system consisting of hardware complex, computer operating system(s), and application which is used to provide the support functions.

OUT OF SERVICE: Customer has no dial tone and cannot call out.

P Q

PMAP: Performance Measurement Analysis Platform

PON: Purchase Order Number

POTS: Plain Old Telephone Service

PREDICTOR: A system which is used to administer proactive maintenance and rehabilitation activities on outside plant facilities, provide access to selected work groups to Mechanized Loop Testing and switching system I/O ports.

Preordering: The process and functions by which vital information is obtained, verified, or validated prior to placing a service request.

PRI: Primary Rate ISDN

Provisioning: The process and functions by which necessary work is performed to activate a service requested via an LSR or ASR and to initiate the proper billing and accounting functions.

PSIMS: Product/Service Inventory Management System - A BellSouth database Operations System which contains availability information on switching system features and capabilities and on BellSouth service availability. This database is used to verify the availability of a feature or service in an NXX prior to making a commitment to the customer.

PSIMSORB: PSIMS software contract for feature/service.

R

RNS: Regional Negotiation System - An internal BellSouth service order entry system used by BellSouth Consumer Services to input service orders in BellSouth format.

ROS: Regional Ordering System

RRC: Residence Repair Center - The BellSouth Consumer Services trouble receipt center which serves residential customers.

RSAG: Regional Street Address Guide - The BellSouth database, which contains street addresses validated to be accurate with state and local governments.

RSAGADDR: RSAG software contract for address search.



RSAGTN: RSAG software contract for telephone number search.

S

SAC: Service Advocacy Center

SEEM: Self Effectuating Enforcement Mechanism

SOCS: Service Order Control System - A system which routes service order images among BellSouth drop points and BellSouth OSS during the service provisioning process.

SOIR: Service Order Interface Record - any change effecting activity to a customer account by service order that impacts 911/E911

SONGS: Service Order Negotiation and Generation System.

Syntactically Incorrect Query: A query that cannot be fulfilled due to insufficient or incorrect input data from the end user. For example, A CLEC would like to query the legacy system for the following address: 1234 Main ST. Entering "1234 Main ST" will be considered syntactically correct because valid characters were used in the address field. However, entering "AB34 Main ST" will be considered syntactically incorrect because invalid characters (i.e., alpha characters were entered in numeric slots) were used in the address field.

Т

TAFI: Trouble Analysis Facilitation Interface - The BellSouth Operations System that supports trouble receipt center personnel in taking and handling customer trouble reports.

TAG: Telecommunications Access Gateway – TAG was designed to provide an electronic interface, or machine-to-machine interface for the bi-directional flow of information between BellSouth's OSSs and participating CLECs.

TN: Telephone Number

Total Manual Fallout: The number of LSRs which are entered electronically but require manual entering into a service order generator.

UV

UNE: Unbundled Network Element

UCL: Unbundled Copper Link

USOC: Universal Service Order Code

WXYZ

WATS: Wide Area Telephone Service

WFA: Work Force Administration

WMC: Work Management Center

WTN: Working Telephone Number.



Appendix C: BellSouth Audit Policy

C-1: BellSouth's Internal Audit Policy

BellSouth's internal efforts to make certain that the reports produced by the PMAP platform are of the highest accuracy has been formalized into a Performance Measurements Quality Assurance Plan (PMQAP) that documents and augments existing quality assurance processes integral to the production and validation of Performance Measurements data.

The plan consists of three sections:

- 1. Change Control addresses the quality assurance steps involved in the introduction of new measurements and changes to existing measurements.
- 2. Production addresses the quality assurance steps used to create monthly SQM reports.
- 3. Monthly Validation addresses the quality assurance steps used to ensure accurate posting of monthly results.

The BellSouth PMQAP will ensure that BellSouth effectively and consistently provides accurate performance measurements data for the activities included in the SQM. The BellSouth Internal Audit department will audit this plan and its quality assurance steps annually, beginning in 4Q01.

C-2: BellSouth's External Audit Policy

BellSouth currently provides many CLECs with audit rights as a part of their individual interconnection agreements. BellSouth has developed a proposed Audit Plan for use by the parties to an audit. If requested by a Public Service Commission or by a CLEC exercising contractual audit rights, BellSouth will agree to undergo a comprehensive audit of the current year aggregate level reports for both BellSouth and the CLECs for each of the next five (5) years (2001 - 2005), to be conducted by an independent third party auditor jointly selected by BellSouth and the CLEC. The results of audits will be made available to all the parties subject to proper safeguards to protect proprietary information. Requested audits include the following specifications:

- 1. The cost shall be borne by BellSouth.
- 2. The independent third party auditor shall be selected with input from BellSouth, the PSC, if applicable, and the CLEC(s).
- 3. BellSouth, the PSC and the CLECs shall jointly determine the scope of the audit.

These comprehensive audits are intended to provide the basis for the PSCs and CLECs to determine that the SQM and PMAP produce accurate data that reflects each States Order for performance measurements. Once this has been verified by an initial audit, the BellSouth PMQAP will provide the basis for future audits.

Attachment 10

BellSouth Disaster Recovery Plan

CON	TENT	<u>S</u>		PAGE
1.0	Purpose			2
2.0	Single Point of Contact			2
3.0	Identifying the Problem			2
	3.1	Site Co	ontrol	3
	3.2	Enviro	nmental Concerns	4
4.0	The Emergency Control Center (ECC)			4
5.0	Recovery Procedures			5
	5.1 CLEC Outage		5	
	5.2	BellSouth Outage		5
		5.2.1	Loss of Central Office	6
		5.2.2	Loss of a Central Office with Serving Wire Center Functions	6
		5.2.3	Loss of a Central Office with Tandem Functions	6
		5.2.4	Loss of a Facility Hub	7
	5.3 Combined Outage (CLEC and BellSouth Equipment)		7	
6.0	T1 Identification Procedures			7
7.0	Acronyms			8

1.0 PURPOSE

In the unlikely event of a disaster occurring that affects BellSouth's long-term ability to deliver traffic to a Competitive Local Exchange Carrier (CLEC), general procedures have been developed by BellSouth to hasten the recovery process in accordance with the Telecommunications Service Priority (TSP) Program established by the Federal Communications Commission to identify and prioritize telecommunication services that support national security or emergency preparedness (NS/EP) missions. Since each location is different and could be affected by an assortment of potential problems, a detailed recovery plan is impractical. However, in the process of reviewing recovery activities for specific locations, some basic procedures emerge that appear to be common in most cases.

These general procedures should apply to any disaster that affects the delivery of traffic for an extended time period. Each CLEC will be given the same consideration during an outage, and service will be restored as quickly as possible.

This document will cover the basic recovery procedures that would apply to every CLEC.

2.0 SINGLE POINT OF CONTACT

When a problem is experienced, regardless of the severity, the BellSouth Network Management Center (NMC) will observe traffic anomalies and begin monitoring the situation. Controls will be appropriately applied to insure the sanity of BellSouth's network; and, in the event that a switch or facility node is lost, the NMC will attempt to circumvent the failure using available reroutes.

BellSouth's NMC will remain in control of the restoration efforts until the problem has been identified as being a long-term outage. At that time, the NMC will contact BellSouth's Emergency Control Center (ECC) and relinquish control of the recovery efforts. Even though the ECC may take charge of the situation, the NMC will continue to monitor the circumstances and restore traffic as soon as damaged network elements are revitalized.

The telephone number for the BellSouth Network Management Center in Atlanta, as published in Telcordia's National Network Management Directory, is 404-321-2516.

3.0 IDENTIFYING THE PROBLEM

During the early stages of problem detection, the NMC will be able to tell which CLECs are affected by the catastrophe. Further analysis and/or first hand observation will determine if the disaster has affected CLEC equipment only, BellSouth equipment only or a combination. The initial restoration activity will be largely determined by the equipment that is affected.

Once the nature of the disaster is determined and after verifying the cause of the problem, the NMC will initiate reroutes and/or transfers that are jointly agreed upon by the affected CLECs' Network Management Center and the BellSouth NMC. The type and percentage of controls used will depend upon available network capacity. Controls necessary to stabilize the situation will be invoked and the NMC will attempt to re-establish as much traffic as possible.

For long-term outages, recovery efforts will be coordinated by the Emergency Control Center (ECC). Traffic controls will continue to be applied by the NMC until facilities are re-established. As equipment is made available for service, the ECC will instruct the NMC to begin removing the controls and allow traffic to resume.

3.1 SITE CONTROL

In the total loss of building use scenario, what likely exists will be a smoking pile of rubble. This rubble will contain many components that could be dangerous. It could also contain any personnel on the premises at the time of the disaster. For these reasons, the local fire marshal with the assistance of the police will control the site until the building is no longer a threat to surrounding properties and the companies have secured the site from the general public.

During this time, the majority owner of the building should be arranging for a demolition contractor to mobilize to the site with the primary objective of reaching the cable entrance facility for a damage assessment. The results of this assessment would then dictate immediate plans for restoration, both short term and permanent.

In a less catastrophic event, i.e., the building is still standing and the cable entrance facility is usable, the situation is more complex. The site will initially be controlled by local authorities until the threat to adjacent property has diminished. Once the site is returned to the control of the companies, the following events should occur.

An initial assessment of the main building infrastructure systems (mechanical, electrical, fire and life safety, elevators, and others) will establish building needs. Once these needs are determined, the majority owner should lead the building restoration efforts. There may be situations where the site will not be totally restored within the confines of the building. The companies must individually determine their needs and jointly assess the cost of permanent restoration to determine the overall plan of action.

Multiple restoration trailers from each company will result in the need for designated space and installation order. This layout and control is required to maximize the amount of restoration equipment that can be placed at the site, and the priority of placements.

Care must be taken in this planning to ensure other restoration efforts have logistical access to the building. Major components of telephone and building equipment will need to be removed and replaced. A priority for this equipment must also be jointly established to facilitate overall site restoration. (Example: If the AC switchgear has sustained damage, this would be of the highest priority in order to regain power, lighting, and HVAC throughout the building.)

If the site will not accommodate the required restoration equipment, the companies would then need to quickly arrange with local authorities for street closures, rights of way or other possible options available.

3.2 ENVIRONMENTAL CONCERNS

In the worse case scenario, many environmental concerns must be addressed. Along with the police and fire marshal, the state environmental protection department will be on site to monitor the situation.

Items to be concerned with in a large central office building could include:

- 1. Emergency engine fuel supply. Damage to the standby equipment and the fuel handling equipment could have created "spill" conditions that have to be handled within state and federal regulations.
- 2. Asbestos-containing materials that may be spread throughout the wreckage. Asbestos could be in many components of building, electrical, mechanical, outside plant distribution, and telephone systems.
- 3. Lead and acid. These materials could be present in potentially large quantities depending upon the extent of damage to the power room.
- 4. Mercury and other regulated compounds resident in telephone equipment.
- 5. Other compounds produced by the fire or heat.

Once a total loss event occurs at a large site, local authorities will control immediate clean up (water placed on the wreckage by the fire department) and site access.

At some point, the companies will become involved with local authorities in the overall planning associated with site clean up and restoration. Depending on the clean up approach taken, delays in the restoration of several hours to several days may occur.

In a less severe disaster, items listed above are more defined and can be addressed individually depending on the damage.

In each case, the majority owner should coordinate building and environmental restoration as well as maintain proper planning and site control.

4.0 THE EMERGENCY CONTROL CENTER (ECC)

The ECC is located in the Midtown 1 Building in Atlanta, Georgia. During an emergency, the ECC staff will convene a group of pre-selected experts to inventory the damage and initiate corrective actions. These experts have regional access to BellSouth's personnel and equipment and will assume control of the restoration activity anywhere in the nine-state area.

In the past, the ECC has been involved with restoration activities resulting from hurricanes, ice storms and floods. They have demonstrated their capabilities during these calamities as well as

during outages caused by human error or equipment failures. This group has an excellent record of restoring service as quickly as possible.

During a major disaster, the ECC may move emergency equipment to the affected location, direct recovery efforts of local personnel and coordinate service restoration activities with the CLECs. The ECC will attempt to restore service as quickly as possible using whatever means is available, leaving permanent solutions, such as the replacement of damaged buildings or equipment, for local personnel to administer.

Part of the ECC's responsibility, after temporary equipment is in place, is to support the NMC efforts to return service to the CLECs. Once service has been restored, the ECC will return control of the network to normal operational organizations. Any long-term changes required after service is restored will be made in an orderly fashion and will be conducted as normal activity.

5.0 RECOVERY PROCEDURES

The nature and severity of any disaster will influence the recovery procedures. One crucial factor in determining how BellSouth will proceed with restoration is whether or not BellSouth's equipment is incapacitated. Regardless of whose equipment is out of service, BellSouth will move as quickly as possible to aid with service recovery; however, the approach that will be taken may differ depending upon the location of the problem.

5.1 CLEC OUTAGE

For a problem limited to one CLEC (or a building with multiple CLECs), BellSouth has several options available for restoring service quickly. For those CLECs that have agreements with other CLECs, BellSouth can immediately start directing traffic to a provisional CLEC for completion. This alternative is dependent upon BellSouth having concurrence from the affected CLECs.

Whether or not the affected CLECs have requested a traffic transfer to another CLEC will not impact BellSouth's resolve to re-establish traffic to the original destination as quickly as possible.

5.2 BELLSOUTH OUTAGE

Because BellSouth's equipment has varying degrees of impact on the service provided to the CLECs, restoring service from damaged BellSouth equipment is different. The outage will probably impact a number of Carriers simultaneously. However, the ECC will be able to initiate immediate actions to correct the problem.

A disaster involving any of BellSouth's equipment locations could impact the CLECs, some more than others. A disaster at a Central Office (CO) would only impact the delivery of traffic to and from that one location, but the incident could affect many Carriers. If the Central Office is a Serving Wire Center (SWC), then traffic from the entire area to those Carriers served from that switch would also be impacted. If the switch functions as an Access Tandem, or there is a tandem in the building, traffic from every CO to every CLEC could be interrupted. A disaster that destroys a facility hub could disrupt various traffic flows, even though the switching equipment may be unaffected.

The NMC would be the first group to observe a problem involving BellSouth's equipment. Shortly after a disaster, the NMC will begin applying controls and finding re-routes for the

completion of as much traffic as possible. These reroutes may involve delivering traffic to alternate Carriers upon receiving approval from the CLECs involved. In some cases, changes in translations will be required. If the outage is caused by the destruction of equipment, then the ECC will assume control of the restoration.

5.2.1 Loss of a Central Office

When BellSouth loses a Central Office, the ECC will

- a) Place specialists and emergency equipment on notice;
- b) Inventory the damage to determine what equipment and/or functions are lost;
- c) Move containerized emergency equipment and facility equipment to the stricken area, if necessary;
- d) Begin reconnecting service on a parity basis for Hospitals, Police and other emergency agencies or End Users served by BellSouth or CLEC in accordance with the TSP priority restoration coding scheme entered in the BellSouth Maintenance database immediately prior to the emergency.

5.2.2 Loss of a Central Office with Serving Wire Center Functions

The loss of a Central Office that also serves as a Serving Wire Center (SWC) will be restored as described in Section 5.2.1.

5.2.3 Loss of a Central Office with Tandem Functions

When BellSouth loses a Central Office building that serves as an Access Tandem and as a SWC, the ECC will

- a) Place specialists and emergency equipment on notice;
- b) Inventory the damage to determine what equipment and/or functions are lost;
- c) Move containerized emergency equipment and facility equipment to the stricken area, if necessary;
- d) Begin reconnecting service on a parity basis for Hospitals, Police and other emergency agencies or End Users served by BellSouth or CLEC in accordance with the TSP priority restoration coding scheme entered in the BellSouth Maintenance database immediately prior to the emergency;
- e) Re-direct as much traffic as possible to the alternate access tandem (if available) for delivery to those CLECs utilizing a different location as a SWC;
- f) Begin aggregating traffic to a location near the damaged building. From this location, begin re-establishing trunk groups to the CLECs for the delivery of traffic normally found on the direct trunk groups. (This aggregation point may be the alternate access tandem location or another CO on a primary facility route.)

5.2.4 Loss of a Facility Hub

In the event that BellSouth loses a facility hub, the recovery process is much the same as above. Once the NMC has observed the problem and administered the appropriate controls, the ECC will assume authority for the repairs. The recovery effort will include

- a) Placing specialists and emergency equipment on notice;
- b) Inventorying the damage to determine what equipment and/or functions are lost;
- c) Moving containerized emergency equipment to the stricken area, if necessary;
- d) Reconnecting service on a parity basis for Hospitals, Police and other emergency agencies or End Users served by BellSouth or CLEC in accordance with the TSP priority restoration coding scheme entered in the BellSouth Maintenance database immediately prior to the emergency; and
- e) If necessary, BellSouth will aggregate the traffic at another location and build temporary facilities. This alternative would be viable for a location that is destroyed and building repairs are required.

5.3 COMBINED OUTAGE (CLEC AND BELLSOUTH EQUIPMENT)

In some instances, a disaster may impact BellSouth's equipment as well as the CLECs'. This situation will be handled in much the same way as described in Section 5.2.3. Since BellSouth and the CLECs will be utilizing temporary equipment, close coordination will be required.

6.0 T1 IDENTIFICATION PROCEDURES

During the restoration of service after a disaster, BellSouth may be forced to aggregate traffic for delivery to a CLEC. During this process, T1 traffic may be consolidated onto DS3s and may become unidentifiable to the Carrier. Because resources will be limited, BellSouth may be forced to "package" this traffic entirely differently than normally received by the CLECs. Therefore, a method for identifying the T1 traffic on the DS3s and providing the information to the Carriers is required.

7.0 ACRONYMS

CLEC - Competitive Local Exchange Carrier

CO - Central Office (BellSouth)

DS3 - Facility that carries 28 T1s (672 circuits)

ECC - Emergency Control Center (BellSouth)

NMC - Network Management Center

SWC - Serving Wire Center (BellSouth switch)

T1 - Facility that carries 24 circuits

TSP - Telecommunications Service Priority

Hurricane Information

During a hurricane, BellSouth will make every effort to keep CLECs updated on the status of our network. Information centers will be set up throughout BellSouth Telecommunications. These centers are not intended to be used for escalations, but rather to keep the CLEC informed of network related issues, area damages and dispatch conditions, etc.

Hurricane-related information can also be found on line at http://www.interconnection.bellsouth.com/network/disaster/dis_resp.htm. Information concerning Mechanized Disaster Reports can also be found at this website by clicking on CURRENT MDR REPORTS or by going directly to http://www.interconnection.bellsouth.com/network/disaster/mdrs.htm.

BST Disaster Management Plan

BellSouth maintenance centers have geographical and redundant communication capabilities. In the event of a disaster removing any maintenance center from service another geographical center would assume maintenance responsibilities. The contact numbers will not change and the transfer will be transparent to the CLEC.

Attachment 11

Bona Fide Request and New Business Request Process

BONA FIDE REQUEST AND NEW BUSINESS REQUEST PROCESS

1.0 The Parties agree that Global Connection is entitled to order any Unbundled Network Element, Interconnection option, service option or Resale Service required to be made available by FCC or Commission requirements pursuant to the Communications Act of 1934, as modified by the Telecommunications Act of 1996 (the "Act"). Global Connection also shall be permitted to request the development of new or revised facilities or service options which are not required by the Act. Procedures applicable to requesting the addition of such facilities or service options are specified in this Attachment 11.

2.0 **BONA FIDE REQUEST**

- A Bona Fide Request (BFR) is to be used when Global Connection makes a request of BellSouth to provide a new or modified Unbundled Network Element, Interconnection option, or other service option (Requested Services) pursuant to the Act that was not previously included in this Agreement.
- A BFR shall be submitted in writing by Global Connection and shall specifically identify the requested service date, technical requirements, space requirements and/or such other specifications that clearly define the request such that BellSouth has sufficient information to analyze and prepare a response. Such a request shall also include Global Connection's designation of the request as being pursuant to the Telecommunications Act of 1996 (i.e. a BFR). The request shall be sent to Global Connection's designated BellSouth Sales contact.
- 2.3 If BellSouth determines that the preliminary analysis of the requested BFR is of such complexity that it will cause BellSouth to expend inordinate resources to evaluate the BFR, BellSouth shall notify Global Connection within ten (10) business days of BellSouth's receipt of BFR that a fee will be required prior to the evaluation of the BFR. Global Connection shall submit such fee within thirty (30) business days of BellSouth's notice that a fee is required. Within thirty (30) business days of BellSouth's receipt of the fee, BellSouth shall respond to Global Connection by providing a preliminary analysis of such Requested Services that are the subject of the BFR. The preliminary analysis shall either confirm that BellSouth will offer access to the Requested Services or confirm that BellSouth will not offer the Requested Services, BellSouth will provide an

explanation of why the request is not technically feasible, does not qualify as a BFR for the Requested Services or is otherwise not required to be provided under the Act. If preliminary analysis of the requested BFR is not of such complexity that it will cause BellSouth to expend inordinate resources to evaluate the BFR, within thirty (30) business days of its receipt of the BFR, BellSouth shall respond to Global Connection by providing a preliminary analysis of such Requested Services that are the subject of the BFR. The preliminary analysis shall either confirm that BellSouth will offer access to the Requested Services or confirm that BellSouth will not offer the Requested Services. If the preliminary analysis states that BellSouth will not offer the Requested Services, BellSouth will provide an explanation of why the request is not technically feasible, does not qualify as a BFR for the Requested Services or is otherwise not required to be provided under the Act.

- Global Connection may cancel a BFR at any time. If Global Connection cancels the request more than ten (10) business days after submitting the BFR request, Global Connection shall pay BellSouth's reasonable and demonstrable costs of processing and/or implementing the BFR up to the date of cancellation in addition to any fee submitted in accordance with Section 2.3 above.
- Global Connection will have thirty (30) business days from receipt of preliminary analysis to accept the preliminary analysis or cancel the BFR as set forth in Section 2.4. Acceptance of the preliminary analysis must be in writing and accompanied by all nonrecurring charges quoted in the preliminary analysis. The nonrecurring charges as stated in the preliminary analysis cover the initial work required to develop the project plan, create the design parameters, and establish all activities and resources required to complete the BFR (Development Costs).

 Development costs are non-refundable. If Global Connection fails to respond within this 30-day period, the BFR will be deemed cancelled.
- 2.5.1 BellSouth shall propose a firm price quote and a detailed implementation plan within thirty (30) business days of receipt of Global Connection's acceptance of the preliminary analysis.
- 2.5.2 Global Connection shall have thirty (30) business days from receipt of firm price quote to accept or deny the firm price quote and submit any additional nonrecurring, non-refundable fees quoted in the firm price quote.
- 2.6 Unless Global Connection agrees otherwise, all prices shall be consistent with the pricing principles of the Act, FCC and/or the Commission.

- 2.7 If Global Connection believes that BellSouth's firm price quote is not consistent with the requirements of the Act, or if either Party believes that the other is not acting in good faith in requesting, negotiating or processing the BFR, either Party may seek FCC or Commission arbitration, as appropriate, to resolve the dispute. Any such arbitration applicable to Unbundled Network Elements and/or Interconnection shall be conducted in accordance with standards prescribed in Section 252 of the Act.
- 2.8 Upon agreement to the rates, terms and conditions of a BFR, an amendment to this Agreement may be required.

3.0 NEW BUSINESS REQUEST

- A New Business Request (NBR) is to be used by Global Connection to make a request of BellSouth for a new or modified feature or capability of an existing product or service, a new product or service that is not deployed within the BellSouth network or operations and business support systems, or a new or modified service option that was not previously included in this Agreement (Requested Enhanced Services).
- An NBR shall be submitted in writing by Global Connection and shall specifically identify the requested service date, technical requirements, space requirements and/or such specifications that clearly define the request such that BellSouth has sufficient information to analyze and prepare a response. The request shall be sent to Global Connection's designated BellSouth Sales contact.
- 3.3 If BellSouth determines that the preliminary analysis of the requested NBR is of such complexity that it will cause BellSouth to expend inordinate resources to evaluate the NBR, BellSouth shall notify Global Connection that a fee will be required prior to the evaluation of the NBR. Global Connection shall submit such fee within ten (10) business days of BellSouth's notice that a fee is required. BellSouth shall use reasonable efforts to respond to the NBR within (30) business days following BellSouth's receipt of the fee by providing a preliminary analysis of such Requested Enhanced Services that are the subject of the NBR. The preliminary analysis shall either confirm that BellSouth will offer access to the Requested Enhanced Services or confirm that BellSouth will not offer the Requested Enhanced Services. If the preliminary analysis states that BellSouth will not offer the Requested Services, BellSouth will provide an explanation of why the request is not technically feasible, does not qualify as an NBR for the Requested Services or is otherwise not required to be provided under the Act. If preliminary analysis of the requested NBR is not of such complexity that it will cause BellSouth to

expend inordinate resources to evaluate the NBR, BellSouth will use reasonable efforts to respond to Global Connection within thirty (30) business days of its receipt of an NBR by providing a preliminary analysis of such Requested Services that are the subject of the NBR. The preliminary analysis shall either confirm that BellSouth will offer access to the Requested Enhanced Services or confirm that BellSouth will not offer the Requested Enhanced Services. If the preliminary analysis states that BellSouth will not offer the Requested Services, BellSouth will provide an explanation of why the request is not technically feasible, does not qualify as an NBR for the Requested Services or is otherwise not required to be provided under the Act.

- Global Connection may cancel an NBR at any time. If Global Connection cancels the request more than ten (10) business days after submitting it, Global Connection shall pay BellSouth's reasonable and demonstrable costs of processing and/or implementing the NBR up to the date of cancellation in addition to any fee submitted in accordance with Section 3.3 above.
- 3.5 Global Connection will have thirty (30) business days from receipt of preliminary analysis to accept the preliminary analysis or cancel the NBR as set forth in section 3.4. Acceptance of the preliminary analysis must be in writing and accompanied by all nonrecurring charges quoted in the preliminary analysis. The nonrecurring charges as stated in the preliminary analysis cover the initial work required to develop the project plan, create the design parameters, and establish all activities and resources required to complete the NBR. If Global Connection fails to respond within this 30-day period, the NBR will be deemed cancelled.
- 3.6 If Global Connection accepts the preliminary analysis, BellSouth shall propose a firm price quote and a detailed implementation plan within sixty (60) business days of receipt of Global Connection's acceptance of the preliminary analysis and nonrecurring fees quoted in the preliminary analysis.
- 3.7 Global Connection shall have thirty (30) business days from receipt of the firm price quote to accept or deny the firm price quote and submit any additional nonrecurring, non-refundable fees quoted in the firm price quote.
- 3.8 Upon agreement to the terms of a NBR, an amendment to this Agreement, or a separate agreement, may be required.